

FCC Test Report

| | |
|--------------|--------------------------|
| Product Name | Parafait RF Tag Reader 1 |
| Model No. | PARARFTRDR001 |
| FCC ID | G7H-SPRFTR001 |

| | |
|-----------|---|
| Applicant | Semnox Solutions Private Limited |
| Address | No.4-1-145, 3rd Floor, Punja Building Annexe M G Road, Lalbagh, Mangalore 575003 |

| | |
|-----------------|---------------------|
| Date of Receipt | Dec. 10, 2019 |
| Issued Date | Oct. 26, 2020 |
| Report No. | 19C0167R-RFUSP17V01 |
| Report Version | V1.0 |



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test Report

Issued Date: Oct. 26, 2020


Report No.: 19C0167R-RFUSP17V01



| | |
|---------------------|---|
| Product Name | Parafait RF Tag Reader 1 |
| Applicant | Semnox Solutions Private Limited |
| Address | No.4-1-145, 3rd Floor, Punja Building Annexe M G Road, Lalbagh, Mangalore 575003 |
| Manufacturer | Semnox Solutions Private Limited |
| Model No. | PARARFTRDR001 |
| FCC ID. | G7H-SPRFTR001 |
| EUT Rated Voltage | DC 5V |
| EUT Test Voltage | DC 5V |
| Trade Name | Parafait |
| Trademark | Semnox |
| Applicable Standard | FCC CFR Title 47 Part 15 Subpart C ANSI C63.4: 2014, ANSI C63.10: 2013 |
| Test Result | Complied |

Documented By


:



(Senior Adm. Specialist / Jinn Chen)

Tested By

:



(Senior Engineer / Ivan Chuang)

Approved By

:



(Director / Vincent Lin)

TABLE OF CONTENTS

| Description | Page |
|--|-----------|
| 1. GENERAL INFORMATION | 5 |
| 1.1. EUT Description..... | 5 |
| 1.2. Tested System Details..... | 6 |
| 1.3. Configuration of tested System | 6 |
| 1.4. EUT Exercise Software | 7 |
| 1.5. Test Facility | 8 |
| 1.6. List of Test Equipment | 9 |
| 1.7. Uncertainty | 10 |
| 2. Conducted Emission..... | 11 |
| 2.1. Test Setup | 11 |
| 2.2. Limits | 11 |
| 2.3. Test Procedure | 11 |
| 2.4. Test Result of Conducted Emission..... | 12 |
| 3. Radiated Emission | 14 |
| 3.1. Test Setup | 14 |
| 3.2. Limits | 15 |
| 3.3. Test Procedure | 17 |
| 3.4. Test Result of Radiated Emission..... | 18 |
| 4. Band Edge | 28 |
| 4.1. Test Setup | 28 |
| 4.2. Limits | 29 |
| 4.3. Test Procedure | 29 |
| 4.4. Test Result of Band Edge | 30 |
| 5. 20dB Bandwidth | 32 |
| 5.1. Test Setup | 32 |
| 5.2. Limits | 32 |
| 5.3. Test Procedure | 32 |
| 5.4. Test Result of 20dB Bandwidth..... | 33 |
| 6. Frequency Tolerance | 34 |
| 6.1. Test Setup | 34 |
| 6.2. Limits | 34 |
| 6.3. Test Procedure | 34 |
| 6.4. Test Result of Frequency Stability..... | 35 |
| 7. EMI Reduction Method During Compliance Testing | 37 |
| Attachment 1: EUT Test Photographs | |
| Attachment 2: EUT Detailed Photographs | |

Revision History

| Report No. | Version | Description | Issued Date |
|---------------------|----------------|--------------------------|--------------------|
| 19C0167R-RFUSP17V01 | V1.0 | Initial issue of report. | 2020-10-26 |

1. GENERAL INFORMATION

1.1. EUT Description

| | |
|-----------------|--------------------------|
| Product Name | Parafait RF Tag Reader 1 |
| Trade Name | Parafait |
| Trademark | Semnox |
| Model No. | PARARFTRDR001 |
| FCC ID | G7H-SPRFTR001 |
| Frequency Range | 13.56MHz |
| Modulation | ASK |
| Antenna Type | Coil Antenna |

Frequency of Each Channel:

| Channel | Frequency |
|------------|-----------|
| Channel 1: | 13.56 MHz |

Note:

1. This device is a Parafait RF Tag Reader 1 with a built-in 13.56MHz transceiver.
2. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.225.
3. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

| | |
|-----------|------------------|
| Test Mode | Mode 1: Transmit |
|-----------|------------------|


1.2. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

| | Product | Manufacturer | Model No. | Serial No. | Power Cord |
|---|---------------|--------------|-----------|------------|------------|
| 1 | Power Adapter | Apple | A1385 | N/A | N/A |
| 2 | Tag Card | Semnox | F08 | N/A | N/A |

| Signal Cable Type | Signal cable Description |
|-------------------|-----------------------------------|
| A | USB Cable Shielded, 1.7m |
| B | Power Cable Non-shielded, 1.8m |

1.3. Configuration of tested System



1.4. EUT Exercise Software

1. Setup the EUT as shown in Section 1.3.
2. Use tag card to trigger EUT for signal transmitting.
3. Configure the test mode, the test channel, and the data rate.
4. Press “OK” to start the continuous Transmit.
5. Verify that the EUT works properly.

1.5. Test Facility

Ambient conditions in the laboratory:

| Performed Item | Items | Required | Actual |
|--------------------|------------------|----------|---------|
| Conducted Emission | Temperature (°C) | 10~40 °C | 21.3 °C |
| | Humidity (%RH) | 10~90 % | 42.1 % |
| Radiated Emission | Temperature (°C) | 10~40 °C | 22.5 °C |
| | Humidity (%RH) | 10~90 % | 55.7 % |
| Conductive | Temperature (°C) | 10~40 °C | 23.5 °C |
| | Humidity (%RH) | 10~90 % | 56 % |

USA : FCC Registration Number: TW0023

Canada : IC Registration Number: 25880

Site Description : Accredited by TAF
Accredited Number: 3023

Test Laboratory : DEKRA Testing and Certification Co., Ltd
Address : No.159, Sec. 2, Wenhua 1st Rd., Linkou Dist.,
New Taipei City 24457, Taiwan, R.O.C.

Phone number : 886-2-2602-7968
Fax number : 866-2-2602-3286
Email address : info.tw@dekra.com
Website : <http://www.dekra.com.tw>

1.6. List of Test Equipment

For Conduction measurements /ASR1

| | Equipment | Manufacturer | Model No. | Serial No. | Cali. Data | Due. Data |
|---|--------------------|--------------|-----------|------------|------------|------------|
| X | EMI Test Receiver | R&S | ESR7 | 101601 | 2020.05.28 | 2021.05.27 |
| X | Two-Line V-Network | R&S | ENV216 | 101306 | 2020.03.25 | 2021.03.24 |
| X | Two-Line V-Network | R&S | ENV216 | 101307 | 2020.04.17 | 2021.04.16 |
| X | Coaxial Cable | Quietek | RG400_BNC | RF001 | 2020.05.24 | 2021.05.23 |

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with "X" are used to measure the final test results.
3. Test Software version : DEKRA Testing System V1.2.

For Conducted measurements /ASR3

| | Equipment | Manufacturer | Model No. | Serial No. | Cali. Data | Due. Data |
|---|---------------------|--------------|-------------|------------|------------|------------|
| X | Temperature Chamber | KSON | THS-D4T-100 | A0606 | 2020.04.22 | 2021.04.21 |
| X | Spectrum Analyzer | R&S | FSV40 | 101149 | 2019.12.16 | 2020.12.15 |

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with "X" are used to measure the final test results.

For Radiated measurements /ACB1

| | Equipment | Manufacturer | Model No. | Serial No. | Cali. Data | Due. Data |
|---|-------------------|---------------|--------------|------------|------------|------------|
| X | Loop Antenna | AMETEK | HLA6121 | 49611 | 2020.03.16 | 2021.03.15 |
| X | Bi-Log Antenna | SCHWARZBECK | VULB9168 | 9168-953 | 2020.01.03 | 2021.01.02 |
| | Horn Antenna | ETS-Lindgren | 3117 | 00203800 | 2019.12.12 | 2020.12.11 |
| | Horn Antenna | Com-Power | AH-840 | 101087 | 2020.06.08 | 2021.06.07 |
| X | Pre-Amplifier | EMCI | EMC001330 | 980316 | 2020.06.23 | 2021.06.22 |
| | Pre-Amplifier | EMCI | EMC051835SE | 980311 | 2020.06.23 | 2021.06.22 |
| | Pre-Amplifier | EMCI | EMC05820SE | 980310 | 2020.06.24 | 2021.06.23 |
| | Pre-Amplifier | EMCI | EMC184045SE | 980314 | 2020.06.10 | 2021.06.09 |
| | Filter | MICRO TRONICS | BRM50702 | G251 | 2020.09.17 | 2021.09.16 |
| | Filter | MICRO TRONICS | BRM50716 | G188 | 2020.09.17 | 2021.09.16 |
| X | EMI Test Receiver | R&S | ESR7 | 101602 | 2019.12.16 | 2020.12.15 |
| X | Spectrum Analyzer | R&S | FSV40 | 101148 | 2020.03.16 | 2021.03.15 |
| X | Coaxial Cable | SUHNER | SUCOFLEX 106 | RF002 | 2020.07.03 | 2021.07.02 |
| | Mircoflex Cable | HUBER SUHNER | SUCOFLEX 102 | MY3381/2 | 2020.06.10 | 2021.06.09 |

Note:

1. Loop Antenna is calibrated every two year, the other equipments are calibrated every one year.
2. The test instruments marked with "X" are used to measure the final test results.
3. Test Software version : DEKRA Testing System V1.2.

1.7. Uncertainty

Uncertainties have been calculated according to the DEKRA internal document, and is described in each test chapter of this report.


The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

| Test item | Uncertainty | |
|---------------------|------------------------|------------------------|
| Conducted Emission | ±3.42dB | |
| Radiated Emission | Under 1GHz ±4.06 dB | Above 1GHz ±3.73 dB |
| Band Edge | Under 1GHz ±4.06 dB | Above 1GHz ±3.73 dB |
| Frequency Tolerance | ±682.83 Hz | |

2. Conducted Emission

2.1. Test Setup



2.2. Limits

| FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit | | |
|---|----------------------|----------------------|
| Frequency MHz | Limits | |
| | QP | AV |
| 0.15 - 0.50 | 66-56 ^(註) | 56-46 ^(註) |
| 0.50-5.0 | 56 | 46 |
| 5.0 - 30 | 60 | 50 |

2.3. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.4. Test Result of Conducted Emission

Product : Parafait RF Tag Reader 1
 Test Item : Conducted Emission Test
 Test date : 2020/09/25
 Test Mode : Mode 1: Transmit

L1



| No | Frequency (MHz) | Emission Level (dBuV) | Limit (dBuV) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB) | Detector Type |
|----|-----------------|-----------------------|--------------|-------------|----------------------|---------------------|---------------|
| 1 | 0.15 | 37.83 | 66.00 | -28.16 | 28.17 | 9.66 | QP |
| 2 | 0.15 | 19.62 | 56.00 | -36.38 | 9.96 | 9.66 | AV |
| 3 | 0.541 | 24.36 | 56.00 | -31.64 | 14.69 | 9.66 | QP |
| 4 | 0.541 | 15.49 | 46.00 | -30.51 | 5.83 | 9.66 | AV |
| 5 | 0.768 | 32.29 | 56.00 | -23.71 | 22.61 | 9.68 | QP |
| *6 | 0.768 | 24.46 | 46.00 | -21.54 | 14.78 | 9.68 | AV |
| 7 | 1.399 | 20.88 | 56.00 | -35.12 | 11.18 | 9.70 | QP |
| 8 | 1.399 | 14.05 | 46.00 | -31.95 | 4.35 | 9.70 | AV |
| 9 | 4.666 | 20.33 | 56.00 | -35.67 | 10.54 | 9.79 | QP |
| 10 | 4.666 | 14.43 | 46.00 | -31.57 | 4.65 | 9.79 | AV |
| 11 | 10.251 | 33.13 | 60.00 | -26.87 | 23.24 | 9.89 | QP |
| 12 | 10.251 | 15.82 | 50.00 | -34.18 | 5.92 | 9.89 | AV |

Remark:

1. "*" means this data is the worst emission level; "!" means this data is over limit.
2. Emission Level=Reading Level + Correct Factor(Correct Factor=LISN Factor+Cable Loss).
3. Margin=Emission Level-Limit

Product : Parafait RF Tag Reader 1
 Test Item : Conducted Emission Test
 Test date : 2020/09/25
 Test Mode : Mode 1: Transmit

N



| No | Frequency (MHz) | Emission Level (dBuV) | Limit (dBuV) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB) | Detector Type |
|-----|-----------------|-----------------------|--------------|-------------|----------------------|---------------------|---------------|
| 1 | 0.15 | 37.91 | 66.00 | -28.08 | 28.24 | 9.67 | QP |
| 2 | 0.15 | 19.25 | 56.00 | -36.74 | 9.58 | 9.67 | AV |
| 3 | 0.474 | 24.69 | 56.44 | -31.75 | 15.02 | 9.67 | QP |
| 4 | 0.474 | 13.41 | 46.44 | -33.03 | 3.74 | 9.67 | AV |
| 5 | 0.767 | 29.43 | 56.00 | -26.57 | 19.75 | 9.68 | QP |
| 6 | 0.767 | 23.13 | 46.00 | -22.87 | 13.45 | 9.68 | AV |
| 7 | 1.383 | 19.54 | 56.00 | -36.46 | 9.83 | 9.70 | QP |
| 8 | 1.383 | 14.69 | 46.00 | -31.31 | 4.99 | 9.70 | AV |
| 9 | 2.947 | 20.73 | 56.00 | -35.27 | 10.98 | 9.75 | QP |
| 10 | 2.947 | 15.77 | 46.00 | -30.23 | 6.02 | 9.75 | AV |
| *11 | 11.017 | 40.92 | 60.00 | -19.08 | 30.99 | 9.93 | QP |
| 12 | 11.017 | 23.34 | 50.00 | -26.66 | 13.41 | 9.93 | AV |


Remark:

1. "*" means this data is the worst emission level; "!" means this data is over limit.
2. Emission Level=Reading Level + Correct Factor(Correct Factor=LISN Factor+Cable Loss).
3. Margin=Emission Level-Limit


3. Radiated Emission

3.1. Test Setup

9kHz~30MHz



30MHz~1GHz



3.2. Limits

➤ Fundamental electric field strength Limit

| FCC Part 15 Subpart C Paragraph 15.225 Limits | | | | |
|---|-------------------------------|---------------------|--------|---------------------|
| Fundamental Frequency MHz | Field strength of fundamental | | | |
| | uV/m | Distance (meter) | dBuV/m | Distance (meter) |
| 13.553 – 13.567 | 15848 | 30 | 124 | 3 |
| 13.410 – 13.553 and 13.567 – 13.710 | 334 | 30 | 90.47 | 3 |
| 13.110 – 13.410 and 13.710 – 14.010 | 106 | 30 | 80.50 | 3 |
| Outside of the 13.110 – 14.010 | See 15.209 Limits | | | |

Remarks : 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)

2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

► Spurious electric field strength Limit

| FCC Part 15 Subpart C Paragraph 15.209 Limits | | | |
|--|--------------|-------------------------|---------------------------------|
| Frequency MHz | uV/m | dBuV/m | Measurement distance (meter) |
| 0.009-0.490 | 2400/F(kHz) | See Remark ¹ | 300 |
| 0.490-1.705 | 24000/F(kHz) | See Remark ¹ | 30 |
| 1.705-30 | 30 | 29.5 | 30 |
| 30-88 | 100 | 40 | 3 |
| 88-216 | 150 | 43.5 | 3 |
| 216-960 | 200 | 46 | 3 |
| Above 960 | 500 | 54 | 3 |

- Remarks :
1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
 2. In the Above Table, the tighter limit applies at the band edges.
 3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3.3. Test Procedure

Fundamental electric field strength:

The EUT and its simulators are placed on a turn table which is 1 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum electric field strength.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna which is 1 meter above ground. All X-axis, Y-axis and Z-axis polarization of the antenna are set on measurement.

Spurious electric field strength:

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C6310: 2013 on radiated measurement.

On any frequency the radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurement are included emission measurement below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.


The bandwidth below 30MHz setting on the field strength meter is 9kHz and above 30MHz is 120kHz.

The frequency range from 9kHz to 10th harmonics is checked.

3.4. Test Result of Radiated Emission

Product : Parafait RF Tag Reader 1
 Test Item : Fundamental Radiated Emission
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

X-axis - HORIZONTAL




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| * 1 | 13.11 | 26.29 | 69.50 | -43.21 | 4.03 | 22.26 | QP |
| 2 | 13.41 | 30.19 | 80.50 | -50.31 | 7.92 | 22.27 | QP |
| 3 | 13.553 | 44.64 | 90.47 | -45.83 | 22.36 | 22.28 | QP |
| 4 | 13.56 | 59.63 | 124.00 | -64.37 | 37.35 | 22.28 | QP |
| 5 | 13.567 | 45.78 | 90.47 | -44.69 | 23.50 | 22.28 | QP |
| 6 | 13.71 | 30.11 | 80.50 | -50.39 | 7.82 | 22.29 | QP |
| 7 | 14.01 | 26.12 | 69.50 | -43.38 | 3.82 | 22.30 | QP |

Note:

1. Fundamental Limit=84dBuV/m + 40*Log (30(m)/3(m))=124dBuV/m.
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. “*” means the worst emission level.
4. Emission Level = Reading Level + Correct Factor.

Product : Parafait RF Tag Reader 1
 Test Item : Fundamental Radiated Emission
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

X-axis - VERTICAL




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| 1 | 13.11 | 26.25 | 69.50 | -43.25 | 3.99 | 22.26 | QP |
| 2 | 13.41 | 33.28 | 80.50 | -47.22 | 11.01 | 22.27 | QP |
| 3 | 13.553 | 49.21 | 90.47 | -41.26 | 26.93 | 22.28 | QP |
| 4 | 13.56 | 64.25 | 124.00 | -59.75 | 41.97 | 22.28 | QP |
| * 5 | 13.567 | 50.39 | 90.47 | -40.08 | 28.11 | 22.28 | QP |
| 6 | 13.71 | 33.95 | 80.50 | -46.55 | 11.66 | 22.29 | QP |
| 7 | 14.01 | 26.22 | 69.50 | -43.28 | 3.92 | 22.30 | QP |

Note:

1. Fundamental Limit=84dBuV/m + 40*Log (30(m)/3(m))=124dBuV/m.
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. “*” means the worst emission level.
4. Emission Level = Reading Level + Correct Factor.

Product : Parafait RF Tag Reader 1
 Test Item : Fundamental Radiated Emission
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

Y-axis - HORIZONTAL




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| 1 | 13.11 | 26.25 | 69.50 | -43.25 | 3.99 | 22.26 | QP |
| 2 | 13.41 | 35.13 | 80.50 | -45.37 | 12.86 | 22.27 | QP |
| 3 | 13.553 | 49.81 | 90.47 | -40.66 | 27.53 | 22.28 | QP |
| 4 | 13.56 | 64.80 | 124.00 | -59.20 | 42.52 | 22.28 | QP |
| * 5 | 13.567 | 50.97 | 90.47 | -39.50 | 28.69 | 22.28 | QP |
| 6 | 13.71 | 35.11 | 80.50 | -45.39 | 12.82 | 22.29 | QP |
| 7 | 14.01 | 26.17 | 69.50 | -43.33 | 3.87 | 22.30 | QP |

Note:

1. Fundamental Limit=84dBuV/m + 40*Log (30(m)/3(m))=124dBuV/m.
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. "*" means the worst emission level.
4. Emission Level = Reading Level + Correct Factor.

Product : Parafait RF Tag Reader 1
 Test Item : Fundamental Radiated Emission
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

Y-axis - VERTICAL




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| 1 | 13.11 | 26.42 | 69.50 | -43.08 | 4.16 | 22.26 | QP |
| 2 | 13.41 | 35.49 | 80.50 | -45.01 | 13.22 | 22.27 | QP |
| 3 | 13.553 | 51.02 | 90.47 | -39.45 | 28.74 | 22.28 | QP |
| 4 | 13.56 | 66.02 | 124.00 | -57.98 | 43.74 | 22.28 | QP |
| * 5 | 13.567 | 52.18 | 90.47 | -38.29 | 29.90 | 22.28 | QP |
| 6 | 13.71 | 36.02 | 80.50 | -44.48 | 13.73 | 22.29 | QP |
| 7 | 14.01 | 26.16 | 69.50 | -43.34 | 3.86 | 22.30 | QP |

Note:

1. Fundamental Limit=84dBuV/m + 40*Log (30(m)/3(m))=124dBuV/m.
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. “*” means the worst emission level.
4. Emission Level = Reading Level + Correct Factor.

Product : Parafait RF Tag Reader 1
 Test Item : Fundamental Radiated Emission
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

Z-axis- HORIZONTAL




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| 1 | 13.11 | 26.19 | 69.50 | -43.31 | 3.93 | 22.26 | QP |
| 2 | 13.41 | 34.87 | 80.50 | -45.63 | 12.60 | 22.27 | QP |
| 3 | 13.553 | 49.57 | 90.47 | -40.90 | 27.29 | 22.28 | QP |
| 4 | 13.56 | 64.53 | 124.00 | -59.47 | 42.25 | 22.28 | QP |
| * 5 | 13.567 | 50.72 | 90.47 | -39.75 | 28.44 | 22.28 | QP |
| 6 | 13.71 | 35.03 | 80.50 | -45.47 | 12.74 | 22.29 | QP |
| 7 | 14.01 | 26.12 | 69.50 | -43.38 | 3.82 | 22.30 | QP |

Note:

1. Fundamental Limit=84dBuV/m + 40*Log (30(m)/3(m))=124dBuV/m.
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. "*" means the worst emission level.
4. Emission Level = Reading Level + Correct Factor.

Product : Parafait RF Tag Reader 1
 Test Item : Fundamental Radiated Emission
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

Z-axis - VERTICAL




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| 1 | 13.11 | 26.21 | 69.50 | -43.29 | 3.95 | 22.26 | QP |
| 2 | 13.41 | 35.33 | 80.50 | -45.17 | 13.06 | 22.27 | QP |
| 3 | 13.553 | 50.91 | 90.47 | -39.56 | 28.63 | 22.28 | QP |
| 4 | 13.56 | 65.93 | 124.00 | -58.07 | 43.65 | 22.28 | QP |
| * 5 | 13.567 | 52.08 | 90.47 | -38.39 | 29.80 | 22.28 | QP |
| 6 | 13.71 | 35.84 | 80.50 | -44.66 | 13.55 | 22.29 | QP |
| 7 | 14.01 | 26.25 | 69.50 | -43.25 | 3.95 | 22.30 | QP |

Note:

1. Fundamental Limit=84dBuV/m + 40*Log (30(m)/3(m))=124dBuV/m.
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. “*” means the worst emission level.
4. Emission Level = Reading Level + Correct Factor.

Product : Parafait RF Tag Reader 1
 Test Item : General Radiated Emission Data (below 30MHz)
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

Horizontal




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| * 1 | 4.928 | 26.60 | 69.54 | -42.94 | 5.83 | 20.77 | QP |
| 2 | 5.347 | 26.25 | 69.54 | -43.29 | 5.36 | 20.89 | QP |
| 3 | 6.667 | 25.50 | 69.54 | -44.04 | 4.27 | 21.23 | QP |
| 4 | 9.696 | 25.90 | 69.54 | -43.64 | 3.88 | 22.02 | QP |
| 5 | 17.854 | 25.74 | 69.54 | -43.80 | 3.25 | 22.49 | QP |
| 6 | 21.423 | 25.31 | 69.54 | -44.23 | 2.64 | 22.67 | QP |

Note:

1. Limit=29.54dBuV/m + 40*Log (30(m)/3(m))=69.54dBuV/m.
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. "*" means the worst emission level.
4. Emission Level = Reading Level + Correct Factor.

Product : Parafait RF Tag Reader 1
 Test Item : General Radiated Emission Data (below 30MHz)
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

Vertical




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| 1 | 3.518 | 24.68 | 69.54 | -44.86 | 4.55 | 20.13 | QP |
| 2 | 5.227 | 28.84 | 69.54 | -40.70 | 7.98 | 20.86 | QP |
| 3 | 8.706 | 25.99 | 69.54 | -43.55 | 4.23 | 21.76 | QP |
| * 4 | 17.974 | 32.91 | 69.54 | -36.63 | 10.41 | 22.50 | QP |
| 5 | 22.082 | 26.65 | 69.54 | -42.89 | 3.95 | 22.70 | QP |
| 6 | 24.872 | 26.54 | 69.54 | -43.00 | 3.70 | 22.84 | QP |

Note:

1. Limit=29.54dBuV/m + 40*Log (30(m)/3(m))=69.54dBuV/m.
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. “*” means the worst emission level.
4. Emission Level = Reading Level + Correct Factor.

Product : Parafait RF Tag Reader 1
 Test Item : General Radiated Emission Data (above 30MHz)
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

Horizontal




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| 1 | 67.83 | 33.99 | 40.00 | -6.01 | 46.36 | -12.37 | QP |
| 2 | 121.18 | 31.19 | 43.50 | -12.31 | 44.26 | -13.07 | QP |
| 3 | 148.34 | 33.77 | 43.50 | -9.73 | 44.15 | -10.38 | QP |
| 4 | 284.14 | 33.95 | 46.00 | -12.05 | 43.24 | -9.29 | QP |
| * 5 | 311.3 | 41.85 | 46.00 | -4.15 | 50.46 | -8.61 | QP |
| 6 | 955.38 | 31.39 | 46.00 | -14.61 | 28.77 | 2.62 | QP |

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. “*” means the worst emission level.
3. Emission Level = Reading Level + Correct Factor

Product : Parafait RF Tag Reader 1
 Test Item : General Radiated Emission Data (above 30MHz)
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

Vertical



| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| 1 | 40.67 | 34.94 | 40.00 | -5.06 | 45.76 | -10.82 | QP |
| * 2 | 66.86 | 38.20 | 40.00 | -1.80 | 50.46 | -12.26 | QP |
| 3 | 81.41 | 33.93 | 40.00 | -6.07 | 49.10 | -15.17 | QP |
| 4 | 148.34 | 32.51 | 43.50 | -10.99 | 42.89 | -10.38 | QP |
| 5 | 311.3 | 36.08 | 46.00 | -9.92 | 44.69 | -8.61 | QP |
| 6 | 722.58 | 31.87 | 46.00 | -14.13 | 32.42 | -0.55 | QP |


Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. "*" means the worst emission level.
3. Emission Level = Reading Level + Correct Factor


4. Band Edge

4.1. Test Setup

RF Conducted Measurement:



RF Radiated Measurement:



4.2. Limits

In any 9 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50 dB below that in the 9 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

4.3. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.


Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated measurement.

The bandwidth below 30MHz setting on the field strength meter is 9kHz and above 30MHz is 120kHz.

4.4. Test Result of Band Edge

Product : Parafait RF Tag Reader 1
 Test Item : Band Edge Data
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

HORIZONTAL




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| 1 | 13.11 | 26.02 | 69.54 | -43.52 | 3.76 | 22.26 | QP |
| 2 | 13.36 | 28.20 | 69.54 | -41.34 | 5.93 | 22.27 | QP |
| * 3 | 13.41 | 35.11 | 69.54 | -34.43 | 12.84 | 22.27 | QP |
| 4 | 14.01 | 26.02 | 69.54 | -43.52 | 3.72 | 22.30 | QP |

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Emission Level = Reading Level + Correct Factor.

Product : Parafait RF Tag Reader 1
 Test Item : Band Edge Data
 Test date : 2020/10/05
 Test Mode : Mode 1: Transmit

VERTICAL




| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Reading Level (dBuV) | Correct Factor (dB/m) | Detector Type |
|-----|-----------------|-------------------------|----------------|-------------|----------------------|-----------------------|---------------|
| 1 | 13.11 | 26.21 | 69.54 | -43.33 | 3.95 | 22.26 | QP |
| 2 | 13.36 | 28.32 | 69.54 | -41.22 | 6.05 | 22.27 | QP |
| * 3 | 13.41 | 35.16 | 69.54 | -34.38 | 12.89 | 22.27 | QP |
| 4 | 14.01 | 26.12 | 69.54 | -43.42 | 3.82 | 22.30 | QP |

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Emission Level = Reading Level + Correct Factor.

5. 20dB Bandwidth

5.1. Test Setup



5.2. Limits

§15.215

(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through §15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

§15.225

Operation within the band 13.11MHz ~ 14.010MHz.


5.3. Test Procedure

The spectrum analyzer connects to the receiver antenna and setting the RBW = 10KHz, the VBW is set to 3 times or more than RBW.

5.4. Test Result of 20dB Bandwidth

Product : Parafait RF Tag Reader 1
 Test Item : 20dB Bandwidth
 Test date : 2020/10/23
 Test Mode : Mode 1: Transmit


| Test Frequency (MHz) | Measurement Level (MHz) | Limit (MHz) | Result |
|----------------------|-------------------------|-------------|--------|
| 13.56 | 13.3402 | >13.11 | PASS |
| | 13.7798 | <14.01 | |
| 20dB Bandwidth | 0.4396 | -- | |



Date: 23.OCT.2020 15:46:48

6. Frequency Tolerance

6.1. Test Setup



6.2. Limits

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency.

6.3. Test Procedure

The over operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

6.4. Test Result of Frequency Stability

Product : Parafait RF Tag Reader 1
 Test Item : Frequency Tolerance
 Test Site : Temperature Chamber
 Test date : 2020/10/18
 Test Mode : Mode 1: Transmit

| Temperature (°C) | Voltage (V) | Observe Time | Declared Frequency (MHz) | Read Frequency (MHz) | Tolerance (%) | Limit (%) |
|------------------|-------------|--------------|--------------------------|----------------------|---------------|-----------|
| 20 | 5 | start | 13.56 | 13.56014 | 0.001032 | ±0.01 % |
| | | 2mins | 13.56 | 13.56014 | 0.001032 | |
| | | 5mins | 13.56 | 13.56014 | 0.001032 | |
| | | 10mins | 13.56 | 13.56014 | 0.001032 | |
| 20 | 5.75 | start | 13.56 | 13.56014 | 0.001032 | ±0.01 % |
| | | 2mins | 13.56 | 13.56014 | 0.001032 | |
| | | 5mins | 13.56 | 13.56014 | 0.001032 | |
| | | 10mins | 13.56 | 13.56014 | 0.001032 | |
| 20 | 4.25 | start | 13.56 | 13.56014 | 0.001032 | ±0.01 % |
| | | 2mins | 13.56 | 13.56014 | 0.001032 | |
| | | 5mins | 13.56 | 13.56014 | 0.001032 | |
| | | 10mins | 13.56 | 13.56014 | 0.001032 | |
| 50 | 5 | start | 13.56 | 13.56007 | 0.000516 | ±0.01 % |
| | | 2mins | 13.56 | 13.56007 | 0.000516 | |
| | | 5mins | 13.56 | 13.56007 | 0.000516 | |
| | | 10mins | 13.56 | 13.56007 | 0.000516 | |
| 40 | 5 | start | 13.56 | 13.56007 | 0.000516 | ±0.01 % |
| | | 2mins | 13.56 | 13.56007 | 0.000516 | |
| | | 5mins | 13.56 | 13.56007 | 0.000516 | |
| | | 10mins | 13.56 | 13.56007 | 0.000516 | |
| 30 | 5 | start | 13.56 | 13.56014 | 0.001032 | ±0.01 % |
| | | 2mins | 13.56 | 13.56014 | 0.001032 | |
| | | 5mins | 13.56 | 13.56014 | 0.001032 | |
| | | 10mins | 13.56 | 13.56014 | 0.001032 | |

| | | | | | | |
|-----|---|--------|-------|----------|-----------|----------|
| 10 | 5 | start | 13.56 | 13.56000 | 0.000000 | ± 0.01 % |
| | | 2mins | 13.56 | 13.56000 | 0.000000 | |
| | | 5mins | 13.56 | 13.55900 | -0.007375 | |
| | | 10mins | 13.56 | 13.56050 | 0.003687 | |
| 0 | 5 | start | 13.56 | 13.56021 | 0.001549 | ± 0.01 % |
| | | 2mins | 13.56 | 13.56021 | 0.001549 | |
| | | 5mins | 13.56 | 13.56021 | 0.001549 | |
| | | 10mins | 13.56 | 13.56021 | 0.001549 | |
| -10 | 5 | start | 13.56 | 13.56021 | 0.001549 | ± 0.01 % |
| | | 2mins | 13.56 | 13.56021 | 0.001549 | |
| | | 5mins | 13.56 | 13.56021 | 0.001549 | |
| | | 10mins | 13.56 | 13.56021 | 0.001549 | |
| -20 | 5 | start | 13.56 | 13.56021 | 0.001549 | ± 0.01 % |
| | | 2mins | 13.56 | 13.56021 | 0.001549 | |
| | | 5mins | 13.56 | 13.56021 | 0.001549 | |
| | | 10mins | 13.56 | 13.56021 | 0.001549 | |

7. EMI Reduction Method During Compliance Testing

No modification was made during testing.