Report #: 2004234 FCC ID: G8JHHI01 Model #: 52808G505 Standard: FCC Part 90 Date: January 24, 2005

APPENDIX A: RF EXPOSURE; FCC RULES AND REGULATIONS PART 1.1307, 1.1310, 2.1091, 2.1093

- 1. General Information: FCCID: G8JHHI01 Environment: General Population/Uncontrolled Exposure Device category: Mobile per Part 2.1091
- 2. Antenna Data:

Antenna	Туре	Gain (dBi)	Numeric Gain	Frequency Used (MHz)
Whip	Omni	3.2	2.1	451.355

3. MPE Calculation:

The limit for general population/uncontrolled exposure environment is f/1500 mW/cm^2 , or

 $0.3 \, mW \, / \, cm^2$.

The maximum distance, from the antenna at which MPE is met or exceeded, is calculated from the equation relating field strength E in V/m, transmit power P in Watts, transmit antenna numeric gain G, and separation distance in meters. The Electric field generated for a 1mW/cm^2 exposure (S) is calculated as follows:

$$S = \frac{E^2}{Z}$$
 where: S = Power density; E = Electric field; and Z = Impedance
or $E(V/m) = \sqrt{S \times Z}$ and 0.3 mW/cm² = 3 W/m² and the impedance of free space is 337 ohms,

where E and H fields are perpendicular. Thus: $E(V/m) = \sqrt{3 \times 377} = 33.63 \text{ V/m}$

from the formula
$$P = \frac{E(V/m)^2 \times d^2}{30 \times G}$$
 or $d = \frac{\sqrt{30 \times P \times G}}{E(V/m)}$

Substitution yields: 0.

$$24m = \frac{\sqrt{30 \times 1 \times 2.1}}{33.63}$$

Separation Distance				
Power (Watt)	(cm)			
1	24			

$$S = \frac{P \times G}{P \times G}$$

 $3^{-}\overline{4 \times p \times d^{2}}$ Where: S = power density; P = power (W); G = numeric gain; d = distance to radiation center

Substitution yields:

$$S = \frac{1000 \times 3.2}{4 \times \boldsymbol{p} \times 20^2} = 0.64 m W / cm^2$$

Power Density Limit	Calculated Power density at 20 cm distance	
0.3 mW/cm ²	0.64 mW/ cm ²	

Report #:2004234FCC ID:G8JHHI01Model #:52808G505Standard:FCC Part 90Date:January 24, 2005

CONCLUSION: To insure the device complies with the MPE requirements by providing a safe separation distance between the antenna, including any radiating structure, and any persons, the separation distance should be 24 cm.

Proposed RF exposure safety information to include in User's Manual:

CAUTION: Antenna Installation Requirement

.

The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 24 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.