

RF Exposure Report

EUT Name: Real Time Mobile Interrogator

EUT Model: RTMI / 7S1900G001

FCC ID: G8JMMI01 ,

FCC Title 47, Part 15, SubpartC, RSS-210 Issue 7

Prepared for:

Mark Holman
Elster Solutions, LLC
208 South Rogers Lane
Raleigh, NC 27610
Tel: 919 212-4899
Fax: 919 250-5439

Prepared by:

TUV Rheinland of North America
762 Park Avenue
Youngsville, NC 27596
Tel: (919) 554-0901
Fax: (919) 556-2043
<http://www.tuv.com/>

Report/Issue Date: 25 May 2010

Report Number: Supplement to 31061184.001 - MPE for FCC

1 RF Exposure Measurement (Mobile Device) FCC Part 1.1310

1.1 Test Methodology

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Semi-Anechoic Chamber, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

1.2 RF Exposure Limit

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	$f / 300$	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	$f / 1500$	30
1500-100,000	1.0	30

f = Frequency in MHz

1.3 EUT Operating condition

The EUT is a single channel frequency device. It is intended to operate in an Occupational / Control Exposure environment.

1.4 Classification

The antenna of the product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. Therefore, this device is classified as a **Mobile Device**.

1.5 Test Results

1.5.1 Antenna Gain

The published Gain of the antenna is 5.0 dB = 3.16 (numeric).

1.5.2 Output Power into Antenna & RF Exposure value at distance 20cm:

The typical transmission is initiated 25 times a second for a duration of approximately 18.4 milliseconds.

$25 * 18.4\text{ms} = 460\text{ms}$ of on time per second

$20 \log(460\text{ms}/1000\text{ms}) = 20 \log(0.46) = -6.74\text{dB}$ (time averaged power correction factor)

$P_{\text{out}} = 38.58 \text{ dBm} - 6.74\text{dB} = 31.84 \text{ dBm} = 1527.57 \text{ mW}$ (time averaged power output)

Calculations for this report are based on highest power measurement and the highest gain of the antenna.

Limit for MPE (from FCC part 1.1310 table 1) is; $f \text{ (MHz)} / 300 = 451.34 / 1500 = 1.58 \text{ mW/cm}^2$

Highest antenna gain (in linear scale) is 3.16, R is 20cm, and $f = 451.34 \text{ MHz}$

$P_d = (1527.57 * 3.16) / (1600\pi) = \underline{\mathbf{0.96 \text{ mW/cm}^2}}$, which is below to the 1.58 mW/cm^2 limit.

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

1.6 Sample Calculation

The Friis transmission formula: $P_d = (P_{\text{out}} * G) / (4 * \pi * R^2)$

Where;

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi \approx 3.1416$

R = distance between observation point and center of the radiator in cm

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition, Page 640, Eq. (11-133).