



# Radio Exposure Evaluation Report

**FCC ID** : G95-CGA437A

**Equipment** : DOCSIS 3.1 Residential Voice Gateway

**Brand Name** : Technicolor

**Model Name** : CGA437ATCH5 ; CGA437AXXXX (where X can be alphanumeric, -, or blank)

**Applicant** : Technicolor Connected Home USA LLC  
4855 Peachtree Industrial Blvd.  
Suite 200  
Norcross, Georgia 30092

**Manufacturer** : Technicolor Connected Home USA LLC  
4855 Peachtree Industrial Blvd.  
Suite 200  
Norcross, Georgia 30092

**Standard** : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Jun. 18, 2022, and testing was started from Jun. 18, 2022 and completed on Dec. 06, 2022. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

  
Approved by: Jackson Tsai

**SPORTON INTERNATIONAL INC. Hsinhua Laboratory**  
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



# Table of Contents

**HISTORY OF THIS TEST REPORT .....3**

**1 GENERAL DESCRIPTION .....5**

1.1 Information.....5

1.2 Applicable Standards .....8

1.3 Testing Location .....8

**2 MAXIMUM PERMISSIBLE EXPOSURE .....9**

2.1 Limit of Maximum Permissible Exposure .....9

2.2 RF Exposure Exempt Measurement .....10

2.3 Multiple RF Sources Exposure .....11

2.4 MPE Calculation Method .....12

2.5 Calculated Result and Limit.....13

**Photographs of EUT V01**





### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
None

Reviewed by: Ben Tseng

Report Producer: Amber Chiu



# 1 General Description

## 1.1 Information

### 1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)

### 1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector
1	Technicolor	2G1 - PerpTall	Murphy	N/A
2	Technicolor	2G2 - Dumbo2	Murphy	N/A
3	Technicolor	2G3 - PerpFold	Murphy	N/A
4	Technicolor	5G1 - Para2	Murphy	N/A
5	Technicolor	5G2 - Perp2	Murphy	N/A
6	Technicolor	5G3 - Para2	Murphy	N/A
7	Technicolor	5G4 - Perp2	Murphy	N/A



Ant.	Port	Gain (dBi)				
		2.4G	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
1	1	3.61	-	-	-	-
2	2	4.70	-	-	-	-
3	3	2.81	-	-	-	-
4	1	-	2.52	2.34	2.20	2.37
5	2	-	2.87	2.38	2.89	2.43
6	3	-	2.08	2.58	2.44	2.26
7	4	-	2.14	2.75	2.13	2.10

Composite Gain (dBi)				
2.4G	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
4.49	3.77	3.36	5.16	3.85

Note 1: The EUT has seven antennas.

**For 2.4GHz function:**

For IEEE 802.11 b/g/n/VHT/ax mode (3TX/3RX)

Ant. 1 (port 1) ~ Ant. 3 (port 3) could transmit/receive simultaneously.

**For 5GHz function:**

For IEEE 802.11 a/n/ac/ax mode (4TX/4RX)

Ant. 4 (port 1) ~ Ant. 7 (port 4) could transmit/receive simultaneously.

**1.1.3 Table for Multiple Listing**

The brand/model names in the following table are all refer to the identical product.

Brand Name	Model Name	Description
Technicolor	CGA437ATCH5	All the models are identical, the difference model served as marketing strategy.
Technicolor	CGA437AXXXXX (where X can be alphanumeric, -, or blank)	

**1.1.4 Table for Permissive Change**

This product is an extension of original one reported under Sporton project number: FA232914-01. Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
(1) 5G FEM chip: Brand:Richwave/Model:RTC7676D→ Brand:Skyworks/Model:SKY85755-11 (2) LAN: 3x1Gb+1x2.5Gb(Brand:TNK/Model:QT24A1 55→4x1Gb(Brand:TNK/Model:QT48A17) (3) adding Reset IC	1. Exposure evaluation was evaluated 2. Photographs of EUT.

**1.1.5 Accessories**

Accessories				
	Brand Name	SHENZHEN HONOR	Model Name	ADS-36FKJ-12 12036EPCU
AC Adapter	Power Rating	I/P: 100 - 240Vac, 1.0 A, O/P: 12 Vdc, 3.0A		
	Power Cord	1.5 meter, non-shielded cable, w/o ferrite core		

Reminder: Regarding to more detail and other information, please refer to user manual.

## 1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

## 1.3 Testing Location

<b>Test Lab. : Sporton International Inc. Hsinhua Laboratory</b>		
<input checked="" type="checkbox"/>	Hsinhua (TAF: 3785)	<b>ADD:</b> No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.) <b>TEL:</b> 886-3-327-3456 <b>FAX:</b> 886-3-327-0973
Test site Designation No. TW3785 with FCC.		
<input type="checkbox"/>	Wen 33rd.St. (TAF: 3785)	<b>ADD:</b> No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) <b>TEL:</b> 886-3-318-0787 <b>FAX:</b> 886-3-318-0287
Test site Designation No. TW0008 with FCC.		



## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

#### Multiple Transmitters Condition

Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.

Co-transmitting mode: WLAN 2.4GHz+WLAN 5GHz

## 2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x & \rightarrow d \leq 20cm \\ ERP_{20cm} & \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left( \frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040 f (mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060 (mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920 R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450 R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128 R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ <p>f is in MHz; R is in m; <math>R &gt; \lambda / 2\pi</math></p>

### 2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	<p>The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)</p>
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ <p>a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added.</p> <p>b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.</p> <p>c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.</p> <p>P<sub>i</sub> = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).</p> <p>P<sub>th,i</sub> = the exemption threshold power ( P<sub>th</sub> ) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.</p> <p>ERP<sub>j</sub> = the ERP of fixed, mobile, or portable RF source j.</p> <p>ERP<sub>th,j</sub> = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.</p> <p>Evaluated<sub>k</sub> = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.</p> <p>Evaluated Limit<sub>k</sub> = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.</p>



## 2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

## 2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

WLAN 2.4G Function:

<Non-Beamforming>

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	4.70	24.80	29.50	0.50	609.69	20	0.19894	1.00000	B	3060	0.1992
2.4G;D1D	4.70	29.18	33.88	0.50	1,671.51	20	0.54542	1.00000	B	3060	0.5462

<Beamforming>

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.49	23.31	27.80	0.50	412.20	20	0.13450	1.00000	B	3060	0.1347

WLAN 5G Function:

<Non-Beamforming>

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	2.87	27.13	30.00	0.50	684.08	20	0.22322	1.00000	B	3060	0.2236
5.3G;D1D	2.75	23.90	26.65	0.50	316.31	20	0.10321	1.00000	B	3060	0.1034
5.6G;D1D	2.89	23.87	26.76	0.50	324.42	20	0.10586	1.00000	B	3060	0.1060
5.8G;D1D	2.43	20.78	23.21	0.50	143.26	20	0.04674	1.00000	B	3060	0.0468

<Beamforming>

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	3.77	27.15	30.92	0.50	845.49	20	0.27589	1.00000	B	3060	0.2763
5.3G;D1D	3.36	23.82	27.18	0.50	357.36	20	0.11661	1.00000	B	3060	0.1168
5.6G;D1D	5.16	23.89	29.05	0.50	549.68	20	0.17936	1.00000	B	3060	0.1796
5.8G;D1D	3.85	23.07	26.92	0.50	336.60	20	0.10983	1.00000	B	3060	0.1100

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)



Simultaneous Transmission Analysis Mode: WLAN 2.4GHz+WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	4.70	29.18	33.88	0.50	32.23	20	0.33245	1.00000	B	3060	0.5462
5.2G;D1D	3.77	27.15	30.92	0.50	845.49	20	0.27589	1.00000	B	3060	0.2763
										Sum Ratio	0.8225
										Ratio Limit	1

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

Option	Sum TL Ratio_B	Option	Sum TL Ratio_C	Option	Sum TL Ratio_E
B	$\sum_{i=1}^a \frac{P_i}{P_{th,i}}$	C	$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$	E	$\sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k}$

Note: The above antenna gain was declared by manufacturer.

—————THE END—————