



**L C I E**

Bluetooth Low Energy Template: Release August 20th, 2016

# TEST REPORT

N°: 144014-691281-A

Version : 02

## Subject

**Radio spectrum matters  
tests according to standards:  
47 CFR Part 15.247 & RSS-247 Issue 1 & RSS-Gen Issue 4**

## Issued to

**Technicolor**  
975, Avenue des Champs Blancs CS17616  
35576 – Cesson-Sévigné Cedex  
France

## FCC/IC registered contact

5030 Sugarloaf Parkway Building 6  
30044 - Lawrenceville  
United States

## Apparatus under test

Product **OTT STB**  
Trade mark **AirTV Player**  
Manufacturer **Technicolor (project ECHOSTAR)**  
Model under test **UIW4010ECH**  
Serial number **N°002**  
FCC ID **G95-UIW4010ECH**  
IC ID **431C-UIW4010ECH**

## Test date

: August 31, 2016 to October 14, 2016

## Test location

Fontenay Aux Roses & Ecuelles

## Composition of document

36 pages

## Document issued on

October 19, 2016

**Written by :**  
Arnaud FAYETTE  
**Tests operator**



This document shall not be reproduced, except in full, without the written approval of the LCIE. This document contains results related only to the items tested. It does not imply the conformity of the whole production to the items tested. Unless otherwise specified, the decision of conformity takes into account the uncertainty of measurement. This document doesn't anticipate any certification decision.

**LCIE**

Laboratoire Central des Industries Electriques  
Une société de Bureau Veritas

33, Av du Général Leclerc  
92266 Fontenay Aux Roses  
FRANCE

Tél : +33 1 40 95 60 60  
contact@lcie.fr  
www.lcie.fr



## PUBLICATION HISTORY

<b>Version</b>	<b>Date</b>	<b>Author</b>	<b>Modification</b>
01	October 6, 2016	Arnaud FAYETTE	Creation of the document
02	October 19, 2016	Arnaud FAYETTE	Photo suppression & retest 6dB bandwidth measurement



## SUMMARY

1.	TEST PROGRAM .....	4
2.	EQUIPMENT UNDER TEST: CONFIGURATION (DECLARED BY PROVIDER) .....	5
3.	OCCUPIED BANDWIDTH .....	7
4.	6DB EMISSION BANDWIDTH .....	9
5.	DUTY CYCLE .....	11
6.	MAXIMUM CONDUCTED OUTPUT POWER .....	13
7.	POWER SPECTRAL DENSITY .....	15
8.	UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS AT THE BAND EDGE	17
9.	UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS.....	19
10.	AC POWER LINE CONDUCTED EMISSIONS.....	22
11.	UNWANTED EMISSIONS IN RESTRICTED FREQUENCY BANDS .....	26
12.	UNCERTAINTIES CHART .....	36

## 1. TEST PROGRAM

### References

- 47 CFR Part 15.247
- RSS 247 Issue 1
- RSS Gen Issue 4
- KDB 558074 D01 DTS Meas Guidance v03r05
- ANSI C63.10-2013

### Radio requirement:

Clause (47CFR Part 15.407 & RSS-247 Issue 1 & RSS-Gen Issue 4) Test Description	Test result - Comments			
Occupied Bandwidth <a href="#">Pb</a>	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
6dB Bandwidth <a href="#">Pb</a>	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA()	<input type="checkbox"/> NP(1)
Duty Cycle <a href="#">Pb</a>	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Maximum Conducted Output Power <a href="#">Pb</a>	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Power Spectral Density <a href="#">Pb</a>	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Conducted Spurious Emission at the Band Edge <a href="#">Pb</a>	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA()	<input type="checkbox"/> NP(1)
Unwanted Emissions into Non-Restricted Frequency Bands <a href="#">Pb</a>	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA()	<input type="checkbox"/> NP(1)
AC Power Line Conducted Emission <a href="#">Pb</a>	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA(2)	<input type="checkbox"/> NP(1)
Unwanted Emissions into Restricted Frequency Bands <a href="#">Pb</a>	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Receiver Radiated emissions <a href="#">Pb</a>	<input checked="" type="checkbox"/> PASS (3)	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
This table is a summary of test report, see conclusion of each clause of this test report for detail.				

(1): Limited program

(2): EUT not directly or indirectly connected to the AC Power Public Network

(3): Include in unwanted emission into non restricted frequency band

PASS: EUT complies with standard's requirement

FAIL: EUT does not comply with standard's requirement

NA: Not Applicable

NP: Test Not Performed



## 2. EQUIPMENT UNDER TEST: CONFIGURATION (DECLARED BY PROVIDER)

### 2.1. HARDWARE IDENTIFICATION (EUT AND AUXILIARIES):

#### Equipment under test (EUT):

AirTV Player UIW4010ECH

Serial Number: N°002

#### Inputs/outputs - Cable:

Access	Type	Length used (m)	Declared <3m	Shielded	Under test	Comments
1	Power Supply	-	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	-
2	HDMI	1,8	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	-

#### Auxiliary equipment used during test:

Type	Reference	Sn	Comments
Laptop	LCIE	-	Use to set the EUT

#### Equipment information:

Bluetooth LE Type:	<input checked="" type="checkbox"/> BLE	<input type="checkbox"/> v4.0	<input checked="" type="checkbox"/> v4.1	<input type="checkbox"/> v4.2
Frequency band:	[2400 – 2483.5] MHz			
Number of Channel:	40			
Spacing channel:	2MHz			
Channel bandwidth:	1MHz			
Antenna Type:	<input checked="" type="checkbox"/> Integral	<input type="checkbox"/> External	<input type="checkbox"/> Dedicated	
Antenna connector:	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> Temporary for test	
Transmit chains:	1			
	Single antenna			
Receiver chains:	1			
Type of equipment:	<input checked="" type="checkbox"/> Stand-alone	<input type="checkbox"/> Plug-in	<input type="checkbox"/> Combined	
Ad-Hoc mode:	<input checked="" type="checkbox"/> Yes		<input type="checkbox"/> No	
Duty cycle:	<input checked="" type="checkbox"/> Continuous duty	<input type="checkbox"/> Intermittent duty	<input type="checkbox"/> 100% duty	
Equipment type:	<input checked="" type="checkbox"/> Production model		<input type="checkbox"/> Pre-production model	
Operating temperature range:	Tmin:	<input type="checkbox"/> -20°C	<input checked="" type="checkbox"/> 0°C	<input type="checkbox"/> X°C
	Tnom:	20°C		
	Tmax:	<input type="checkbox"/> 35°C	<input type="checkbox"/> 55°C	<input checked="" type="checkbox"/> 40°C
Type of power source:	<input checked="" type="checkbox"/> AC power supply	<input type="checkbox"/> DC power supply	<input type="checkbox"/> Battery	
Operating voltage range:	Vnom:	<input checked="" type="checkbox"/> 120V/60Hz	<input type="checkbox"/> X Vdc	

#### Antenna Characteristic

Antenna assembly	Gain (dBi)	Frequency Band (MHz)	Impedance(Ω)
1	5,4	2400-2483.5	50



L C I E

### CHANNEL PLAN

Channel	Frequency (MHz)	Channel	Frequency (MHz)
<b>Cmin: 0</b>	2402	<b>Cmid: 20</b>	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	<b>Cmax: 39</b>	2480

### DATA RATE

Data Rate (Mbps)	Modulation Type	Worst Case Modulation
1	GFSK	<input checked="" type="checkbox"/>

## 2.2. RUNNING MODE

The EUT is set in the following modes during tests:

- Permanent emission with modulation on a fixed channel in the data rate that produced the highest power
- Permanent reception

The product is capable of simultaneous emission in WIFI (2.4GHz or 5GHz) and Bluetooth (EDR or LE).

Following commands with the specific test software "DutApiMimoBtFmBridgeEt" are used to set the product:

- See document "UIW4010ECH\_BT control\_V03.docx" for the command used during test

## 2.3. EQUIPMENT MODIFICATION

None       Modification:



### 3. OCCUPIED BANDWIDTH

#### 3.1. TEST CONDITIONS

Test performed by : Arnaud FAYETTE  
Date of test : September 5, 2016  
Ambient temperature : 23 °C  
Relative humidity : 45 %

#### 3.2. TEST SETUP

- The Equipment Under Test is installed:

- On a table  
 In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method  
 Radiated Method

- Test Procedure:

- RSS-Gen Issue 4 § 6.6  
 ANSI C63.10 § 6.9.2

#### 3.1. LIMIT

None

#### 3.2. TEST EQUIPMENT LIST



DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Calibration date	Calibration due
Multi-meter	KEITHLEY	2000	A1242090	2016/05	2018/05
Programmable AC/DC power supply	-; KIKUSUI	PCR500M	A7049006	Verified with calibrated multimeter	Verified with calibrated multimeter
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2015/03	2016/10
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2015/10	2016/10

Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E

### 3.3. RESULTS



Channel	Occupied Bandwidth (MHz)
Cmin	1,020
Cnom	1,019
Cmax	1,019

### 3.1. CONCLUSION

Occupied Channel Bandwidth measurement performed on the sample of the product **AirTV Player UIW4010ECH**, SN: **N°002**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS-GEN ISSUE 4** limits.





## 4. 6dB EMISSION BANDWIDTH

### 4.1. TEST CONDITIONS

Test performed by : Arnaud FAYETTE  
Date of test : October 14, 2016  
Ambient temperature : 23 °C  
Relative humidity : 44 %

### 4.2. TEST SETUP

- The Equipment Under Test is installed:

- On a table  
 In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method  
 Radiated Method

- Test Procedure:

- KDB 558074 D01 DTS Meas Guidance v03r05 § 8.1  
 KDB 558074 D01 DTS Meas Guidance v03r05 § 8.2

### 4.3. LIMIT



The 6dB bandwidth shall be at least 500kHz

### 4.4. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Calibration date	Calibration due
Multi-meter	KEITHLEY	2000	A1242090	2016/05	2018/05
Programmable AC/DC power supply	-; KIKUSUI	PCR500M	A7049006	Verified with calibrated multimeter	Verified with calibrated multimeter
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2015/03	2016/10
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2015/10	2016/10

Note: In our quality system, the test equipment calibration due is more & less 2 months

#### 4.5. RESULTS



Channel	6dB Emission Bandwidth (MHz)
Cmin	0,665
Cnom	0,665
Cmax	0,665

#### 4.6. CONCLUSION

6dB Emission Bandwidth measurement performed on the sample of the product **AirTV Player UIW4010ECH**, SN: **N°002**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 1** limits.



## 5. DUTY CYCLE

### 5.1. TEST CONDITIONS

Test performed by : Arnaud FAYETTE  
Date of test : September 5, 2016  
Ambient temperature : 24 °C  
Relative humidity : 43 %

### 5.2. TEST SETUP

- The Equipment Under Test is installed:

- On a table  
 In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method  
 Radiated Method

- Test Procedure:

- KDB 558074 D01 DTS Meas Guidance v03r05 § 6.0 b)

### 5.3. LIMIT


None

### 5.4. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Calibration date	Calibration due
Multi-meter	KEITHLEY	2000	A1242090	2016/05	2018/05
Programmable AC/DC power supply	-; KIKUSUI	PCR500M	A7049006	Verified with calibrated multimeter	Verified with calibrated multimeter
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2015/03	2016/10
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2015/10	2016/10

Note: In our quality system, the test equipment calibration due is more & less 2 months

## 5.5. RESULTS



## 5.6. CONCLUSION

Duty Cycle measurement performed on the sample of the product **AirTV Player UIW4010ECH**, SN: **N°002**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 1** limits.



## 6. MAXIMUM CONDUCTED OUTPUT POWER

### 6.1. TEST CONDITIONS

Test performed by : Arnaud FAYETTE  
Date of test : August 31, 2016  
Ambient temperature : 24 °C  
Relative humidity : 45 %

### 6.2. TEST SETUP

- The Equipment Under Test is installed:

- On a table  
 In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method  
 Radiated Method

- Test Procedure:

- KDB 558074 D01 DTS Meas Guidance v03r05 § 9.1.1 (RBW $\geq$ DTS bandwidth)  
 KDB 558074 D01 DTS Meas Guidance v03r05 § 9.2.2.2 (Method AVGSA-1)  
 KDB 558074 D01 DTS Meas Guidance v03r05 § 9.2.2.4 (Method AVGSA-2)

### 6.3. LIMIT

Maximum Conducted Output power:

2400MHz-2483.5MHz: Shall not exceed 30dBm

Limits are reduced by G-6dBi if Overall Antenna Gain above 6dBi

### 6.4. TEST EQUIPMENT LIST


DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Calibration date	Calibration due
Multi-meter	KEITHLEY	2000	A1242090	2016/05	2018/05
Programmable AC/DC power supply	-; KIKUSUI	PCR500M	A7049006	Verified with calibrated multimeter	Verified with calibrated multimeter
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2015/03	2016/10
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2015/10	2016/10

Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E

## 6.5. RESULTS



## 6.6. CONCLUSION

Maximum Conducted Output Power measurement performed on the sample of the product **AirTV Player UIW4010ECH**, SN: **N°002**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 1** limits.



## 7. POWER SPECTRAL DENSITY

### 7.1. TEST CONDITIONS

Test performed by : Arnaud FAYETTE  
Date of test : August 31, 2016  
Ambient temperature : 23 °C  
Relative humidity : 45 %

### 7.2. TEST SETUP

- The Equipment Under Test is installed:

- On a table  
 In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method  
 Radiated Method

- Test Procedure:

- KDB 558074 D01 DTS Meas Guidance v03r05 § 10.2 (Method PKPSD)  
 KDB 558074 D01 DTS Meas Guidance v03r05 § 10.3 (Method AVGPSD-1)

### 7.3. LIMIT

Power Spectral Density:

2400MHz-2483.5MHz: Shall not exceed 8dBm/3kHz

Limits are reduced by G-6dBi if Overall Antenna Gain above 6dBi

### 7.4. TEST EQUIPMENT LIST



DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Calibration date	Calibration due
Multi-meter	KEITHLEY	2000	A1242090	2016/05	2018/05
Programmable AC/DC power supply	-; KIKUSUI	PCR500M	A7049006	Verified with calibrated multimeter	Verified with calibrated multimeter
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2015/03	2016/10
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2015/10	2016/10

Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E

## 7.5. RESULTS



Channel	Offset Cable + Att (dB)	Antenna Gain (dBi)	Power Spectral Density (dBm/3kHz)	Limit ((dBm/3kHz)
Cmin	21,4	5,4	-11,91	8
Cnom	21,4	5,4	-12,18	8
Cmax	21,4	5,4	-12,36	8

## 7.6. CONCLUSION

Power Spectral Density measurement performed on the sample of the product **AirTV Player** UIW4010ECH, SN: **N°002**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 1** limits.





## 8. UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS AT THE BAND EDGE

### 8.1. TEST CONDITIONS

Test performed by : Arnaud FAYETTE  
Date of test : October 3, 2016  
Ambient temperature : 23 °C  
Relative humidity : 41 %

### 8.2. TEST SETUP

- The Equipment Under Test is installed:

- On a table  
 In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method  
 Radiated Method

- Test Procedure:

- KDB 558074 D01 DTS Meas Guidance v03r05 § 11

### 8.3. LIMIT

All Spurious Emissions must be at least Choose limit below the Fundamental Radiator Level at the Band Edge Edge  
"2400MHz & 2483,5MHz"

### 8.4. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Calibration date	Calibration due
Multi-meter	KEITHLEY	2000	A1242090	2016/05	2018/05
Programmable AC/DC power supply	-; KIKUSUI	PCR500M	A7049006	Verified with calibrated multimeter	Verified with calibrated multimeter
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2015/03	2016/10
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2015/10	2016/10


Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E

## 8.5. RESULTS

### Unwanted Emission into non-restricted frequency bands at the band edge Cmin/Cnom/Cmax



Conducted Spurious Emission at the Band Edge (MHz)	2400	2483,5
Spurious Level (dBc)	-45,07	-51,26

## 8.6. CONCLUSION

Unwanted Emission into non-restricted frequency bands at the band edge measurement performed on the sample of the product **AirTV Player UIW4010ECH**, SN: **N°002**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 1** limits.



## 9. UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS

### 9.1. TEST CONDITIONS

Test performed by : Arnaud FAYETTE  
Date of test : August 31, 2016  
Ambient temperature : 24 °C  
Relative humidity : 35 %

### 9.2. TEST SETUP

- The Equipment Under Test is installed:

- On a table  
 In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method  
 Radiated Method

- Test Procedure:

- KDB 558074 D01 DTS Meas Guidance v03r05 § 11

### 9.3. LIMIT


All Spurious Emissions must be at least Choose limit below the Fundamental Radiator Level

### 9.4. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Calibration date	Calibration due
Multi-meter	KEITHLEY	2000	A1242090	2017/06	2017/06
Programmable AC/DC power supply	-; KIKUSUI	PCR500M	A7040079	-	-
EMI receiver	ROHDE & SCHWARZ	ESI40 1088 740K40	A2642010	2016/07	2017/07
Cable	sans; ATEM	SMA 0.5m	A5329645	2015/08	2016/08
Rejector filter 2,4GHz	-	2.45GHz	A7484048	2015/12	2016/12

Note: In our quality system, the test equipment calibration due is more & less 2 months

## 9.5. RESULTS





Frequency (MHz)	Spurious Level (dBm)	Spurious Level (dBc)
2242	-58,94	63,11
2282	-58,06	62,51
2320	-57,93	62,51
2562	-58,70	62,87
2602	-58,69	63,14
2640	-57,45	62,03
4804	-54,74	58,91
4883	-52,46	56,91
4959	-57,03	61,61

## 9.6. CONCLUSION

Unwanted Emission into non-restricted frequency bands measurement performed on the sample of the product **AirTV Player** UIW4010ECH, SN: **N°002**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 1** limits.

## 10. AC POWER LINE CONDUCTED EMISSIONS

### 10.1. TEST CONDITIONS

Test performed by : Laurent DENEUX  
 Date of test : September 19, 2016  
 Ambient temperature : 20°C  
 Relative humidity : 47%

### 10.2. TEST SETUP

The product has been tested according to ANSI C63.10 (2013) method. The EUT is placed on the ground reference plane, at 80cm from the LISN. The distance between the EUT and the vertical ground plane is 40cm. Auxiliaries are powered by another LISN. The cable has been shorted to 1meter length. The EUT is powered through the LISN. Measurement is made with a receiver in peak mode. This was followed by a Quasi-Peak, i.e. CISPR measurement for any strong signal. If the average limit is met when using a Quasi-Peak detector, the EUT shall be deemed to meet both limits and measurement with the average detector is unnecessary. The LISN (measure) is 50Ω / 50μH. Interconnecting cables and equipment's were moved to position that maximized emission.

### 10.3. LIMIT

#### Quasi-Peak

0,15kHz to 0,5MHz: 66dBμV to 56dBμV\*

0,5MHz to 5MHz: 56dBμV

5MHz to 30MHz: 60dBμV

#### Average

0,15kHz to 0,5MHz: 56dBμV to 46dBμV\*

0,5MHz to 5MHz: 46dBμV

5MHz to 30MHz: 50dBμV

\*Decreases with the logarithm of the frequency

### 10.4. TEST EQUIPMENT LIST

Test Equipment Used					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
EMI Test Receiver	ROHDE & SCHWARZ	ESR	101403	2016-06	2017-06
V ISLN	ROHDE & SCHWARZ	ESH2-Z5	C2322001	2016-05	2017-05
Pulse limiter	ROHDE & SCHWARZ	ESH3-Z2	A2649008	2016-03	2017-03
Cable	-	-	A5329417	2015-10	2016-10
Ground plane	LCIE	-	-	-	

Note: In our quality system, the test equipment calibration due is more & less 2 months



## 10.5. DIVERGENCE, ADDITION OR SUPPRESSION ON THE TEST SPECIFICATION


None       Divergence:




L C I E

## 10.6. RESULTS

### Channel Phase



### Neutral







Phase Line					
Frequency (MHz)	Peak Level (dB $\mu$ V)	Quasi-Peak Level (dB $\mu$ V)	Quasi-Peak Limit (dB $\mu$ V)	Average Level (dB $\mu$ V)	Average Limit (dB $\mu$ V)
0.162	44.2	-	65.3	30	55.3
0.342	42.6	-	58.9	35	48.9
0.672	26.5	-	56	21	46
7.856	24	-	60	17	50
23.13	23	-	60	19	50

Neutral Line					
Frequency (MHz)	Peak Level (dB $\mu$ V)	Quasi-Peak Level (dB $\mu$ V)	Quasi-Peak Limit (dB $\mu$ V)	Average Level (dB $\mu$ V)	Average Limit (dB $\mu$ V)
0.162	44.5	-	65.3	27.8	55.3
0.343	41.2	-	58.9	34.6	48.9
0.673	29	-	56	23	46
7.338	25.8	-	60	16	50
23.13	23	-	60	17	50

## 10.7. CONCLUSION

Ac Power Line Conducted Emission measurement performed on the sample of the product **AirTV Player UIW4010ECH**, SN: **N°002**, in configuration and description presented in this test report, show levels **compliant** to the 47 CFR PART 15.407 & RSS 247 ISSUE 1 limits.



## 11. UNWANTED EMISSIONS IN RESTRICTED FREQUENCY BANDS

### 11.1. TEST CONDITIONS

Test performed by : Laurent DENEUX  
 Date of test : September 19, 2016 to September 20, 2016  
 Ambient temperature : 22°C  
 Relative humidity : 51%

### 11.2. TEST SETUP

The product has been tested according to ANSI C63.10 (2013). The EUT is placed **on an open area test site**. Distance between measuring antenna and the EUT is **10m**. Test is performed in horizontal (H) and vertical (V) polarization with **bilog** antenna below 1GHz and with a horn antenna above 1GHz. Measurement bandwidth was 120kHz below 1GHz and 1MHz above 1GHz. The level has been maximised by the turntable rotation of 360 degrees range on the 3 axis of EUT. Antenna height search was performed from 1 to 4m. The EUT is placed at 1.5m high above 1GHz and at 0.8m high under 1GHz.

### 11.3. LIMIT

#### Limit at 10m:

30MHz to 88MHz: 29.5dB $\mu$ V/m QPeak  
 88MHz to 216MHz: 33dB $\mu$ V/m QPeak  
 216MHz to 960MHz: 35.5dB $\mu$ V/m QPeak  
 960MHz to 1000MHz: 43.5dB $\mu$ V/m QPeak  
 Above 1000MHz: 63.5B $\mu$ V/m Peak  
 43.5B $\mu$ V/m Average

### 11.4. TEST EQUIPMENT LIST

Test Equipment Used					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
EMI Test Receiver	ROHDE & SCHWARZ	ESR	101403	2016-06	2017-06
Open test site	LCIE	-	F2000400	2016-05	2017-05
Preamplifier	HEWLETT PACKARD	8449B	A4069002	2016-01	2017-01
Bilog antenna	CHASE	CBL 6112A	C2040040	2016-01	2017-01
Horn antenna	AH SYSTEMS	SAS-572	C2042026	2016-04	2018-04
Horn antenna	EMCO	.3115	C2042016	2016-02	2017-02
Cable	-	-	A5329542	2016-02	2017-02
Cable	-	-	A5329449	2015-11	2016-11
Cable	-	-	A5329368	2015-11	2016-11
cable	-	-	A5329444	2015-11	2016-11

Note: In our quality system, the test equipment calibration due is more & less 2 months



### 11.5. DIVERGENCE, ADDITION OR SUPPRESSION ON THE TEST SPECIFICATION

None       Divergence:


## 11.6. RESULTS

Below 1GHz

Cnom

Vertical & horizontal Polarization

— FCC Part 15 (Intentional radiator) §209 - Classe - - OCrite/10.0m/  
 — Mes. Q-Peak (Verticale)  
 — Mes. Q-Peak (Horizontale)  
 — Finaux Manuel (Verticale)  
 — Finaux Manuel (Horizontale)






L C I E


Above 1GHz

Cmin

Vertical Polarization



Horizontal polarization






L C I E


### Above 1GHz

Cnom

### Vertical Polarization



### Horizontal polarization






L C I E


### Above 1GHz

### Cmax

### Vertical Polarization



### Horizontal polarization





L C I E

Below 1GHz			
Polarization	Frequency (MHz)	QPeak Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
Vertical	30.6	21.8	29.5
Vertical	33.5	20.49	29.5
Vertical	38.2	19.73	29.5
Vertical	41.6	20.43	29.5
Vertical	43.5	21.24	29.5
Vertical	47.8	23.09	29.5
Vertical	49.8	23.66	29.5
Vertical	51.8	23.29	29.5
Vertical	53.6	20.82	29.5
Vertical	55.3	20.52	29.5
Vertical	63.6	20.23	29.5
Vertical	103.4	16.33	33
Vertical	107.3	20.96	33
Vertical	108.8	26.38	33
Vertical	110.3	23.69	33
Vertical	111.6	25.89	33
Vertical	114.2	21.19	33
Vertical	117.1	20.65	33
Vertical	125	26.06	33
Vertical	150	24.01	33
Vertical	159.1	18.99	33
Vertical	168	19.45	33
Vertical	179.3	19.87	33
Vertical	185	23.53	33
Vertical	194	18.81	33
Vertical	206.9	18.94	33
Vertical	215.4	20.33	33
Vertical	224.6	19.53	35.5
Vertical	250	23.04	35.5
Vertical	297	24.36	35.5
Vertical	375	26.92	35.5
Vertical	398.3	29.42	35.5
Vertical	500	30.4	35.5
Vertical	800	29.74	35.5
Vertical	891.1	25.82	35.5





L C I E

Below 1GHz			
Polarization	Frequency (MHz)	QPeak Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
Horizontal	108.8	19.57	33
Horizontal	113.9	19.59	33
Horizontal	116.3	21.5	33
Horizontal	125	18.15	33
Horizontal	250	28.82	35.5
Horizontal	375	26.21	35.5
Horizontal	398.4	21.98	35.5



L C I E

Above 1GHz						
Cmin						
Polarization	Frequency (MHz)	Average Level (dBµV/m)	Average Level + Duty Cycle (dBµV/m)	Average Limit (dBµV/m)	Peak Level (dBµV/m)	Peak Limit (dBµV/m)
Vertical	1023,7	28,74	30,84	43.5	35.92	63.5
Vertical	1103,5	30,51	32,61	43.5	34.78	63.5
Vertical	1125	30,08	32,18	43.5	34.46	63.5
Vertical	1200	26,11	28,21	43.5	34.53	63.5
Vertical	1250	26,37	28,47	43.5	30.41	63.5
Vertical	1397	31,85	33,95	43.5	41.21	63.5
Vertical	1548,7	28,51	30,61	43.5	37.98	63.5
Vertical	2390	27,6	29,7	43.5	38.1	63.5
Vertical	2483,5	27,8	29,9	43.5	38.4	63.5
Horizontal	1000,4	27,31	29,41	43.5	36.14	63.5
Horizontal	1199,8	29,54	31,64	43.5	36.56	63.5
Horizontal	1400,1	30,82	32,92	43.5	39.64	63.5
Horizontal	1549,2	29,52	31,62	43.5	37.29	63.5
Horizontal	1992,2	24,4	26,5	43.5	30.96	63.5
Horizontal	2390	24	26,1	43.5	35.2	63.5
Horizontal	2483,5	34,5	36,6	43.5	36.4	63.5

Above 1GHz						
Cnom						
Polarization	Frequency (MHz)	Average Level (dBµV/m)	Average Level + Duty Cycle (dBµV/m)	Average Limit (dBµV/m)	Peak Level (dBµV/m)	Peak Limit (dBµV/m)
Vertical	1023,7	28,74	30,84	43.5	35.92	63.5
Vertical	1103,5	30,51	32,61	43.5	34.78	63.5
Vertical	1125	30,08	32,18	43.5	34.46	63.5
Vertical	1200	26,11	28,21	43.5	34.53	63.5
Vertical	1250	26,37	28,47	43.5	30.41	63.5
Vertical	1397	31,85	33,95	43.5	41.21	63.5
Vertical	1548,7	28,51	30,61	43.5	37.98	63.5
Vertical	2390	27,2	29,3	43.5	38.6	63.5
Vertical	2483,5	27,6	29,7	43.5	38.3	63.5
Horizontal	1000,4	27,31	29,41	43.5	36.14	63.5
Horizontal	1199,8	29,54	31,64	43.5	36.56	63.5
Horizontal	1400,1	30,82	32,92	43.5	39.64	63.5
Horizontal	1549,2	29,52	31,62	43.5	37.29	63.5
Horizontal	1992,2	24,4	26,5	43.5	30.96	63.5
Horizontal	2390	23,5	25,6	43.5	34.5	63.5
Horizontal	2483,5	24,8	26,9	43.5	35.8	63.5



L C I E

Above 1GHz						
Cmax						
Polarization	Frequency (MHz)	Average Level (dBµV/m)	Average Level + Duty Cycle (dBµV/m)	Average Limit (dBµV/m)	Peak Level (dBµV/m)	Peak Limit (dBµV/m)
Vertical	1023,7	28,74	30,84	43.5	35.92	63.5
Vertical	1103,5	30,51	32,61	43.5	34.78	63.5
Vertical	1125	30,08	32,18	43.5	34.46	63.5
Vertical	1200	26,11	28,21	43.5	34.53	63.5
Vertical	1250	26,37	28,47	43.5	30.41	63.5
Vertical	1397	31,85	33,95	43.5	41.21	63.5
Vertical	1548,7	28,51	30,61	43.5	37.98	63.5
Vertical	2390	27,6	29,7	43.5	37.6	63.5
Vertical	2483,5	28	30,1	43.5	39.2	63.5
Horizontal	1000,4	27,31	29,41	43.5	36.14	63.5
Horizontal	1199,8	29,54	31,64	43.5	36.56	63.5
Horizontal	1400,1	30,82	32,92	43.5	39.64	63.5
Horizontal	1549,2	29,52	31,62	43.5	37.29	63.5
Horizontal	1992,2	24,4	26,5	43.5	30.96	63.5
Horizontal	2390	23,3	25,4	43.5	34.7	63.5
Horizontal	2483,5	25	27,1	43.5	39	63.5

## 11.7. CONCLUSION

Unwanted Emission in restricted frequency bands measurement performed on the sample of the product **AirTV Player UIW4010ECH**, SN: **N°002**, in configuration and description presented in this test report, show levels **compliant** to the 47 CFR PART 15.247 & RSS 247 ISSUE 1 limits.

## 12. UNCERTAINTIES CHART

47 CFR Part 15.209 & 15.207 Kind of test	Wide uncertainty laboratory (k=2) ±x(dB) / (Hz)/ ms	Uncertainty limit
Measurement of conducted disturbances in voltage on the AC power port (9 kHz – 150 kHz)	2,67	3.8
Measurement of conducted disturbances in voltage on the AC power port (150 kHz – 30 MHz)	2,67	3.4
Measurement of conducted disturbances in voltage on the telecommunication port. (AAN)	3,67	5.0
Measurement of conducted disturbances in current (current clamp)	2,73	2.9
Measurement of disturbance power	2,67	4.5
Measurement of radiated magnetic field from 10kHz to 30MHz in SAC V01	4,48	/
Measurement of radiated magnetic field from 10kHz to 30MHz in SAC C01	4,48	/
Measurement of radiated electric field from 30 to 1000MHz in horizontal position on the OATS (Ecuellas)	4,88	6.3
Measurement of radiated electric field from 1 to 18GHz on the Ecuellas site	5.16	/
Measurement of radiated electric field from 30 to 1000MHz in vertical position on the OATS (Ecuellas)	4,99	6.3
Measurement of radiated electric field from 30 to 1000MHz in horizontal position in SAC C01	5,08	6.3
Measurement of radiated electric field from 30 to 1000MHz in vertical position in SAC C01	5,16	6.3
Measurement of radiated electric field from 30 to 1000MHz in horizontal position in SAC V01	5,08	6.3
Measurement of radiated electric field from 30 to 1000MHz in vertical position in SAC V01	5,15	6.3
Measurement of radiated electric field from 1 to 6 GHz C01	5,1	5.2
Measurement of radiated electric field from 1 to 6 GHz V01	4,85	5.2
Measurement of radiated magnetic field from 10kHz to 30MHz on the OATS (Ecuellas)	4,48	/

The uncertainty values calculated by the laboratory are lower than limit uncertainty values defined by the CISPR. The conformity of the sample is directly established by the applicable limits values. This table includes all uncertainties maximum feasible for testing in the laboratory, whether or not made in this report