THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF TECHNICOLOR AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION.

SHT.: 1 of 1 R.K. McNeely

SPECIFICATION, DCI401MCS

echnicolor LABEL PREPRINTED

REVISIONS

This Label may require review by Product Certification and Compliance. Create & Release See Specification, "Component Safety Requirements" 15092970 paragraph 5. 17027280.

Safety Critical

(S)

Label Feed Direction

R.K.M 06/07/12

Note: Arial Narrow 6pt font

Part Number: 17027280

Perf in liner between labels.

SULUSTED SCC II E229301 FCC ID: G95DCI401MCS Rating +5VDC === 1.5A Manufactured under license from Dolby Laboratories. Made in China for Technicolor. **Dimensions: Inches**

- 1) Labels must be suitable for use in a Thermal Printer. Reference Material Fasson 12906. (Contact User Plants for printer models)
- 2) Blank face stock and adhesive to meet the following requirements.
 - A.) Peel Test: 1lb/in Applied @ 180 degree angle.
 - B.) This label must pass environmental durability test spec 1533282% for permanent labels.
 - C.) This label must comply with the test for permanence described in "Marking and Instructions" UI6500.
- 3) Preprinted graphics to be black printing.
- 4) Labels to be supplied on rolls with 3 inch I.D. Core and not to exceed 8 inch O.D.
- 5) Die cut labels to have trim removed.
- 6) Samples to be supplied to Technicolor R&D Department for Approval.
- 7) All parts on this document/drawing must comply with the requirements and procedures specified in the Technicolor green (RoHS) supplier handbook 36033050.