

FCC Test Report

(Co-located)

Report No.: RFCGJR-WTW-P23010147A-1

FCC ID: G95EWM322T

Test Model: EWM322TTCH2

Variant Model: EGM322TTCH2, EWM322Tabcn, EGM322Tabcn
(refer to item 3.1 for more details)

Received Date: 2023/2/13

Test Date: 2023/3/30 ~ 2023/5/15

Issued Date: 2023/7/25

Applicant: Vantiva USA LLC

Address: 4855 Peachtree Industrial Blvd. Suite 200 Norcross, Georgia 30092.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan

**FCC Registration /
Designation Number:** 281270 / TW0032



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty.....	5
2.2 Modification Record	5
3 General Information	6
3.1 General Description of EUT.....	6
3.2 Description of Test Modes.....	11
3.2.1 Test Mode Applicability and Tested Channel Detail.....	17
3.3 Description of Support Units	19
3.3.1 Configuration of System under Test	19
3.4 General Description of Applied Standards.....	20
4 Test Types and Results	21
4.1 Radiated Emission and Bandedge Measurement	21
4.1.1 Limits of Radiated Emission and Bandedge Measurement	21
4.1.2 Test Instruments	25
4.1.3 Test Procedures.....	27
4.1.4 Deviation from Test Standard	28
4.1.5 Test Setup.....	28
4.1.6 EUT Operating Conditions.....	29
4.1.7 Test Results	30
4.2 Conducted Out of Band Emission Measurement	40
4.2.1 Limits of Conducted Out of Band Emission Measurement.....	40
4.2.2 Test Setup.....	40
4.2.3 Test Instruments	40
4.2.4 Test Procedure	40
4.2.5 Deviation from Test Standard	41
4.2.6 EUT Operating Condition	41
4.2.7 Test Results	41
5 Pictures of Test Arrangements	42
Appendix – Information of the Testing Laboratories	43

Release Control Record

Issue No.	Description	Date Issued
RFCGJR-WTW-P23010147A-1	Original Release	2023/7/25

1 Certificate of Conformity

Product: Wireless Access Point

Brand: technicolor

Test Model: EWM322TTCH2

Variant Model: EGM322TTCH2, EWM322Tabcn, EGM322Tabcn
(refer to item 3.1 for more details)

Sample Status: Engineering Sample

Applicant: Vantiva USA LLC

Test Date: 2023/3/30 ~ 2023/5/15

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
47 CFR FCC Part 15, Subpart E (Section 15.407)
ANSI C63.10-2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Vera Huang, **Date:** 2023/7/25
Vera Huang / Specialist

Approved by : Jeremy Lin, **Date:** 2023/7/25
Jeremy Lin / Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247) 47 CFR FCC Part 15, Subpart E (Section 15.407) ANSI C63.10-2013			
FCC Clause	Test Item	Result	Remarks
15.205 / 15.209 / 15.247(d) / 15.407(b)(9) 15.407(b) (1/10) 15.407(b) (4(i)/10) 15.407(b) (6/10)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -0.9 dB at 2483.50 MHz.

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (\pm)
Radiated Emissions up to 1 GHz	9 kHz ~ 30 MHz	3.59 dB
	30 MHz ~ 1 GHz	3.6 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.29 dB
	18 GHz ~ 40 GHz	2.29 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Wireless Access Point	
Brand	technicolor	
Test Model	EWM322TTCH2	
Variant Model	EGM322TTCH2, EWM322Tabcn, EGM322Tabcn	
Model Difference	Refer to Note	
Status of EUT	Engineering Sample	
Power Supply Rating	Refer to Note	
Modulation Type	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in VHT/11ac mode 1024QAM for OFDMA in 11ax HE mode
	BT LE	GFSK
	Zigbee	O-QPSK
Data Rate	WLAN	802.11a: 54/48/36/24/18/12/9/6Mbps 802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to 600 Mbps VHT: up to 800 Mbps (For 2.4G) 802.11ac: up to 3466.7Mbps (For 5G) 802.11ax: up to 1147.1 Mbps (For 2.4G) 802.11ax: up to 4803.9Mbps (For 5G / 6G)
	BT LE	Up to 1 Mbps
	Zigbee	250kb/s
Operating Frequency	WLAN	2412 ~ 2462 MHz 5180 ~ 5250 MHz, 5250 ~ 5320 MHz, 5500 ~ 5720 MHz, 5745 ~ 5825 MHz 5955 ~ 6415MHz, 6435 ~ 6525MHz, 6535 ~ 6865MHz, 6875 ~ 7095MHz
	BT LE	2402 ~ 2480 MHz
	Zigbee	2405 ~ 2480 MHz

Number of Channel	WLAN	<p>2.4G: 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20):11 802.11n (HT40), VHT40, 802.11ax (HE40):7</p> <p>5G: 5180 ~ 5250MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 4 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1 5250 ~ 5320 MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 4 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1 802.11ac (VHT160), 802.11ax (HE160): 1 5500 ~ 5720 MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 12 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 6 802.11ac (VHT80), 802.11ax (HE80): 3 802.11ac (VHT160), 802.11ax (HE160): 1 5745 ~ 5825MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 5 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1</p> <p>6G: 802.11a/ax (HE20): 58 802.11ax (HE40): 29 802.11ax (HE80): 14 802.11ax (HE160): 7</p>
	BT LE	40
	Zigbee	16
	Antenna Type	Refer to Note as below
Antenna Connector	Refer to Note as below	
Accessory Device	Refer to Note as below	
Data Cable Supplied	N/A	

Note:

1. This report is issued as a supplementary report to BV CPS report no. RFCGJR-WTW-P23010147-6. The difference compared with original report is listed as below.
 - Add 5250 ~ 5320 MHz and 5500 ~ 5720 MHz by software
 - Add variant model
2. All models are listed as below. (New added is marked in gray)

Brand	Model	Difference
technicolor	EWM322TTCH2	for marketing purpose
	EGM322TTCH2	
	EWM322Tabcn	
	EGM322Tabcn	

Variable	Range of variable	Content
abc	Each character cab be a-z or A-Z	For marketing purpose only (customer abbreviation)
n	1-4 or blank	For marketing purpose only (sales territory)

3. The EUT uses following accessories.

AC Adapter 1			
Brand	Model	Part Number	Specification
Honor	ADS-42FI-12 12042EPCU-L	6322120A	AC Input : 100-120V, 50/60Hz DC Output : 12V, 3.5A DC Output Cable : 1.8m Plug : US

4. The EUT incorporates a MIMO function.

2.4 GHz Band		
Modulation Mode	TX & RX Configuration	
802.11b	4TX	4TX
802.11g	4TX	4TX
802.11n (HT20)	4TX	4TX
802.11n (HT40)	4TX	4TX
VHT20	4TX	4TX
VHT40	4TX	4TX
802.11ax (HE20)	4TX	4TX
802.11ax (HE40)	4TX	4TX
5 GHz Band		
Modulation Mode	TX & RX Configuration	
802.11a	4TX	4TX
802.11n (HT20)	4TX	4TX
802.11n (HT40)	4TX	4TX
802.11ac (VHT20)	4TX	4TX
802.11ac (VHT40)	4TX	4TX
802.11ac (VHT80)	4TX	4TX
802.11ac (VHT160)	4TX	4TX
802.11ax (HE20)	4TX	4TX
802.11ax (HE40)	4TX	4TX
802.11ax (HE80)	4TX	4TX
802.11ax (HE160)	4TX	4TX
6 GHz Band		
Modulation Mode	TX & RX Configuration	
802.11a	4TX	4TX
802.11ax (HE20)	4TX	4TX
802.11ax (HE40)	4TX	4TX
802.11ax (HE80)	4TX	4TX
802.11ax (HE160)	4TX	4TX

*The EUT not support partial RU.

5. The following antennas were provided to the EUT.

Antenna NO.	RF Chain NO.	Brand	Model	Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type
DB1	2.4G core3	Technicolor	EWM322T/EWA322T	3.92	2.4~2.4835GHz	Dipole	ipex(MHF)
	5G core0	Technicolor	EWM322T/EWA322T	5.61	5.15~5.25GHz	Dipole	ipex(MHF)
				4.91	5.25~5.35GHz	Dipole	ipex(MHF)
				5.45	5.47~5.725GHz	Dipole	ipex(MHF)
				5.47	5.725~5.85GHz	Dipole	ipex(MHF)
DB2	2.4G core2	Technicolor	EWM322T/EWA322T	3.49	2.4~2.4835GHz	Dipole	ipex(MHF)
	5G core1	Technicolor	EWM322T/EWA322T	5.96	5.15~5.25GHz	Dipole	ipex(MHF)
				5.77	5.25~5.35GHz	Dipole	ipex(MHF)
				5.91	5.47~5.725GHz	Dipole	ipex(MHF)
				5.53	5.725~5.85GHz	Dipole	ipex(MHF)
DB3	2.4G core1	Technicolor	EWM322T/EWA322T	4.18	2.4~2.4835GHz	Dipole	ipex(MHF)
	5G core2	Technicolor	EWM322T/EWA322T	4.21	5.15~5.25GHz	Dipole	ipex(MHF)
				4.21	5.25~5.35GHz	Dipole	ipex(MHF)
				4.81	5.47~5.725GHz	Dipole	ipex(MHF)
				4.80	5.725~5.85GHz	Dipole	ipex(MHF)
DB4	2.4G core0	Technicolor	EWM322T/EWA322T	4.52	2.4~2.4835GHz	Dipole	ipex(MHF)
	5G core3	Technicolor	EWM322T/EWA322T	3.96	5.15~5.25GHz	Dipole	ipex(MHF)
				4.18	5.25~5.35GHz	Dipole	ipex(MHF)
				4.06	5.47~5.725GHz	Dipole	ipex(MHF)
				3.86	5.725~5.85GHz	Dipole	ipex(MHF)
6G1	6G core 3	Technicolor	EWM322T/EWA322T	5.83	5.925~6.425GHz	Dipole	ipex(MHF)
				5.31	6.425~6.525GHz	Dipole	ipex(MHF)
				5.17	6.525~6.875GHz	Dipole	ipex(MHF)
				5.48	6.875~7.125GHz	Dipole	ipex(MHF)
6G2	6G core 2	Technicolor	EWM322T/EWA322T	5.38	5.925~6.425GHz	Dipole	ipex(MHF)
				5.38	6.425~6.525GHz	Dipole	ipex(MHF)
				5.64	6.525~6.875GHz	Dipole	ipex(MHF)
				5.51	6.875~7.125GHz	Dipole	ipex(MHF)
6G3	6G core 1	Technicolor	EWM322T/EWA322T	5.68	5.925~6.425GHz	Dipole	ipex(MHF)
				5.56	6.425~6.525GHz	Dipole	ipex(MHF)
				5.76	6.525~6.875GHz	Dipole	ipex(MHF)
				5.76	6.875~7.125GHz	Dipole	ipex(MHF)
6G4	6G core 0	Technicolor	EWM322T/EWA322T	6.27	5.925~6.425GHz	Dipole	ipex(MHF)
				6.27	6.425~6.525GHz	Dipole	ipex(MHF)
				6.16	6.525~6.875GHz	Dipole	ipex(MHF)
				5.79	6.875~7.125GHz	Dipole	ipex(MHF)
BT/Zigbee	-	Technicolor	EWM322T/EWA322T	3.95	2.4~2.4835GHz	PIFA	ipex(MHF)

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

6. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

WLAN 2.4G

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40), VHT40, 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

WLAN 5G

5180 ~ 5250 MHz

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency
42	5210 MHz

5250 ~ 5320 MHz

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
52	5260 MHz	60	5300 MHz
56	5280 MHz	64	5320 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
54	5270 MHz	62	5310 MHz

1 channels are provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency
58	5290 MHz

1 channels are provided for 802.11ac (VHT160), 802.11ax (HE160):

Channel	Frequency
50	5250 MHz

5500 ~ 5720 MHz

12 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
100	5500 MHz	124	5620 MHz
104	5520 MHz	128	5640 MHz
108	5540 MHz	132	5660 MHz
112	5560 MHz	136	5680 MHz
116	5580 MHz	140	5700 MHz
120	5600 MHz	144	5720 MHz

6 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
102	5510 MHz	126	5630 MHz
110	5550 MHz	134	5670 MHz
118	5590 MHz	142	5710 MHz

3 channels are provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency	Channel	Frequency
106	5530 MHz	138	5690 MHz
122	5610 MHz		

1 channels are provided for 802.11ac (VHT160), 802.11ax (HE160):

Channel	Frequency
114	5570 MHz

5745 ~ 5825 MHz

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz		

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
151	5755 MHz	159	5795 MHz

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency
155	5775 MHz

WLAN 6G

U-NII-5

24 channels are provided for 802.11a, 802.11ax (HE20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	5955 MHz	5	5975 MHz	9	5995 MHz	13	6015 MHz
17	6035 MHz	21	6055 MHz	25	6075 MHz	29	6095 MHz
33	6115 MHz	37	6135 MHz	41	6155 MHz	45	6175 MHz
49	6195 MHz	53	6215 MHz	57	6235 MHz	61	6255 MHz
65	6275 MHz	69	6295 MHz	73	6315 MHz	77	6335 MHz
81	6355 MHz	85	6375 MHz	89	6395 MHz	93	6415 MHz

12 channels are provided for 802.11ax (HE40):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
3	5965 MHz	11	6005 MHz	19	6045 MHz	27	6085 MHz
35	6125 MHz	43	6165 MHz	51	6205 MHz	59	6245 MHz
67	6285 MHz	75	6325 MHz	83	6365 MHz	91	6405 MHz

6 channel is provided for 802.11ax (HE80):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
7	5985 MHz	23	6065 MHz	39	6145 MHz	55	6225 MHz
71	6305 MHz	87	6385 MHz				

3 channels are provided for 802.11ax (HE160):

Channel	Frequency	Channel	Frequency	Channel	Frequency
15	6025 MHz	47	6185 MHz	79	6345 MHz

U-NII-6

5 channels are provided for 802.11a, 802.11ax (HE20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
97	6435 MHz	101	6455 MHz	105	6475 MHz	109	6495 MHz
113	6515 MHz						

3 channels are provided for 802.11ax (HE40):

Channel	Frequency	Channel	Frequency	Channel	Frequency
99	6445 MHz	107	6485 MHz	*115	6525 MHz

1 channel are provided for 802.11ax (HE80):

Channel	Frequency
103	6465 MHz

1 channel is provided for 802.11ax (HE160):

Channel	Frequency
*111	6505 MHz

U-NII-7

17 channels are provided for 802.11a, 802.11ax (HE20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
117	6535 MHz	121	6555 MHz	125	6575 MHz	129	6595 MHz
133	6615 MHz	137	6635 MHz	141	6655 MHz	145	6675 MHz
149	6695 MHz	153	6715 MHz	157	6735 MHz	161	6755 MHz
165	6775 MHz	169	6795 MHz	173	6815 MHz	177	6835 MHz
181	6855 MHz						

8 channels are provided for 802.11ax (HE40):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
123	6565 MHz	131	6605 MHz	139	6645 MHz	147	6685 MHz
155	6725 MHz	163	6765 MHz	171	6805 MHz	179	6845 MHz

5 channels are provided for 802.11ax (HE80):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
*119	6545 MHz	135	6625 MHz	151	6705 MHz	167	6785 MHz
*183	6865 MHz						

2 channels are provided for 802.11ax (HE160):

Channel	Frequency	Channel	Frequency
143	6665 MHz	*175	6825 MHz

U-NII-8

12 channels are provided for 802.11a, 802.11ax (HE20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
*185	6875 MHz	189	6895 MHz	193	6915 MHz	197	6935 MHz
201	6955 MHz	205	6975 MHz	209	6995 MHz	213	7015 MHz
217	7035 MHz	221	7055 MHz	225	7075 MHz	229	7095 MHz

6 channels are provided for 802.11ax (HE40):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
*187	6885 MHz	195	6925 MHz	203	6965 MHz	211	7005 MHz
219	7045 MHz	227	7085 MHz				

2 channel is provided for 802.11ax (HE80):

Channel	Frequency	Channel	Frequency
199	6945 MHz	215	7025 MHz

1 channel is provided for 802.11ax (HE160):

Channel	Frequency
207	6985 MHz

Note: * mean this's straddle channel.

BT LE

40 channels are provided for BT-LE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Zigbee

16 channels are provided to this EUT:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
11	2405	15	2425	19	2445	23	2465
12	2410	16	2430	20	2450	24	2470
13	2415	17	2435	21	2455	25	2475
14	2420	18	2440	22	2460	26	2480

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to			Description
	RE \geq 1G	RE<1G	OB	
-	√	√	√	-

Where RE \geq 1G: Radiated Emission above 1GHz & Bandedge Measurement RE<1G: Radiated Emission below 1GHz

OB: Conducted Out-Band Emission Measurement

Note: The EUT is designed to be positioned on the X-plane only.

Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Range	Tested Channel	Modulation
-	802.11b + 802.11ax (HE40) + 802.11ax (HE160) + BT LE	2412~2462 MHz	11 + 142 + 47 + 19	DBPSK
		5180 ~ 5250MHz, 5250 ~ 5320 MHz, 5500 ~ 5720 MHz 5745 ~ 5825MHz		OFDMA
		5955 ~ 6415MHz, 6435 ~ 6525MHz, 6535 ~ 6865MHz, 6875 ~ 7095MHz		OFDMA
		2402 ~ 2480 MHz		GFSK
		2412~2462 MHz		DBPSK
-	802.11b + 802.11ax (HE40) + 802.11ax (HE160) + Zigbee	2412~2462 MHz	11 + 142 + 47 + 11	DBPSK
		5180 ~ 5250MHz, 5250 ~ 5320 MHz, 5500 ~ 5720 MHz 5745 ~ 5825MHz		OFDMA
		5955 ~ 6415MHz, 6435 ~ 6525MHz, 6535 ~ 6865MHz, 6875 ~ 7095MHz		OFDMA
		2405 ~ 2480 MHz		O-QPSK
		2412~2462 MHz		DBPSK

Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Range	Tested Channel	Modulation
-	802.11b + 802.11ax (HE40) + 802.11ax (HE160) + BT LE	2412~2462 MHz	11 + 142 + 47 + 19	DBPSK
		5180 ~ 5250MHz, 5250 ~ 5320 MHz, 5500 ~ 5720 MHz 5745 ~ 5825MHz		OFDMA
		5955 ~ 6415MHz, 6435 ~ 6525MHz, 6535 ~ 6865MHz, 6875 ~ 7095MHz		OFDMA
		2402 ~ 2480 MHz		GFSK
-	802.11b + 802.11ax (HE40) + 802.11ax (HE160) + Zigbee	2412~2462 MHz	11 + 142 + 47 + 11	DBPSK
		5180 ~ 5250MHz, 5250 ~ 5320 MHz, 5500 ~ 5720 MHz 5745 ~ 5825MHz		OFDMA
		5955 ~ 6415MHz, 6435 ~ 6525MHz, 6535 ~ 6865MHz, 6875 ~ 7095MHz		OFDMA
		2405 ~ 2480 MHz		O-QPSK

Conducted Out-Band Emission Measurement:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Range	Tested Channel	Modulation
-	802.11b + 802.11ax (HE40)	2412~2462 MHz	11 + 142	DBPSK
		5180 ~ 5250MHz, 5250 ~ 5320 MHz, 5500 ~ 5720 MHz 5745 ~ 5825MHz		OFDMA

Test Condition:

Applicable to	Environmental Conditions	Input Power (System)	Tested by
RE≥1G	23 deg. C, 67 % RH	120 Vac, 60 Hz	Adair Peng
RE<1G	23 deg. C, 67 % RH	120 Vac, 60 Hz	Adair Peng
OB	23 deg. C, 67 % RH	120 Vac, 60 Hz	Wayne Lin


3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Notebook	DELL	E6420	D3T96R1	N/A	Provided by Lab
B	Load	N/A	N/A	N/A	N/A	Provided by Lab
C	Load	N/A	N/A	N/A	N/A	Provided by Lab
D	FLASH	sandisk	SDDDC3-032G	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	LAN Cable	1	6	N	N	Provided by Lab
2	LAN Cable	1	1.5	N	N	Provided by Lab
3	LAN Cable	1	1.5	N	N	Provided by Lab
4	LAN Cable	1	1.5	N	N	Provided by Lab
5	LAN Cable	1	1.5	N	N	Provided by Lab
6	Tel. Cable	1	1.5	N	N	Provided by Lab
7	Tel. Cable	1	1.5	N	N	Provided by Lab

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC Part 15, Subpart C (15.247)

FCC Part 15, Subpart E (15.407)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 789033 D02 General UNII Test Procedure New Rules v02r01

KDB 662911 D01 Multiple Transmitter Output v02r01

KDB 987594 D02 U-NII 6 GHz EMC Measurement v01v01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

WLAN2.4G

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

WLAN5G

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Limits of Unwanted Emission Out of the Restricted Bands

Applicable To		Limit	
789033 D02 General UNII Test Procedures New Rules v02r01		Field Strength at 3 m	
		PK: 74 (dBµV/m)	AV: 54 (dBµV/m)
Frequency Band	Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
5150~5250 MHz	15.407(b)(1)	PK: -27 (dBm/MHz)	PK: 68.2 (dBµV/m)
5250~5350 MHz	15.407(b)(2)		
5470~5725 MHz	15.407(b)(3)		
5725~5850 MHz	<input checked="" type="checkbox"/> 15.407(b)(4)(i)	PK:-27 (dBm/MHz) ^{*1} PK:10 (dBm/MHz) ^{*2} PK:15.6 (dBm/MHz) ^{*3} PK:27 (dBm/MHz) ^{*4}	PK: 68.2 (dBµV/m) ^{*1} PK:105.2 (dBµV/m) ^{*2} PK: 110.8 (dBµV/m) ^{*3} PK:122.2 (dBµV/m) ^{*4}
	<input type="checkbox"/> 15.407(b)(4)(ii)	Emission limits in section 15.247(d)	
^{*1} beyond 75 MHz or more above of the band edge. ^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. ^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. ^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.			

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

WLAN6G

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Frequencies (MHz)	EIRP Limit	Equivalent Field Strength at 3m
5925MHz > F > 7125MHz	Peak:-7 (dBm/MHz)	88.2(dBμV/m)
	Average: -27 (dBm/MHz)	68.2(dBμV/m)

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

BT / Zigbee

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

4.1.2 Test Instruments

For Radiated emission below 1 GHz test

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Bi_Log Antenna Schwarbeck	VULB9168	9168-160	2022/10/20	2023/10/19
Loop Antenna EMCI	EM-6879	269	2022/09/19	2023/09/18
Loop Antenna TESEQ	HLA 6121	45745	2022/07/27	2023/07/26
Pre-amplifier EMCI	EMC001340	980201	2022/09/23	2023/09/22
Preamplifier Agilent	8447D	2944A10638	2022/05/14	2023/05/13
RF Coaxial Cable EMCI	5D-NM-BM	140903+140902	2023/01/07	2024/01/06
RF Coaxial Cable WOKEN	8D-FB	Cable-CH9-01	2022/05/14	2023/05/13
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Spectrum Analyzer R&S	FSW43	101867	2022/12/30	2023/12/29
Test Receiver KEYSIGHT	N9038A	MY55420137	2022/04/27	2023/04/26
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4.
2. Tested Date: 2023/3/30

For Radiated emission above 1 GHz test

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	5	N/A	N/A
Horn Antenna Schwarzbeck	9120D	9120D-1169	2022/11/13	2023/11/12
	BBHA 9170	9170-480	2022/11/13	2023/11/12
		BBHA9170243	2022/11/13	2023/11/12
Pre-Amplifier EMCI	EMC 184045	980116	2022/10/1	2023/9/30
Preamplifier Agilent	8449B	3008A02367	2023/2/15	2024/2/14
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	2022/7/9	2023/7/8
	EMC102-KM-KM-3000	150929	2022/7/9	2023/7/8
RF Coaxial Cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9- (250795/4)	2023/1/7	2024/1/6
RF Coaxial Cable HUBER+SUHNER&EMCI	SUCOFLEX 104& EMC104-SM-SM8000	CABLE-CH9-02 (248780+171006)	2023/1/7	2024/1/6
RF FLITER MICRO-TRONICS	BRM17690	004	2023/1/11	2024/1/10
	BRM50716	060	2023/1/11	2024/1/10
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Spectrum Analyzer R&S	FSW43	101867	2022/12/30	2023/12/29
Test Receiver KEYSIGHT	N9038A	MY55420137	2022/4/27	2023/4/26
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4.
2. Tested Date: 2023/3/30

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz. (RBW = 1MHz, VBW = 1kHz)
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

1. Placed the EUT on the testing table.
2. Set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1 GHz Data :

802.11b + 802.11ax (HE40) + 802.11ax (HE160) + BT LE

Channel	Ch 11 + 142 + 47 + 19	Detector Function	Peak (PK) Average (AV)
Frequency Range	1GHz ~ 25GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	113.4 PK			1.18 H	259	79.6	33.8
2	*2440.00	112.5 AV			1.18 H	259	78.7	33.8
3	*2462.00	116.2 PK			1.99 H	315	82.3	33.9
4	*2462.00	113.9 AV			1.99 H	315	80.0	33.9
5	2483.50	62.4 PK	74.0	-11.6	1.99 H	315	28.6	33.8
6	2483.50	51.7 AV	54.0	-2.3	1.99 H	315	17.9	33.8
7	4880.00	52.0 PK	74.0	-22.0	2.29 H	33	41.5	10.5
8	4880.00	41.6 AV	54.0	-12.4	2.29 H	33	31.1	10.5
9	4924.00	52.4 PK	74.0	-21.6	2.22 H	235	42.0	10.4
10	4924.00	50.9 AV	54.0	-3.1	2.22 H	235	40.5	10.4
11	7320.00	62.4 PK	74.0	-11.6	2.55 H	333	44.2	18.2
12	7320.00	51.4 AV	54.0	-2.6	2.55 H	333	33.2	18.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	113.8 PK			2.69 V	170	80.0	33.8
2	*2440.00	113.1 AV			2.69 V	170	79.3	33.8
3	*2462.00	117.1 PK			1.69 V	60	83.2	33.9
4	*2462.00	114.6 AV			1.69 V	60	80.7	33.9
5	2483.50	64.8 PK	74.0	-9.2	1.69 V	60	31.0	33.8
6	2483.50	53.1 AV	54.0	-0.9	1.69 V	60	19.3	33.8
7	4880.00	51.8 PK	74.0	-22.2	1.57 V	339	41.3	10.5
8	4880.00	41.6 AV	54.0	-12.4	1.57 V	339	31.1	10.5
9	4924.00	52.8 PK	74.0	-21.2	2.18 V	259	42.4	10.4
10	4924.00	45.8 AV	54.0	-8.2	2.18 V	259	35.4	10.4
11	7320.00	62.2 PK	74.0	-11.8	1.81 V	350	44.0	18.2
12	7320.00	51.4 AV	54.0	-2.6	1.81 V	350	33.2	18.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

Channel	Ch 11 + 142 + 47 + 19	Detector Function	Peak (PK) Average (AV)
Frequency Range	1GHz ~ 25GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5470.00	62.5 PK	68.2	-5.7	3.93 H	119	41.1	21.4
2	*5710.00	116.3 PK			3.93 H	119	74.5	41.8
3	*5710.00	103.2 AV			3.93 H	119	61.4	41.8
4	5850.00	62.1 PK	68.2	-6.1	3.93 H	119	39.6	22.5
5	11420.00	64.6 PK	74.0	-9.4	3.37 H	122	37.5	27.1
6	11420.00	49.5 AV	54.0	-4.5	3.37 H	122	22.4	27.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5470.00	62.7 PK	68.2	-5.5	3.39 V	10	41.3	21.4
2	*5710.00	116.4 PK			3.39 V	10	74.6	41.8
3	*5710.00	103.7 AV			3.39 V	10	61.9	41.8
4	5850.00	63.1 PK	68.2	-5.1	3.39 V	10	40.6	22.5
5	11420.00	65.2 PK	74.0	-8.8	3.00 V	26	38.1	27.1
6	11420.00	49.7 AV	54.0	-4.3	3.00 V	26	22.6	27.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	Ch 11 + 142 + 47 + 19	Detector Function	Peak (PK) Average (AV)
Frequency Range	1GHz ~ 25GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5925.00	47.9 PK	88.2	-40.3	1.80 H	350	41.4	6.5
2	5925.00	45.3 PK	88.2	-42.9	1.80 H	350	38.8	6.5
3	*6185.00	108.9 PK			1.80 H	350	67.5	41.4
4	*6185.00	96.4 AV			1.80 H	350	55.0	41.4
5	12370.00	54.2 PK	74.0	-19.8	1.91 H	342	38.2	16.0
6	12370.00	41.2 AV	54.0	-12.8	1.91 H	342	25.2	16.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5925.00	48.2 PK	88.2	-40.0	3.42 V	275	41.7	6.5
2	5925.00	45.6 AV	68.2	-22.6	3.42 V	275	39.1	6.5
3	*6185.00	109.3 PK			3.42 V	275	67.9	41.4
4	*6185.00	97.0 AV			3.42 V	275	55.6	41.4
5	12370.00	54.3 PK	74.0	-19.7	1.61 V	272	38.3	16.0
6	12370.00	41.4 AV	54.0	-12.6	1.61 V	272	25.4	16.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

802.11b + 802.11ax (HE40) + 802.11ax (HE160) + Zigbee

Channel	Ch 11 + 142 + 47 + 11	Detector Function	Peak (PK) Average (AV)
Frequency Range	1GHz ~ 25GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	58.7 PK	74.0	-15.3	1.25 H	290	25.0	33.7
2	2390.00	46.2 AV	54.0	-7.8	1.25 H	290	12.5	33.7
3	*2405.00	114.8 PK			1.25 H	290	81.1	33.7
4	*2405.00	110.6 AV			1.25 H	290	76.9	33.7
5	*2462.00	116.3 PK			1.99 H	315	82.4	33.9
6	*2462.00	114.0 AV			1.99 H	315	80.1	33.9
7	2483.50	62.3 PK	74.0	-11.7	1.99 H	315	28.5	33.8
8	2483.50	51.9 AV	54.0	-2.1	1.99 H	315	18.1	33.8
9	4810.00	51.7 PK	74.0	-22.3	1.75 H	29	41.6	10.1
10	4810.00	39.6 AV	54.0	-14.4	1.75 H	29	29.5	10.1
11	4924.00	52.3 PK	74.0	-21.7	2.20 H	235	41.9	10.4
12	4924.00	51.0 AV	54.0	-3.0	2.20 H	235	40.6	10.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.0 PK	74.0	-15.0	3.52 V	225	25.3	33.7
2	2390.00	46.4 AV	54.0	-7.6	3.52 V	225	12.7	33.7
3	*2405.00	113.0 PK			3.52 V	225	79.3	33.7
4	*2405.00	109.2 AV			3.52 V	225	75.5	33.7
5	*2462.00	116.9 PK			1.69 V	57	83.0	33.9
6	*2462.00	114.5 AV			1.69 V	57	80.6	33.9
7	2483.50	64.9 PK	74.0	-9.1	1.69 V	57	31.1	33.8
8	2483.50	53.0 AV	54.0	-1.0	1.69 V	57	19.2	33.8
9	4810.00	52.2 PK	74.0	-21.8	1.58 V	320	42.1	10.1
10	4810.00	40.1 AV	54.0	-13.9	1.58 V	320	30.0	10.1
11	4924.00	52.7 PK	74.0	-21.3	2.28 V	260	42.3	10.4
12	4924.00	45.8 AV	54.0	-8.2	2.28 V	260	35.4	10.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

Channel	Ch 11 + 142 + 47 + 11	Detector Function	Peak (PK) Average (AV)
Frequency Range	1GHz ~ 25GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5470.00	62.4 PK	68.2	-5.8	3.90 H	115	41.0	21.4
2	*5710.00	116.4 PK			3.90 H	115	74.6	41.8
3	*5710.00	103.3 AV			3.90 H	115	61.5	41.8
4	5850.00	62.2 PK	68.2	-6.0	3.90 H	115	39.7	22.5
5	11420.00	64.8 PK	74.0	-9.2	3.36 H	125	37.7	27.1
6	11420.00	49.6 AV	54.0	-4.4	3.36 H	125	22.5	27.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5470.00	62.8 PK	68.2	-5.4	3.33 V	8	41.4	21.4
2	*5710.00	116.5 PK			3.33 V	8	74.7	41.8
3	*5710.00	103.8 AV			3.33 V	8	62.0	41.8
4	5850.00	63.2 PK	68.2	-5.0	3.33 V	8	40.7	22.5
5	11420.00	65.3 PK	74.0	-8.7	2.97 V	22	38.2	27.1
6	11420.00	49.8 AV	54.0	-4.2	2.97 V	22	22.7	27.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	Ch 11 + 142 + 47 + 11	Detector Function	Peak (PK) Average (AV)
Frequency Range	1GHz ~ 25GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5925.00	47.7 PK	88.2	-40.5	1.84 H	352	41.2	6.5
2	5925.00	45.2 AV	68.2	-23.0	1.84 H	352	38.7	6.5
3	*6185.00	108.8 PK			1.84 H	352	67.4	41.4
4	*6185.00	96.3 AV			1.84 H	352	54.9	41.4
5	12370.00	54.1 PK	74.0	-19.9	1.93 H	347	38.1	16.0
6	12370.00	41.0 AV	54.0	-13.0	1.93 H	347	25.0	16.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5925.00	48.1 PK	88.2	-40.1	3.48 V	270	41.6	6.5
2	5925.00	45.5 AV	68.2	-22.7	3.48 V	270	39.0	6.5
3	*6185.00	109.1 PK			3.48 V	270	67.7	41.4
4	*6185.00	96.9 AV			3.48 V	270	55.5	41.4
5	12370.00	54.2 PK	74.0	-19.8	1.57 V	270	38.2	16.0
6	12370.00	41.3 AV	54.0	-12.7	1.57 V	270	25.3	16.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Below 1GHz data


802.11b + 802.11ax (HE40) + 802.11ax (HE160) + BT LE

Channel	Ch 11 + 142 + 47 + 19	Detector Function	Quasi-Peak (QP)
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	35.0 QP	40.0	-5.0	2.00 H	244	45.2	-10.2
2	95.96	35.3 QP	43.5	-8.2	1.00 H	259	49.4	-14.1
3	167.74	35.0 QP	43.5	-8.5	1.50 H	17	43.9	-8.9
4	221.09	36.4 QP	46.0	-9.6	1.00 H	69	47.5	-11.1
5	503.36	28.5 QP	46.0	-17.5	1.00 H	68	30.8	-2.3
6	776.90	32.9 QP	46.0	-13.1	1.50 H	72	30.0	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




Channel	Ch 11 + 48 + 47 + 19	Detector Function	Quasi-Peak (QP)
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	60.07	35.1 QP	40.0	-4.9	1.49 V	185	44.6	-9.5
2	97.90	34.7 QP	43.5	-8.8	1.00 V	186	48.5	-13.8
3	119.24	34.5 QP	43.5	-9.0	1.00 V	227	45.7	-11.2
4	221.09	34.1 QP	46.0	-11.9	1.49 V	185	45.2	-11.1
5	544.10	32.7 QP	46.0	-13.3	1.00 V	100	34.5	-1.8
6	679.90	31.1 QP	46.0	-14.9	1.00 V	238	30.2	0.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




802.11b + 802.11ax (HE40) + 802.11ax (HE160) + Zigbee

Channel	Ch 11 + 142 + 47 + 11	Detector Function	Quasi-Peak (QP)
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	73.65	34.6 QP	40.0	-5.4	1.50 H	20	46.5	-11.9
2	95.96	35.0 QP	43.5	-8.5	1.00 H	7	49.1	-14.1
3	119.24	33.4 QP	43.5	-10.1	1.00 H	221	44.6	-11.2
4	167.74	35.8 QP	43.5	-7.7	1.00 H	335	44.7	-8.9
5	221.09	36.0 QP	46.0	-10.0	1.50 H	226	47.1	-11.1
6	739.07	30.7 QP	46.0	-15.3	1.00 H	148	28.9	1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




Channel	Ch 11 + 142 + 47 + 11	Detector Function	Quasi-Peak (QP)
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.95	34.0 QP	40.0	-6.0	2.00 V	119	44.2	-10.2
2	95.96	35.4 QP	43.5	-8.1	1.00 V	59	49.5	-14.1
3	167.74	35.3 QP	43.5	-8.2	1.50 V	10	44.2	-8.9
4	221.09	31.8 QP	46.0	-14.2	2.00 V	159	42.9	-11.1
5	383.08	26.9 QP	46.0	-19.1	1.00 V	75	31.9	-5.0
6	543.13	32.1 QP	46.0	-13.9	1.00 V	102	33.9	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




4.2 Conducted Out of Band Emission Measurement

4.2.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.2.2 Test Setup



4.2.3 Test Instruments

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Software BV	ADT_RF Test Software V6.6.5.4	N/A	N/A	N/A
Spectrum Analyzer R&S	FSV40	100980	2023/05/03	2024/05/02

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2023/5/15

4.2.4 Test Procedure

MEASUREMENT PROCEDURE REF

- a. Set the RBW = 100 kHz.
- b. Set the VBW \geq 300 kHz.
- c. Detector = peak.
- d. Sweep time = auto couple.
- e. Trace mode = max hold.
- f. Allow trace to fully stabilize.
- g. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

- a. Set RBW = 100 kHz.
- b. Set VBW \geq 300 kHz.
- c. Detector = peak.
- d. Sweep = auto couple.
- e. Trace Mode = max hold.
- f. Allow trace to fully stabilize.
- g. Use the peak marker function to determine the maximum amplitude level.

4.2.5 Deviation from Test Standard

No deviation.


4.2.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.2.7 Test Results

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

802.11b, CH11 + 802.11ax (HE40), CH142



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---