

FCC RF Exposure Report

Report No.: MFBEDV-WTW-P23030565-1

FCC ID: G95MGA5331

Model No.: MGA5331

Received Date: 2023/3/16

Issued Date: 2023/7/27

Applicant: Vantiva USA LLC

Address: 4855 Peachtree Industrial Blvd. Suite 200 Norcross, Georgia 30092

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

| | |
|--|-----------|
| Release Control Record | 3 |
| 1 Certificate of Conformity | 4 |
| 2 General Information | 5 |
| 2.1 General Description of EUT | 5 |
| 3 RF Exposure | 10 |
| 3.1 Limits for Maximum Permissible Exposure (MPE) | 10 |
| 3.2 MPE Calculation Formula | 10 |
| 3.3 Classification | 10 |
| 4 Calculation Result of Maximum Conducted Power | 11 |

Release Control Record

| Issue No. | Description | Date Issued |
|------------------------|------------------|-------------|
| MFBEDV-WTW-P23030565-1 | Original release | 2023/7/27 |

1 Certificate of Conformity

Product: WIFI Gateway

Brand: Vantiva

Test Model: MGA5331

Sample Status: Engineering sample

Applicant: Vantiva USA LLC

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

We, **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, declare that the equipment above has been found compliance with the requirement limits of applicable standards. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate under the standards herein specified.

Prepared by :

Vera Huang

Date:

2023/7/27

Vera Huang / Specialist

Approved by :

Jeremy Lin

Date:

2023/7/27

Jeremy Lin / Project Engineer

2 General Information

2.1 General Description of EUT

| | | |
|-----------------------|--------------------|---|
| Product | WIFI Gateway | |
| Brand | Vantiva | |
| Test Model | MGA5331 | |
| Status of EUT | Engineering sample | |
| Input Power | Refer to Note | |
| Modulation Type | WLAN | 2.4GHz Band: CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in VHT mode 1024QAM for OFDMA in 11ax mode only 5.0GHz Band: 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode 1024QAM for OFDMA in 11ax HE mode |
| | LTE | QPSK, 16QAM, 64QAM, 256QAM |
| | 5G NR | $\pi/2$ BPSK, QPSK, 16QAM, 64QAM, 256QAM |
| Modulation Technology | WLAN | DSSS, OFDM, OFDMA |
| Transfer Rate | WLAN | 2.4GHz Band: 802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to 600 Mbps VHT: up to 800 Mbps 802.11ax: up to 1147.1 Mbps 5.0GHz Band 802.11a: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 600Mbps 802.11ac: up to 3466.7Mbps 802.11ax: up to 4803.9Mbps |
| Operating Frequency | WLAN | 2.4GHz: 2412MHz ~ 2462MHz 5.0GHz: 5180 ~ 5250MHz, 5250 ~ 5320MHz, 5500 ~ 5720MHz, 5745 ~ 5825MHz |

| | | |
|---------------------|-------------------|---|
| Operating Frequency | LTE Band 2 | 1850MHz ~ 1910MHz |
| | LTE Band 4 | 1710MHz ~ 1755MHz |
| | LTE Band 5 | 824MHz ~ 849MHz |
| | LTE Band 7 | 2500MHz ~ 2570MHz |
| | LTE Band 12 | 699MHz ~ 716MHz |
| | LTE Band 13 | 777MHz ~ 787MHz |
| | LTE Band 25 | 1850MHz ~ 1915MHz |
| | LTE Band 26 | 814MHz ~ 849MHz |
| | LTE Band 38 | 2570MHz ~ 2620MHz |
| | LTE Band 41 | 2496MHz ~ 2690MHz |
| | LTE Band 48 | 3550MHz ~ 3700MHz |
| | LTE Band 66 | 1710MHz ~ 1780MHz |
| | LTE Band 71 | 663MHz ~ 698MHz |
| | 5G NR n2 | 1850MHz ~ 1910MHz |
| | 5G NR n5 | 824MHz ~ 849MHz |
| | 5G NR n12 | 699MHz ~ 716MHz |
| | 5G NR n25 | 1850MHz ~ 1915MHz |
| | 5G NR n38 | 2570MHz ~ 2620MHz |
| | 5G NR n41 | 2570MHz ~ 2620MHz |
| | 5G NR n66 | 1710MHz ~ 1780MHz |
| 5G NR n71 | 663MHz ~ 698MHz | |
| 5G NR n77 | 3450MHz ~ 3700MHz | |
| Number of Channel | WLAN 2.4GHz | 2412MHz ~ 2472MHz: 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20):11 802.11n (HT40), VHT40, 802.11ax (HE40):7 |
| | WLAN 5.0GHz | 5180 ~ 5250MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 4 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1 5250 ~ 5320MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 4 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1 802.11ac (VHT160), 802.11ax (HE160): 1 5500 ~ 5720MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 12 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 6 802.11ac (VHT80), 802.11ax (HE80): 3 802.11ac (VHT160), 802.11ax (HE160): 1 5745 ~ 5825MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 5 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1 |

| | | |
|--------------|-------|---------------|
| Antenna Type | WLAN | Refer to note |
| | WCDMA | Refer to note |
| | LTE | Refer to note |
| | 5G NR | Refer to note |

Note:

1. The EUT contains certified module with FCC ID: G95RG525FNA.
2. The EUT uses following accessories.

| AC Adapter | | |
|------------|-------------------------|---|
| Brand | Model | Specification |
| HONOR | ADS-42FI-12 12042EPCU-L | AC Input: 100-120V~ 50/60Hz 1.2A max. DC Output: 12VDC, 3.5A, 42W DC Output Cable: 1.5m, Non-Shielded |

3. The EUT incorporates a MIMO function:

| 2.4 GHz Band | | |
|-----------------|-----------------------|-----|
| Modulation Mode | TX & RX Configuration | |
| 802.11b | 4TX | 4RX |
| 802.11g | 4TX | 4RX |
| 802.11n (HT20) | 4TX | 4RX |
| 802.11n (HT40) | 4TX | 4RX |
| VHT20 | 4TX | 4RX |
| VHT40 | 4TX | 4RX |
| 802.11ax (HE20) | 4TX | 4RX |
| 802.11ax (HE40) | 4TX | 4RX |

Note:

1. All of modulation mode support beamforming function except 802.11b/g modulation mode.
2. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
3. The EUT device modulation technique OFDMA does not support partial RUs (resource units) and channel puncturing/bandwidth reduction mechanisms.

| 5 GHz Band | | |
|-------------------|-----------------------|-----|
| Modulation Mode | TX & RX Configuration | |
| 802.11a | 4TX | 4RX |
| 802.11n (HT20) | 4TX | 4RX |
| 802.11n (HT40) | 4TX | 4RX |
| 802.11ac (VHT20) | 4TX | 4RX |
| 802.11ac (VHT40) | 4TX | 4RX |
| 802.11ac (VHT80) | 4TX | 4RX |
| 802.11ac (VHT160) | 4TX | 4RX |
| 802.11ax (HE20) | 4TX | 4RX |
| 802.11ax (HE40) | 4TX | 4RX |
| 802.11ax (HE80) | 4TX | 4RX |
| 802.11ax (HE160) | 4TX | 4RX |

Note:

1. All of modulation mode support beamforming function except 802.11a modulation mode.
2. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
3. The modulation and bandwidth are similar for 802.11n mode for 20 MHz (40 MHz), 802.11ac mode for 20 MHz (40 MHz, 80 MHz, 160 MHz) and 802.11ax mode for 20 MHz (40 MHz, 80 MHz, 160 MHz), therefore the manufacturer will control the power for 802.11n/ac mode is the same as the 802.11ax or more lower than it and investigated worst case to representative mode in test report.
4. The EUT device modulation technique OFDMA does not support partial RUs (resource units) and channel puncturing/bandwidth reduction mechanisms.

4. The WLAN antenna information is listed as below.

| Antenna Type | PCB | | | |
|----------------|----------------|---------|---------|---------|
| Connector Type | ipex(MHF) | | | |
| Band | Max Gain (dBi) | | | |
| | Chain 0 | Chain 1 | Chain 2 | Chain 3 |
| 2.4GHz | 1.28 | -0.72 | -4.58 | -2.14 |
| 5G Band 1 | 1.51 | -0.18 | 0.73 | -0.12 |
| 5G Band 2 | 1.03 | 1.28 | 2.03 | 0.09 |
| 5G Band 3 | 2.62 | -0.26 | 2.19 | 2.19 |
| 5G Band 4 | 0.47 | -0.29 | 2.81 | 0.47 |

| Band | Directional Gain (dBi) |
|-----------|------------------------|
| 2.4GHz | 3.21 |
| 5G Band 1 | 5.6 |
| 5G Band 2 | 5.48 |
| 5G Band 3 | 6.01 |
| 5G Band 4 | 6.48 |

5. The WWAN antenna information is listed as below.

| Antenna Type | PCB | | | |
|-------------------|------------------------------|---------------------------|------------|------|
| Antenna Connector | Ipx(MHF) | | | |
| Item | Band | TX Ant | Gain (dBi) | |
| | | | ANT0 | ANT3 |
| LTE | Band 2 | Ant 0 | 5.05 | 3.47 |
| | Band 4 | Ant 0 | 4.84 | 3.96 |
| | Band 5 | Ant 0 | 2.38 | 1.58 |
| | Band 7 | Ant 3 | 5.02 | 5.70 |
| | Band 12 | Ant 0 | 1.12 | 1.99 |
| | Band 13 | Ant 0 | 1.59 | 0.87 |
| | Band 25 | Ant 0 | 5.05 | 3.47 |
| | Band 26 (Part 22) | Ant 0 | 2.38 | 1.75 |
| | Band 26 (Part 90) | Ant 0 | 2.30 | 1.58 |
| | Band 38 | Ant 3 | 5.43 | 6.11 |
| | Band 41 | Ant 3 | 5.43 | 6.17 |
| | Band 66 | Ant 0 | 4.84 | 3.96 |
| | Band 71 | Ant 0 | 1.12 | 1.99 |
| 5G NR FR1 | n2 | Ant 0 | 5.05 | 3.47 |
| | n5 | Ant 0 | 2.38 | 1.58 |
| | n12 | Ant 0 | 1.12 | 1.99 |
| | n25 | Ant 0 | 5.05 | 3.47 |
| | n38 | Ant 3 | 5.43 | 6.11 |
| | n41 | Ant 3 UL-MIMO: Ant 0+3 | 5.43 | 6.17 |
| | n66 | Ant 0 | 4.84 | 3.96 |
| | n71 | Ant 0 | 1.12 | 1.99 |
| | n77/n78 (3450MHz-3550MHz) | Ant 0 UL-MIMO: Ant 0+3 | 3.65 | 3.72 |
| | n77/n78 (3700MHz-3980MHz) | Ant 0 UL-MIMO: Ant 0+3 | 5.37 | 4.59 |

* Detail antenna specification please refer to antenna datasheet an antenna gain measurement report.

3 RF Exposure

3.1 Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| Limits For General Population / Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f ²)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | ... | ... | f/1500 | 30 |
| 1500-100,000 | ... | ... | 1.0 | 30 |

f = Frequency in MHz; *Plane-wave equivalent power density

3.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

r = distance between observation point and center of the radiator in cm

3.3 Classification

The antenna of this product, under normal use condition, is at least 25cm away from the body of the user. So, this device is classified as **Mobile Device**.

4 Calculation Result of Maximum Conducted Power

| Mode | Max Power (dBm) | Antenna Gain (dBi) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|-----------------------|-----------------|--------------------|---------------|-------------------------------------|-----------------------------|
| CDD mode | | | | | |
| WLAN 2.4GHz | 29.80 | 1.28 | 25 | 0.163 | 1.00 |
| WLAN 5.18 ~ 5.25GHz | 29.75 | 1.51 | 25 | 0.170 | 1.00 |
| WLAN 5.25 ~ 5.32GHz | 23.97 | 2.03 | 25 | 0.051 | 1.00 |
| WLAN 5.50 ~ 5.720GHz | 23.81 | 2.62 | 25 | 0.056 | 1.00 |
| WLAN 5.745 ~ 5.825GHz | 29.93 | 2.81 | 25 | 0.239 | 1.00 |
| Beamforming mode | | | | | |
| WLAN 2.4GHz | 29.23 | 3.21 | 25 | 0.223 | 1.00 |
| WLAN 5.18 ~ 5.25GHz | 29.75 | 5.6 | 25 | 0.436 | 1.00 |
| WLAN 5.25 ~ 5.32GHz | 23.97 | 5.48 | 25 | 0.112 | 1.00 |
| WLAN 5.50 ~ 5.720GHz | 23.81 | 6.01 | 25 | 0.122 | 1.00 |
| WLAN 5.745 ~ 5.825GHz | 29.44 | 6.48 | 25 | 0.498 | 1.00 |

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.4GHz: Directional gain = 3.21dBi

5.18 ~ 5.25GHz: Directional gain = 5.6dBi

5.25 ~ 5.32GHz: Directional gain = 5.48dBi

5.50 ~ 5.720GHz: Directional gain = 6.01dBi

5.745 ~ 5.825GHz: Directional gain = 6.48dBi

| Mode | EIRP (dBm) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|-------------|------------|---------------|-------------------------------------|-----------------------------|
| LTE Band 2 | 26.57 | 25 | 0.058 | 1.000 |
| LTE Band 4 | 26.31 | 25 | 0.054 | 1.000 |
| LTE Band 7 | 27.38 | 25 | 0.070 | 1.000 |
| LTE Band 25 | 26.68 | 25 | 0.059 | 1.000 |
| LTE Band 38 | 30.42 | 25 | 0.140 | 1.000 |
| LTE Band 41 | 30.50 | 25 | 0.143 | 1.000 |
| LTE Band 48 | 20.63 | 25 | 0.015 | 1.000 |
| LTE Band 66 | 26.39 | 25 | 0.055 | 1.000 |

| Function | Frequency Band (MHz) | ERP (dBm) | EIRP (dBm) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|-----------------------|----------------------|-----------|------------|---------------|-------------------------------------|-----------------------------|
| LTE Band 5 | 824.7-848.3 | 22.89 | 25.04 | 25 | 0.041 | 0.550 |
| LTE Band 26 (Part 22) | 824.7-848.3 | 22.63 | 24.78 | 25 | 0.038 | 0.550 |
| LTE Band 12 | 699.7-715.3 | 21.58 | 23.73 | 25 | 0.030 | 0.466 |
| LTE Band 13 | 779.5-784.5 | 22.25 | 24.40 | 25 | 0.035 | 0.520 |
| LTE Band 26 (Part 90) | 814.7-823.3 | 22.47 | 24.62 | 25 | 0.037 | 0.543 |
| LTE Band 71 | 665.5-695.5 | 21.41 | 23.56 | 25 | 0.029 | 0.444 |

| Mode | EIRP (dBm) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|----------------------|------------|---------------|-------------------------------------|-----------------------------|
| SA | | | | |
| 5G NR n2 | 27.34 | 25 | 0.069 | 1.000 |
| 5G NR n25 | 27.44 | 25 | 0.071 | 1.000 |
| 5G NR n38 | 31.63 | 25 | 0.185 | 1.000 |
| 5G NR n41 | 32.09 | 25 | 0.206 | 1.000 |
| 5G NR n66 | 26.95 | 25 | 0.063 | 1.000 |
| 5G NR n77 (Part 27Q) | 29.52 | 25 | 0.114 | 1.000 |
| 5G NR n77 (Part 27O) | 29.98 | 25 | 0.127 | 1.000 |
| UL-MIMO | | | | |
| 5G NR n41 | 25.57 | 25 | 0.046 | 1.000 |
| 5G NR n77 (Part 27Q) | 24.41 | 25 | 0.035 | 1.000 |
| 5G NR n77 (Part 27O) | 25.61 | 25 | 0.046 | 1.000 |

| Function | ERP (dBm) | EIRP (dBm) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|-----------|-----------|------------|---------------|-------------------------------------|-----------------------------|
| 5G NR n5 | 23.05 | 25.20 | 25 | 0.042 | 0.549 |
| 5G NR n12 | 21.96 | 24.11 | 25 | 0.033 | 0.466 |
| 5G NR n71 | 21.99 | 24.14 | 25 | 0.033 | 0.442 |

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

WLAN 2.4G & WLAN 5GHz & WWAN can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$WLAN\ 2.4GHz + WLAN\ 5GHz + WWAN = 0.223 / 1 + 0.498 / 1 + 0.206 / 1 = 0.927$$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---