

March 24, 2005

CCT R&D Ltd.
18/F., CCT Telecom Building,
11 Wo Shing Street, Fotan,
Shatin, N.T., Hong Kong.
Tel. : (852) 2695 8333
Fax. : (852) 2694 8660

Dear Mr. Ronilo Paredes:

Enclosed you will find your file copy of a Part 15 Certification (FCC ID: G9H2-3200A).

For your reference, TCB will normally take another 15-20 days for reviewing the report.
Approval will then be granted when no query is sorted.

Please contact me if you have any questions regarding the enclosed material.

Sincerely,



Tommy Leung
Assistant Manager

Enclosure

The Intertek logo consists of the word "Intertek" in white, bold, sans-serif font, enclosed within a black rounded rectangle.

ETL SEMKO

ATLINKS USA, Inc.

Application
For
Certification

2.4GHz Frequency Hopping Spread Spectrum Cordless Phone with Caller ID
and Cell Docking System

(FCC ID: G9H2-3200A)

05007061
TL/Ann Choy
March 24, 2005

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2741 1693 Website: www.hk.intertek-etlsemko.com

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labelling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual
<i>EXHIBIT 9:</i>	Security Code Information
<i>EXHIBIT 10:</i>	Confidentiality Request

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

ATLINKS USA, Inc.- MODEL: 23200XXX-A, 23210XXX-A
FCC ID: G9H2-3200A

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DSS-Part 15 Spread Spectrum Transmitter and JBP - Class
B Personal Computer Peripheral

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until : _____
dae

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be
issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [12-
08-03 Edition] provision.

Report prepared by:

Tommy Leung
Intertek Testing Services
2/F., Garment Centre,
576 Castle Peak Road,
Kowloon, Hong Kong.
Phone: 852-2173-8538
Fax: 852-2741-1693

INTERTEK TESTING SERVICES

Table of Contents

1.0 <u>Summary of test results</u>	2
2.0 <u>General Description</u>	4
2.1 Product Description	4
2.2 Related Submittal(s) Grants	5
2.3 Test Methodology	5
2.4 Test Facility	5
3.0 <u>System Test Configuration</u>	7
3.1 Justification	7
3.2 EUT Exercising Software	7
3.3 Support Equipment List and Description	8
3.4 Measurement Uncertainty	9
3.5 Equipment Modification	9
4.0 <u>Measurement Results</u>	11
4.1 Maximum Conducted Output Power at Antenna Terminals	11
4.2 Maximum 20 dB RF Bandwidth	14
4.3 Minimum Number of Hopping Frequencies	17
4.4 Minimum Hopping Channel Carrier Frequency Separation	18
4.5 Average Time of Occupancy	21
4.6 Out of Band Conducted Emissions	22
4.7 Out of Band Radiated Emissions	23
4.8 Transmitter Radiated Emissions in Restricted Bands	24
4.9 Field Strength Calculation	25
4.10 Radiated Emission Configuration Photograph - Base Unit	26
4.11 Radiated Emission Data - Base Unit	27
4.12 Radiated Emission Configuration Photograph - Handset	31
4.13 Radiated Emission Data - Handset	32
4.14 Radiated Emission Configuration Photograph - Docking Station	36
4.15 Radiated Emission Data - Docking Station	37
4.16 AC Line Conducted Emission	41
4.17 Line Conducted Configuration Photograph - Base Unit	42
4.18 Line Conducted Emission Configuration Data	43
4.19 Line Conducted Configuration Photograph - Class B Personal Computer Peripheral	44
4.20 Line Conducted Emission Configuration Data	45
4.21 Radiated Emission from Digital Section of Transceiver and Class B Personal Computer Peripheral	46
4.22 Transmitter Duty Cycle Calculation and Measurements	51
5.0 <u>Equipment Photographs</u>	53
6.0 <u>Product Labelling</u>	55
7.0 <u>Technical Specifications</u>	57
8.0 <u>Instruction Manual</u>	59
9.0 <u>Security Code Information</u>	61
10.0 <u>Confidentiality Request</u>	63

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	filename
Cover Page	Confidentiality Request	request.pdf
Test Report	Test Report	report.pdf
Operation Description	Technical Description	descri.pdf
Test Setup Photo	Radiated Emission for Base	config photos.doc
Test Setup Photo	Radiated Emission for Handset	config photos.doc
Test Setup Photo	Radiated Emission for Docking Station	config photos.doc
Test Report	Maximum Output Power Plot	bmaxop.pdf, hmaxop.pdf, dmaxop.pdf
Test Report	20 dB Bandwidth Plot	b20dB.pdf, h20dB.pdf, d20dB.pdf
Test Report	Minimum Number of Hopping Frequencies	bchno.pdf, hchno.pdf, dchno.pdf
Test Report	Minimum Hopping Channel Carrier Frequency Separation	bfsepa.pdf, hfsepa.pdf, dfsepa.pdf
Test Report	Average Channel Occupancy Time	bavetime.pdf, havetime.pdf, davetime.pdf
Test Report	Out Band Antenna Conducted Emission Plot	bobantcon.pdf, hobantcon.pdf, dobantcon.pdf
Test Report	Duty Cycle Calculation and Measurement	bdcc.pdf, hdcc.pdf, ddcc.pdf
Test Setup Photo	Conducted Emission	config photos.doc
Test Report	Conducted Emission Test Result	conduct.pdf
External Photo	External Photo	external photos.doc
Internal Photo	Internal Photo	internal photos_b.doc internal photos_h.doc internal photos_d.doc
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
User Manual	FCC Information	FCC information.pdf
RF Exposure Info	RF Safety	RF exposure info.pdf
Operation Description	Security Code Information	security code information.pdf

EXHIBIT 1
SUMMARY OF TEST RESULTS

INTERTEK TESTING SERVICES

1.0 Summary of Test

ATLINKS USA, Inc.- MODEL: 23200XXX-A, 23210XXX-A
FCC ID: G9H2-3200A

TEST	REFERENCE	RESULTS
Max. Output Power	15.247(b)	Pass
Min. No. of Hopping Frequencies	15.247(a)(1)	Pass
Min. Hopping Channel Carrier Frequency Separation	15.247(a)(1)	Pass
Average Time of Occupancy	15.247(a)(1)	Pass
Out of Band Antenna Conducted Emission	15.247(c)	Pass
Radiated Emission in Restricted Bands	15.247(c)	Pass
AC Conducted Emission	15.207	Pass
Radiated Emission from Digital Part	15.109	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses a permanently attached antenna which, in accordance to Section 15.203, is considered sufficient to comply with the provisions of this section.

EXHIBIT 2
GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

2.0 **General Description**

2.1 Product Description

The 23200XXX-A is a 2.4GHz Frequency Hopping Spread Spectrum Cordless Phone with Caller ID and Cell Docking System. It operates at frequency range of 2401.808MHz to 2478.509MHz with 87 physical hopping frequencies and 75 logical hopping frequencies. The unit is capable of either tone or pulse dialing. The internal power supply's isolation is accomplished through a power transformer having an adequate dielectric rating. The circuit wiring is consistent under the requirement of part 68.

The base unit has a page key, which is used to communicate with handset unit.

The handset unit consists of a keypad with twelve standard keys (0,...9,*,#), twelve function keys (memory, speaker, CID/vol+, CID/vol-, redial, voicemail, hold, intercom, format/conference, delete, flash/exit, prog/mute). A home key is provided to control pick/release telephone line in a toggle base.

The docking station is a universal cradle for different types of cell phones, which allows a user use a cordless handset to dial out or receive calls via the cell network. It consists of four function keys (Program, Left, Right, Exit). It also is a charger for charging the compatible cellular phone, and a user can upgrade the firmware of this unit through the USB cable.

The antennas used in base unit, handset, and docking station are integral, and the test sample is a prototype.

The model 23210XXX-A is an additional handset with an extra charger for selling a handset standalone, and it is the same as the handset of model 23200XXX-A in hardware aspect. The letters "XXX", on the model numbers are in term of any letters or numbers with different color of cabinet and applicant's identification code. The difference in model numbers serve as marketing strategy.

The circuit description, frequency hopping algorithm, and RF IC specification are saved with filename: descri.pdf

Connection between the device and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

INTERTEK TESTING SERVICES

2.2 Related Submittal(s) Grants

This is an application for Certification of a DSS-Part 15 Spread Spectrum Cordless Telephone System and a Class B Personal Computer Peripheral. Three transmitters are included in this application. The device is also subject to Part 68 Registration.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2001). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

EXHIBIT 3
SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

3.0 **System Test Configuration**

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The handset was powered by a fully charged battery.

For the measurements, the EUT is attached to a plastic stand if necessary and placed on the wooden turntable. If the base unit attaches to peripherals, they are connected and operational (as typical as possible). The handset is remotely located as far from the antenna and the base as possible to ensure full power transmission from the base. Else, the base is wired to transmit full power without modulation.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Detector function is in peak mode. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1MHz or greater for frequencies above 1000MHz.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9kHz to 25GHz.

A connection cable supporting UART or FBUS interface has been tested, and the worst-case data is included in this report.

3.2 EUT Exercising Software

The EUT exercise program (Toshiba Updater) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

INTERTEK TESTING SERVICES

3.3 Support Equipment List and Description

The FCC ID's for all equipment, plus descriptions of all cables used in the tested system (included inserted cards, which have grants) are:

HARDWARE:

The unit was operated standalone. AC adaptors and a battery (provided with the unit) were used to power the device. Their description are listed below.

- (1) An AC adaptor (120VAC to 9VDC 350mA, Model: DU35090035C) for Base Unit
- (2) A "Ni-MH" type rechargeable battery (3.6V 700mAh) for Handset
- (3) An AC adaptor (120VAC to 9VDC 500mA & 7VDC 300mA, Model: DU48090050M) for Docking Station

CABLES:

- (1) A telecommunication cable with RJ11C connectors (1m, unshielded), terminated for Base Unit
- (2) An USB cable with 1 meter long for Docking Station (Supplied by Client)
- (3) Connection cables for Docking Station (Supplied by Client):
 - (a) A cable with 14cm long for Nokia 9-pin cellular phone (Model: 5-2663)
 - (b) A cable with 14cm long for Nokia 14-pin cellular phone (Model: 5-2664)
 - (c) A cable with 14cm long for Sony Ericsson cellular phone (Model: 5-2662)
 - (d) A cable with 14cm long for Motorola cellular phone (Model: 5-2666)
 - (e) A cable with 14cm long for Motorola Nextel cellular phone (Model: 5-2665)
- (4) A serial cable with 1m long for a PC set
- (5) A parallel cable with 1m long for a PC set

OTHERS:

- (1) A telephone headset with 1.2m unshielded cable permanently affixed for handset (Supplied by Intertek)
- (2) A PC set for Radiated Emission Test of Docking Station (Supplied by Intertek):
 - (a) HP Computer, Model: D530S, S/N: CNG4110DX, DOC Product
 - (b) Philips LCD Monitor, Model: 150B4CG, S/N: CX000409301774, DOC Product
 - (c) HP Keyboard, Model: SDM4700P, S/N: 323686-B31, DOC Product
 - (d) HP Mouse, Model: M-S69, S/N: 323614-001, FCCID: JNZ211443
 - (e) HP Printer, Model: C2642A, S/N: SG67B131RY, FCCID: B94C2642X
 - (f) Hayes Modem, Model: 6800CN, S/N: A00900153317, FCCID: BFJ9D907-00038

INTERTEK TESTING SERVICES

3.3 Support Equipment List and Description - cont'd

OTHERS:

- (3) A PC set for Conducted Emission Test of Docking Station (Supplied by Intertek):
 - (a) HP Computer, Model: Vectra VL420, S/N: SG20409996, DOC Product
 - (b) Samsung LCD Monitor, Model 152N, S/N: NB15HMEWA08764W, DOC Product
 - (c) HP Keyboard, Model: SK-2502, S/N: C0205303122, FCCID: GYUR41SK
 - (d) HP Mouse, Model: M-S34, S/N: LZA71977598, FCCID: DZL211029
 - (e) HP Printer, Model: C2642A, S/N: SG67B131RY, FCCID: B94C2642X
 - (f) Hayes Modem, Model: 6800CN, S/N: A00900153317, FCCID: BFJ9D907-00038
- (4) A Cellular Phone for Docking Station (Supplied by Client):
 - (a) Cellular Phone, Model: Nokia 6820, IMEI: 352506/00/24188/2, FCCID: PYANHL-9
 - (b) Cellular Phone, Model: Nokia 6310I, IMEI: 350984/20/053610/1, FCCID: PPINPL-1

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification


Any modifications installed previous to testing by ATLINKS USA, Inc. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by ETL Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 3.0 of this report are confirmed by:

Confirmed by:

*Tommy Leung
Assistant Manager
Intertek Testing Services Hong Kong Ltd.
Agent for ATLINKS USA, Inc.*



Signature

Mar 24, 2005

Date

EXHIBIT 4
MEASUREMENT RESULTS

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b) :

- ☐ The antenna power of the EUT was connected to the input of a power meter. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.
- ☒ The antenna port of the EUT was connected to the input of a spectrum analyzer. The analyzer was set for RBW>20dB bandwidth and power was read directly in dBm. External attenuation and cable loss were compensated for using the OFFSET function of the analyser.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm).

(Base Unit) Antenna Gain = 2 dBi		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2401.856	17.39	54.83
Middle Channel: 2440.199	18.29	67.45
High Channel: 2478.465	18.75	74.99

Cable loss : 0.5 dB External Attenuation : N/A dB

Cable loss, external attenuation: ☐ included in OFFSET function
☐ added to SA raw reading

dBm max. output level = 18.75 dBm (30 dBm or less)

Please refer to the attached plots for details:

Plot B1a: Low Channel Output Power
Plot B1b: Middle Channel Output Power
Plot B1c: High Channel Output Power

For electronic filing, the above plots are saved with filename: bmaxop.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b) - Continued:

(Handset Unit) Maximum Antenna Gain = 1 dBi		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2401.844	16.03	40.09
Middle Channel: 2440.191	17.16	52.00
High Channel: 2478.583	18.18	65.77

Cable loss : 0.5 dB External Attenuation : N/A dB

Cable loss, external attenuation: [x] included in OFFSET function
[] added to SA raw reading

dBm max. output level = 18.18 dBm (30 dBm or less)

Please refer to the attached plots for details:

Plot H1a: Low Channel Output Power
Plot H1b: Middle Channel Output Power
Plot H1c: High Channel output Power

For electronic filing, the above plots are saved with filename: hmaxop.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b) - Continued:

(Docking Station) Maximum Antenna Gain = 2 dBi		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2401.980	16.24	42.07
Middle Channel: 2440.134	17.53	56.62
High Channel: 2478.509	18.73	74.64

Cable loss : 0.5 dB External Attenuation : N/A dB

Cable loss, external attenuation: [x] included in OFFSET function
[] added to SA raw reading

dBm max. output level = 18.73 dBm (30 dBm or less)

Please refer to the attached plots for details:

Plot D1a: Low Channel Output Power
Plot D1b: Middle Channel Output Power
Plot D1c: High Channel output Power

For electronic filing, the above plots are saved with filename: dmaxop.pdf.

For RF Safety of base unit, handset, and docking station, the information is saved with filename: RF exposure info.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.2 Maximum 20 dB RF Bandwidth, FCC Rule 15.247(a)(1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 20 dB lower than PEAK level. The 20 dB bandwidth was determined from where the channel output spectrum intersected the display line.

(Base Unit)	
Frequency (MHz)	20 dB Bandwidth (kHz)
2401.736	750

Refer to the following plots for 20 dB bandwidth sharp:

Plot B2a: Low Channel 20 dB RF Bandwidth

Plot B2b: Middle Channel 20 dB RF Bandwidth

Plot B2c: High Channel 20 dB RF Bandwidth

For electronic filing, the above plots are saved with filename: b20dB.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

Maximum 20 dB RF Bandwidth, FCC Rule 15.247(a)(1) - Continued:

(Handset Unit)	
Frequency (MHz)	20 dB Bandwidth (kHz)
2401.748	804

Refer to the following plots for 20 dB bandwidth sharp:

Plot H2a: Low Channel 20 dB RF Bandwidth

Plot H2b: Middle Channel 20 dB RF Bandwidth

Plot H2c: High Channel 20 dB RF Bandwidth

For electronic filing, the above plots are saved with filename: h20dB.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

Maximum 20 dB RF Bandwidth, FCC Rule 15.247(a)(1) - Continued:

(Docking Station)	
Frequency (MHz)	20 dB Bandwidth (kHz)
2401.784 & 2478.509	744

Refer to the following plots for 20 dB bandwidth sharp:

Plot D2a: Low Channel 20 dB RF Bandwidth

Plot D2b: Middle Channel 20 dB RF Bandwidth

Plot D2c: High Channel 20 dB RF Bandwidth

For electronic filing, the above plots are saved with filename: d20dB.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.3 Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1)(iii) :

The RF passband of the EUT was divided into 5 approximately equal bands. With the analyzer set to MAX HOLD readings were taken for 2-3 minutes in each band. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

Base Unit, Handset, and Docking Station	
No. of hopping channels	75

Minimum Requirements: at least 15 non-overlapping channels for 2400MHz-2483.5MHz.

For electronic filing, the above plots are saved with filename: bchno.pdf, hchno.pdf, and dchno.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.4 Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1) :

Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit.

[] 25 kHz [x] 20 dB bandwidth of hopping channel: 750kHz

Base Unit	
Channel Separation	900 kHz

Plot B4: Channel Separation

Requirement: The frequency separation is more than 20dB bandwidth of hopping channel.

For electronic filing, the above plots are saved with filename: bfsepa.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1) - Continued:

Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit.

[] 25 kHz [x] 20 dB bandwidth of hopping channel: 804kHz

Handset	
Channel Separation	896 kHz

Plot H4: Channel Separation

Requirement: The frequency separation is more than 20dB bandwidth of hopping channel.

For electronic filing, the above plots are saved with filename: hfsepa.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1) - Continued:

Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit.

[] 25 kHz [x] 20 dB bandwidth of hopping channel: 744kHz

Docking Station	
Channel Separation	900 kHz

Plot D4: Channel Separation

Requirement: The frequency separation is more than 20dB bandwidth of hopping channel.

For electronic filing, the above plots are saved with filename: dfsepa.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.5 Average Channel Occupancy Time, FCC Ref: 15.247(a)(1)(iii)

The spectrum analyzer center frequency was set to one of the known hopping channels. The SWEEP was set to 10ms, the SPAN was set to ZERO SPAN, and the TRIGGER was set to VIDEO. The time duration of the transmission so captured was measured with the MARKER DELTA function.

The SWEEP was then set to the time required by the regulation (20 seconds for 902-928 MHz devices, if the 20dB bandwidth is less than 250kHz, 10 seconds for 902-928 MHz if the 20dB bandwidth is or greater than 250kHz, "0.4 seconds x Number of hopping channels employed" seconds for 2400-2483.5 MHz, 30 seconds for 5725-5850 MHz). The analyzer was set to SINGLE SWEEP, the total ON time was added and compared against the limit (0.4 seconds).

Average 0.4 seconds maximum occupancy in 30 seconds, (0.4sec. x 75) for 2400MHz-2483.5MHz.

Base Unit (4 handsets operation)	
Average Occupancy Time = $940\mu\text{s} \times 4 \times 40$	150.4 ms

Refer to attached spectrum analyzer plots B5a-d.

Handset Unit (Double slot in worst-case)	
Average Occupancy Time = $940\mu\text{s} \times 2 \times 40$	75.2 ms

Refer to attached spectrum analyzer plots H5a-d

Docking Station (Double slot in worst-case)	
Average Occupancy Time = $940\mu\text{s} \times 2 \times 40$	75.2 ms

Refer to attached spectrum analyzer plots D5a-d.

For electronic filing, the above plots are saved with filename: bavetime.pdf, havetime.pdf, davetime.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.6 Out of Band Radiated Emissions, FCC Rule 15.247(c):

In any 100 kHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the following plots for out of band conducted emissions data:

Base Unit:

Plot B6a.1- B6a.2: Low Channel Emissions
Plot B6b.1- B6b.2: Middle Channel Emissions
Plot B6c.1- B6c.2: High Channel Emissions
Plot B6d.1- B6d.2: Modulation Products Emissions*

Handset:

Plot H6a.1- H6a.2: Low Channel Emissions
Plot H6b.1- H6b.2: Middle Channel Emissions
Plot H6c.1- H6c.2: High Channel Emissions
Plot H6d.1- H6d.2: Modulation Products Emissions*

Docking Station:

Plot D6a.1- D6a.2: Low Channel Emissions
Plot D6b.1- D6b.2: Middle Channel Emissions
Plot D6c.1- D6c.2: High Channel Emissions
Plot D6d.1- D6d.2: Modulation Products Emissions*

The plots showed the 2nd harmonic and modulation products at the band edges of 2400 MHz and 2483.5 MHz. In addition, all spurious emission and up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

Furthermore, delta measurement technique for measuring bandedge emissions was incorporated in the test of the edge at 2483.5MHz.

*These 3 plots are shown the worst-case which has been already considered between enable and disable the hopping function of the EUT.

For electronic filing, the above plots are saved with filenames: bobantcon.pdf, hobantcon.pdf, dobantcon.pdf.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.7 Out of Band Radiated Emissions (for emissions in 4.6 above that are less than 20 dB below carrier), FCC Rule 15.247(c):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- ☒ Not required, all emissions more than 20dB below fundamental
- ☐ See attached data sheet

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.8 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.9 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.10 Radiated Emission Configuration Photograph - Base Unit

Worst Case Radiated Emission
at
7320.477 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.11 Radiated Emission Data - Base Unit

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 9.7 dB compare with the peak limit

TEST PERSONNEL:



Tester Signature

Jess Tang, Engineer
Typed/Printed Name

March 24, 2005
Date

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode : TX-Channel 1

Date of Test: January 13-February 19, 2005

Table 1, Base Unit

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	*4803.617	56.9	34	34.0	56.9	28.4	28.5	54	-25.5
H	*12009.042	49.6	34	40.2	55.8	28.4	27.4	54	-26.6
V	*19214.468	41.6	34	45.3	52.9	28.4	24.5	54	-29.5

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode : TX-Channel 44

Date of Test: January 13-February 19, 2005

Table 2, Base unit

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	*4880.318	58.9	34	34.0	58.9	28.4	30.5	54	-23.5
V	*7320.477	61.3	34	37.0	64.3	28.4	35.9	54	-18.1
V	*12200.795	50.7	34	40.2	56.9	28.4	28.5	54	-25.5
V	*19521.271	43.1	34	45.3	54.4	28.4	26.0	54	-28.0

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function, and this is the worst-case of 9.7dB margin at 7320.477MHz.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode : TX-Channel 87

Date of Test: January 13-February 19, 2005

Table 3, Base unit

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	**2478.509	120.1	34	29.1	115.2	28.4	86.8	---	---
V	*4957.019	62.3	34	34.0	62.3	28.4	33.9	54	-20.1
V	*7435.528	61.1	34	37.0	64.1	28.4	35.7	54	-18.3
V	*12392.547	50.8	34	40.2	57.0	28.4	28.6	54	-25.4
V	*19828.075	44.3	34	45.3	55.6	28.4	27.2	54	-26.8
V	*22306.584	41.9	34	45.3	53.2	28.4	24.8	54	-29.2

NOTES: 1. Peak detector is used for the emission measurement.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

** Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.12 Radiated Emission Configuration Photograph - Handset

Worst Case Radiated Emission
at
12200.795 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.13 Radiated Emission Data - Handset

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 12.8 dB compare with the peak limit

TEST PERSONNEL:



Tester Signature

Jess Tang, Engineer
Typed/Printed Name

March 24, 2005
Date

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode : TX-Channel 1

Date of Test: January 13-February 19, 2005

Table 4, Handset

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	*4803.617	56.9	34	34.0	56.9	34.5	22.4	54	-31.6
H	*12009.042	52.3	34	40.2	58.5	34.5	24.0	54	-30.0
H	*19214.468	40.8	34	45.3	52.1	34.5	17.6	54	-36.4

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode : TX-Channel 44

Date of Test: January 13-February 19, 2005

Table 5, Handset

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	*4880.318	57.3	34	34.0	57.3	34.5	22.8	54	-31.2
H	*7320.477	57.8	34	37.0	60.8	34.5	26.3	54	-27.7
H	*12200.795	55.0	34	40.2	61.2	34.5	26.7	54	-27.3
H	*19521.271	40.7	34	45.3	52.0	34.5	17.5	54	-36.5

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function, and this is the worst-case of 12.8dB margin at 12200.795MHz.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode : TX-Channel 87

Date of Test: January 13-February 19, 2005

Table 6, Handset

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	**2478.509	117.3	34	29.1	112.4	34.5	77.9	---	---
H	*4957.019	59.8	34	34.0	59.8	34.5	25.3	54	-28.7
H	*7435.528	55.6	34	37.0	58.6	34.5	24.1	54	-29.9
H	*12392.547	54.2	34	40.2	60.4	34.5	25.9	54	-28.1
H	*19828.075	40.3	34	45.3	51.6	34.5	17.1	54	-36.9
H	*22306.584	39.6	34	45.3	50.9	34.5	16.4	54	-37.6

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.
- ** Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.14 Radiated Emission Configuration Photograph - Docking Station

Worst Case Radiated Emission
at
4880.318 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.15 Radiated Emission Data - Docking Station

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 13.2 dB compare with the peak limit

TEST PERSONNEL:



Tester Signature

Jess Tang, Engineer
Typed/Printed Name

March 24, 2005
Date

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode : TX - Channel 1

Date of Test: January 13-February 19, 2005

Table 7, Docking Station

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	*4803.617	60.2	34	34.0	60.2	34.5	25.7	54	-28.3
V	*12009.042	49.2	34	40.2	55.4	34.5	20.9	54	-33.1
V	*19214.468	41.9	34	45.3	53.2	34.5	18.7	54	-35.3

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode : TX - Channel 44

Date of Test: January 13-February 19, 2005

Table 8, Docking Station

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	*4880.318	60.8	34	34.0	60.8	34.5	26.3	54	-27.7
V	*7320.477	54.1	34	37.0	57.1	34.5	22.6	54	-31.4
V	*12200.795	50.2	34	40.2	56.4	34.5	21.9	54	-32.1
V	*19521.271	41.8	34	45.3	53.1	34.5	18.6	54	-35.4

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function, and this is the worst-case of 13.2dB margin at 4880.318MHz.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
 Model: 23200XXX-A
 Mode : TX - Channel 87

Date of Test: January 13-February 19, 2005

Table 9, Docking Station

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	**2478.509	118.9	34	29.1	114.0	34.5	79.5	---	---
V	*4957.019	60.5	34	34.0	60.5	34.5	26.0	54	-28.0
V	*7435.528	54.2	34	37.0	57.2	34.5	22.7	54	-31.3
V	*12392.547	51.6	34	40.2	57.8	34.5	23.3	54	-30.7
V	*19828.075	42.8	34	45.3	54.1	34.5	19.6	54	-34.4
V	*22306.584	41.1	34	45.3	52.4	34.5	17.9	54	-36.1

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.
- ** Fundamental emission was measured for determining band-edge compliance of using delta measurement technique.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.16 AC Line Conducted Emission, FCC Rule 15.207:

☐ Not required; battery operation only

☒ Test data attached

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.17 Line Conducted Configuration Photograph - Base

Worst Case Line-Conducted Configuration

For electronic filing, the worst case line conducted configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.18 Line Conducted Emission Data

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by more than 20 dB margin

For electronic filing, the worst case line conducted emission data are saved with filename: conduct.pdf

TEST PERSONNEL:



Tester Signature

Jess Tang, Engineer
Typed/Printed Name

March 24, 2005
Date

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.19 Line Conducted Configuration Photograph - Class B Personal Computer Peripheral

Worst Case Line-Conducted Configuration

For electronic filing, the worst case line conducted configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.20 Line Conducted Emission Data

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by more than 20 dB margin

For electronic filing, the worst case line conducted emission data are saved with filename: conduct.pdf

TEST PERSONNEL:



Tester Signature

Jess Tang, Engineer
Typed/Printed Name

March 24, 2005
Date

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.21 Radiated Emissions from Digital Section of Transceiver (Transmitter) and Class B Personal Computer Peripheral, FCC Ref: 15.109

☐ Not required - No digital part

☒ Test results are attached

☐ Included in the separated DOC report.

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode: Talk

Date of Test: January 13-February 19, 2005

Table 10, Base Unit

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	73.726	35.8	16	7.1	26.9	40.0	-13.1
V	147.452	32.2	16	11.6	27.8	43.5	-15.7
V	221.178	32.7	16	11.8	28.5	46.0	-17.5
V	294.905	32.1	16	13.3	29.4	46.0	-16.6
V	368.631	32.3	16	14.9	31.2	46.0	-14.8
V	442.357	29.9	16	16.3	30.2	46.0	-15.8

- NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode: Talk

Date of Test: January 13-February 19, 2005

Table 11, Handset

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	73.726	35.6	16	7.1	26.7	40.0	-13.3
V	147.452	32.1	16	11.6	27.7	43.5	-15.8
V	221.178	32.6	16	11.8	28.4	46.0	-17.6
V	294.905	32.2	16	13.3	29.5	46.0	-16.5
V	368.631	31.9	16	14.9	30.8	46.0	-15.2
V	442.357	30.7	16	15.9	30.6	46.0	-15.4

- NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode: Data Receiving

Date of Test: January 13-February 19, 2005

Table 12, Docking Station

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	126.025	33.4	16	12.6	30.0	43.5	-13.5
H	130.516	35.3	16	12.3	31.6	43.5	-11.9
H	139.516	33.8	16	11.9	29.7	43.5	-13.8
H	175.516	33.1	16	15.5	32.6	43.5	-10.9
H	180.031	34.8	16	16.2	35.0	43.5	-8.5
H	184.516	32.9	16	16.2	33.1	43.5	-10.4
H	198.031	33.7	16	17.3	35.0	43.5	-8.5
H	225.045	46.2	16	11.4	41.6	46.0	-4.4
H	234.019	46.7	16	11.4	42.1	46.0	-3.9
H	243.022	44.6	16	11.4	40.0	46.0	-6.0
H	252.022	41.2	16	12.4	37.6	46.0	-8.4
H	270.022	41.4	16	12.4	37.8	46.0	-8.2
H	288.042	38.5	16	13.3	35.8	46.0	-10.2
H	333.045	36.4	16	14.6	35.0	46.0	-11.0
H	342.042	37.0	16	14.6	35.6	46.0	-10.4
H	360.042	36.5	16	14.9	35.4	46.0	-10.6
H	378.050	36.6	16	15.4	36.0	46.0	-10.0
H	387.043	35.7	16	15.4	35.1	46.0	-10.9
H	423.042	34.7	16	15.9	34.6	46.0	-11.4

- NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A
Mode: Download (with PC)

Date of Test: January 13-February 19, 2005

Table 13, Docking Station

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	36.003	33.4	16	11.2	28.6	40.0	-11.4
V	72.006	39.4	16	7.1	30.5	40.0	-9.5
H	130.578	33.5	16	12.3	29.8	43.5	-13.7
H	139.564	34.7	16	11.9	30.6	43.5	-12.9
H	144.012	35.8	16	11.7	31.5	43.5	-12.0
H	180.015	32.4	16	16.2	32.6	43.5	-10.9
H	216.018	37.6	16	11.8	33.4	46.0	-12.6
H	234.659	38.8	16	11.4	34.2	46.0	-11.8
H	252.021	36.2	16	12.4	32.6	46.0	-13.4
H	324.656	33.8	16	14.3	32.1	46.0	-13.9
H	341.050	32.3	16	14.6	30.9	46.0	-15.1
H	351.629	31.3	16	14.9	30.2	46.0	-15.8

- NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: ATLINKS USA, Inc.
Model: 23200XXX-A

Date of Test: January 13-February 19, 2005

4.22 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The transmitter ON time was determined from the resultant time-amplitude display:

Base Unit:

Duty cycle (DC) = Maximum ON time in 100ms/100ms
= (0.940ms x 4)/100ms for 4 handsets operation

Duty cycle correction, dB = $20 \cdot \log(\text{DC})$
= $20 \cdot \log(0.0376)$
= -28.4 dB

Handset:

Duty cycle (DC) = Maximum ON time in 100ms/100ms
= (0.940ms x 2)/100ms for double slot in worst-case

Duty cycle correction, dB = $20 \cdot \log(\text{DC})$
= $20 \cdot \log(0.0188)$
= -34.5 dB

Docking Station:

Duty cycle (DC) = Maximum ON time in 100ms/100ms
= (0.940ms x 2)/100ms for double slot in worst-case

Duty cycle correction, dB = $20 \cdot \log(\text{DC})$
= $20 \cdot \log(0.0188)$
= -34.5 dB

X	See attached spectrum analyzer chart (s) for transmitter timing Base Unit: Plot B7, Handset: Plot H7, Docking Station: Plot D7
	See transmitter timing diagram provided by manufacturer
	Not applicable, duty cycle was not used.

For electronic filing, the above plots are saved with filenames: bdcc.pdf, hdcc.pdf, ddcc.pdf.

EXHIBIT 5
EQUIPMENT PHOTOGRAPHS

5.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.doc

EXHIBIT 6
PRODUCT LABELLING

6.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and location is saved with filename:
label.pdf

EXHIBIT 7
TECHNICAL SPECIFICATIONS

7.0 **Technical Specifications**

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 8
INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

8.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

Please note that the required FCC Information to the User is saved with filename: FCC information.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 9
SECURITY CODE INFORMATION

9.0 **Security code information**

For electronic filing, security code information is saved with filename: security code information.pdf.

EXHIBIT 10
CONFIDENTIALITY REQUEST

10.0 **Confidentiality Request**

For electronic filing, confidentiality request is saved with filename: request.pdf.