

EXHIBIT A

[FCC Ref. 2.1033(b)(6)]

"Report of Measurements"

**TABLE OF CONTENTS**

**TEST REPORT CONTAINING:**

Exhibit A(1)	Table of Contents
Exhibit A(2)	Product Description
Exhibit A(3)-1 to -3	15.249(a), (b) and (c) Field Strength of Emissions
Exhibit A(4)-1 to -3	Test Equipment List and Facility
Exhibit A(5)-1 to -3	Frequency List Table
Exhibit A(6)	Test Set Up Photo

**PRODUCT DESCRIPTION**

The Model 26999XXX-A is a 900MHz single-line cordless telephone with caller ID and answering machine that operates from 902.100 MHz to 927.850 MHz. This model is identical to previously registered Model 26943XXX-A except for model designation, new base TX antenna, base and handset pcb layout change and base circuit added due to addition of answering machine feature.

The antenna used for the base and handset are permanently attached to the EUT.

Refer to Exhibit A(5)-1 to -3 for complete frequency list.

**15.249 (a), (b) and (c) FIELD STRENGTH OF EMISSIONS****Requirements:**

Fundamental Frequency	Field Strength of Harmonics	15.209	
94dB $\mu$ V	54 dB $\mu$ V/m@ 3m	30-88 MHz	40 dB $\mu$ V/m@ 3m
		88-216 MHz	43.5
		216-960 MHz	46
		Above 960 MHz	54

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in 15.209, whichever is the lesser attenuation.

Emissions that fall in the restricted bands (15.205) must be less than 54dB $\mu$ V/m

**Procedure**

The test procedure used was ANSI STANDARD C63.4-1992 and DA-00-705 using an appropriate spectrum analyzer, as listed in the Test Equipment List. The bandwidth (RBW) of the spectrum analyzer was 100KHz/120KHz up to 1GHz with an appropriate sweep speed. The RBW above 1.0GHz was = 1.0MHz. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the EUT was 24°C with a humidity of 60%.

**Test Data:**

Refer to Exhibit A(3)-2 and -3

**FIELD STRENGTH OF EMISSIONS****MODEL 26999XXX-A  
BASE UNIT**

<b>Emission Frequency MHz</b>	<b>Meter Reading @3m dBμV</b>	<b>Antenna</b>	<b>Cable and ACF dB</b>	<b>Field Strength dBμV/M</b>	<b>FCC Limit dBμV/M</b>	<b>Margin dB</b>	<b>Detector &amp; BW KHz</b>
<b><u>Channel 1</u></b>							
<b>902.100</b>	<b>51.00</b>	<b>RT4 V</b>	<b>33.30</b>	<b>84.30</b>	<b>94</b>	<b>-9.70</b>	<b>PK 100</b>
1353.170	11.00	LP V	36.39	47.39	54	-6.61	PK 1000
1804.200	11.00	Horn V	33.18	44.18	54	-9.82	PK 1000
<b><u>Channel 40</u></b>							
<b>904.040</b>	<b>49.00</b>	<b>RT4 V</b>	<b>33.30</b>	<b>82.30</b>	<b>94</b>	<b>-11.70</b>	<b>PK 100</b>
1356.100	11.00	LP V	36.45	47.45	54	-6.55	PK 1000
1808.080	11.00	Horn V	33.18	44.18	54	-9.82	PK 1000

**FIELD STRENGTH OF EMISSIONS****MODEL 26999XXX-A  
HANDSET**

<b>Emission Frequency MHz</b>	<b>Meter Reading @3m dBμV</b>	<b>Antenna</b>	<b>Cable and ACF dB</b>	<b>Field Strength dBμV/M</b>	<b>FCC Limit dBμV/M</b>	<b>Margin dB</b>	<b>Detector &amp; BW KHz</b>
<b><u>Channel 1</u></b>							
<b>925.900</b>	<b>55.60</b>	<b>RT4 V</b>	<b>33.40</b>	<b>89.00</b>	<b>94</b>	<b>-5.00</b>	<b>PK 100</b>
1388.700	9.00	LP V	36.61	45.61	54	-8.39	PK 1000
1851.800	11.00	Horn V	33.06	44.06	54	-9.94	PK 1000
2314.780	9.00	Horn V	33.22	42.22	54	-11.78	PK 1000
<b><u>Channel 40</u></b>							
<b>927.860</b>	<b>55.60</b>	<b>RT4 V</b>	<b>33.40</b>	<b>89.00</b>	<b>94</b>	<b>-5.00</b>	<b>PK 100</b>
1391.820	9.00	LP V	36.61	45.61	54	-8.39	PK 1000
1855.720	11.00	Horn V	33.06	44.06	54	-9.94	PK 1000
2319.690	9.00	Horn V	33.22	42.22	54	-11.78	PK 1000

**TEST FACILITY AND EQUIPMENT LIST**

**FACILITIES:**

Radiated      ANSI C63.4 (FCC OET/55) open field 3 metre test range. This test range is protected from the cold and moisture by a non-conductive enclosure.

**EQUIPMENT**

Anritsu 2601A Spectrum Analyzer  
Advantest R3261A Spectrum Analyzer  
Hewlett-Packard RF generator # 8640 B with an 002 doubler  
A.H. Systems biconical antenna; ..... 20 MHz to 330 MHz  
A.H. Systems log periodic antenna; ..... 300 MHz to 1.8 GHz  
Compliance Design P950 Preamp (16 dB) ... 25 MHz to 1.0 GHz

**NOTE:**

The Anritsu 2601A Spectrum Analyzer and the Advantest R3261A Spectrum Analyzer are calibrated annually, and that calibration is directly traceable to the National Research Council of Canada. (NRC)  
This equipment is only used by qualified technicians and only for the purpose of EMI measurements. The three metre test range has been carefully evaluated to the ANSI document C63.4 and will be remeasured for reflections and losses every three years.

**ADDITIONAL TEST EQUIPMENT LIST**

1. Spectrum Analyzer: HP 8591EM, S/N 3639A00995, (9KHz - 1.8GHz), Calibration Due June 2005
2. Spectrum Analyzer: ANRITSU 2601A, S/N MT64544, (10KHz - 2.2GHz), Calibration Due June 2005
3. Spectrum Analyzer: IFR AN940, S/N 635001039, (9KHz - 26.5GHz), Calibration Due April 2006
4. Preamp: HP 8449B, S/N 3008A00378, (1 - 26.5GHz), Calibration Due August 2005
5. Horn Antenna: Q-PAR 6878/24, S/N 1721, (1.5-18GHz)
6. Horn Antenna: A. H. Systems SAS 572, S/N 164 (18 - 26.5GHz)
7. Line Impedance Stabilization Network.: Marstech, Calibration Due July 2005
8. Horn Antenna: Radar System (Flange 3/4" Square) MIL F 3922/68 (26.5 - 40GHz)
9. OML Mixer: M28HWD, S/N Ka31114-1 (26.5 - 40GHz), Calibration Due Nov. 2005
10. OML Diplexer: DPL.313A (Unit plugs into M28HWD)
11. Semflex Cable: Used with M28HWD and DPL.313A



**FEDERAL COMMUNICATIONS COMMISSION**

Laboratory Division  
7435 Oakland Mills Road  
Columbia, MD 21046

August 22, 2003

Registration Number: 90578

Electrohome Electronics Ltd.  
809 Wellington St. N.  
Kitchener, Ontario, N2G 4J6  
Canada  
Attention: Tuat Huynh

Re: Measurement facility located at Roseville  
3 meter site  
Date of Renewal: August 22, 2003

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website [www.fcc.gov](http://www.fcc.gov) under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,



Ms. Phyllis Parrish  
Information Technician