FCC Part 15 EMI TEST REPORT

of

E.U.T.: 5.8GHz DECT Multi-handset

Answering System

FCC ID. ::G9H2-8032A

MODEL: 28032XXX-A

(extra handset+charger)

for

APPLICANT: Thomson Inc.

ADDRESS : 10330 North Meridian Street Indianapolis, IN 46290

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN

NO.34, LIN 5, DINGFU TSUEN, LINKOU SHIANG TAIPEI COUNTY, TAIWAN, 24442, R.O.C.

Tel: (02)26023052 Fax: (02)26010910 http://www.etc.org.tw; e-mail: r00@etc.org.tw

Report Number: 07-05-RBF-156-02

TEST REPORT CERTIFICATION

Applicant : Thomson Inc.

10330 North Meridian Street Indianapolis, IN 46290

Manufacturer : Huiyang CCT Telecomunications Products Co., Ltd.

CCT Techonology Park, San He Economic Development Zone, Huiyang District, Huizhou City, Guangdong Province, PRC

Description of EUT

a) Type of EUT : 5.8GHz DECT Multi-handset Answering System

b) Trade Name : GE

c) Model No. : 28032XXX-A (extra handset+charger)

d) Power Supply : Handset Battery: DC3.6V 550mAh

Charger's Adaptor: I/P 120Vac 60Hz 2.4W

O/P 7.5Vdc 150mA

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C (2006)

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note: 1. The result of the testing report relate only to the item tested.

2. The testing report shall not be reproduced expect in full, without the written approval of ETC.

Date Test Item Received : Mar. 30, 2007
Date Test Campaign Completed : Jul. 03, 2007
Date of Issue : Jul. 03, 2007

Test Engineer :

Falcon Shi

Approve & Authorized Signer:

Will Yauo, Manager

EMC Dept. II of ELECTRONICS TESTING CENTER, TAIWAN

Table of Contents	Page
1 GENERAL INFORMATION	1
1.1 Product Description	1
1.2 Characteristics of Device	1
1.3 Test Methodology	1
1.4 Test Facility	1
2 PROVISIONS APPLICABLE	2
2.1 Definition	2
2.2 Requirement for Compliance	3
2.3 Restricted Bands of Operation	5
2.4 Labeling Requirement	5
2.5 User Information	6
3. SYSTEM TEST CONFIGURATION	7
3.1 Justification	7
3.2 Devices for Tested System	7
4 RADIATED EMISSION MEASUREMENT	8
4.1 Applicable Standard	8
4.2 Measurement Procedure	8
4.3 Measuring Instrument	10
4.4 Radiated Emission Data	
4.5 Field Strength Calculation	
4.6 Photos of Radiation Measuring Setup	16
5 CONDUCTED EMISSION MEASUREMENT	18
5.1 Standard Applicable	
5.2 Measurement Procedure	
5.3 Conducted Emission Data	
5.4 Result Data Calculation	21
5.5 Conducted Measurement Equipment	21
5.6 Photos of Conduction Measuring Setup	22
6 ANTENNA REQUIREMENT	23
6.1 Standard Applicable	23
6.2 Antenna Construction and Directional Gain	23
7 EMISSION BANDWIDTH MEASUREMENT	24
7.1 Standard Applicable	24
7.2 Measurement Procedure	24

7.3 Measurement Equipment	24
7.4 Measurement Data	25
8 OUTPUT POWER MEASUREMENT	29
8.1 Standard Applicable	29
8.2 Measurement Procedure	29
8.3 Measurement Equipment	29
8.4 Measurement Data	30
9 100 KHZ BANDWIDTH OF BAND EDGES MEASUREMENT	34
9.1 Standard Applicable	34
9.2 Measurement Procedure	34
9.3 Measurement Equipment	34
9.4 Measurement Data	35
10 POWER DENSITY MEASUREMENT	38
10.1 Standard Applicable	38
10.2 Measurement Procedure	38
10.3 Measurement Equipment	38
10.4 Measurement Data	39
11. OUT-OF-BAND CONDUCTED EMISSION MEASUREMENT	43
11.1 Standard Applicable	43
11.2 Measurement Procedure	43
11.3 Measurement Equipment	43
11.4 Measurement Data	44

Sheet 1 of 50Sheets FCC ID.: G9H2-8032A

1 GENERAL INFORMATION

1.1 Product Description

a) Type of EUT : 5.8GHz DECT Multi-handset Answering System

b) Trade Name : GE

c) Model No. : 28032XXX-A (extra handset+charger)

d) Power Supply : Handset Battery:DC3.6V 550mAh

Charger's Adaptor: I/P 120Vac 60Hz 2.4W

O/P 7.5Vdc 150mA

1.2 Characteristics of Device

5.8GHz DECT Multi-handset Answering System

1.3 Test Methodology

Both conducted and radiated emissions were performed according to the procedures illustrated in ANSI C63.4 (2003). Other required measurements were illustrated in separate sections of this test report for details.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at NO.34, LIN 5, DINGFU TSUEN, LINKOU SHIANG TAIPEI COUNTY, TAIWAN, 24442, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Oct. 20, 2005.

Sheet 2 of 50Sheets FCC ID.: G9H2-8032A

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device:

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business of industrial environment. Example of such devices that are marketed for the general public.

Note: A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

Sheet 3 of 50Sheets FCC ID.: G9H2-8032A

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

Except for Class A digital devices, for equpment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a $50\mu\text{H}/50$ ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

^{*} Decreases with the logarithm of the frequency

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μV/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Sheet 4 of 50Sheets FCC ID.: G9H2-8032A

(4) Bandwidth Requirement

For direct sequence system, according to 15.247(a)(2), the minimum 6dB bandwidth shall be at least 500 kHz.

(5) Output Power Requirement

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

(7) Power Density Requirement

According to 15.247(d), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.15
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

^{**:} Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Sheet 6 of 50Sheets FCC ID.: G9H2-8032A

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -- Reorient or relocate the receiving antenna.
- -- Increase the separation between the equipment and receiver.
- -- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- -- Consult the dealer or an experienced radio / TV technician for help.

Sheet 7 of 50Sheets FCC ID.: G9H2-8032A

3. SYSTEM TEST CONFIGURATION

3.1 Justification

For both radiated and conducted emissions below 1 GHz, the system was configured for testing in a typical fashion as a customer would normally use it. The peripherals other than EUT were connected in normally standing by situation. Measurement was performed under the condition that a computer program was exercised to simulate data communication of EUT, and the transmission rate was set to maximum allowed by EUT. Three highest emissions were verified with varying placement of the transmitting antenna connected to EUT to maximize the emission from EUT.

For conducted emissions, only measured on TX and RX operation, for the digital circuits portion also function normally whenever TX or RX is operated. For radiated emissions, whichever RF channel is operated, the digital circuits function identically. As the reason, measurement of radiated emissions from digital circuits is only performed with channel 7 by transmitting mode.

During the preliminary test, the worse case is the antenna with a cable, and data presented in this test report just shows the worse case.

3.2 Devices for Tested System

Device	Manufacture	Model / FCC ID.	Cable Description
5.8GHz DECT	Huiyang CCT	28032XXX-A (extra	1.8m Unshielded AC
Multi-handset	Telecomunicatio	handset+charger)/	Adaptor Power Cord (Charger)
Answering	ns Products Co.,	G9H2-8032A	
System *	Ltd.		

Remark "*" means equipment under test.

Sheet 8 of 50Sheets FCC ID.: G9H2-8032A

4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §15.109(a). For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and direct sequence spread spectrum, and the out band emission shall be comply with §15.247 (c)

4.2 Measurement Procedure

- 1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
- 2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
- 4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
- 5. Repeat step 4 until all frequencies need to be measured were complete.
- 6. Repeat step 5 with search antenna in vertical polarized orientations.
- 7. Check the three frequencies of highest emission with varying the placement of cables associated with EUT to obtain the worse case and record the result.





Figure 1: Frequencies measured below 1 GHz configuration

Figure 2: Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement:

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Test Receiver	Rohde & Schwarz	ESVS30	2007/03/22	2008/03/20
Spectrum	Advantest	R3162	2007/01/29	2008/01/28
Bi-Log Antenna	Schaffner	CBL 6111C	2006/12/22	2007/12/21
Log-periodic Antenna	EMCO	3146	2006/10/13	2007/10/12
Biconical Antenna	EMCO	3110B	2007/02/01	2008/01/31
Double Ridged Antenna	EMCO	3115	2007/04/27	2008/04/26
Amplifier	HP	8449B	2006/10/09	2007/10/08
Amplifier	HP	83051A	2007/05/06	2008/05/05
Amplifier	HP	8447D	2006/10/09	2007/10/08
Spectrum	Rohde & Schwarz	FSP40	2006/08/08	2007/08/07

Measuring instrument setup in measured frequency band when specified detector function is used:

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
30 to 1000	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

ETC Report No.: 07-05-RBF-156-02

Sheet 11 of 50Sheets FCC ID.: G9H2-8032A

4.4 Radiated Emission Data

4.4.1 RF Portion

Mode: Handset Unit

a) CH Low

Operation Mode : <u>Receiving / Transmitting</u>

Fundamental Frequency: <u>5816.830</u> MHz (Local Frequency: <u>5816.830</u> MHz)

Test Date : Jun. 26, 2007 Temperature : 23 °C Humidity : 55 %

Frequency	Reading (dBuV)			Factor	Result	: @3m	Limit	@3m	Margin	Table	Ant.	
	F	1	\	/	(dB)	(dBu	V/m)	(dBu	(dBuV/m)		Deg.	High
(MHz)	Peak	Ave	Peak	Ave	Corr.	Peak	Ave	Peak	Ave	(dB)	(Deg.)	(m)
* 5816.830					4.5			74.0	54.0			
* 11633.660					7.2			74.0	54.0			
* 17450.490								74.0	54.0			
* 23267.320		-				-	-	74.0	54.0		-	-
* 29084.150		-				-	-	74.0	54.0		-	-
11633.660	52.8	32.9	49.1	32.8	7.2	60.0	40.1	74.0	54.0	-13.9	67	1.5
17450.490	55.3	33.3	55.8	33.5	16.4	72.2	49.9	74.0	54.0	-1.8	86	1.3
23267.320		-			10.6	-	-	74.0	54.0		-	-
29084.150								74.0	54.0			
34900.980								74.0	54.0			

Note:

- 1. Item of margin shown in above table refer to average limit.
- 2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.
- 3. Remark "---" means that the emissions level is too low to be measured.
- 4. Item "Margin" referred to Average limit while there is only peak result.
- 5. The expanded uncertainty of the radiated emission tests is 3.53 dB.
- 6. Remark "*" means the receiving local frequency and the harmonics.

Sheet 12 of 50Sheets FCC ID.: G9H2-8032A

b) CH Middle

Operation Mode : <u>Receiving / Transmitting</u>

Fundamental Frequency : <u>5829.390</u> MHz (Local Frequency : <u>5829.390</u> MHz)

Test Date : Jun. 26, 2007 Temperature : 23 °C Humidity : 55 %

Frequency	Reading (dBuV)			Factor	Result	@3m	Limit	@3m	Margin	Table	Ant.	
	F	1	١	/	(dB)	(dBu	V/m)	(dBu	V/m)		Deg.	High
(MHz)	Peak	Ave	Peak	Ave	Corr.	Peak	Ave	Peak	Ave	(dB)	(Deg.)	(m)
* 5829.390					4.5			74.0	54.0			
* 11658.780					7.2			74.0	54.0			
* 17488.170								74.0	54.0			
* 23317.560								74.0	54.0			
* 29146.950		1	-	1		1	-	74.0	54.0			
11658.780	53.5	33.1	51.0	33.0	7.2	60.7	40.3	74.0	54.0	-13.3	97	1.3
17488.170	55.5	33.3	57.0	32.9	16.4	73.4	49.7	74.0	54.0	-0.6	102	1.6
23317.560					10.6			74.0	54.0			
29146.950								74.0	54.0			
34976.340							-	74.0	54.0			

Note:

- 1. Item of margin shown in above table refer to average limit.
- 2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.
- 3. Remark "---" means that the emissions level is too low to be measured.
- 4. Item "Margin" referred to Average limit while there is only peak result.
- 5. The expanded uncertainty of the radiated emission tests is 3.53 dB.
- 6. Remark "*" means the receiving local frequency and the harmonics.

Sheet 13 of 50Sheets FCC ID.: G9H2-8032A

c) CH High

Operation Mode : <u>Receiving / Transmitting</u>

Fundamental Frequency: <u>5839.795</u> MHz (Local Frequency: <u>5839.795</u> MHz)

Test Date : Jun. 26, 2007 Temperature : 23 °C Humidity : 55 %

Frequency	Reading (dBuV)			Factor	Result	@3m	Limit	@3m	Margin	Table	Ant.	
	F	1	١	/	(dB)	(dBu	V/m)	(dBu	V/m)		Deg.	High
(MHz)	Peak	Ave	Peak	Ave	Corr.	Peak	Ave	Peak	Ave	(dB)	(Deg.)	(m)
* 5839.795					4.5			74.0	54.0			
* 11679.590					7.2			74.0	54.0			
* 17519.385								74.0	54.0			
* 23359.180								74.0	54.0			
* 29198.975								74.0	54.0			
11679.590	54.8	33.0	49.8	32.6	7.2	62.0	40.2	74.0	54.0	-12.0	104	1.2
17519.385	55.6	33.2	54.4	32.6	16.6	72.2	49.8	74.0	54.0	-1.8	88	1.5
23359.180					10.6			74.0	54.0			
29198.975								74.0	54.0			
35038.770						-	-	74.0	54.0			

Note:

- 1. Item of margin shown in above table refer to average limit.
- 2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.
- 3. Remark "---" means that the emissions level is too low to be measured.
- 4. Item "Margin" referred to Average limit while there is only peak result.
- 5. The expanded uncertainty of the radiated emission tests is 3.53 dB.
- 6. Remark "*" means the receiving local frequency and the harmonics.

4.4.2 Other Emission

A. Mode: Handset Unit On Line

a) Emission frequencies below 1 GHz

Operation Mode: Receiving / Transmitting

Test Date : Jun. 21, 2007 Temperature : 22 °C Humidity : 54 %

Frequency	Ant-Pol	Meter	Corrected	Result	Limit	Margin	Table	Ant.
		Reading	Factor	@3m	@3m	(dB)	Degree	High
(MHz)	H/V	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)		(Deg.)	(m)
118.020	Н	38.1	-11.0	27.1	43.5	-16.4	78	2.2
166.620	Н	31.9	-9.2	22.7	43.5	-20.8	182	1.8
179.580	Н	32.6	-9.1	23.5	43.5	-20.0	296	1.4
227.370	Н	31.4	-5.3	26.1	46.0	-19.9	54	1.5
250.050	Н	31.2	-3.9	27.3	46.0	-18.7	238	1.6
287.580	Н	31.9	-2.2	29.7	46.0	-16.3	21	1.7

Note:

- 1. Remark "---" means that the emissions level is too low to be measured.
- 2. The expanded uncertainty of the radiated emission tests is 3.53 dB.
 - b) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.

B. Mode: Handset Unit Charging

a) Emission frequencies below 1 GHz

Operation Mode: Receiving / Transmitting

Test Date : Jun. 21, 2007 Temperature : 22 °C Humidity : 54 %

Frequency	Ant-Pol	Meter	Corrected	Result	Limit @3m	Margin	Table	Ant.
		Reading	Factor	@3m	(dBuV/m)	(dB)	Degree	High
(MHz)	H/V	(dBuV)	(dB)	(dBuV/m)			(Deg.)	(m)
178.770	V	32.0	-9.1	22.9	43.5	-20.6	67	1.2
188.490	V	32.1	-8.5	23.6	43.5	-19.9	102	1.6
208.740	V	31.6	-6.6	25.0	43.5	-18.5	183	1.4
238.980	V	31.6	-4.6	27.0	46.0	-19.0	133	1.5
257.610	V	32.3	-3.9	28.4	46.0	-17.6	96	1.6
268.140	V	32.6	-3.7	28.9	46.0	-17.1	38	1.5

Note:

- 1. Remark "---" means that the emissions level is too low to be measured.
- 2. The expanded uncertainty of the radiated emission tests is 3.53 dB.
 - b) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

where

Corrected Factor = Antenna FACTOR + Cable Loss + High Pass Filter Loss - Amplifier Gain

4.6 Photos of Radiation Measuring Setup













5 CONDUCTED EMISSION MEASUREMENT

5.1 Standard Applicable

For unintentional and intentional device, Line Conducted Emission Limits are in accordance to § 15.107(a) and § 15.207(a) respectively. Both Limits are identical specification.

5.2 Measurement Procedure

- 1. Setup the configuration per figure 3.
- 2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
- 3. Record the 6 or 8 highest emissions relative to the limit.
- 4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
- 5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
- 6. Repeat all above procedures on measuring each operation mode of EUT.

Vertical Reference
Ground Plane

Test Receiver

EUT

Reference Ground Plane

Figure 3: Conducted emissions measurement configuration

5.3 Conducted Emission Data


Operation Mode : <u>Handset Unit Charging</u>

Test Date : Jun. 21, 2007 Temperature : 22 °C Humidity : 54 %

Mode: <u>Handset Unit Charging</u> Neutral

Frequency	Meter R	Reading	Factor	Res	ult	Lin	nit	Mar	gin
	(dB	μV)	ractor	(dB	μV)	(dB	μV)	(dB	μV)
(MHz)	Q.P	AVG	(dB)	Q.P	AVG	Q.P	AVG	Q.P	AVG
0.189	17.1		0.2	17.3		64.1	54.1	-46.8	
3.792	10.7		0.6	11.3		56.0	46.0	-44.7	
4.972	11.0		0.6	11.6		56.0	46.0	-44.4	
19.445	14.6		1.4	16.0		60.0	50.0	-44.0	
22.601	12.8		1.5	14.3		60.0	50.0	-45.7	
27.839	14.2		1.9	16.1		60.0	50.0	-43.9	

Note: The expanded uncertainty of the conducted emission tests is 2.45 dB.




Mode: Handset Unit Charging

1	.1	n	e
- 1	л	п	C

Frequency	Meter R	Reading	Factor	Res	ult	Lin	nit	Mar	gin
	(dB	μV)	1 uctor	(dB	μV)	(dB	μV)	(dB	μV)
(MHz)	Q.P	AVG	(dB)	Q.P	AVG	Q.P	AVG	Q.P	AVG
0.189	17.0		0.2	17.2		64.1	54.1	-46.9	
4.914	11.1		0.6	11.7		56.0	46.0	-44.3	
18.066	13.1		1.3	14.4		60.0	50.0	-45.6	
26.894	13.5		1.8	15.3		60.0	50.0	-44.7	
27.207	12.9		1.8	14.7		60.0	50.0	-45.3	
28.636	13.7		2.0	15.7		60.0	50.0	-44.3	

Note: The expanded uncertainty of the conducted emission tests is $2.45\ dB$.



Sheet 21 of 50Sheets FCC ID.: G9H2-8032A

5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$RESULT = READING + LISN FACTOR$$

Assume a receiver reading of 22.5 dB μ V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB μ V.

RESULT = 22.5 + 0.1 = 22.6 dB
$$\mu$$
 V
Level in μ V = Common Antilogarithm[(22.6 dB μ V)/20]
= 13.48 μ V

5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test.

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date	
EMI Test Receiver	Rohde & Schwarz	ESCI	2006/12/25	2007/12/24	
LISN	EMCO	3825/2	2006/10/09	2007/10/08	
LISN	Rohde & Schwarz	ESH2-Z5	2006/09/13	2007/09/12	

5.6 Photos of Conduction Measuring Setup

Mode: Handset Unit Charging





6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to §15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.2 Antenna Construction and Directional Gain

The antenna is L -ANTENNA type, no consideration of replacement. Please see photos submitted in Exhibit B.

Sheet 24 of 50Sheets FCC ID.: G9H2-8032A

7 EMISSION BANDWIDTH MEASUREMENT


7.1 Standard Applicable

According to 15.247(a)(2), for direct sequence system, the minimum 6dB bandwidth shall be at least 500 kHz.

7.2 Measurement Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Figure 4: Emission bandwidth measurement configuration.



7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP 40	2006/08/08	2007/08/07
Attenuator	WEINSCHEL	AS3696	2006/08/07	2007/08/06
	ENGINEERING			

Sheet 25 of 50Sheets FCC ID.: G9H2-8032A

7.4 Measurement Data


Test Date: Jun. 26, 2007 Temperature: 23 °C Humidity: 55 %

Mode: Handset Unit

a) Channel Low : 6 dB Emission Bandwidth is
b) Channel Middle : 6 dB Emission Bandwidth is
c) Channel High : 6 dB Emission Bandwidth is
980 KHz


Note: The expanded uncertainty of the emission bandwidth tests is 1500Hz.

Handset Unit/ Mode: Channel Low




Date: 26.JUN.2007 13:35:37

Handset Unit/ Mode: Channel Middle



Date: 26.JUN.2007 14:03:23

Handset Unit/ Mode: Channel High



Date: 26.JUN.2007 14:24:01

Sheet 29 of 50Sheets FCC ID.: G9H2-8032A

8 OUTPUT POWER MEASUREMENT


8.1 Standard Applicable

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Measurement Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in figure 5 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3. Set RBW of spectrum analyzer to 1 MHz and VBW to 1 MHz.
- 4. Use channel power function and record the level displayed.
- 5. Repeat above procedures until all frequencies measured were complete.

Figure 5: Output power and measurement configuration.



8.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP 40	2006/08/08	2007/08/07
Attenuator	WEINSCHEL	AS3696	2006/08/07	2007/08/06
	ENGINEERING			

Sheet 30 of 50Sheets FCC ID.: G9H2-8032A

8.4 Measurement Data


Test Date: Jun. 26, 2007 Temperature: 23 °C Humidity: 55 %

Mode: Handset Unit

a) Channel Low
 b) Channel Middle
 c) Channel High
 d) Cutput Peak Power is 19.78 dBm = 95.060 mW
 d) Channel High
 e) Output Peak Power is 19.63 dBm = 91.833 mW


Note: The expanded uncertainty of the output power tests is 2dB.

Handset Unit/ Mode: Channel Low




Date: 26.JUN.2007 11:50:26

Handset Unit/ Mode: Channel Middle



Date: 26.JUN.2007 11:46:26

Handset Unit/ Mode: Channel High



Date: 26.JUN.2007 11:48:03

Sheet 34 of 50Sheets FCC ID.: G9H2-8032A

9 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT

9.1 Standard Applicable

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

9.2 Measurement Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in figure 5 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3. Set both RBW of spectrum analyzer to 100kHz and VBW to 1 MHz with a convenient frequency span including 100kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP 40	2006/08/08	2007/08/07
Attenuator	WEINSCHEL	AS3696	2006/08/07	2007/08/06
	ENGINEERING			

ETC Report No.: 07-05-RBF-156-02 Sheet 35 of 50Sheets FCC ID.: G9H2-8032A

9.4 Measurement Data

Test Date: Jun. 26, 2007 Temperature: 23 °C Humidity: 55 %

Mode: Handset Unit


a) Lower Band Edge: All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

b) Upper Band Edge: All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.


Note: 1. Please see appendix 4 for Plotted Data


2. The expanded uncertainty of the 100 khz bandwidth of band edges tests is 2dB.

Handset Unit/Lowest



Date: 26.JUN.2007 13:57:51





Date: 26.JUN.2007 14:49:12

Sheet 38 of 50Sheets FCC ID.: G9H2-8032A

10 POWER DENSITY MEASUREMENT

10.1 Standard Applicable

According to 15.247(d), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

10.2 Measurement Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set EUT to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3. Adjust the center frequency of spectrum analyzer on highest level appearing on spectral display within a 300 kHz frequency span.
- 4. Set the spectrum analyzer on a 3 kHz resolution bandwidth and 300 kHz video bandwidth as well as max hold function.
- 5. Repeat above procedures until all measured frequencies were complete.

10.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP 40	2006/08/08	2007/08/07
Attenuator	WEINSCHEL	AS3696	2006/08/07	2007/08/06
	ENGINEERING			

Sheet 39 of 50Sheets FCC ID.: G9H2-8032A

10.4 Measurement Data


Test Date: Jun. 26, 2007 Temperature: 23 °C Humidity: 55 %

Mode: Handset Unit

a) Channel Low : Maximun Power Density of 3 kHz Bandwidth is -13.76 + 14.77 =-1.01dBm
 b) Channel Middle : Maximun Power Density of 3 kHz Bandwidth is -13.70 + 14.77 =-1.07dBm
 c) Channel High : Maximun Power Density of 3 kHz Bandwidth is -14.06 + 14.77 =-0.73dBm


Note: The expanded uncertainty of the power density tests is 2dB.

Handset Unit/ Mode: Channel Low




Date: 26.JUN.2007 13:55:34

Handset Unit/ Mode: Channel Middle



Date: 26.JUN.2007 14:22:30

Handset Unit/ Mode: Channel High



Date: 26.JUN.2007 14:44:09

Sheet 43 of 50Sheets FCC ID.: G9H2-8032A

11. OUT-OF-BAND CONDUCTED EMISSION MEASUREMENT

11.1 Standard Applicable

According to 15.247(c), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

11.2 Measurement Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3. Use the following spectrum analyzer settings:
 - Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

 $VBW \ge RBW$

Sweep = auto

Detector function = peak

Trace = max hold

- 4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. Plot the result on the screen of spectrum analyzer.
- 5. Repeat above procedures until all measured frequencies were complete.

11.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP 40	2006/08/08	2007/08/07
Attenuator	WEINSCHEL	AS3696	2006/08/07	2007/08/06
	ENGINEERING			

Sheet 44 of 50Sheets FCC ID.: G9H2-8032A

11.4 Measurement Data

Test Date: Jun. 26, 2007 Temperature: 23 °C Humidity: 55 %

Mode: Handset Unit

Model: CH Low

- a) 1 GHz to 6 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 6 GHz to 40 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Model: CH Middle


- a) 1 GHz to 6 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 6 GHz to 40 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Model: CH High


- a) 1 GHz to 6 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 6 GHz to 40 GHz frequency band: All emissions are attenuated more than 20dB from the carrier

Note: The expanded uncertainty of the out-of-band conducted emission tests is 2dB.

Mode: Handset Unit




Date: 26.JUN.2007 13:59:48




Date: 26.JUN.2007 14:00:14


Sheet 47 of 50Sheets FCC ID.: G9H2-8032A




Date: 26.JUN.2007 14:01:59



Date: 26.JUN.2007 14:01:25



Date: 26.JUN.2007 14:52:02



Date: 26.JUN.2007 14:54:13