

Marstech Limited

11 Kelfield Street, Etobicoke, Ontario, Canada, M9W 5A1
Telephone (416) 246-1116, Fax (416) 246-1020

Authorized by:
Professional Engineers
Ontario



Engineering &
Administrative



Testing For FCC
Submissions/Verifications

Industry Canada
Industry Canada
Approved Test Facility



TEST REPORT			
REPORT DATE:		14 April 2004	
REPORT NO:		24002D	
CONTENTS:	See Table of Contents		
SUBMITTOR:	ATLINKS USA, Inc. 101 West 103 rd Street Indianapolis, IN 46290-1102 USA		
SUBJECT:	Model No:	25825XXX-A (Base) [identical to previously registered Model 25830XXX-M (Base) except for model designation, pcb layout change, component/value changes and additional features such as answering machine and handset speakerphone and supports 2 handsets. This also covers Model 25826XXX-A which is identical to Model 25825XXX-A except for model designation and it is sold with charger and extra handset (i.e. Model 25802XXX-A)]	
	FCC ID:	G9HFH58R19	
TEST SPECIFICATION	FCC CFR 47 Part 15 FCC DA 00-705 "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems." NOTE: Tests Conducted Are "Type" Tests.		
DATE SAMPLE RECEIVED:	15 January 2004 and 07 April 2004	DATE TESTED:	20 January 2004; 19 & 20 February 2004; and 08 April 2004
RESULTS:	Equipment tested complies with referenced specifications. Please also note that the Model 25825XXX-A (also covers Model 25826XXX-A) meets the new rules (150KHz to 30MHz) FCC Power Line Conducted Limits.		
ALTERATIONS	None		
Tested by:		Approved by:	
	Edward Chang	Date:	14 April 2004
THIS REPORT SHALL NOT BE REPRODUCED, EXCEPT IN FULL, WITHOUT THE WRITTEN APPROVAL OF MARSTECH LIMITED. This report was prepared by Marstech Limited for the account of the "Submittor". The material in it reflects Marstech's judgement in light of the information available to it at the time of preparation. Any use which a Third Party makes of this report, or any reliance on decisions to be made based on it, are the responsibility of such Third Parties. Marstech accepts no responsibility for damages, if any, suffered by any Third Party as a result of decisions made or actions based on this report			

MARSTECH LIMITED

TECHNICAL REPORT - FCC 2.1033(b)

Applicant

ATLINKS USA, Inc.
101 West 103rd Street
Indianapolis, IN
46290-1102 USA

FCC Identifier

G9HFH58R19

Manufacturer

Dongguan Humen Taida Electric Co. Ltd.
National Highway 107, Cuntou Cun, Humen Town
Dongguan, Guangdong, China

TABLE OF CONTENTS

<u>Exhibit</u>	<u>Description</u>	<u>FCC Ref.</u>	<u>Page</u>
A	Installation and Operating Instructions Furnished to the User.	2.1033(b)(3)	Exhibit A Exhibit A(1)
B	Description of Circuit Functions and Frequency Hopping Description Statement of Security Code	2.1033(b)(4)	Exhibit B Exhibit B(1)-1 to -7 Exhibit B(2)-1 to -6 Exhibit B(3)
C	Block Diagram Schematic Diagram	2.1033(b)(5)	Exhibit C Exhibit C(1)-1 to -2 Exhibit C(2)-1 to -9
D	Report of Measurements	2.1033(b)(6)	Exhibit D
E	Photographs Label Equipment -	2.1033(b)(7)	Exhibit E Exhibit E(1)-1 to -6 Exhibit E(2)-1 to -12
F	Verification Report (Not Part of Certification Package)		Exhibit F(1)-1 to -3

EXHIBIT D

[FCC Ref. 2.1033(b)(6)]

"Report of Measurements"

TABLE OF CONTENTS

TEST REPORT CONTAINING:

Exhibit D(1)	Table of Contents
Exhibit D(2)	Product Description
Exhibit D(3)-1	15.107(a) Power Line Conducted Interference
Exhibit D(3)-2 to -4	15.205(c)/15.209 Spurious Radiated Emissions in Restricted Bands and Field Strength of Emissions
Exhibit D(3)-5	15.247(a)(1) Hopping Channel Separation
Exhibit D(3)-6	15.247(a)(1) Frequency Hopping Systems (Channel Bandwidth)
Exhibit D(3)-7	15.247(a)(1) Frequency Hopping Systems (Dwell Time)
Exhibit D(3)-8	15.247(b)(1) Maximum Peak Output Power (ERP)
Exhibit D(3)-9	15.247(c) Bandwidth of Band Edge Measurement
Exhibit D(3)-10 to -11	15.247(g) and 15.247(h)
Exhibit D(4)-1 to -2	Test Equipment List and Facility
Exhibit D(5)	3M Test Site FCC Letter
Exhibit D(6)-1 to -2	Test Setup Photos
Exhibit D(7)	Test Setup Diagram for AC Conducted Line Testing
Exhibit D(8)-1 to -2	FCC RF Exposure Requirements
Appendix 1 to 4	Plots for Power Line Conducted Interference
Appendix 5 to 7	Plots for Hopping Channel Separation
Appendix 8 to 10	Plots for 20 dB Bandwidth
Appendix 11 to 12	Plots for Dwell Time
Appendix 13 to 14	Plots for Band Edge

PRODUCT DESCRIPTION

The Model 25825XXX-A (base unit) is a 5.8GHz single line, spread spectrum, frequency hopping, cordless telephone with answering machine, that operates from 5755.104 to 5819.040 MHz. This model is identical to previously registered Model 25830XXX-M (base unit) except for model designation, pcb layout changed, component/value changes, addition of answering machine and supports 2 handsets. This also covers Model 25826XXX-A which is identical to Model 25825XXX-A except for model designation and it is sold with charger and extra handset Model 25802XXX-A. The base unit Models 25825XXX-A and 25826XXX-A will also bear the same FCC ID: G9HFH58R19 as the original Model 25830XXX-M.

The antenna used for the base is permanently attached to the EUT.

Refer to Exhibit B(1)-6 and B(1)-7 for channel frequency table.

NOTE: 1. The base uses **75** Channels.

15.107 (a) POWER LINE CONDUCTED INTERFERENCE

Requirements:

Frequency of Emission (MHZ)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Test Procedure:

ANSI STANDARD C63.4-1992. using a 50uH LISN. Both lines were observed with the EUT transmitting. The bandwidth of the spectrum analyzer was 9KHz QP with an appropriate sweep speed. The ambient temperature of the EUT was 24°C with a humidity of 60%.

The spectrum was scanned from 0.15 to 30MHz.

Test Data:

The highest emission read for LINE was 45.20 dBμV@ 0.15 MHz.

The highest emission read for NEUTRAL was 44.70 dBμV@ 0.15 MHz.

The graphs on Appendix 1 to 4 represent the emissions taken for this device.

Test Results:

Both lines were observed. The measurements indicate that the unit DOES appear to meet the FCC requirements for this class of equipment.

15.205(c)/15.209

**SPURIOUS RADIATED EMISSIONS INCLUDING
RESTRICTED BANDS****Procedure**

The test procedure used was ANSI STANDARD C63.4-1992 and DA-00-705 using an appropriate spectrum analyzer, as listed in the Test Equipment List. The bandwidth (RBW) of the spectrum analyzer was 100KHz/120KHz up to 1GHz with an appropriate sweep speed. The RBW above 1.0GHz was = 1.0MHz. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the EUT was 24°C with a humidity of 60%.

Requirements:

Emissions that fall in the restricted bands (15.205) must be less than 54dBμV/m

15.209	
30-88 MHz	40 dBμV/m@ 3m
88-216 MHz	43.5
216-960 MHz	46
Above 960 MHz	54

Test Data:

Refer to Exhibit D(3)-3 and -4

Note: Emissions falling in the band 30 MHz to 1000 MHz were more than 20 dB below the limit.

15.205(c)/15.209

FIELD STRENGTH OF RADIATED EMISSIONS INCLUDING RESTRICTED BANDS**BASE UNIT**

Frequency Band MHz	Meter Reading (Peak) @3m dBuV/M	Meter Reading (Average) @3m dBuV/M	Antenna and Polarization	Cable & Antenna Factor	Peak F. S. dBuV/M	Average F. S. dBuV/M	Average FCC Limit	Margin dB
Channel 1								
5755.104	83.00	—	Horn V	39.48	122.48	—	—	—
11510.208	11.00	0.00	Horn H	47.75	58.75	47.75	54	-6.25
17265.312	16.00	-4.00	Horn H	54.16	70.16	50.16	54	-3.84
Channel 38								
5782.752	83.00	—	Horn V	39.57	122.57	—	—	—
11565.504	11.00	0.00	Horn H	47.79	58.79	47.79	54	-6.21
17348.256	16.00	-4.00	Horn H	54.24	70.24	50.24	54	-3.76
Channel 75								
5819.040	83.00	—	Horn V	39.66	122.66	—	—	—
11638.080	11.00	0.00	Horn H	47.80	58.80	47.80	54	-6.20
17457.120	16.00	-4.00	Horn H	54.36	70.36	50.36	54	-3.64

1. If the peak meets the average limit, nothing further is required.
2. If the peak exceeds the average limit, then an average measurement is required (may be calculated) and must be below the average limit and also;
3. The peak measurement cannot exceed the average limit +20dB.

15.205(c)/15.209

FIELD STRENGTH OF RADIATED EMISSIONS INCLUDING RESTRICTED BANDS**BASE UNIT**

Emission Frequency MHz	Meter Reading @3m dBμV/M (Peak)	Antenna Polarity	Total Correction Factor dB	Field Strength dBμV/M (Peak)	FCC Limit dB	Margin dB	Detector & BW Khz
Channel 1							
28775.52	35.00	V	56.04	91.04	102.48	-11.44	PK 1000
34530.62	36.00	V	58.25	94.25	102.48	-8.23	PK 1000
Channel 38							
28935.36	35.00	V	56.15	91.15	102.57	-11.42	PK 1000
34722.43	36.00	V	58.40	94.40	102.57	-8.17	PK 1000
Channel 75							
29095.20	35.00	V	56.26	91.26	102.66	-11.40	PK 1000
34914.24	36.00	V	58.57	94.57	102.66	-8.09	PK 1000

15.247(a)(1) HOPPING CHANNEL SEPARATION

Requirements:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Frequency hopping systems in the 2.4GHz band may have hopping channel carrier frequencies separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems employ fewer than 75 hopping channels and operate with an output power no greater than 125 mW.

Measurement Procedure

1. Position the EUT without connection to the Spectrum Analyzer (SA). Turn on the EUT and connect it to the SA. Then set it to any one convenient frequency within its operating range.
2. By using the MaxHold function record the separation of two adjacent channels.
3. Measure the frequency difference of these two adjacent channels by SA MARK function and then plot the result on the SA screen.
4. Repeat above procedures until all frequencies measured were complete.

Measurement Data - Refer Appendix 5 to 7 for plotted data

Base Unit

Channel 1/2:	Adjacent Hopping Channel Separation is 908 kHz.
Channel 37/38:	Adjacent Hopping Channel Separation is 920 kHz.
Channel 74/75:	Adjacent Hopping Channel Separation is 915 kHz.

15.247(a)(1) FREQUENCY HOPPING SYSTEMS

Page 1 of 2

CHANNEL BANDWIDTH [15.247(a)]

Requirements:

The 20dB bandwidth of the hopping channel is less than 1 MHz.

Measurement Procedure

1. Position the EUT without connection to the Spectrum Analyzer (SA). Turn on the EUT and connect it to the SA. Then set it to any one convenient frequency within its operating range. Set a reference level on the SA equal to the highest peak value.
2. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
3. Repeat above procedures until all frequencies measured were complete.

Measurement Data - Refer Appendix 8 to 10 for plotted data

<u>Base</u>	Channel 1:	Channel Bandwidth is 710 kHz.
	Channel 38:	Channel Bandwidth is 740 kHz.
	Channel 75:	Channel Bandwidth is 750 kHz.

15.247(a)(1)(ii) FREQUENCY HOPPING SYSTEMS (continued)

Page 2 of 2

DWELL TIME ON EACH CHANNEL

Requirements:

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a (0.4 x 75) 30 second period.

Measurement Procedure

1. Position the EUT without connection to Spectrum Analyzer (SA). Turn on the EUT and connect its antenna terminal to SA via a low loss cable and set it to any one measured frequency within its operating range and ensure that the SA is operated in its linear range.
2. Adjust the centre frequency of SA on any frequency to be measured and set SA to zero span mode. Set RBW and VBW of SA to proper value.
3. Measure the time duration of one transmission on the measured frequency and then plot the result with the time difference of this time duration.
4. Repeat the above procedures until all frequencies measured were complete.

Measurement Data - Refer Appendix 11 and 12 for plotted data.

Base Unit

The dwell time is $(1.08 \text{ mS} \times 4) \times 40 = 172.8 \text{ mS}$

The maximum time of occupancy for a particular channel is **172.8 mS** in any 30 second period.

15.247(b) (1) MAXIMUM PEAK OUTPUT POWER [ERP]

Requirements:

For frequency hopping systems in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 Watt. For all other frequency hopping systems in the 2400-2483.5 band: 0.125 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Measurement Procedure

1. Position the EUT without connection to Spectrum Analyzer (SA). Turn on the EUT and connect its antenna terminal to SA via a low loss cable and set it to any one measured frequency within its operating range and ensure that the SA is operated in its linear range.
2. Set RBW of SA to 5MHz and VBW to NONE.
3. Measure the highest amplitude appearing on spectral display and record the level to calculate result data.
4. Repeat the above procedures until all frequencies measured were complete.

Measurement Data -

<u>Base</u>	Channel 1:	Output Peak Power is 0.323 W (ERP) .
	Channel 38:	Output Peak Power is 0.330 W (ERP) .
	Channel 75:	Output Peak Power is 0.337 W (ERP) .

15.247(c) BANDWIDTH OF BAND EDGE MEASUREMENT

Requirements:

In any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

Measurement Procedure

1. Position the EUT without connection to Spectrum Analyzer (SA). Turn on the EUT and connect its antenna terminal to SA via a low loss cable and set it to any one measured frequency within its operating range and ensure that the SA is operated in its linear range.
2. Set RBW to 120 kHz and suitable frequency span 500 KHz or 1000 kHz; VBW = none.
3. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
4. Repeat the above procedures until all frequencies measured were complete.
5. Note: Measurements made with hopping and modulation.

Measurement Data - Refer Appendix 13 and 14 for plotted data

Base Unit

Channel 1: All emissions in this 100 kHz bandwidth are attenuated more than **51.24** dB.

Channel 75: All emissions in this 100 kHz bandwidth are attenuated more than **50.30** dB.

Part 15.247(g):

Exhibit D(3)-11 provides information on how the system is designed while the transmitter is presented with a continuous voice stream and a description of the system transmitting short bursts.

Part 15.247(h):

Exhibit D(3)-11 provides information concerning the avoidance of simultaneous occupancy of hopping frequencies by multiple transmitters, system synchronization procedure, frequency hopping algorithm, hopping tables, and dual slot diversity.

Part 15.247 (g). Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both transmitter and the receiver, must be designed to comply with all the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing a short transmission burst must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

In active mode (there is voice communication), the information (voice) are transmitted continuously.

In idle mode (there is no voice communication), the base will broadcast a pilot signal which is distributed in 16 channels.

Part 15.247 (h). The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

We do not use co-ordination frequency system. The system will adjust its hopping sequence and hopping channel according to the operating mode.

In idle mode, the base will continue to check the pilot signal from other base. If the sequence of pilot signal is same, the base will change to another sequence to avoid the jamming.

In active mode, the base and handset will continue to check the jamming from other system. When a jamming is found, the jammed channel will be skipped, but the total number of channel will be kept greater than 15.

TEST FACILITY AND EQUIPMENT LIST

FACILITIES:

- Radiated ANSI C63.4 (FCC OET/55) open field 3 metre test range. This test range is protected from the cold and moisture by a non-conductive enclosure.
- Conducted 2.5m Anechoic Chamber

EQUIPMENT:

Anritsu 2601A Spectrum Analyzer
Advantest R3261A Spectrum Analyzer
Hewlett-Packard RF generator # 8640 B with an 002 doubler
A.H. Systems biconical antenna; 20 MHz to 330 MHz
A.H. Systems log periodic antenna; 300 MHz to 1.8 GHz
Compliance Design P950 Preamp (16 dB) ... 25 MHz to 1.0 GHz

NOTE:

The Anritsu 2601A Spectrum Analyzer and the Advantest R3261A Spectrum Analyzer are calibrated annually, and that calibration is directly traceable to the National Research Council of Canada. (NRC)
This equipment is only used by qualified technicians and only for the purpose of EMI measurements. The three metre test range has been carefully evaluated to the ANSI document C63.4 and will be remeasured for reflections and losses every three years.

ADDITIONAL TEST EQUIPMENT LIST

1. Spectrum Analyzer: HP 8591EM, S/N 3639A00995, (9KHz - 1.8GHz), Calibrated April 2003
2. Spectrum Analyzer: ANRITSU 2601A, S/N MT64544, (10KHz - 2.2GHz), Calibrated May 2003
3. Spectrum Analyzer: IFR AN940, S/N 635001039, (9KHz - 26.5GHz), Calibrated March 2003
4. Preamp: HP 8449B, S/N 3008A00378, (1 - 26.5GHz), Calibrated August 2003
5. Horn Antenna: Q-PAR 6878/24, S/N 1721, (1.5-18GHz)
6. Horn Antenna: A. H. Systems SAS 572, S/N 164 (18 - 26.5GHz)
7. Line Impedance Stabilization Network.: Marstech, Cal. July 2003
8. Horn Antenna: Radar System (Flange 3/4" Square) MIL F 3922/68 (26.5 - 40GHz)
9. OML Mixer: M28HWD, S/N Ka31114-1 (26.5 - 40GHz), Calibration Due Nov. 10, 2004
10. OML Diplexer: DPL.313A (Unit plugs into M28HWD)
11. Semflex Cable: Used with M28HWD and DPL.313A