



Hermon Laboratories Ltd.
Harakevet Industrial Zone, Binyamina 30500,
Israel
Tel. +972-4-6288001
Fax. +972-4-6288277
E-mail: mail@hermonlabs.com

TEST REPORT

ACCORDING TO: FCC CFR 47 PART 15 subpart C, section 15.231(a) and
subpart B

FOR:

**Rosslare Enterprises Ltd. and its
subsidiaries**

**Professional Wireless Elderly Assist
combined with alarm system
Model: SP-03V2G**

This report is in conformity with ISO/ IEC 17025. The "A2LA Accredited" symbol endorsement applies only to the tests and calibrations that are listed in the scope of Hermon Laboratories accreditation. The test results relate only to the items tested. This test report shall not be reproduced in any form except in full with the written approval of Hermon Laboratories Ltd.

Table of contents

1	Applicant information	3
2	Equipment under test attributes	3
3	Manufacturer information	3
4	Test details	3
5	Tests summary	4
6	EUT description	5
6.1	General information	5
6.2	EUT modules and sub-assemblies	5
6.3	Ports and lines	5
6.4	Operating frequencies	5
6.5	Changes made in EUT	5
6.6	Test configuration	5
6.7	Transmitter characteristics	6
7	Transmitter tests according to 47CFR part 15 subpart C requirements	7
7.1	Periodic operation requirements	7
7.2	Field strength of emissions of 433.52 MHz carrier	11
7.3	Field strength of emissions of 433.92 MHz carrier	25
7.4	Occupied bandwidth test	41
7.5	Conducted emissions	44
7.6	Antenna requirements	47
8	Emissions tests according to FCC 47CFR part 15 subpart B requirements	48
8.1	Conducted emissions	48
8.2	Radiated emission measurements	51
9	APPENDIX A Test equipment and ancillaries used for tests	56
10	APPENDIX B Measurement uncertainties	57
11	APPENDIX C Test laboratory description	58
12	APPENDIX D Specification references	58
13	APPENDIX E Test equipment correction factors	59
14	APPENDIX F Abbreviations and acronyms	66

1 Applicant information

Client name: Rosslare Enterprises Ltd. and its subsidiaries
Address: Flat 12, 9 Floor, Wing Fat Ind. Bldg., 12 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong
Telephone: +852 2795 5630
Fax: +852 2795 1508
E-mail: leonid.beckman@rosslaresecurity.com
Contact name: Mr. Leonid Beckman

2 Equipment under test attributes

Product name: Professional Wireless Elderly Assist combined with alarm system
Product type: Transceiver
Model(s): SP-03V2G
Serial number: 000047
Hardware version: 0101-0290042+20
Software release: V050411
Receipt date: 10/21/2010

3 Manufacturer information

Manufacturer name: Rosslare Enterprises Ltd. and its subsidiaries
Address: Flat 12, 9 Floor, Wing Fat Ind. Bldg., 12 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong
Telephone: +852 2795 5630
Fax: +852 2795 1508
E-Mail: leonid.beckman@rosslaresecurity.com
Contact name: Mr. Leonid Beckman

4 Test details





Project ID: 21310
Location: Hermon Laboratories Ltd. Harakevet Industrial Zone, Binyamina 30500, Israel
Test started: 10/21/2010
Test completed: 5/04/2011
Test specification(s): FCC Part 15, subpart C, §15.231(a); subpart B, class B

5 Tests summary

Test	Status
Transmitter characteristics	
Section 15.231(a), Periodic operation requirements	Pass
Section 15.231(b), Field strength of emissions	Pass
Section 15.231(c), Occupied bandwidth	Pass
Section 15.207(a), Conducted emission	Pass
Section 15.203, Antenna requirement	Pass
Unintentional emissions	
Section 15.107, Conducted emission at AC power port	Pass
Section 15.109, Radiated emission	Pass
Section 15.111, Conducted emission at receiver antenna port	Not required

Testing was completed against all relevant requirements of the test standard. The results obtained indicate that the product under test complies in full with the requirements tested.
The test results relate only to the items tested. Pass/ fail decision was based on nominal values.

This test report replaces the previously issued test report identified by Doc ID:ROSRAD_FCC.21310.

	Name and Title	Date	Signature
Tested by:	Mr. S. Samokha, test engineer	May 4, 2011	
	Mrs. E. Pitt, test engineer		
Reviewed by:	Mrs. M. Cherniavsky, certification engineer	May 17, 2011	
Approved by:	Mr. M. Nikishin, EMC and Radio group manager	May 30, 2011	



6 EUT description

6.1 General information

The EUT is a wireless security panel with an elderly phone. The device features the playing of recorded messages and two-way voice communications with a remote party, initiated by pressing a wireless button, even when the phone is off the hook, the line is busy, or when an alarm has been activated. The highly sensitive sound system allows users to speak and listen without having to lift the handset, when they are far from the unit.

The EUT supports 16 wireless detectors, 16 remote control / panic buttons, wireless sirens, and remote keypads. Reporting can be performed over TCP/IP, via telephony or by using an optional GSM module.

The accompanying PC software enables users to manage accounts, to configure, and to remotely control the system via TCP/IP, telephony, or via a local USB port. The transceiver operates at 2 frequencies: 433.52 MHz and 433.92 MHz.

6.2 EUT modules and sub-assemblies

Description	Manufacturer	Model or P/N	Serial number
Response system	Rosslare	SP-03V2H	9003801
AC/DC adapter	FP	LR103915	NA

6.3 Ports and lines

Port type	Port description	Connected from	Connected to	Qty.	Cable type	Cable length
Power	AC power	AC/DC adapter	AC mains	1	Wall outlet	NA
Power	DC power	AC/DC adapter	Control panel	1	Unshielded	2


6.4 Operating frequencies

Source	Frequency, MHz					
Tx/Rx	433.52			433.92		
Crystal	0.032768	4.92	20	25	26	
Clock	48					

6.5 Changes made in EUT

No changes were implemented in the EUT.

6.6 Test configuration





6.7 Transmitter characteristics

Type of equipment					
X	Stand-alone (Equipment with or without its own control provisions)				
	Combined equipment (Equipment where the radio part is fully integrated within another type of equipment)				
	Plug-in card (Equipment intended for a variety of host systems)				
Operating frequencies		433.52 MHz, 433.92 MHz			
Maximum rated output power		Maximum field strength			95.22 dB(μ V/m) at 3 m test distance
Is transmitter output power variable?	X	No			
		Yes	continuous variable		
			stepped variable with stepsize		dB
			minimum RF power	dBm	
		maximum RF power	dBm		
Antenna connection					
unique coupling	standard connector	X	integral	with temporary RF connector	
				X	without temporary RF connector
Antenna characteristics					
Type	Manufacturer	Model number	Gain		
Wired	Rosslare	0152-0300003+00	0 dBi		
Type of modulation		AM			
Modulating test signal (baseband)		OOK			
Transmitter power source					
	Battery	Nominal rated voltage	Battery type		
X	AC mains	Nominal rated voltage	120 VAC	Frequency	60 Hz
Common power source for transmitter and receiver			X	yes	no

Test specification:	Section 15.231(a), Periodic operation requirements		
Test procedure:	Supplier declaration		
Test mode:	Compliance	Verdict:	PASS
Date:	10/21/2010		
Temperature: 23 °C	Air Pressure: 1013 hPa	Relative Humidity: 46 %	Power Supply: 120 VAC
Remarks:			

7 Transmitter tests according to 47CFR part 15 subpart C requirements

7.1 Periodic operation requirements

7.1.1 General

The EUT was verified for compliance with periodic operation requirements listed below:

- Continuous transmissions such as voice, video and the radio control of toys are not permitted;
- A manually operated transmitter shall employ switch that will automatically deactivate the transmitter within not more than 5 seconds of being released;
- A transmitter activated automatically shall cease transmission within 5 seconds after activation;
- Periodic transmissions, excluding polling or supervision transmissions, at regular predetermined intervals are not permitted;
- Total duration of polling or supervision transmissions, including data, to determine system integrity in security or safety applications shall not exceed 2 seconds per hour;
- Transmission of set-up information for security systems may exceed the transmission duration limits of 5 seconds, provided such transmissions are under the control of a professional installer and do not exceed ten seconds after a manually operated switch is released or a transmitter is activated automatically. Such set-up information may include data.

The rationale for compliance with the above requirements was either test results or supplier declaration. The summary of results is provided in Table 7.1.1.

7.1.2 Test procedure for transmitter shut down test

7.1.2.1 The EUT was set up as shown in Figure 7.1.1.

7.1.2.2 The spectrum analyzer center frequency was adjusted to the EUT carrier, span set to zero and video triggered for transmission.

7.1.2.3 The transmitter was activated either manually or automatically. Once manually operated transmitter was activated, the switch was immediately released.

7.1.2.4 The transmission time was captured and shown in Plot 7.1.1.

7.1.3 Test procedure for measurements of polling / supervision transmission duration

7.1.3.1 The EUT was set up as shown in Figure 7.1.1.

7.1.3.2 The spectrum analyzer center frequency was adjusted to the EUT carrier, span set to zero and video triggered for transmission.

7.1.3.3 The transmission time was captured and shown in **Error! Reference source not found..**

Figure 7.1.1 Setup for transmitter shut down test






Test specification: Section 15.231(a), Periodic operation requirements	
Test procedure:	Supplier declaration
Test mode:	Compliance
Date:	10/21/2010
Verdict: PASS	
Temperature: 23 °C	Air Pressure: 1013 hPa
Relative Humidity: 46 %	Power Supply: 120 VAC
Remarks:	

Table 7.1.1 Periodic operation requirements


Requirement	Rationale	Verdict
Continuous transmissions are not permitted	Supplier declaration	Comply
A manually operated transmitter shall be deactivated within not more than 5 seconds of switch being released	NA	NA
Transmitter activated automatically shall cease transmission within 5 seconds	Plot 7.1.1	Comply
Periodic transmissions at regular predetermined intervals are not permitted	Supplier declaration	Comply
Total duration of polling or supervision transmissions shall not exceed 2 seconds per hour	NA	Comply
Transmission of set-up information for security systems may exceed the transmission duration limits of 5 seconds, provided such transmissions are under the control of a professional installer and do not exceed ten seconds after a manually operated switch is released or a transmitter is activated automatically. Such set-up information may include data.	NA	Comply

Test specification:	Section 15.231(a), Periodic operation requirements		
Test procedure:	Supplier declaration		
Test mode:	Compliance	Verdict:	PASS
Date:	10/21/2010		
Temperature: 23 °C	Air Pressure: 1013 hPa	Relative Humidity: 46 %	Power Supply: 120 VAC
Remarks:			

Plot 7.1.1 Transmitter shut down test result, 433.52 MHz



Plot 7.1.2 Transmitter shut down test result, 433.92 MHz





Test specification:		Section 15.231(a), Periodic operation requirements	
Test procedure:		Supplier declaration	
Test mode:	Compliance	Verdict:	PASS
Date:	10/21/2010		
Temperature: 23 °C	Air Pressure: 1013 hPa	Relative Humidity: 46 %	Power Supply: 120 VAC
Remarks:			

Table 7.1.2 Total duration of polling / supervision transmissions

Duration, ms	Repetition period, ms	Maximum number of transmissions within 1 hour	Total duration within 1 hour, ms
EUT has not periodic operations*			

*The RF section of the SP-03V2G is based on one direction protocol with all sensors except of siren and keypad (KE-30). The mechanism of the supervision transmission: every 20 minutes (in standby mode) accessories (sensors, sirens or keypads) send the supervision transmissions. The supervision transmissions are only in one direction from accessories to the panel.
If during one hour (programmable parameter) the panel doesn't get supervision transmission from some sensor, it will send the "Supervision Alarm" to the CMS or to the private.

Reference numbers of test equipment used

HL 3818							
---------	--	--	--	--	--	--	--

Full description is given in Appendix A.

Test specification: Section 15.231(b), Field strength of emissions	
Test procedure: ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date: 3/27/2011	
Temperature: 23 °C	Air Pressure: 1017 hPa
Relative Humidity: 50 %	
Power Supply: 120 VAC	
Remarks: 433.52 MHz	

7.2 Field strength of emissions of 433.52 MHz carrier

7.2.1 General

This test was performed to measure field strength of fundamental and spurious emissions from the EUT. Specification test limits are given in Table 7.2.1 and Table 7.2.2.

Table 7.2.1 Radiated fundamental emission limits

Fundamental frequency, MHz	Field strength at 3 m, dB(μV/m)	
	Peak	Average
433.52	100.81	80.81

Table 7.2.2 Radiated spurious emissions limits

Frequency, MHz	Field strength at 3 m, dB(μV/m)				
	Within restricted bands			Outside restricted bands	
	Peak	Quasi Peak	Average	Peak	Average
0.009 – 0.090	148.5 – 128.5	NA	128.5 – 108.5**	80.81	60.81
0.090 – 0.110	NA	108.5 – 106.8**	NA		
0.110 – 0.490	126.8 – 113.8	NA	106.8 – 93.8**		
0.490 – 1.705	NA	73.8 – 63.0**	NA		
1.705 – 30.0*		69.5			
30 – 88		40.0			
88 – 216		43.5			
216 – 960		46.0			
960 - 1000		54.0			
Above 1000	74.0	NA	54.0		

*- The limit for 3 m test distance was calculated using the inverse square distance extrapolation factor as follows:

$$\text{Lim}_{S_2} = \text{Lim}_{S_1} + 40 \log(S_1/S_2),$$

where S_1 and S_2 – standard defined and test distance respectively in meters.

**- The limit decreases linearly with the logarithm of frequency.

Note 1: The fundamental emission limit in dB(μV/m) was calculated as follows:

$$\text{Lim}_{AVR} = 20 \times \log(56.81818 \times F - 6136.3636) - \text{within } 130 - 174 \text{ MHz band};$$

$$\text{Lim}_{AVR} = 20 \times \log(41.6667 \times F - 7083.3333) - \text{within } 260 - 470 \text{ MHz band},$$

where F is the carrier frequency in MHz.

The limit for spurious emissions was 20 dB lower than fundamental emission limit.

The above limits provided in terms of average values, peak limit was 20 dB above the average limit.

Note 2: The above field strength limits applied from the lowest radio frequency generated in the device, without going below 9 kHz up to the tenth harmonic of the highest fundamental frequency.



Test specification:		Section 15.231(b), Field strength of emissions	
Test procedure:		ANSI C63.4, Section 13.1.4	
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			

7.2.2 Test procedure for spurious emission field strength measurements in 9 kHz to 30 MHz band

- 7.2.2.1 The EUT was set up as shown in Figure 7.2.1, energized and the performance check was conducted.
- 7.2.2.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna was rotated around its vertical axis.
- 7.2.2.3 The worst test results (the lowest margins) were recorded in Table 7.2.3, Table 7.2.5 and shown in the associated plots.

7.2.3 Test procedure for spurious emission field strength measurements above 30 MHz

- 7.2.3.1 The EUT was set up as shown in Figure 7.2.2, energized and the performance check was conducted.
- 7.2.3.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360°, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal.
- 7.2.3.3 The worst test results (the lowest margins) were recorded in Table 7.2.3, Table 7.2.5 and shown in the associated plots.

Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			

Figure 7.2.1 Setup for spurious emission field strength measurements below 30 MHz





Figure 7.2.2 Setup for spurious emission field strength measurements above 30 MHz



Test specification:		Section 15.231(b), Field strength of emissions			
Test procedure:		ANSI C63.4, Section 13.1.4			
Test mode:	Compliance	Verdict:		PASS	
Date:	3/27/2011				
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC		
Remarks: 433.52 MHz					

Table 7.2.3 Field strength of fundamental emission, spurious emissions outside restricted bands and within restricted bands at frequencies above 1 GHz

TEST DISTANCE: 3 m
 EUT POSITION: Typical (Horizontal)
 MODULATION: OOK
 BIT RATE: 2400 bps
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 INVESTIGATED FREQUENCY RANGE: 0.009 - 4500 MHz
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: 1.0 kHz (9 kHz – 150 kHz)
 9.0 kHz (150 kHz – 30 MHz)
 120 kHz (30 MHz – 1000 MHz)
 1.0 MHz (above 1000 MHz)
 VIDEO BANDWIDTH: ≥ Resolution bandwidth
 TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)
 Biconilog (30 MHz – 1000 MHz)
 Double ridged guide (above 1000 MHz)

F, MHz	Antenna		Azimuth, degrees*	Peak field strength			Avr factor, dB	Average field strength			Verdict
	Pol.	Height, m		Measured, dB(μV/m)	Limit, dB(μV/m)	Margin, dB**		Measured, dB(μV/m)	Limit, dB(μV/m)	Margin, dB**	
Fundamental emission***											
433.52	Hor	1	0	79.08	100.81	-21.73	-1	78.08	80.81	-2.73	Pass
Spurious emissions											
1300.44	Hor	1	0	41.52	74.0	-32.48	-1	40.52	54.0	-13.48	Pass

*- EUT front panel refers to 0 degrees position of turntable.
 **- Margin = dB below (negative if above) specification limit.
 *** Max value was obtained at Unom input power voltage.

Table 7.2.4 Average factor calculation

Transmission pulse		Transmission burst		Transmission train duration, ms	Average factor, dB
Duration, ms	Period, ms	Duration, ms	Period, ms		
1.925	2.150	296.4	NA	1776	-1.0

*- Average factor was calculated as follows
 for pulse train shorter than 100 ms: $Average\ factor = 20 \times \log_{10} \left(\frac{Pulse\ duration}{Pulse\ period} \times \frac{Burst\ duration}{Train\ duration} \times Number\ of\ bursts\ within\ pulse\ train \right)$
 for pulse train longer than 100 ms: $Average\ factor = 20 \times \log_{10} \left(\frac{Pulse\ duration}{Pulse\ period} \times \frac{Burst\ duration}{100\ ms} \times Number\ of\ bursts\ within\ 100\ ms \right)$

Reference numbers of test equipment used

HL 0446	HL 0521	HL 0604	HL 1984	HL 2871	HL 3623		
---------	---------	---------	---------	---------	---------	--	--

Full description is given in Appendix A.

Test specification: Section 15.231(b), Field strength of emissions	
Test procedure: ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date: 3/27/2011	
Temperature: 23 °C	Air Pressure: 1017 hPa
Relative Humidity: 50 %	
Power Supply: 120 VAC	
Remarks: 433.52 MHz	

Table 7.2.5 Field strength of emissions below 1 GHz within restricted bands

TEST DISTANCE: 3 m
 EUT POSITION: Typical (Horizontal) /
 MODULATION: OOK
 BIT RATE: 2400 bps
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 INVESTIGATED FREQUENCY RANGE: 0.009 – 1000 MHz
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: 1.0 kHz (9 kHz – 150 kHz)
 9.0 kHz (150 kHz – 30 MHz)
 120 kHz (30 MHz – 1000 MHz)
 VIDEO BANDWIDTH: ≥ Resolution bandwidth
 TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)
 Biconilog (30 MHz – 1000 MHz)

Frequency, MHz	Peak emission, dB(μV/m)	Quasi-peak			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
		Measured emission, dB(μV/m)	Limit, dB(μV/m)	Margin, dB*				
131.08	31.42	28.52	43.50	-14.98	Vertical	1	0	Pass

*- Margin = Measured emission - specification limit.

** - EUT front panel refer to 0 degrees position of turntable.

Table 7.2.6 Restricted bands

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.37625 - 8.38675	73 - 74.6	399.9 - 410	2690 - 2900	10.6 - 12.7
0.495 - 0.505	8.41425 - 8.41475	74.8 - 75.2	608 - 614	3260 - 3267	13.25 - 13.4
2.1735 - 2.1905	12.29 - 12.293	108 - 121.94	960 - 1240	3332 - 3339	14.47 - 14.5
4.125 - 4.128	12.51975 - 12.52025	123 - 138	1300 - 1427	3345.8 - 3358	15.35 - 16.2
4.17725 - 4.17775	12.57675 - 12.57725	149.9 - 150.05	1435 - 1626.5	3600 - 4400	17.7 - 21.4
4.20725 - 4.20775	13.36 - 13.41	156.52475 - 156.52525	1645.5 - 1646.5	4500 - 5150	22.01 - 23.12
6.215 - 6.218	16.42 - 16.423	156.7 - 156.9	1660 - 1710	5350 - 5460	23.6 - 24
6.26775 - 6.26825	16.69475 - 16.69525	162.0125 - 167.17	1718.8 - 1722.2	7250 - 7750	31.2 - 31.8
6.31175 - 6.31225	16.80425 - 16.80475	167.72 - 173.2	2200 - 2300	8025 - 8500	36.43 - 36.5
8.291 - 8.294	25.5 - 25.67	240 - 285	2310 - 2390	9000 - 9200	Above 38.6
8.362 - 8.366	37.5 - 38.25	322 - 335.4	2483.5 - 2500	9300 - 9500	

Reference numbers of test equipment used


HL 0446	HL 0521	HL 0604	HL 2871	HL 3623			
---------	---------	---------	---------	---------	--	--	--

Full description is given in Appendix A.

Test specification:	Section 15.231(b), Field strength of emissions		
Test procedure:	ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			


Plot 7.2.1 Radiated emission measurements at the fundamental frequency

TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical
 EUT POSITION: Typical (Horizontal)
 INPUT VOLTAGE: Unom



Plot 7.2.2 Radiated emission measurements at the fundamental frequency


TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Horizontal
 EUT POSITION: Typical (Horizontal)
 INPUT VOLTAGE: Unom



Test specification:	Section 15.231(b), Field strength of emissions		
Test procedure:	ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			


Plot 7.2.3 Radiated emission measurements at the fundamental frequency

TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical
 EUT POSITION: Typical (Horizontal)
 INPUT VOLTAGE: 115%U_{nom}



Plot 7.2.4 Radiated emission measurements at the fundamental frequency


TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Horizontal
 EUT POSITION: Typical (Horizontal)
 INPUT VOLTAGE: 115%U_{nom}



Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			


Plot 7.2.5 Radiated emission measurements at the fundamental frequency

TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical
 EUT POSITION: Typical (Horizontal)
 INPUT VOLTAGE: 85%Unom



Plot 7.2.6 Radiated emission measurements at the fundamental frequency


TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Horizontal
 EUT POSITION: Typical (Horizontal)
 INPUT VOLTAGE: 85%Unom



Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			


Plot 7.2.7 Radiated emission measurements from 9 to 150 kHz

TEST SITE: Anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical
EUT POSITION: Typical (Horizontal)



Plot 7.2.8 Radiated emission measurements from 0.15 to 30 MHz


TEST SITE: Anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical
EUT POSITION: Typical (Horizontal)



Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			


Plot 7.2.9 Radiated emission measurements from 30 to 1000 MHz

TEST SITE: Anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical
EUT POSITION: Typical (Horizontal)



Plot 7.2.10 Radiated emission measurements from 30 to 1000 MHz


TEST SITE: Anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Horizontal
EUT POSITION: Typical (Horizontal)



Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			


Plot 7.2.11 Radiated emission measurements from 1 to 4.5 GHz

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical
EUT POSITION: Typical (Horizontal)



Plot 7.2.12 Radiated emission measurements from 1 to 4.5 GHz


TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Horizontal
EUT POSITION: Typical (Horizontal)



Test specification:	Section 15.231(b), Field strength of emissions		
Test procedure:	ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			


Plot 7.2.13 Radiated emission measurements at the second harmonic frequency

TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical & Horizontal
 EUT POSITION: Typical (Horizontal)




Plot 7.2.14 Radiated emission measurements at the third harmonic frequency

TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical and Horizontal
 EUT POSITION: Typical (Horizontal)




Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			

Plot 7.2.15 Transmission pulse duration, 433.52 MHz




Plot 7.2.16 Transmission pulse period, 433.52 MHz




Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.52 MHz			

Plot 7.2.17 Transmission burst duration, 433.52 MHz



T = 296.4 ms

Plot 7.2.18 Transmission train duration, 433.52 MHz



T = 1776 ms

Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			

7.3 Field strength of emissions of 433.92 MHz carrier

7.3.1 General

This test was performed to measure field strength of fundamental and spurious emissions from the EUT. Specification test limits are given in Table 7.3.1 and Table 7.3.2.

Table 7.3.1 Radiated fundamental emission limits

Fundamental frequency, MHz	Field strength at 3 m, dB(μV/m)	
	Peak	Average
433.92	100.83	80.83

Table 7.3.2 Radiated spurious emissions limits

Frequency, MHz	Field strength at 3 m, dB(μV/m)				
	Within restricted bands			Outside restricted bands	
	Peak	Quasi Peak	Average	Peak	Average
0.009 – 0.090	148.5 – 128.5	NA	128.5 – 108.5**	80.83	60.83
0.090 – 0.110	NA	108.5 – 106.8**	NA		
0.110 – 0.490	126.8 – 113.8	NA	106.8 – 93.8**		
0.490 – 1.705	NA	73.8 – 63.0**	NA		
1.705 – 30.0*		69.5			
30 – 88		40.0			
88 – 216		43.5			
216 – 960		46.0			
960 - 1000		54.0			
Above 1000	74.0	NA	54.0		

*- The limit for 3 m test distance was calculated using the inverse square distance extrapolation factor as follows:

$$\text{Lim}_{S_2} = \text{Lim}_{S_1} + 40 \log(S_1/S_2),$$

where S_1 and S_2 – standard defined and test distance respectively in meters.

**- The limit decreases linearly with the logarithm of frequency.

Note 1: The fundamental emission limit in dB(μV/m) was calculated as follows:

$$\text{Lim}_{AVR} = 20 \times \log(56.81818 \times F - 6136.3636) - \text{within } 130 - 174 \text{ MHz band};$$

$$\text{Lim}_{AVR} = 20 \times \log(41.6667 \times F - 7083.3333) - \text{within } 260 - 470 \text{ MHz band},$$

where F is the carrier frequency in MHz.

The limit for spurious emissions was 20 dB lower than fundamental emission limit.

The above limits provided in terms of average values, peak limit was 20 dB above the average limit.

Note 2: The above field strength limits applied from the lowest radio frequency generated in the device, without going below 9 kHz up to the tenth harmonic of the highest fundamental frequency.



Test specification:		Section 15.231(b), Field strength of emissions	
Test procedure:		ANSI C63.4, Section 13.1.4	
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			

7.3.2 Test procedure for spurious emission field strength measurements in 9 kHz to 30 MHz band

- 7.3.2.1 The EUT was set up as shown in Figure 7.3.1, energized and the performance check was conducted.
- 7.3.2.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna was rotated around its vertical axis.
- 7.3.2.3 The worst test results (the lowest margins) were recorded in Table 7.3.3, Table 7.3.5 and shown in the associated plots.

7.3.3 Test procedure for spurious emission field strength measurements above 30 MHz

- 7.3.3.1 The EUT was set up as shown in Figure 7.3.2, energized and the performance check was conducted.
- 7.3.3.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360°, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal.
- 7.3.3.3 The worst test results (the lowest margins) were recorded in Table 7.3.3, Table 7.3.5 and shown in the associated plots.

Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			

Figure 7.3.1 Setup for spurious emission field strength measurements below 30 MHz





Figure 7.3.2 Setup for spurious emission field strength measurements above 30 MHz



Test specification:		Section 15.231(b), Field strength of emissions			
Test procedure:		ANSI C63.4, Section 13.1.4			
Test mode:	Compliance	Verdict:		PASS	
Date:	3/27/2011				
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC		
Remarks: 433.92 MHz					

Table 7.3.3 Field strength of fundamental emission, spurious emissions outside restricted bands and within restricted bands at frequencies above 1 GHz

TEST DISTANCE: 3 m
 EUT POSITION: Typical (Horizontal)
 MODULATION: OOK
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 INVESTIGATED FREQUENCY RANGE: 0.009 – 4500 MHz
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: 1.0 kHz (9 kHz – 150 kHz)
 9.0 kHz (150 kHz – 30 MHz)
 120 kHz (30 MHz – 1000 MHz)
 1.0 MHz (above 1000 MHz)
 VIDEO BANDWIDTH: ≥ Resolution bandwidth
 TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)
 Biconical (30 MHz – 200 MHz)
 Double ridged guide (above 1000 MHz)

F, MHz	Antenna		Azimuth, degrees*	Peak field strength			Avr factor, dB	Average field strength			Verdict
	Pol.	Height, m		Measured, dB(μV/m)	Limit, dB(μV/m)	Margin, dB**		Measured, dB(μV/m)	Limit, dB(μV/m)	Margin, dB**	
Fundamental emission											
433.905	Hor	1.2	0	95.22	100.83	-5.61	-16.4	78.82	80.83	-2.01	Pass
Spurious emissions											
1301.711	Hor	1.2	0	51.66	74.00	-22.34	-16.4	35.26	54.00	-18.74	Pass
2169.531	Hor	1.2	0	44.54	80.83	-36.29	-16.4	28.14	60.83	-32.69	

*- EUT front panel refers to 0 degrees position of turntable.
 **- Margin = dB below (negative if above) specification limit.
 *** Max value was obtained 85%Unom input power voltage.

Table 7.3.4 Average factor calculation

Transmission pulse		Transmission burst		Transmission train duration, ms	Average factor, dB
Duration, ms	Period, ms	Duration, ms	Period, ms		
NA	NA	15.50	24.12	469	-16.4

*- Average factor was calculated as follows

for pulse train shorter than 100 ms:

$$\text{Average factor} = 20 \times \log_{10} \left(\frac{\text{Pulse duration}}{\text{Pulse period}} \times \frac{\text{Burst duration}}{\text{Train duration}} \times \text{Number of bursts within pulse train} \right)$$

for pulse train longer than 100 ms:

$$\text{Average factor} = 20 \times \log_{10} \left(\frac{\text{Pulse duration}}{\text{Pulse period}} \times \frac{\text{Burst duration}}{100 \text{ ms}} \times \text{Number of bursts within 100 ms} \right)$$

Average factor = 20*log (15.5/100) = -16.4 dB, where

Preamble Ton = 2.25 ms * 0.5 = 1.125 ms

Data bit, Ton = 19.53 * 2/3 = 14.40 ms

Total Ton duration 15.5 ms.

Reference numbers of test equipment used

HL 0446	HL 0521	HL 0604	HL 1984	HL 2871	HL 3623		
---------	---------	---------	---------	---------	---------	--	--

Full description is given in Appendix A.

Test specification: Section 15.231(b), Field strength of emissions	
Test procedure: ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date: 3/27/2011	
Temperature: 23 °C	Air Pressure: 1017 hPa
Relative Humidity: 50 %	
Power Supply: 120 VAC	
Remarks: 433.92 MHz	

Table 7.3.5 Field strength of emissions below 1 GHz within restricted bands

TEST DISTANCE: 3 m
 EUT POSITION: Typical (Horizontal)
 MODULATION: OOK
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 INVESTIGATED FREQUENCY RANGE: 0.009 – 1000 MHz
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: 1.0 kHz (9 kHz – 150 kHz)
 9.0 kHz (150 kHz – 30 MHz)
 120 kHz (30 MHz – 1000 MHz)
 VIDEO BANDWIDTH: ≥ Resolution bandwidth
 TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)
 Biconilog (30 MHz – 1000 MHz)

Frequency, MHz	Peak emission, dB(μV/m)	Quasi-peak			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
		Measured emission, dB(μV/m)	Limit, dB(μV/m)	Margin, dB*				
37.60	34.14	24.16	40.0	-15.8	Vertical	1.0	0	Pass
127.06	23.23	21.20	43.5	-22.3	Vertical	1.0	5	Pass
240.02	33.45	33.45	46.0	-12.5	Vertical	1.2	355	Pass
262.16	31.52	28.86	46.0	-16.1	Vertical	1.0	10	Pass

*- Margin = Measured emission - specification limit.

**-. EUT front panel refer to 0 degrees position of turntable.

Table 7.3.6 Restricted bands

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.37625 - 8.38675	73 - 74.6	399.9 - 410	2690 - 2900	10.6 - 12.7
0.495 - 0.505	8.41425 - 8.41475	74.8 - 75.2	608 - 614	3260 - 3267	13.25 - 13.4
2.1735 - 2.1905	12.29 - 12.293	108 - 121.94	960 - 1240	3332 - 3339	14.47 - 14.5
4.125 - 4.128	12.51975 - 12.52025	123 - 138	1300 - 1427	3345.8 - 3358	15.35 - 16.2
4.17725 - 4.17775	12.57675 - 12.57725	149.9 - 150.05	1435 - 1626.5	3600 - 4400	17.7 - 21.4
4.20725 - 4.20775	13.36 - 13.41	156.52475 - 156.52525	1645.5 - 1646.5	4500 - 5150	22.01 - 23.12
6.215 - 6.218	16.42 - 16.423	156.7 - 156.9	1660 - 1710	5350 - 5460	23.6 - 24
6.26775 - 6.26825	16.69475 - 16.69525	162.0125 - 167.17	1718.8 - 1722.2	7250 - 7750	31.2 - 31.8
6.31175 - 6.31225	16.80425 - 16.80475	167.72 - 173.2	2200 - 2300	8025 - 8500	36.43 - 36.5
8.291 - 8.294	25.5 - 25.67	240 - 285	2310 - 2390	9000 - 9200	Above 38.6
8.362 - 8.366	37.5 - 38.25	322 - 335.4	2483.5 - 2500	9300 - 9500	

Reference numbers of test equipment used


HL 0446	HL 0521	HL 0604	HL 2871	HL 3623		
---------	---------	---------	---------	---------	--	--

Full description is given in Appendix A.

Test specification:	Section 15.231(b), Field strength of emissions		
Test procedure:	ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			


Plot 7.3.1 Radiated emission measurements at the fundamental frequency

TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical
 EUT POSITION: Typical (Horizontal)
 INPUT VOLTAGE: Unom



Plot 7.3.2 Radiated emission measurements at the fundamental frequency


TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Horizontal
 EUT POSITION: Typical (Horizontal)
 INPUT VOLTAGE: Unom



Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			


Plot 7.3.3 Radiated emission measurements at the fundamental frequency

TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical
 EUT POSITION: Typical (Horizontal)
 INPUT VOLTAGE: 115%U_{nom}



Plot 7.3.4 Radiated emission measurements at the fundamental frequency


TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Horizontal
 EUT POSITION: Typical (Horizontal)
 INPUT VOLTAGE: 115%U_{nom}



Test specification:	Section 15.231(b), Field strength of emissions		
Test procedure:	ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			


Plot 7.3.5 Radiated emission measurements at the fundamental frequency

TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical
 EUT POSITION: Typical (/Horizontal)
 INPUT VOLTAGE: 85%Unom



Plot 7.3.6 Radiated emission measurements at the fundamental frequency


TEST SITE: Anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Horizontal
 EUT POSITION: Typical (/Horizontal)
 INPUT VOLTAGE: 85%Unom



Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			


Plot 7.3.7 Radiated emission measurements from 9 to 150 kHz

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical
EUT POSITION: Typical (Horizontal)



Plot 7.3.8 Radiated emission measurements from 0.15 to 30 MHz


TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical
EUT POSITION: Typical (Horizontal)



Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			


Plot 7.3.9 Radiated emission measurements from 30 to 420 MHz

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal
EUT POSITION: Typical (Horizontal)



Plot 7.3.10 Radiated emission measurements from 420 to 450 MHz


TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal
EUT POSITION: Typical (Horizontal)



Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			


Plot 7.3.11 Radiated emission measurements from 450 to 1000 MHz

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal
EUT POSITION: Typical (Horizontal)



Plot 7.3.12 Radiated emission measurements from 1000 to 4500 MHz


TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal
EUT POSITION: Typical (Horizontal)



Test specification:	Section 15.231(b), Field strength of emissions		
Test procedure:	ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			


Plot 7.3.13 Radiated emission measurements at the second harmonic frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical & Horizontal
EUT POSITION: Typical (Horizontal)



Plot 7.3.14 Radiated emission measurements at the third harmonic frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical & Horizontal
EUT POSITION: Typical (Horizontal)






HERMON LABORATORIES

Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			


Plot 7.3.15 Radiated emission measurements at the fourth harmonic frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical & Horizontal
EUT POSITION: Typical (Horizontal)




Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			

Plot 7.3.16 Transmission burst duration, 433.92 MHz



Preamble Ton = 2.25 ms * 0.5 = 1.125 ms


Plot 7.3.17 Transmission burst duration, 433.92 MHz



Data bit, Ton = 21.60 * 2/3 = 14.40ms


Test specification: Section 15.231(b), Field strength of emissions			
Test procedure: ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			

Plot 7.3.18 Transmission burst duration, 433.92 MHz



T = 24.12 ms


Plot 7.3.19 Transmission burst period, 433.92 MHz



130 ms

Test specification:		Section 15.231(b), Field strength of emissions	
Test procedure:		ANSI C63.4, Section 13.1.4	
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks: 433.92 MHz			

Plot 7.3.20 Transmission train duration, 433.92 MHz



Test specification: Section 15.231(c), Occupied bandwidth	
Test procedure: ANSI C63.4, Section 13.1.7	
Test mode: Compliance	Verdict: PASS
Date: 3/27/2011	
Temperature: 23 °C	Air Pressure: 1017 hPa
Relative Humidity: 50 %	
Power Supply: 120 VAC	
Remarks:	

7.4 Occupied bandwidth test

7.4.1 General

This test was performed to measure transmitter occupied bandwidth. Specification test limits are given in Table 7.4.1.

Table 7.4.1 Occupied bandwidth limits

Assigned frequency, MHz	Modulation envelope reference points*, dBc	Maximum allowed bandwidth, % of the carrier frequency
70 - 900	20.0	0.25
Above 900		0.50

*- Modulation envelope reference points provided in terms of attenuation below modulated carrier.

7.4.2 Test procedure

7.4.2.1 The EUT was set up as shown in Figure 7.4.1, energized and its proper operation was checked.

7.4.2.2 The EUT was set to transmit modulated carrier.

7.4.2.3 The transmitter occupied bandwidth was measured with spectrum analyzer as frequency delta between reference points on modulation envelope and provided in Table 7.4.2 and associated plot.

Figure 7.4.1 Occupied bandwidth test setup





HERMON LABORATORIES

Test specification: Section 15.231(c), Occupied bandwidth	
Test procedure: ANSI C63.4, Section 13.1.7	
Test mode: Compliance	Verdict: PASS
Date: 3/27/2011	
Temperature: 23 °C	Air Pressure: 1017 hPa
Relative Humidity: 50 %	
Power Supply: 120 VAC	
Remarks:	

Table 7.4.2 Occupied bandwidth test results

DETECTOR USED: Peak hold
 RESOLUTION BANDWIDTH: 3 kHz
 VIDEO BANDWIDTH: 30 kHz
 MODULATION ENVELOPE REFERENCE POINTS: 20 dBc
 MODULATION: OOK
 MODULATING SIGNAL: ID code

Carrier frequency, MHz	Occupied bandwidth, kHz	Limit		Margin, kHz	Verdict
		% of the carrier frequency	kHz		
433.52	19.5	0.25	1080	-1060.5	Pass
433.92	19.3	0.25	1080	-1060.7	Pass


Reference numbers of test equipment used

HL 0521	HL 0604	HL 2871	HL 3623					
---------	---------	---------	---------	--	--	--	--	--


Full description is given in Appendix A.

Test specification:		Section 15.231(c), Occupied bandwidth	
Test procedure:		ANSI C63.4, Section 13.1.7	
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks:			

Plot 7.4.1 Occupied bandwidth test result at 433.92 MHz



Plot 7.4.2 Occupied bandwidth test result at 433.52 MHz



Test specification: Section 15.207(a), Conducted emission			
Test procedure: ANSI C63.4, Section 13.1.3			
Test mode: Compliance	Verdict: PASS		
Date: 3/24/2011			
Temperature: 24 °C	Air Pressure: 1013 hPa	Relative Humidity: 43 %	Power Supply: 120 VAC
Remarks:			

7.5 Conducted emissions

7.5.1 General

This test was performed to measure common mode conducted emissions at the power port. Specification test limits are given in Table 7.5.1.

Table 7.5.1 Limits for conducted emissions

Frequency, MHz	Class B limit, dB(μ V)	
	QP	AVRG
0.15 - 0.5	66 - 56*	56 - 46*
0.5 - 5.0	56	46
5.0 - 30	60	50

* The limit decreases linearly with the logarithm of frequency.

7.5.2 Test procedure


7.5.2.1 The EUT was set up as shown in Figure 7.5.1, energized and the performance check was conducted.

7.5.2.2 The measurements were performed at power terminals with the LISN, connected to a spectrum analyzer in the frequency range referred to in Table 7.5.2. Unused coaxial connector of the LISN was terminated with 50 Ohm. Quasi-peak and average detectors were used throughout the testing.

7.5.2.3 The position of the device cables was varied to determine maximum emission level.

7.5.2.4 The worst test results (the lowest margins) were recorded in Table 7.5.2 and shown in the associated plots.

Figure 7.5.1 Setup for conducted emission measurements, table-top equipment





HERMON LABORATORIES

Test specification: Section 15.207(a), Conducted emission	
Test procedure: ANSI C63.4, Section 13.1.3	
Test mode: Compliance	Verdict: PASS
Date: 3/24/2011	
Temperature: 24 °C	Air Pressure: 1013 hPa
Relative Humidity: 43 %	
Power Supply: 120 VAC	
Remarks:	

Table 7.5.2 Conducted emission test results

LINE: AC mains
 EUT OPERATING MODE: Transmit
 EUT SET UP: TABLE-TOP
 TEST SITE: SHIELDED ROOM
 DETECTORS USED: PEAK / QUASI-PEAK / AVERAGE
 FREQUENCY RANGE: 150 kHz - 30 MHz
 RESOLUTION BANDWIDTH: 9 kHz

Frequency, MHz	Peak emission, dB(µV)	Quasi-peak			Average			Line ID	Verdict
		Measured emission, dB(µV)	Limit, dB(µV)	Margin, dB*	Measured emission, dB(µV)	Limit, dB(µV)	Margin, dB*		
0.150000	52.69	45.96	66.00	-20.04	12.62	56.00	-43.38	L1	Pass
0.386580	48.49	40.34	58.15	-17.81	7.30	48.15	-40.85		
0.401270	49.31	40.84	57.85	-17.01	8.35	47.85	-39.50		
0.421970	49.37	40.86	57.46	-16.60	7.50	47.46	-39.96		
0.471705	48.25	39.74	56.53	-16.79	6.26	46.53	-40.27		
0.500270	48.58	39.99	56.00	-16.01	6.55	46.00	-39.45		
0.151890	52.98	46.33	65.91	-19.58	13.31	55.91	-42.60	L2	Pass
0.300000	49.61	42.05	60.27	-18.22	9.06	50.27	-41.21		
0.350000	48.68	41.04	59.02	-17.98	7.98	49.02	-41.04		
0.400000	48.04	40.14	57.87	-17.73	7.83	47.87	-40.04		
0.431770	47.81	39.68	57.28	-17.60	6.70	47.28	-40.58		
0.450040	47.70	39.42	56.93	-17.51	6.39	46.93	-40.54		

*- Margin = Measured emission - specification limit.

Reference numbers of test equipment used


HL 0447	HL 0787	HL 1205	HL 1425	HL 1513	HL 3415	HL 3612	
---------	---------	---------	---------	---------	---------	---------	--

Full description is given in Appendix A.

Test specification: Section 15.207(a), Conducted emission			
Test procedure: ANSI C63.4, Section 13.1.3			
Test mode: Compliance	Verdict: PASS		
Date: 3/24/2011			
Temperature: 24 °C	Air Pressure: 1013 hPa	Relative Humidity: 43 %	Power Supply: 120 VAC
Remarks:			


Plot 7.5.1 Conducted emission measurements

LINE: L1
EUT OPERATING MODE: Transmit
LIMIT: QUASI-PEAK, AVERAGE
DETECTOR: PEAK



Plot 7.5.2 Conducted emission measurements

LINE: L2
EUT OPERATING MODE: Transmit
LIMIT: QUASI-PEAK, AVERAGE
DETECTOR: PEAK



Test specification:	Section 15.203, Antenna requirement		
Test procedure:	Visual inspection / supplier declaration		
Test mode:	Compliance	Verdict:	PASS
Date:	3/29/2011		
Temperature: 23 °C	Air Pressure: hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks:			

7.6 Antenna requirements

The EUT was verified for compliance with antenna requirements. A transmitter shall be designed to ensure that no antenna other than that furnished by the responsible party will be used with the device. It may be either permanently attached or employs a unique antenna connector for every antenna proposed for use with the EUT. This requirement does not apply to professionally installed transmitters. The rationale for compliance with the above requirements was either visual inspection results or supplier declaration. The summary of results is provided in Table 7.6.1.

Table 7.6.1 Antenna requirements

Requirement	Rationale	Verdict
The transmitter antenna is permanently attached	Visual inspection	Comply
The transmitter employs a unique antenna connector	NA	
The transmitter requires professional installation	NA	

Photograph 7.6.1 Antenna assembly



Test specification: Section 15.107, Conducted emission at AC power port	
Test procedure: ANSI C63.4, Sections 11.5 and 12.1.3	
Test mode: Compliance	Verdict: PASS
Date: 3/29/2011	
Temperature: 23 °C	Air Pressure: hPa
Relative Humidity: 50 %	
Power Supply: 120 VAC	
Remarks:	

8 Emissions tests according to FCC 47CFR part 15 subpart B requirements

8.1 Conducted emissions

8.1.1 General

This test was performed to measure the common mode conducted emissions at the EUT power port. The specification test limits are given in Table 8.1.1.

Table 8.1.1 Limits for conducted emissions


Frequency, MHz	Class B limit, dB(μ V)		Class A limit, dB(μ V)	
	QP	AVRG	QP	AVRG
0.15 - 0.5	66 - 56*	56 - 46*	79	66
0.5 - 5.0	56	46	73	60
5.0 - 30	60	50	73	60

* - The limit decreases linearly with the logarithm of frequency.

8.1.2 Test procedure

- 8.1.2.1 The EUT was set up as shown in Figure 8.1.1, energized and the EUT performance was checked.
- 8.1.2.2 The measurements were performed at the EUT power terminals with the LISN connected to the EMI receiver in the frequency range referred to in Table 8.1.2. The unused coaxial connector of the LISN was terminated with 50 Ohm.
- 8.1.2.3 The position of the EUT cables was varied to find the highest emission.
- 8.1.2.4 The worst test results with respect to the limits were recorded in Table 8.1.2 and shown in the associated plots.

Figure 8.1.1 Setup for conducted emission measurements, table-top EUT



Test specification:		Section 15.107, Conducted emission at AC power port	
Test procedure:		ANSI C63.4, Sections 11.5 and 12.1.3	
Test mode:	Compliance	Verdict:	PASS
Date:	3/29/2011		
Temperature: 23 °C	Air Pressure: hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks:			

Table 8.1.2 Conducted emission test results

LINE: AC mains
LIMIT: Class B
EUT OPERATING MODE: Receive / Stand-by
EUT SET UP: TABLE-TOP
TEST SITE: SHIELDED ROOM
DETECTORS USED: PEAK / QUASI-PEAK / AVERAGE
FREQUENCY RANGE: 150 kHz - 30 MHz
RESOLUTION BANDWIDTH: 9 kHz

Frequency, MHz	Peak emission, dB(μV)	Quasi-peak			Average			Line ID	Verdict
		Measured emission, dB(μV)	Limit, dB(μV)	Margin, dB*	Measured emission, dB(μV)	Limit, dB(μV)	Margin, dB*		
0.150000	52.69	45.96	66.00	-20.04	12.62	56.00	-43.38	L1	Pass
0.386580	48.49	40.34	58.15	-17.81	7.30	48.15	-40.85		
0.401270	49.31	40.84	57.85	-17.01	8.35	47.85	-39.50		
0.421970	49.37	40.86	57.46	-16.60	7.50	47.46	-39.96		
0.471705	48.25	39.74	56.53	-16.79	6.26	46.53	-40.27		
0.500270	48.58	39.99	56.00	-16.01	6.55	46.00	-39.45	L2	Pass
0.151890	52.98	46.33	65.91	-19.58	13.31	55.91	-42.60		
0.300000	49.61	42.05	60.27	-18.22	9.06	50.27	-41.21		
0.350000	48.68	41.04	59.02	-17.98	7.98	49.02	-41.04		
0.400000	48.04	40.14	57.87	-17.73	7.83	47.87	-40.04		
0.431770	47.81	39.68	57.28	-17.60	6.70	47.28	-40.58		
0.450040	47.70	39.42	56.93	-17.51	6.39	46.93	-40.54		

*- Margin = Measured emission - specification limit.

Reference numbers of test equipment used


HL 0447	HL 0787	HL 1205	HL 1425	HL 1513	HL 3415	HL 3612	
---------	---------	---------	---------	---------	---------	---------	--

Full description is given in Appendix A.

Test specification: Section 15.107, Conducted emission at AC power port			
Test procedure: ANSI C63.4, Sections 11.5 and 12.1.3			
Test mode: Compliance	Verdict: PASS		
Date: 3/29/2011			
Temperature: 23 °C	Air Pressure: hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks:			


Plot 8.1.1 Conducted emission measurements

LINE: L1
LIMIT: QUASI-PEAK, AVERAGE
DETECTOR: PEAK



Plot 8.1.2 Conducted emission measurements

LINE: L2
LIMIT: QUASI-PEAK, AVERAGE
DETECTOR: PEAK



Test specification:		Section 15.109, Radiated emission	
Test procedure:		ANSI C63.4, Sections 11.6 and 12.1.4	
Test mode:	Compliance	Verdict:	PASS
Date:	3/27/2011		
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks:			

8.2 Radiated emission measurements

8.2.1 General

This test was performed to measure radiated emissions from the EUT enclosure. The specification test limits are given in Table 8.2.1.

Table 8.2.1 Radiated emission test limits

Frequency, MHz	Class B limit, dB(μV/m)		Class A limit, dB(μV/m)	
	10 m distance	3 m distance	10 m distance	3 m distance
30 - 88	29.5*	40.0	39.0	49.5*
88 - 216	33.0*	43.5	43.5	54.0*
216 - 960	35.5*	46.0	46.4	56.9*
Above 960	43.5*	54.0	49.5	60.0*

* - The limit for a test distance other than specified was calculated using the inverse linear distance extrapolation factor as follows: $Lim_{S_2} = Lim_{S_1} + 20 \log(S_1/S_2)$, where S_1 and S_2 – the standard defined and the test distance respectively in meters.

8.2.2 Test procedure


8.2.2.1 The EUT was set up as shown in Figure 8.2.1, energized and the EUT performance was checked.

8.2.2.2 The measurements were performed in the anechoic chamber at 3 m test distance. The specified frequency range was investigated with the antenna connected to the EMI receiver. To find the highest emission the turntable was rotated 360° and the measuring antenna height was swept from 1 to 4 m in both, vertical and horizontal polarizations. The EUT cables position was varied to maximize emission.

8.2.2.3 The worst test results with respect to the limits were recorded in Table 8.2.2 and shown in the associated plots.

Test specification: Section 15.109, Radiated emission			
Test procedure: ANSI C63.4, Sections 11.6 and 12.1.4			
Test mode: Compliance		Verdict: PASS	
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks:			

Figure 8.2.1 Setup for radiated emission measurements in anechoic chamber, table-top EUT



Test specification: Section 15.109, Radiated emission	
Test procedure: ANSI C63.4, Sections 11.6 and 12.1.4	
Test mode: Compliance	Verdict: PASS
Date: 3/27/2011	
Temperature: 23 °C	Air Pressure: 1017 hPa
Relative Humidity: 50 %	
Power Supply: 120 VAC	
Remarks:	

Table 8.2.2 Radiated emission test results

EUT SET UP: TABLE-TOP
TEST SITE: SEMI ANECHOIC CHAMBER
TEST DISTANCE: 3 m
DETECTORS USED: PEAK / QUASI-PEAK
FREQUENCY RANGE: 30 MHz – 1000 MHz
RESOLUTION BANDWIDTH: 120 kHz

Frequency, MHz	Peak emission, dB(μV/m)	Quasi-peak			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
		Measured emission, dB(μV/m)	Limit, dB(μV/m)	Margin, dB*				
34.423663	36.31	28.34	40.00	-11.66	ver	1	0	Pass
131.085700	29.44	26.53	43.50	-16.97	ver	1.15	0	
144.000000	29.41	25.80	43.50	-17.70	ver	1	0	
192.015000	42.11	41.14	43.50	-2.36	ver	1.30	0	
288.022800	38.42	36.08	46.00	-9.92	hor	1	0	
312.019000	34.80	32.40	46.00	-13.60	hor	1	0	
336.015500	38.79	36.87	46.00	-9.13	hor	1.20	260	
384.013000	44.85	43.59	46.00	-2.41	hor	1.10	0	
432.036250	39.81	38.12	46.00	-7.88	hor	1.10	0	

TEST SITE: SEMI ANECHOIC CHAMBER
TEST DISTANCE: 3 m
DETECTORS USED: PEAK / AVERAGE
FREQUENCY RANGE: 1000 MHz – 2000 MHz
RESOLUTION BANDWIDTH: 1000 kHz

Frequency, MHz	Peak			Average			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
	Measured emission, dB(μV/m)	Limit, dB(μV/m)	Margin, dB*	Measured emission, dB(μV/m)	Limit, dB(μV/m)	Margin, dB*				
No emission was found										Pass

*- Margin = Measured emission - specification limit.
**- EUT front panel refers to 0 degrees position of turntable.

Reference numbers of test equipment used


HL 0521	HL 0604	HL1984	HL 2871	HL 3623			
---------	---------	--------	---------	---------	--	--	--

Full description is given in Appendix A.

Test specification: Section 15.109, Radiated emission			
Test procedure: ANSI C63.4, Sections 11.6 and 12.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks:			


Plot 8.2.1 Radiated emission measurements in 30 - 1000 MHz range, vertical antenna polarization

TEST SITE: Anechoic chamber
TEST DISTANCE: 3 m



Plot 8.2.2 Radiated emission measurements in 30 - 1000 MHz range, horizontal antenna polarization

TEST SITE: Anechoic chamber
TEST DISTANCE: 3 m






HERMON LABORATORIES

Test specification: Section 15.109, Radiated emission			
Test procedure: ANSI C63.4, Sections 11.6 and 12.1.4			
Test mode: Compliance	Verdict: PASS		
Date: 3/27/2011			
Temperature: 23 °C	Air Pressure: 1017 hPa	Relative Humidity: 50 %	Power Supply: 120 VAC
Remarks:			

Plot 8.2.3 Radiated emission measurements above 1000 MHz, vertical and horizontal antenna polarization

TEST SITE: Anechoic chamber
TEST DISTANCE: 3 m



9 APPENDIX A Test equipment and ancillaries used for tests

HL No	Description	Manufacturer	Model	Ser. No.	Last Cal.	Due Cal.
0446	Antenna, Loop, Active, 10 kHz - 30 MHz	EMCO	6502	2857	29-Jun-10	29-Jun-11
0447	LISN, 16/2, 300V RMS, 50 Ohm/50 uH + 5 Ohm, STD CISPR 16-1	Hermon Laboratories	LISN 16 - 1	066	26-Oct-10	26-Oct-11
0521	EMI Receiver (Spectrum Analyzer) with RF filter section 9 kHz-6.5 GHz	Hewlett Packard	8546A	3617A 00319, 3448A002 53	25-Aug-10	25-Aug-11
0604	Antenna BiconiLog Log-Periodic/T Bow-TIE, 26 - 2000 MHz	EMCO	3141	9611-1011	11-Jan-11	11-Jan-12
0787	Transient Limiter 9 kHz-200 MHz	Hewlett Packard	11947A	3107A018 77	18-Oct-10	18-Oct-11
1205	One phase voltage regulator, 2kVA, 0-250V	Hermon Laboratories	TDGC-2	109	18-Jul-10	18-Jul-11
1425	EMI Receiver, 9 kHz - 2.9 GHz, System: HL1426, HL1427	Agilent Technologies	8542E	3710A002 22, 3705A002 04	24-Aug-10	24-Aug-11
1513	Cable RF, 8 m, BNC/BNC	Belden	M17/167 MIL-C-17	1513	01-Sep-10	01-Sep-11
1984	Antenna, Double-Ridged Waveguide Horn, 1-18 GHz, 300 W	EMC Test Systems	3115	9911-5964	11-Jun-10	11-Jun-11
2871	Microwave Cable Assembly, 18 GHz, 6.4 m, SMA - SMA	Huber-Suhner	198-8155-00	2871	14-Sep-10	14-Sep-11
3415	Telephone Line Simulator	TELTONE	TLS-5B-01	007811	16-Feb-11	16-Feb-12
3612	Cable RF, 17.5 m, N type-N type	Teldor	RG-214/U	NA	01-Dec-10	01-Dec-11
3623	Cable RF, 6.0 m, N type-N type, DC-6.5 GHz	Belden	MIL C-17	NA	27-May-10	27-May-11
3818	PSA Series Spectrum Analyzer, 3 Hz- 44 GHz	Agilent Technologies	E4446A	MY482502 88	25-Sep-09	25-Sep-11

10 APPENDIX B Measurement uncertainties

Expanded uncertainty at 95% confidence in Hermon Labs EMC measurements

Test description	Expanded uncertainty
Conducted emissions with LISN	9 kHz to 150 kHz: ± 3.9 dB 150 kHz to 30 MHz: ± 3.8 dB
Radiated emissions at 10 m measuring distance Horizontal polarization Vertical polarization	Biconilog antenna: ± 5.0 dB Biconical antenna: ± 5.0 dB Log periodic antenna: ± 5.1 dB Double ridged horn antenna: ± 5.3 dB Biconilog antenna: ± 5.5 dB Biconical antenna: ± 5.5 dB Log periodic antenna: ± 5.6 dB Double ridged horn antenna: ± 5.8 dB
Radiated emissions at 3 m measuring distance Horizontal polarization Vertical polarization	Biconilog antenna: ± 5.3 dB Biconical antenna: ± 5.0 dB Log periodic antenna: ± 5.3 dB Double ridged horn antenna: ± 5.3 dB Biconilog antenna: ± 6.0 dB Biconical antenna: ± 5.7 dB Log periodic antenna: ± 6.0 dB Double ridged horn antenna: ± 6.0 dB
Conducted emissions at RF antenna connector	9 kHz to 2.9 GHz: ± 2.6 dB 2.9 GHz to 6.46 GHz: ± 3.5 dB 6.46 GHz to 13.2 GHz: ± 4.3 dB 13.2 GHz to 22.0 GHz: ± 5.0 dB 22.0 GHz to 26.8 GHz: ± 5.5 dB 26.8 GHz to 40.0 GHz: ± 4.8 dB
Duty cycle, timing (Tx ON / OFF) and average factor measurements	± 1.0 %
Occupied bandwidth	± 8.0 %

Hermon Laboratories is accredited by A2LA for calibration according to present requirements of ISO/IEC 17025 and NCSL Z540-1. The accreditation is granted to perform calibration of parameters that are listed in the Scope of Hermon Laboratories Accreditation.

Hermon Laboratories calibrates its reference and transfer standards by calibration laboratories accredited to ISO/IEC 17025 by a mutually recognized Accreditation Body or by a recognized national metrology institute. All reference and transfer standards used in the calibration system are traceable to national or international standards.

In-house calibration of all test and measurement equipment is performed on a regular basis according to Hermon Laboratories calibration procedures, manufacturer calibration/verification procedures or procedures defined in the relevant standards. The Hermon Laboratories test and measurement equipment is calibrated within the tolerances specified by the manufacturers and/or by the relevant standards.

11 APPENDIX C Test laboratory description

Tests were performed at Hermon Laboratories Ltd., which is a fully independent, private, EMC, safety, environmental and telecommunication testing facility.

Hermon Laboratories is listed by the Federal Communications Commission (USA) for all parts of Code of Federal Regulations 47 (CFR 47), Registration Numbers 90624 for OATS and 90623 for the anechoic chamber; by Industry Canada for electromagnetic emissions (file numbers IC 2186A-1 for OATS, IC 2186A-2 for anechoic chamber, IC 2186A-3 for full-anechoic chamber for RE measurements above 1 GHz), certified by VCCI, Japan (the registration numbers are R-808 for OATS, R-1082 for anechoic chamber, G-27 for full-anechoic chamber for RE measurements above 1 GHz, C-845 for conducted emissions site, T-1606 for conducted emissions at telecommunication ports), has a status of a Telefication - Listed Testing Laboratory, Certificate No. L138/00. The laboratory is accredited by American Association for Laboratory Accreditation (USA) according to ISO/IEC 17025 for electromagnetic compatibility, product safety, telecommunications testing and environmental simulation (for exact scope please refer to Certificate No. 839.01). The FCC Designation Number is US1003.

Address: P.O. Box 23, Binyamina 30500, Israel.
Telephone: +972 4628 8001
Fax: +972 4628 8277
e-mail: mail@hermonlabs.com
website: www.hermonlabs.com

Person for contact: Mr. Alex Usoskin, CEO.

12 APPENDIX D Specification references

47CFR part 15: 2010	Radio Frequency Devices
ANSI C63.2: 1996	American National Standard for Instrumentation-Electromagnetic Noise and Field Strength, 10 kHz to 40 GHz-Specifications.
ANSI C63.4: 2003	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

13 APPENDIX E Test equipment correction factors

Correction factor
Line impedance stabilization network
Model LISN 16 - 1
Hermon Laboratories, HL 0447

Frequency, kHz	Correction factor, dB
10	4.9
15	2.86
20	1.83
25	1.25
30	0.91
35	0.69
40	0.53
50	0.35
60	0.25
70	0.18
80	0.14
90	0.11
100	0.09
125	0.06
150	0.04

The correction factor in dB is to be added to meter readings of an interference analyzer or a spectrum analyzer.

Antenna factor
Active loop antenna
Model 6502, S/N 2857, HL 0446

Frequency, MHz	Magnetic antenna factor, dB	Electric antenna factor, dB
0.009	-32.8	18.7
0.010	-33.8	17.7
0.020	-38.3	13.2
0.050	-41.1	10.4
0.075	-41.3	10.2
0.100	-41.6	9.9
0.150	-41.7	9.8
0.250	-41.6	9.9
0.500	-41.8	9.8
0.750	-41.9	9.7
1.000	-41.4	10.1
2.000	-41.5	10.0
3.000	-41.4	10.2
4.000	-41.4	10.1
5.000	-41.5	10.1
10.000	-41.9	9.6
15.000	-41.9	9.6
20.000	-42.2	9.3
25.000	-42.8	8.7
30.000	-44.0	7.5

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).

Antenna factor
Biconilog antenna EMCO Model 3141
Ser.No.1011, HL 0604

Frequency, MHz	Antenna Factor, dB(1/m)	Frequency, MHz	Antenna Factor, dB(1/m)
26	7.8	940	24.0
28	7.8	960	24.1
30	7.8	980	24.5
40	7.2	1000	24.9
60	7.1	1020	25.0
70	8.5	1040	25.2
80	9.4	1060	25.4
90	9.8	1080	25.6
100	9.7	1100	25.7
110	9.3	1120	26.0
120	8.8	1140	26.4
130	8.7	1160	27.0
140	9.2	1180	27.0
150	9.8	1200	26.7
160	10.2	1220	26.5
170	10.4	1240	26.5
180	10.4	1260	26.5
190	10.3	1280	26.6
200	10.6	1300	27.0
220	11.6	1320	27.8
240	12.4	1340	28.3
260	12.8	1360	28.2
280	13.7	1380	27.9
300	14.7	1400	27.9
320	15.2	1420	27.9
340	15.4	1440	27.8
360	16.1	1460	27.8
380	16.4	1480	28.0
400	16.6	1500	28.5
420	16.7	1520	28.9
440	17.0	1540	29.6
460	17.7	1560	29.8
480	18.1	1580	29.6
500	18.5	1600	29.5
520	19.1	1620	29.3
540	19.5	1640	29.2
560	19.8	1660	29.4
580	20.6	1680	29.6
600	21.3	1700	29.8
620	21.5	1720	30.3
640	21.2	1740	30.8
660	21.4	1760	31.1
680	21.9	1780	31.0
700	22.2	1800	30.9
720	22.2	1820	30.7
740	22.1	1840	30.6
760	22.3	1860	30.6
780	22.6	1880	30.6
800	22.7	1900	30.6
820	22.9	1920	30.7
840	23.1	1940	30.9
860	23.4	1960	31.2
880	23.8	1980	31.6
900	24.1	2000	32.0
920	24.1		

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).

**Antenna factor
Double-ridged wave guide horn antenna
Model 3115, S/N 9911-5964, HL1984**

Frequency, MHz	Antenna factor, dB(1/m)
1000.0	24.7
1500.0	25.7
2000.0	27.6
2500.0	28.9
3000.0	31.2
3500.0	32.0
4000.0	32.5
4500.0	32.7
5000.0	33.6
5500.0	35.1
6000.0	35.4
6500.0	34.9
7000.0	36.1
7500.0	37.8
8000.0	38.0
8500.0	38.1
9000.0	39.1
9500.0	38.3
10000.0	38.6
10500.0	38.2
11000.0	38.7
11500.0	39.5
12000.0	40.0
12500.0	40.4
13000.0	40.5
13500.0	41.1
14000.0	41.6
14500.0	41.7
15000.0	38.7
15500.0	38.2
16000.0	38.8
16500.0	40.5
17000.0	42.5
17500.0	45.9
18000.0	49.4

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).

Cable loss
Cable coaxial, Huber-Suhner, 18 GHz, 6.4 m, SMA - SMA, model 198-8155-00,
HL 2871

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
10	0.12	5750	2.34	12000	3.55
30	0.14	6000	2.39	12250	3.61
100	0.27	6250	2.46	12500	3.67
250	0.45	6500	2.52	12750	3.74
500	0.63	6750	2.58	13000	3.79
750	0.76	7000	2.64	13250	3.82
1000	0.89	7250	2.68	13500	3.83
1250	1.01	7500	2.73	13750	3.83
1500	1.12	7750	2.78	14000	3.88
1750	1.23	8000	2.83	14250	3.93
2000	1.32	8250	2.88	14500	3.96
2250	1.41	8500	2.94	14750	4.01
2500	1.49	8750	2.97	15000	4.00
2750	1.58	9000	3.02	15250	4.01
3000	1.66	9250	3.07	15500	4.00
3250	1.73	9500	3.13	15750	4.13
3500	1.80	9750	3.18	16000	4.22
3750	1.87	10000	3.21	16250	4.29
4000	1.93	10250	3.26	16500	4.29
4250	2.01	10500	3.30	16750	4.32
4500	2.06	10750	3.36	17000	4.37
4750	2.12	11000	3.39	17250	4.45
5000	2.17	11250	3.44	17500	4.49
5250	2.24	11500	3.48	17750	4.53
5500	2.29	11750	3.52	18000	4.55

Cable loss
Cable coaxial, RG-214/U, N type-N type, 17 m
Teldor, HL 3612

Frequency, GHz	Cable loss, dB
0.1	0.05
0.5	0.07
1	0.10
3	0.22
5	0.29
10	0.39
30	0.68
50	0.90
100	1.27
150	1.58
200	1.80
250	2.12
300	2.36
350	2.60
400	2.82
450	2.99
500	3.23
550	3.40
600	3.56
650	3.71
700	3.90
750	4.04
800	4.23
850	4.39
900	4.55
950	4.65
1000	4.79

Cable loss
Cable coaxial, MIL C-17, N type-N type, 6 m
Belden, HL 3623

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
10	0.13	2600	4.38	5400	7.76
30	0.25	2700	4.53	5500	7.79
50	0.33	2800	4.64	5600	7.88
100	0.49	2900	4.79	5700	7.93
200	0.76	3000	4.93	5800	8.05
300	0.97	3100	5.02	5900	8.03
400	1.18	3200	5.18	6000	8.07
500	1.38	3300	5.27	6100	8.14
600	1.54	3400	5.41	6200	8.21
700	1.71	3500	5.57	6300	8.28
800	1.88	3600	5.65	6400	8.35
900	2.04	3700	5.82	6500	8.43
1000	2.19	3800	5.89		
1100	2.38	3900	6.02		
1200	2.61	4000	6.15		
1300	2.63	4100	6.26		
1400	2.79	4200	6.37		
1500	2.90	4300	6.52		
1600	3.08	4400	6.63		
1700	3.21	4500	6.74		
1800	3.31	4600	6.86		
1900	3.47	4700	6.98		
2000	3.59	4800	7.09		
2100	3.74	4900	7.17		
2200	3.86	5000	7.30		
2300	3.98	5100	7.41		
2400	4.12	5200	7.59		
2500	4.24	5300	7.71		

14 APPENDIX F Abbreviations and acronyms

A	ampere
AC	alternating current
AM	amplitude modulation
AVRG	average (detector)
BB	broad band
cm	centimeter
dB	decibel
dBm	decibel referred to one milliwatt
dB(μ V)	decibel referred to one microvolt
dB(μ V/m)	decibel referred to one microvolt per meter
dB(μ A)	decibel referred to one microampere
DC	direct current
EIRP	equivalent isotropically radiated power
ERP	effective radiated power
EUT	equipment under test
F	frequency
GHz	gigahertz
GND	ground
H	height
HL	Hermon laboratories
Hz	hertz
k	kilo
kHz	kilohertz
LO	local oscillator
m	meter
MHz	megahertz
min	minute
mm	millimeter
ms	millisecond
μ s	microsecond
NA	not applicable
NB	narrow band
OATS	open area test site
Ω	Ohm
PCB	printed circuit board
PM	pulse modulation
QP	quasi-peak
RE	radiated emission
RF	radio frequency
rms	root mean square
Rx	receive
s	second
T	temperature
Tx	transmit
V	volt
VA	volt-ampere
WB	wideband

END OF DOCUMENT