

2.2 OPERATIONAL DESCRIPTION

This device is a Wireless mouse included wireless transmitter of mouse and receiver.
 This device is 16 channel with two frequency hopping carrier per each channel.
 The channel control are set by manufacturer and only one channel is used for end users.
 End users can not change channel by themselves.
 The device is operated in 2.412 to 2.475GHz with GFSK modulation.
 The Receiver is USB interface and it is capable to receive signal from transmitter to control PC or notebook.
 Another information please refer to users manual.

2.3 TEST MODES & EUT COMPONENTS DESCRIPTION

EUT: Wireless Mouse, M/N: Transmitter: F670		
The EUT tested with PC System. (DELL, M/N: Latitude D600 PPO5L)		
Test Mode	Mode 1	Mode 2
	Transmitter	Charge Mode

2.4 SUMMARY OF TEST PROCEDURE AND TEST RESULTS

Test Item	Applied Standard Section	Test Result
Radistion Emission	15.209, ANSI C63.4 Section 8	Pass (refer to section 3.7)
Peak Power Output	15.249(a), ANSI C63.4 Section 13 & Annex I	Pass (refer to section 3.7)
Band Edge	15.249(d) , ANSI C63.4 Section 13 & Annex I	Pass (refer to section 4.6)