



## FCC / ISED Test Report

**For:**  
Xirgo Technologies, LLC

**Model Name:**  
XT1520

**Product Description:**  
Proximity Bluetooth beacons with a single chip Bluetooth 5 + ARM mounted to distribution carts, which are used in conjunction with XT49xx devices installed on trailers.

**FCC ID:** GKM-XT1520  
**IC ID:** 10281A-XT1520

Applied Rules and Standards:  
47 CFR Part 15.247 (DTS)  
RSS-247 Issue 2 (DTSs) & RSS-Gen Issue 5

REPORT #: EMC\_XIRGO-132-20001\_15.247\_BTLE\_DTS\_REV1

DATE: 2020-07-07



A2LA Accredited

IC recognized #  
3462B-1

**CETECOM Inc.**

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: [info@cetecom.com](mailto:info@cetecom.com) ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571



**TABLE OF CONTENTS**

**1 ASSESSMENT..... 3**

**2 ADMINISTRATIVE DATA ..... 4**

2.1 IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT ..... 4

2.2 IDENTIFICATION OF THE CLIENT ..... 4

2.3 IDENTIFICATION OF THE MANUFACTURER..... 4

**3 EQUIPMENT UNDER TEST (EUT)..... 5**

3.1 EUT SPECIFICATIONS ..... 5

3.2 EUT SAMPLE DETAILS ..... 6

3.3 ACCESSORY EQUIPMENT (AE) DETAILS..... 6

3.4 TEST SAMPLE CONFIGURATION ..... 6

3.5 JUSTIFICATION FOR WORST CASE MODE OF OPERATION..... 7

**4 SUBJECT OF INVESTIGATION ..... 8**

**5 MEASUREMENT RESULTS SUMMARY ..... 8**

**6 MEASUREMENT UNCERTAINTY..... 9**

6.1 ENVIRONMENTAL CONDITIONS DURING TESTING:..... 9

6.2 DATES OF TESTING: ..... 9

**7 MEASUREMENT PROCEDURES ..... 10**

7.1 RADIATED MEASUREMENT..... 10

7.2 POWER LINE CONDUCTED MEASUREMENT PROCEDURE ..... 12

7.3 RF CONDUCTED MEASUREMENT PROCEDURE ..... 12

**8 TEST RESULT DATA ..... 13**

8.1 MAXIMUM PEAK CONDUCTED OUTPUT POWER..... 13

8.2 POWER SPECTRAL DENSITY ..... 20

8.3 DUTY CYCLE..... 27

8.4 BAND EDGE COMPLIANCE ..... 29

8.5 EMISSION BANDWIDTH 6dB AND 99% OCCUPIED BANDWIDTH..... 42

8.6 RADIATED TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BANDS ..... 56

**9 TEST SETUP PHOTOS ..... 69**

**10 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING ..... 69**

**11 HISTORY ..... 70**



## 1 Assessment

The following device was evaluated against the applicable criteria specified in FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations and the relevant ISED Canada standard RSS-247.

No deviations were ascertained.

Company	Description	Model #
Xirgo Technologies, LLC	Proximity Bluetooth beacons with a single chip Bluetooth 5 + ARM mounted to distribution carts, which are used in conjunction with XT49xx devices installed on trailers.	XT1520

### Responsible for Testing Laboratory:

2020-07-07	Compliance	Cindy Li (EMC Lab Manager)	
Date	Section	Name	Signature

### Responsible for the Report:

2020-07-07	Compliance	Chin Ming Lui (Associate EMC Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3. CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.



## 2 Administrative Data

### 2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

<b>Company Name:</b>	CETECOM Inc.
<b>Department:</b>	Compliance
<b>Street Address:</b>	411 Dixon Landing Road
<b>City/Zip Code</b>	Milpitas, CA 95035
<b>Country</b>	USA
<b>Telephone:</b>	+1 (408) 586 6200
<b>Fax:</b>	+1 (408) 586 6299
<b>EMC Lab Manager:</b>	Cindy Li
<b>Responsible Project Leader:</b>	Akanksha Baskaran

### 2.2 Identification of the Client

<b>Client's Name:</b>	Xirgo Technologies, LLC
<b>Street Address:</b>	188 Camino Ruiz
<b>City/Zip Code</b>	Camarillo, CA 93012
<b>Country</b>	USA
<b>Contact Person:</b>	Ed Gabrelian
<b>Phone No.</b>	(805) 568-8466
<b>e-mail:</b>	EGabrelian@xirgo.com

### 2.3 Identification of the Manufacturer

<b>Manufacturer's Name:</b>	Same as Client /-----
<b>Manufacturers Address:</b>	-----
<b>City/Zip Code</b>	-----
<b>Country</b>	-----

### 3 Equipment Under Test (EUT)

#### 3.1 EUT Specifications

<b>Model No:</b>	XT1520
<b>HW Version :</b>	Rev D
<b>SW Version :</b>	NV11.1125AA1.1
<b>FCC-ID :</b>	GKM-XT1520
<b>IC-ID:</b>	10281A-XT1520
<b>FWIN:</b>	N/A
<b>HVIN:</b>	XT1520
<b>PMN:</b>	Vuvuzela Proximity Beacon
<b>Product Description:</b>	Proximity Bluetooth beacons with a single chip Bluetooth 5 + ARM mounted to distribution carts, which are used in conjunction with XT49xx devices installed on trailers.
<b>Frequency Range / number of channels:</b>	Nominal band: 2400 MHz – 2483.5 MHz; Center to center: 2402 MHz (ch 0) – 2480 MHz (ch 39), 40 channels
<b>Radio Information:</b>	<u>Bluetooth Low Energy (BLE):</u> <ul style="list-style-type: none"> <li>• Manufacturer: Nordic Semiconductor</li> <li>• Module Name: Bluetooth 5.2 SoC supporting Bluetooth Low Energy</li> <li>• Module Number: nRF52810</li> <li>• Modes of Operation: LE 1 Mbps &amp; LE 2 Mbps in advertising mode</li> <li>• Modulation: GFSK</li> </ul>
<b>Antenna Information as declared:</b>	<u>Main Antenna:</u> <ul style="list-style-type: none"> <li>• Type: PCB</li> <li>• Location: Internal</li> <li>• Maximum Gain: 3.3 dBi</li> <li>• Frequency Band: 2.4 GHz ISM</li> </ul>
<b>Max. Peak Output Power:</b>	Conducted Power: 4.50 dBm
<b>Power Supply/ Rated Operating Voltage Range:</b>	2 AA Alkaline Batteries – Vmin: 2.2 VDC / Vnom: 2.7 VDC / Vmax: 3.3 VDC
<b>Operating Temperature Range</b>	-20 °C to 54 °C
<b>Sample Revision</b>	<input type="checkbox"/> Prototype Unit; <input checked="" type="checkbox"/> Production Unit; <input type="checkbox"/> Pre-Production



### 3.2 EUT Sample details

EUT #	Serial Number	HW Version	SW Version	Notes/Comments
1	201700017	Rev D	NV11.1125AA1.1	Conducted Emissions
2	201700006	Rev D	NV11.1125AA1.1	Radiated Emissions

### 3.3 Accessory Equipment (AE) details

N/A

### 3.4 Test Sample Configuration

EUT Set-up #	Combination of AE used for test set up	Comments
1	EUT #1	<p><u>Conducted Setup:</u>                      The radio of the EUT was configured using the “Direct Test Mode Tool” from Nordic Semiconductor:</p> <ul style="list-style-type: none"> <li>• Mode: Transmitter</li> <li>• Single Channel (Fixed):                             <ul style="list-style-type: none"> <li>○ Ch. 0 (Low, 2402 MHz)</li> <li>○ Ch. 19 (Mid, 2440 MHz)</li> <li>○ Ch. 39 (High, 2480 MHz)</li> </ul> </li> <li>• Transmit Radio Control:                             <ul style="list-style-type: none"> <li>○ Tx Power: 4 dBm</li> <li>○ Payload Model: PRBS9</li> <li>○ Payload Length: 255 Bytes</li> </ul> </li> <li>• Mode of Operation:                             <ul style="list-style-type: none"> <li>○ LE 1Mbps</li> <li>○ LE 2Mbps</li> </ul> </li> </ul> <p>The “Direct Test Mode Tool” will not be available to the end user.</p> <p>The measurement equipment was connected to the 50 ohm RF port of the EUT.</p>

2	EUT #2	<p><u>Radiated Setup:</u> The radio of the EUT was configured using the “Direct Test Mode Tool” from Nordic Semiconductor:</p> <ul style="list-style-type: none"><li>• Mode: Transmitter</li><li>• Single Channel (Fixed):<ul style="list-style-type: none"><li>○ Ch. 0 (Low, 2402 MHz)</li><li>○ Ch. 19 (Mid, 2440 MHz)</li><li>○ Ch. 39 (High, 2480 MHz)</li></ul></li><li>• Transmit Radio Control:<ul style="list-style-type: none"><li>○ Tx Power: 4 dBm</li><li>○ Payload Model: PRBS9</li><li>○ Payload Length: 255 Bytes</li></ul></li><li>• Mode of Operation:<ul style="list-style-type: none"><li>○ LE 2Mbps</li></ul></li></ul> <p>The “Direct Test Mode Tool” will not be available to the end user.</p> <p>The internal antenna was connected.</p>
---	--------	--

### 3.5 Justification for Worst Case Mode of Operation

During the testing process, the EUT was tested with transmitter sets on low, mid and high channels, and highest possible duty cycle of 85.3% for LE 1 Mbps and 57.3% for LE 2 Mbps.

For radiated measurements, LE 2 Mbps was chosen for evaluation, which is the worst case operating mode supported, based on the maximum peak conducted output power measured. All data in this report show the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.



#### 4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations and Radio Standard Specification RSS-247 of ISED Canada.

This test report is to support a request for new equipment authorization under the FCC ID: GKM-XT1520, IC ID: 10281A-XT1520

Testing procedures are based on 558074 D01 15.247 Meas Guidance v05r02 – “GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

#### 5 Measurement Results Summary

Test Specification	Test Case	Temperature and Voltage Conditions	Operating Mode	Pass	NA	NP	Result
§15.247(a)(1) RSS-247 5.2(a)	Emission Bandwidth	Nominal	LE 1 Mbps LE 2 Mbps	■	□	□	Complies
§15.247(e) RSS-247 5.2(b)	Power Spectral Density	Nominal	LE 1 Mbps LE 2 Mbps	■	□	□	Complies
§15.247(b)(1) RSS-247 5.4(d)	Maximum Conducted Output Power and EIRP	Nominal	LE 1 Mbps LE 2 Mbps	■	□	□	Complies
§15.247(d) RSS-247 5.5	Band edge compliance Unrestricted Band Edges	Nominal	LE 1 Mbps LE 2 Mbps	■	□	□	Complies
§15.247; 15.209; 15.205 RSS-Gen 8.9; 8.10	Band edge compliance Restricted Band Edges	Nominal	LE 1 Mbps LE 2 Mbps	■	□	□	Complies
§15.247(d); §15.209 RSS-Gen 6.13	TX Spurious emissions- Radiated	Nominal	LE 2 Mbps	■	□	□	Complies
§15.207(a) RSS Gen 8.8	AC Conducted Emissions	Nominal	N/A	□	□	■	See Note 2

**Note 1:** NA= Not Applicable; NP= Not Performed.

**Note 2:** EUT is battery powered, hence AC Conducted Emissions testing not applicable



## 6 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor  $k=1$ .

### Radiated measurement

9 kHz to 30 MHz	$\pm 2.5$ dB (Magnetic Loop Antenna)
30 MHz to 1000 MHz	$\pm 2.0$ dB (Biconilog Antenna)
1 GHz to 40 GHz	$\pm 2.3$ dB (Horn Antenna)

### Conducted measurement

150 kHz to 30 MHz	$\pm 0.7$ dB (LISN)
-------------------	---------------------

RF conducted measurement	$\pm 0.5$ dB
--------------------------	--------------

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error.

### 6.1 Environmental Conditions During Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25° C
- Relative humidity: 40-60%

### 6.2 Dates of Testing:


06/03/2020 - 06/08/2020

## 7 Measurement Procedures


### 7.1 Radiated Measurement

The radiated measurement is performed according to ANSI C63.10 (2013)


- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.



### Radiated Emissions Test Setup 30MHz-1GHz Measurements



### Radiated Emissions Test Setup above 1GHz Measurements



### 7.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dBμV
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:


Frequency (MHz)	Measured SA (dBμV)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dBμV/m)
1000	80.5	3.5	14	98.0

### 7.2 Power Line Conducted Measurement Procedure

AC Power Line conducted emissions measurements performed according to: ANSI C63.4 (2014)

### 7.3 RF Conducted Measurement Procedure

Testing procedures are based on 558074 D01 15.247 Meas Guidance v05r02 – “GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.



- Connect the equipment as shown in the above diagram.
- Adjust the settings of the SA (Rohde-Schwarz Spectrum Analyzer) to connect the EUT at the required mode of test.
- Measurements are to be performed with the EUT set to the low, middle and high channels and for worst case modulation schemes.



## 8 Test Result Data

### 8.1 Maximum Peak Conducted Output Power

#### 8.1.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

##### Spectrum Analyzer settings:

- RBW  $\geq$  DTS bandwidth
- VBW  $\geq$  3 x RBW
- Span  $\geq$  3 x RBW
- Sweep = Auto couple
- Detector function = Peak
- Trace = Max hold
- Use peak marker function to determine the peak amplitude level

#### 8.1.2 Limits:

##### Maximum Peak Output Power:

- FCC §15.247 (b)(1): 1 W
- IC RSS-247: 1 W

#### 8.1.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22.0 °C	1	BTLE fixed channel: LE 1 Mbps & LE 2 Mbps	2.7 VDC	3.3 dBi


#### 8.1.4 Measurement result:


Plot #	EUT operating mode	Channel	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	EIRP (dBm)	Limit (dBm)	Result
1	LE 1 Mbps	Low: 0	2402	4.44	7.74	30 (Pk) / 36 (EIRP)	Pass
2	LE 1 Mbps	Mid: 19	2440	4.32	7.62	30 (Pk) / 36 (EIRP)	Pass
3	LE 1 Mbps	High: 39	2480	4.13	7.43	30 (Pk) / 36 (EIRP)	Pass
4	LE 2 Mbps	Low: 0	2402	4.50	7.80	30 (Pk) / 36 (EIRP)	Pass
5	LE 2 Mbps	Mid: 19	2440	4.39	7.69	30 (Pk) / 36 (EIRP)	Pass
6	LE 2 Mbps	High: 39	2480	4.17	7.47	30 (Pk) / 36 (EIRP)	Pass



### 8.1.5 Measurement Plots:










1 PK  
MAX

2  
EVL  
300











## 8.2 Power Spectral Density

### 8.2.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

#### Spectrum Analyzer settings for Peak PSD method:

- Set analyzer center frequency to DTS channel center frequency
- Set the span to 1.5 x DTS bandwidth
- Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- Set the VBW  $\geq 3 \times \text{RBW}$
- Detector = Peak
- Sweep time = Auto couple
- Trace mode = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level within the RBW
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat

### 8.2.2 Limits:

#### FCC§15.247(e) & RSS-247 5.2(b)

- For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 8.2.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22.0 °C	1	BTLE fixed channel: LE 1 Mbps & LE 2 Mbps	2.7 VDC	3.3 dBi


### 8.2.4 Measurement result:


Plot #	EUT operating mode	Channel	Frequency (MHz)	Maximum Power Spectral Density (dBm / 3 kHz)	Limit (dBm / 3 kHz)	Result
1	LE 1 Mbps	Low: 0	2402	-11.75	8	Pass
2	LE 1 Mbps	Mid: 19	2440	-11.87	8	Pass
3	LE 1 Mbps	High: 39	2480	-12.10	8	Pass
4	LE 2 Mbps	Low: 0	2402	-13.63	8	Pass
5	LE 2 Mbps	Mid: 19	2440	-14.00	8	Pass
6	LE 2 Mbps	High: 39	2480	-14.03	8	Pass




### 8.2.5 Measurement Plots:


















### 8.3 Duty cycle

#### 8.3.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02


##### Spectrum Analyzer settings:

- Set the center frequency and of the instrument to the center frequency of the transmission
- Zero span
- Set RBW  $\geq$  OBW if possible; otherwise, set RBW to the largest available value
- Detector = Peak or average

#### 8.3.2 Measurement result



- Duty cycle = 85.3%
- Duty cycle correction factor =  $10 \cdot \log(1/0.853) = 0.69$  dB



- Duty cycle = 57.3%
- Duty cycle correction factor =  $10 \cdot \log(1/0.573) = 2.42$  dB

## 8.4 Band Edge Compliance

### 8.4.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

#### Spectrum Analyzer settings for band edge:

- Set the center frequency and span to encompass frequency range to be measured
- RBW = 100 kHz
- VBW  $\geq 3 \times$  RBW
- Sweep Time: Auto couple
- Detector = Peak
- Trace = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level
- Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge

### 8.4.2 Limits non restricted band:

#### FCC§15.247 (d)

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### RSS-247 5/5

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB.

#### Spectrum Analyzer settings for restricted band:

- Peak measurements are made using a peak detector and RBW=1 MHz

**8.4.3 Limits restricted band §15.247/15.209/15.205 and RSS-Gen 8.9/8.10**

- \*PEAK LIMIT= 74 dBµV/m @3m =-21.23 dBm
- \*AVG. LIMIT= 54 dBµV/m @3m =-41.23 dBm
- Start frequency & stop frequency according to frequency range specified in the restricted band table in FCC section 15.205 & RSS-Gen 8.10
- Measurements with a peak detector were used to show compliance to average limits, thus showing compliance to both peak and average limits.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

**8.4.4 Test conditions and setup:**

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22.0 °C	1	BTLE fixed channel: LE 1 Mbps & LE 2 Mbps	2.7 VDC	3.3 dBi



**8.4.5 Measurement result:**

Plot #	EUT operating mode	Band Edge	Band Edge Delta (dBc)	Limit (dBc)	Result
1	LE 1 Mbps	Lower, Non-restricted	-47.24	-20	Pass
2	LE 2 Mbps	Lower, Non-restricted	-31.66	-20	Pass


Plot #	EUT operating mode	Band Edge	Measured Peak Value (dBm)	Corrected by Duty Cycle (dB) <sup>Note</sup>	Corrected by Antenna Gain (dBm)	Limit (dBm)	Result
3	LE 1 Mbps	Lower Restricted Peak	-44.99	N/A	-41.69	-21.23 Peak	Pass
4	LE 1 Mbps	Lower Restricted AVG	-51.71	-51.02	-47.72	-41.23 AVG	Pass
5	LE 1 Mbps	Upper Restricted Peak	-37.20	N/A	-33.90	-21.23 Peak	Pass
6	LE 1 Mbps	Upper Restricted AVG	-54.75	-54.06	-50.76	-41.23 AVG	Pass
7	LE 2 Mbps	Lower Restricted Peak	-45.16	N/A	-41.86	-21.23 Peak	Pass
8	LE 2 Mbps	Lower Restricted AVG	-53.92	-51.50	-48.20	-41.23 AVG	Pass
9	LE 2 Mbps	Upper Restricted Peak	-35.94	N/A	-32.64	-21.23 Peak	Pass
10	LE 2 Mbps	Upper Restricted AVG	-52.45	-50.03	-46.73	-41.23 AVG	Pass

**Note:**


LE 1 Mbps → EUT operating at 85.3% duty cycle, duty cycle correction factor = 0.69 dB  
 LE 2 Mbps → EUT operating at 57.3% duty cycle, duty cycle correction factor = 2.42 dB





### 8.4.6 Measurement Plots:































## 8.5 Emission Bandwidth 6dB and 99% Occupied Bandwidth

### 8.5.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

#### Spectrum Analyzer settings:

##### 6dB (DTS) Bandwidth:

- Set RBW = 100 kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

##### 99% Occupied Bandwidth:

- Set frequency = nominal EUT channel center frequency
- Set Span = 1.5 x to 5.0 x OBW
- Set RBW = 1% to 5% of OBW
- Set the video bandwidth (VBW)  $\approx 3 \times$  RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

### 8.5.2 Limits:

#### FCC §15.247(a)(2) and RSS-247 5.2(a)

- Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.



**8.5.3 Test conditions and setup:**

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22.0 °C	1	BTLE fixed channel: LE 1 Mbps & LE 2 Mbps	2.7 VDC

**8.5.4 Measurement result:**


Plot #	EUT Operating Mode	Channel	Frequency (MHz)	6dB Emissions Bandwidth (MHz)	Limit (MHz)	Result
1	LE 1 Mbps	Low: 0	2402	0.7051	> 0.5	Pass
2	LE 1 Mbps	Mid: 19	2440	0.7051	> 0.5	Pass
3	LE 1 Mbps	High: 39	2480	0.7051	> 0.5	Pass
4	LE 2 Mbps	Low: 0	2402	1.1699	> 0.5	Pass
5	LE 2 Mbps	Mid: 19	2440	1.1699	> 0.5	Pass
6	LE 2 Mbps	High: 39	2480	1.1699	> 0.5	Pass


Plot #	EUT Operating Mode	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
7	LE 1 Mbps	Low: 0	2402	1.0497	> 0.5	Pass
8	LE 1 Mbps	Mid: 19	2440	1.0497	> 0.5	Pass
9	LE 1 Mbps	High: 39	2480	1.0577	> 0.5	Pass
10	LE 2 Mbps	Low: 0	2402	2.0833	> 0.5	Pass
11	LE 2 Mbps	Mid: 19	2440	2.0833	> 0.5	Pass
12	LE 2 Mbps	High: 39	2480	2.0994	> 0.5	Pass





8.5.5 Measurement Plots:


6 dB Emission Bandwidth























### 99% Occupied Bandwidth














## 8.6 Radiated Transmitter Spurious Emissions and Restricted Bands

### 8.6.1 Measurement according to ANSI C63.10 (2013)

#### Spectrum Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector: Peak
  
- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW= 120 KHz (<1GHz)
  
- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1 MHz
  
- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing frequencies below 30 MHz at distance other than the specified in the standard, the limit conversion is calculated by using the FCC materials for the ANSI 63 committee issued on January, 27 1991.

### 8.6.2 Limits:

#### FCC §15.247

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).





FCC §15.209 & RSS-Gen 8.9

- Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength (µV/m)	Measurement Distance (m)	Field strength @ 3m (dBµV/m)
0.009–0.490	2400/F(kHz) / -----	300	-
0.490–1.705	24000/F(kHz) / -----	30	-
1.705–30.0	30 / (29.5)	30	-
30–88	100	3	40 dBµV/m
88–216	150	3	43.5 dBµV/m
216–960	200	3	46 dBµV/m
Above 960	500	3	54 dBµV/m

FCC §15.205 & RSS-Gen 8.10

- Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).  
 \*PEAK LIMIT= 74 dBµV/m  
 \*AVG. LIMIT= 54 dBµV/m




### 8.6.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22.0 °C	2	Bluetooth LE 2 Mbps	2.7 VDC

### 8.6.4 Measurement result:

Plot #	Channel #	Scan Frequency	Limit	Result
1-3	Low: 0	30 MHz – 18 GHz	See section 8.6.2	Pass
4-8	Mid: 19	9 kHz – 26 GHz	See section 8.6.2	Pass
9-11	High: 39	30 MHz – 18 GHz	See section 8.6.2	Pass

### 8.6.5 Measurement Plots:



Plot #2 Radiated Emissions: 1-3 GHz


Mode of Operation: Bluetooth LE 2 Mbps

Low Channel: 0

57.3% Duty Cycle

Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2273.857	---	48.88	53.98	5.10	500.0	1000.000	163.0	H	194.0	34.4
2273.857	60.87	---	73.98	13.11	500.0	1000.000	163.0	H	194.0	34.4
2529.714	---	50.61	53.98	3.37	500.0	1000.000	206.0	H	205.0	35.6
2529.714	62.69	---	73.98	11.29	500.0	1000.000	206.0	H	205.0	35.6



◆ Preview R result 1-PK+     — FCC 15.209 PK at 3m     - - - FCC 15.209 AVG at 3m  
◆ Final\_Result PK+     ◆ Final\_Result CAV



Plot #3 Radiated Emissions: 3-18 GHz


Mode of Operation: Bluetooth LE 2 Mbps

Low Channel: 0

57.3% Duty Cycle

Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7204.500	---	46.01	53.98	7.97	500.0	1000.000	140.0	V	266.0	-0.6
7204.500	58.90	---	73.98	15.08	500.0	1000.000	140.0	V	266.0	-0.6



◆ Preview Result 1-PK+ Final\_Result PK+
 — FCC 15.209 PK at 3m
 — FCC 15.209 AVG at 3m
 ◆ Final\_Result CAV




Plot #4 Radiated Emissions: 9 KHz – 30 MHz

Mode of Operation: Bluetooth LE 2 Mbps

Mid Channel: 19

57.3% Duty Cycle



- Preview Result 1-PK+ Final\_Result QPK
- Critical\_Freqs PK+ Final\_Result PK+
- FCC 15.209 QP at 3m



Plot #5 Radiated Emissions: 30 MHz – 1 GHz


Mode of Operation: Bluetooth LE 2 Mbps

Mid Channel: 19

57.3% Duty Cycle

Final\_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
900.058	20.38	46.02	25.64	500.0	120.000	250.0	H	73.0	-5.0



Preview Result 1-PK+    FCC 15.209 QP at 3m    Final\_Result QPK    Final\_Result PK+

Plot #6 Radiated Emissions: 1-3 GHz


Mode of Operation: Bluetooth LE 2 Mbps

Mid Channel: 19

57.3% Duty Cycle

Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2311.714	61.99	---	73.98	11.99	500.0	1000.000	140.0	H	196.0	34.7
2311.714	---	49.78	53.98	4.20	500.0	1000.000	140.0	H	196.0	34.7
2567.571	63.44	---	73.98	10.54	500.0	1000.000	140.0	H	208.0	35.8
2567.571	---	50.67	53.98	3.31	500.0	1000.000	140.0	H	208.0	35.8



◆ Preview Result 1-PK+ Final\_Result PK+
 — FCC 15.209 PK at 3m
 - - - FCC 15.209 AVG at 3m
 ◆ Final\_Result CAV



Plot #7 Radiated Emissions: 3-18 GHz


Mode of Operation: Bluetooth LE 2 Mbps

Mid Channel: 19

57.3% Duty Cycle

Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7318.500	---	45.42	53.98	8.56	500.0	1000.000	153.0	V	267.0	-0.5
7318.500	58.12	---	73.98	15.86	500.0	1000.000	153.0	V	267.0	-0.5



◆ Preview Result 1-PK+ Final\_Result PK+
 — FCC 15.209 PK at 3m
 - - - FCC 15.209 AVG at 3m
 ◆ Final\_Result CAV






Plot #8 Radiated Emissions: 18-26 GHz

Mode of Operation: Bluetooth LE 2 Mbps

Mid Channel: 19

57.3% Duty Cycle



- Preview Result 1-PK+
- FCC 15.209 AVG at 1m
- Critical\_Freqs PK+
- Final\_Result PK+
- FCC 15.209 PK at 1m
- Final\_Result CAV



Plot #9 Radiated Emissions: 30 MHz – 1 GHz


Mode of Operation: Bluetooth LE 2 Mbps

High Channel: 39

57.3% Duty Cycle

Final\_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
937.694	21.12	46.02	24.90	500.0	120.000	152.0	V	312.0	-4.2



— Preview Result 1-PK+    — FCC 15.209 QP at 3m    ◆ Final\_Result QPK    ◆ Final\_Result PK+




Plot #10 Radiated Emissions: 1-3 GHz

Mode of Operation: Bluetooth LE 2 Mbps | High Channel: 39 | 57.3% Duty Cycle

Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2351.571	---	49.57	53.98	4.41	500.0	1000.000	163.0	H	209.0	34.8
2351.571	62.40	---	73.98	11.57	500.0	1000.000	163.0	H	209.0	34.8
2608.143	---	51.36	53.98	2.62	500.0	1000.000	286.0	H	228.0	35.9
2608.143	63.68	---	73.98	10.29	500.0	1000.000	286.0	H	228.0	35.9



◆ Preview Result 1-PK+ Final\_Result PK+
 — FCC 15.209 PK at 3m
 — FCC 15.209 AVG at 3m
 ◆ Final\_Result CAV



Plot #11 Radiated Emissions: 3-18 GHz


Mode of Operation: Bluetooth LE 2 Mbps

High Channel: 39

57.3% Duty Cycle

Final\_Result

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7441.500	---	45.17	53.98	8.80	500.0	1000.000	140.0	V	259.0	-0.2
7441.500	57.77	---	73.98	16.21	500.0	1000.000	140.0	V	259.0	-0.2



◆ Preview Result 1-PK+ Final\_Result PK+
 — FCC 15.209 PK at 3m
 - - - FCC 15.209 AVG at 3m
 ◆ Final\_Result CAV



## 9 Test setup photos

Setup photos are included in supporting file name: "EMC\_XIRGO-132-20001\_15.247\_BTLE\_DTS\_Setup\_Photos\_REV1.pdf"

## 10 Test Equipment And Ancillaries Used For Testing

Item Name	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
Loop Antenna	ETS Lindgren	6507	161344	3 years	10/26/2017
Biconlog Antenna	ETS Lindgren	3142E	166067	3 years	03/12/2020
Horn Antenna	ETS Lindgren	3115	35114	3 years	07/31/2017
Horn Antenna	ETS Lindgren	3117-PA	215984	3 years	01/26/2018
Horn Antenna	ETS Lindgren	3116	70497	3 years	10/31/2017
EMI Receiver	R&S	ESU40	100251	3 years	07/16/2019
Spectrum Analyzer	R&S	FSU26	200065	3 years	07/16/2019
Thermometer Humidity Monitor	Control Company	36934-164	191872028	2 years	01/10/2019

**Note:** Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.



## 11 History

<b>Date</b>	<b>Report Name</b>	<b>Changes to report</b>	<b>Report Prepared by</b>
2020-06-30	EMC_XIRGO-132-20001_15.247_BTLE_DTS	Initial Version	Chin Ming Lui
2020-07-07	EMC_XIRGO-132-20001_15.247_BTLE_DTS_REV1	Modified FCC ID & IC ID	Chin Ming Lui

<<< The End >>>