

Partial FCC Test Report

(PART 24)

Report No.: RFBEDW-WTW-P21040353-1

FCC ID: GKR-LN100EG3L

Test Model: Lenovo 100e Chromebook Gen 3*****(*=0~9, A~Z, a~z, "-" or blank, for marketing use only, with no impact on RF compliance of the product)

Received Date: Apr. 21, 2021

Test Date: May 14 ~ Jun. 24, 2021

Issued Date: Jun. 28, 2021

Applicant: Compal Electronics Inc

Address: No. 581 & 581-1, Ruiguang Rd., Neihu District, Taipei City 11492, Taiwan, R.O.C

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration /

Designation Number: 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty.....	5
2.2 Test Site and Instruments	6
3 General Information	7
3.1 General Description of EUT.....	7
3.2 Configuration of System under Test.....	9
3.2.1 Description of Support Units.....	9
3.3 Test Mode Applicability and Tested Channel Detail	10
3.4 EUT Operating Conditions	12
3.5 General Description of Applied Standards and references	12
4 Test Types and Results	13
4.1 Output Power Measurement.....	13
4.1.1 Limits of Output Power Measurement	13
4.1.2 Test Procedures.....	13
4.1.3 Test Setup.....	13
4.1.4 Test Results	14
4.2 Radiated Emission Measurement.....	22
4.2.1 Limits of Radiated Emission Measurement	22
4.2.2 Test Procedure	22
4.2.3 Deviation from Test Standard	22
4.2.4 Test Setup.....	23
4.2.5 Test Results	24
5 Pictures of Test Arrangements	36
Appendix – Information of the Testing Laboratories	37

Release Control Record

Issue No.	Description	Date Issued
RFBEDW-WTW-P21040353-1	Original Release	Jun. 28, 2021

1 Certificate of Conformity

Product: Notebook Computer

Brand: Lenovo

Test Model: Lenovo 100e Chromebook Gen 3*****(*=0~9, A~Z, a~z, "-" or blank, for marketing use only, with no impact on RF compliance of the product)

Sample Status: Engineering Sample

Applicant: Compal Electronics Inc

Test Date: May 14 ~ Jun. 24, 2021

Standards: FCC Part 24, Subpart E

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : , **Date:** Jun. 28, 2021
Polly Chien / Specialist

Approved by : , **Date:** Jun. 28, 2021
Bruce Chen / Senior Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 24 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 24.232	Effective Isotropic Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	N/A	Refer to Note 1
24.232(d)	Peak to Average Ratio	N/A	Refer to Note 1
2.1055 24.235	Frequency Stability	N/A	Refer to Note 1
2.1049	Occupied Bandwidth	N/A	Refer to Note 1
24.238	Band Edge Measurements	N/A	Refer to Note 1
2.1051 24.238	Conducted Spurious Emissions	N/A	Refer to Note 1
2.1053 24.238	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -28.64 dB at 31.41 MHz.

Note:

- This report is a partial report. Therefore, only test item of Effective Isotropic Radiated Power and Radiated Spurious Emissions tests were performed for this report. Other testing data please refer to SPORTON report no.: FG091101A_R01 & FG091101B_R01 for module (Brand: Fibocom, Model: NL668-AM-00)
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	9 kHz ~ 30 MHz	3.04 dB
	30 MHz ~ 200 MHz	3.86 dB
	200 MHz ~ 1000 MHz	3.87 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.29 dB
	18 GHz ~ 40 GHz	2.29 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESR3	102579	Jul. 07, 2020	Jul. 06, 2021
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Sep. 16, 2020	Sep. 15, 2021
BILOG Antenna SCHWARZBECK	VULB9168	9168-171	Nov. 04, 2020	Nov. 03, 2021
HORN Antenna SCHWARZBECK	9120D	209	Nov. 22, 2020	Nov. 21, 2021
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Nov. 22, 2020	Nov. 21, 2021
Loop Antenna EMCI	EM-6879	269	Sep. 17, 2020	Sep. 16, 2021
Preamplifier Agilent (Below 1GHz)	8447D	2944A10738	Aug. 16, 2020	Aug. 15, 2021
Preamplifier Agilent (Above 1GHz)	8449B	3008A02465	Mar. 22, 2021	Mar. 21, 2022
RF Coaxial Cable WOKEN With 5dB PAD	8D-FB	Cable-CH3-01	Aug. 16, 2020	Aug. 15, 2021
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH3-03 (223653/4)	Aug. 16, 2020	Aug. 15, 2021
RF signal cable HUBER+SUHNER& EMCI	SUCOFLEX 104&EMC104-SM-S M-8000	Cable-CH3-03 (309224+170907)	Aug. 16, 2020	Aug. 15, 2021
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Turn Table Controller BV ADT	SC100	SC93021702	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
WIT Standard Temperature And Humidity Chamber	TH-4S-C	W981030	Jun. 01, 2020	May 31, 2021
			Jun. 01, 2021	May 31, 2022
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
True RMS Clamp Meter Fluke	325	31130711WS	Jun. 06, 2020	Jun. 05, 2021
			Jun. 02, 2021	Jun. 01, 2022

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 3.

3 General Information

3.1 General Description of EUT

Product	Notebook Computer		
Brand	Lenovo		
Test Model	Lenovo 100e Chromebook Gen 3*****(*=0~9, A~Z, a~z, "-" or blank, for marketing use only, with no impact on RF compliance of the product)		
Status of EUT	Engineering Sample		
Power Supply Rating	20Vdc from adapter		
Modulation Type	WCDMA	QPSK	
	LTE	QPSK, 16QAM	
Frequency Range	WCDMA	1852.4 ~ 1907.6 MHz	
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1850.7 ~ 1909.3 MHz	
	LTE Band 2 (Channel Bandwidth: 3 MHz)	1851.5 ~ 1908.5 MHz	
	LTE Band 2 (Channel Bandwidth: 5 MHz)	1852.5 ~ 1907.5 MHz	
	LTE Band 2 (Channel Bandwidth: 10 MHz)	1855.0 ~ 1905.0 MHz	
	LTE Band 2 (Channel Bandwidth: 15 MHz)	1857.5 ~ 1902.5 MHz	
	LTE Band 2 (Channel Bandwidth: 20 MHz)	1860.0 ~ 1900.0 MHz	
Max. EIRP Power	WCDMA	91.622mW (19.62dBm)	
		QPSK	16QAM
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	75.683mW (18.79dBm)	58.614mW (17.68dBm)
	LTE Band 2 (Channel Bandwidth: 3 MHz)	74.817mW (18.74dBm)	59.841mW (17.77dBm)
	LTE Band 2 (Channel Bandwidth: 5 MHz)	74.817mW (18.74dBm)	59.566mW (17.75dBm)
	LTE Band 2 (Channel Bandwidth: 10 MHz)	75.509mW (18.78dBm)	59.841mW (17.77dBm)
	LTE Band 2 (Channel Bandwidth: 15 MHz)	75.858mW (18.80dBm)	59.156mW (17.72dBm)
	LTE Band 2 (Channel Bandwidth: 20 MHz)	76.033mW (18.81dBm)	59.841mW (17.77dBm)
Antenna Type	Refer to Note as below		
Accessory Device	Refer to Note as below		
Data Cable Supplied	Refer to Note as below		

Note:

1. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	Lenovo	ADLX65YAC2D	I/P: 100-240Vac, 50-60Hz, 1.8A O/P: 20.0V ===3.25A, 65.0W 1.55M / 1core
Battery	Lenovo	L20D3PG0	11.52 Vdc, 3994 mAh, 46Wh
PCS Licensed Transmitter LTE module	Fibocom	NL668-AM-00	--


2. The antenna information is listed as below.

Ant. Type	Brand	Ant.	Model	Antenna Peak Gain (dBi)		Connector
				WCDMA II	LTE 2	
PIFA	MAGLAYERS	Main	DC33002K410 (FPA-8011-4G0C7-A1)	-3.70	-3.70	-
		Aux.	DC33002K410 (FPA-8011-4G0C7-A1)			
	South Star	Main	DC33002IZ10 (N19-0848-R0A)	-3.91	-3.91	MHF-B13-N-01
		Aux.	DC33002IZ10 (N19-0848-R0A)			

* The Max antenna gain was chosen for final test.

3. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Flash	HP	v250W	05	NA	-
	Flash	HP	v250W	09	NA	-
B.	Monitor	DELL	SE2416Hc	CN-OWJKMC-641 80-66D-013B-A00	FCC DoC Approved	-
C.	Earphone	NA	NA	NA	NA	-
D.	Mouse	Microsoft	ITE78CJ	NA	FCC DoC Approved	-

Note: All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	HDMI cable	1	1.0	N	0	Provided by Lab (Brand: Amber, Model: HDMI-AA120)
2.	Power cable	1	1.75	N	0	Provided by Client
3.	Audio cable	1	1.2	N	0	-
4.	USB cable	1	1.8	N	0	-

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis & NB Mode, and antenna ports.

The worst case was found when positioned on NB mode for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

WCDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA, HSDPA, HSUPA
-	Radiated Emission	9262 to 9538	9262, 9400, 9538	WCDMA

LTE Band 2

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK / 16QAM	1 RB / 0 RB Offset 1 RB / 2 RB Offset 1 RB / 5 RB Offset 3 RB / 0 RB Offset 3 RB / 1 RB Offset 3 RB / 3 RB Offset 6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK / 16QAM	1 RB / 0 RB Offset 1 RB / 7 RB Offset 1 RB / 14 RB Offset 8 RB / 0 RB Offset 8 RB / 3 RB Offset 8 RB / 7 RB Offset 15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK / 16QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK / 16QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK / 16QAM	1 RB / 0 RB Offset 1 RB / 37 RB Offset 1 RB / 74 RB Offset 36 RB / 0 RB Offset 36 RB / 19 RB Offset 36 RB / 39 RB Offset 75 RB / 0 RB Offset
		18675 to 19125	18700, 18900, 19100	20 MHz	QPSK / 16QAM	1 RB / 0 RB Offset 1 RB / 50 RB Offset 1 RB / 99 RB Offset 50 RB / 0 RB Offset 50 RB / 25 RB Offset 50 RB / 50 RB Offset 100 RB / 0 RB Offset
-	Radiated Emission	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK	1 RB / 0 RB Offset

Note:

1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.
2. For radiated emission above 1 GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5 MHz & highest channel bandwidth for final test.
3. For radiated emissions below 1 GHz, select the worst radiated emission channel for final testing.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	23 deg. C, 67 % RH	120 Vac, 60 Hz	Jones Chang
Radiated Emission	23 deg. C, 67 % RH	120 Vac, 60 Hz	Adair Peng

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards and references

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

ANSI 63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-E 2016

NOTE: All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.i.r.p.

4.1.2 Test Procedures

Conducted Power Measurement:

The EUT was set up for the maximum power with WCDMA, LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

Maximum EIRP / ERP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

$$\text{EIRP} = P_{\text{Meas}} + G_{\text{T}}$$

$$\text{ERP} = P_{\text{Meas}} + G_{\text{T}} - 2.15$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively
(expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_{T} gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

4.1.3 Test Setup

Conducted Power Measurement:



4.1.4 Test Results

Conducted Output Power (dBm)

Band	WCDMA II		
	9262	9400	9538
TX Channel	9262	9400	9538
Rx Channel	9662	9800	9938
Frequency	1852.4	1880	1907.6
RMC 12.2K	23.18	23.21	23.32
HSDPA Subtest-1	22.24	22.46	22.55
HSDPA Subtest-2	22.24	22.47	22.55
HSDPA Subtest-3	21.74	21.98	22.17
HSDPA Subtest-4	21.73	21.97	22.16
HSUPA Subtest-1	21.76	22.33	22.17
HSUPA Subtest-2	21.35	21.46	21.50
HSUPA Subtest-3	20.95	21.27	21.50
HSUPA Subtest-4	21.30	21.46	21.47
HSUPA Subtest-5	22.50	22.70	22.80

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18700	18900	19100
		Frequency (MHz)		1860	1880	1900
20M	QPSK	1	0	22.22	22.26	22.51
		1	50	22.15	22.46	22.20
		1	99	22.13	22.14	22.18
		50	0	21.19	21.30	21.48
		50	25	21.12	21.31	21.30
		50	50	20.15	21.32	21.28
		100	0	21.06	21.28	21.36
20M	16QAM	1	0	21.13	21.47	21.28
		1	50	21.09	21.21	21.13
		1	99	21.08	21.18	21.15
		50	0	20.12	20.42	20.36
		50	25	20.11	20.51	20.49
		50	50	20.12	20.44	20.08
		100	0	20.08	20.30	20.25

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18675	18900	19125
		Frequency (MHz)		1857.5	1880	1902.5
15M	QPSK	1	0	22.37	22.48	22.48
		1	37	22.24	22.40	22.50
		1	74	22.04	22.50	22.27
		36	0	21.27	21.39	21.30
		36	19	21.15	21.37	21.30
		36	39	21.13	21.36	21.43
		75	0	21.13	21.42	21.38
15M	16QAM	1	0	21.18	21.29	21.42
		1	37	21.15	21.33	21.28
		1	74	21.02	21.26	21.26
		36	0	20.28	20.42	20.32
		36	19	20.28	20.42	20.27
		36	39	20.07	20.41	20.29
		75	0	20.14	20.55	20.49

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18650	18900	19150
		Frequency (MHz)		1855	1880	1905
10M	QPSK	1	0	22.20	22.21	22.48
		1	24	22.13	22.40	22.18
		1	49	22.10	22.09	22.08
		25	0	21.13	21.21	21.44
		25	12	21.09	21.22	21.26
		25	25	21.13	21.26	21.21
		50	0	21.06	21.24	21.32
10M	16QAM	1	0	21.10	21.47	21.26
		1	24	21.09	21.14	21.06
		1	49	21.04	21.18	21.11
		25	0	20.06	20.32	20.29
		25	12	20.08	20.50	20.43
		25	25	20.12	20.42	20.08
		50	0	20.04	20.28	20.15

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18625	18900	19175
		Frequency (MHz)		1852.5	1880	1907.5
5M	QPSK	1	0	22.20	22.21	22.44
		1	12	22.07	22.42	22.13
		1	24	22.11	22.04	22.18
		12	0	21.14	21.26	21.42
		12	6	21.09	21.26	21.25
		12	13	21.15	21.23	21.20
		25	0	21.04	21.20	21.31
5M	16QAM	1	0	21.04	21.45	21.25
		1	12	21.08	21.15	21.03
		1	24	21.03	21.15	21.11
		12	0	20.12	20.40	20.33
		12	6	20.09	20.44	20.48
		12	13	20.11	20.36	20.04
		25	0	20.02	20.24	20.16

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18615	18900	19185
		Frequency (MHz)		1851.5	1880	1908.5
3M	QPSK	1	0	22.22	22.20	22.44
		1	7	22.08	22.44	22.14
		1	14	22.03	22.14	22.13
		8	0	21.11	21.23	21.41
		8	3	21.12	21.21	21.30
		8	7	21.15	21.24	21.23
		15	0	21.05	21.22	21.29
3M	16QAM	1	0	21.09	21.47	21.20
		1	7	21.03	21.15	21.08
		1	14	21.08	21.17	21.14
		8	0	20.05	20.41	20.27
		8	3	20.02	20.48	20.40
		8	7	20.07	20.35	20.01
		15	0	20.07	20.26	20.21

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18607	18900	19193
		Frequency (MHz)		1850.7	1880	1909.3
1.4M	QPSK	1	0	22.14	22.26	22.47
		1	2	22.05	22.39	22.11
		1	5	22.11	22.11	22.10
		3	0	22.22	22.18	22.49
		3	1	22.08	22.38	22.17
		3	3	22.10	22.10	22.08
		6	0	21.11	21.27	21.48
1.4M	16QAM	1	0	21.11	21.26	21.22
		1	2	21.15	21.27	21.21
		1	5	21.07	21.23	21.29
		3	0	21.13	21.38	21.23
		3	1	21.06	21.11	21.10
		3	3	21.13	21.38	21.23
		6	0	20.05	20.33	20.23

EIRP Power (dBm)

Band	WCDMA II		
	9262	9400	9538
TX Channel	9262	9400	9538
Rx Channel	9662	9800	9938
Frequency	1852.4	1880	1907.6
RMC 12.2K	19.48	19.51	19.62
HSDPA Subtest-1	18.54	18.76	18.85
HSDPA Subtest-2	18.54	18.77	18.85
HSDPA Subtest-3	18.04	18.28	18.47
HSDPA Subtest-4	18.03	18.27	18.46
HSUPA Subtest-1	18.06	18.63	18.47
HSUPA Subtest-2	17.65	17.76	17.80
HSUPA Subtest-3	17.25	17.57	17.80
HSUPA Subtest-4	17.60	17.76	17.77
HSUPA Subtest-5	18.80	19.00	19.10

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18700	18900	19100
		Frequency (MHz)		1860	1880	1900
20M	QPSK	1	0	18.52	18.56	18.81
		1	50	18.45	18.76	18.50
		1	99	18.43	18.44	18.48
		50	0	17.49	17.60	17.78
		50	25	17.42	17.61	17.60
		50	50	16.45	17.62	17.58
		100	0	17.36	17.58	17.66
20M	16QAM	1	0	17.43	17.77	17.58
		1	50	17.39	17.51	17.43
		1	99	17.38	17.48	17.45
		50	0	16.42	16.72	16.66
		50	25	16.41	16.81	16.79
		50	50	16.42	16.74	16.38
		100	0	16.38	16.60	16.55

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18675	18900	19125
		Frequency (MHz)		1857.5	1880	1902.5
15M	QPSK	1	0	18.67	18.78	18.78
		1	37	18.54	18.70	18.80
		1	74	18.34	18.80	18.57
		36	0	17.57	17.69	17.60
		36	19	17.45	17.67	17.60
		36	39	17.43	17.66	17.73
		75	0	17.43	17.72	17.68
15M	16QAM	1	0	17.48	17.59	17.72
		1	37	17.45	17.63	17.58
		1	74	17.32	17.56	17.56
		36	0	16.58	16.72	16.62
		36	19	16.58	16.72	16.57
		36	39	16.37	16.71	16.59
		75	0	16.44	16.85	16.79

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18650	18900	19150
		Frequency (MHz)		1855	1880	1905
10M	QPSK	1	0	18.50	18.51	18.78
		1	24	18.43	18.70	18.48
		1	49	18.40	18.39	18.38
		25	0	17.43	17.51	17.74
		25	12	17.39	17.52	17.56
		25	25	17.43	17.56	17.51
		50	0	17.36	17.54	17.62
10M	16QAM	1	0	17.40	17.77	17.56
		1	24	17.39	17.44	17.36
		1	49	17.34	17.48	17.41
		25	0	16.36	16.62	16.59
		25	12	16.38	16.80	16.73
		25	25	16.42	16.72	16.38
		50	0	16.34	16.58	16.45

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18625	18900	19175
		Frequency (MHz)		1852.5	1880	1907.5
5M	QPSK	1	0	18.50	18.51	18.74
		1	12	18.37	18.72	18.43
		1	24	18.41	18.34	18.48
		12	0	17.44	17.56	17.72
		12	6	17.39	17.56	17.55
		12	13	17.45	17.53	17.50
		25	0	17.34	17.50	17.61
5M	16QAM	1	0	17.34	17.75	17.55
		1	12	17.38	17.45	17.33
		1	24	17.33	17.45	17.41
		12	0	16.42	16.70	16.63
		12	6	16.39	16.74	16.78
		12	13	16.41	16.66	16.34
		25	0	16.32	16.54	16.46

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18615	18900	19185
		Frequency (MHz)		1851.5	1880	1908.5
3M	QPSK	1	0	18.52	18.50	18.74
		1	7	18.38	18.74	18.44
		1	14	18.33	18.44	18.43
		8	0	17.41	17.53	17.71
		8	3	17.42	17.51	17.60
		8	7	17.45	17.54	17.53
		15	0	17.35	17.52	17.59
3M	16QAM	1	0	17.39	17.77	17.50
		1	7	17.33	17.45	17.38
		1	14	17.38	17.47	17.44
		8	0	16.35	16.71	16.57
		8	3	16.32	16.78	16.70
		8	7	16.37	16.65	16.31
		15	0	16.37	16.56	16.51

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18607	18900	19193
		Frequency (MHz)		1850.7	1880	1909.3
1.4M	QPSK	1	0	18.44	18.56	18.77
		1	2	18.35	18.69	18.41
		1	5	18.41	18.41	18.40
		3	0	18.52	18.48	18.79
		3	1	18.38	18.68	18.47
		3	3	18.40	18.40	18.38
		6	0	17.41	17.57	17.78
1.4M	16QAM	1	0	17.41	17.56	17.52
		1	2	17.45	17.57	17.51
		1	5	17.37	17.53	17.59
		3	0	17.43	17.68	17.53
		3	1	17.36	17.41	17.40
		3	3	17.43	17.68	17.53
		6	0	16.35	16.63	16.53

4.2 Radiated Emission Measurement

4.2.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13 dBm.

4.2.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- c. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15 dB.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz.
2. The emission levels were against the limit of frequency range 9 kHz ~ 30 MHz:


The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

4.2.3 Deviation from Test Standard


No deviation.

4.2.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.5 Test Results


BELOW 1GHz

RF Mode	TX WCDMA Band II	Channel	CH 9262 : 1852.4 MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	30.00	-44.75	-13.00	-31.75	1.50 H	306	61.44	-106.19
2	66.55	-52.52	-13.00	-39.52	1.50 H	342	52.99	-105.51
3	148.09	-54.01	-13.00	-41.01	1.00 H	132	49.91	-103.92
4	297.10	-58.18	-13.00	-45.18	1.00 H	108	43.70	-101.88
5	363.17	-55.42	-13.00	-42.42	1.00 H	253	45.13	-100.55
6	429.25	-58.51	-13.00	-45.51	1.00 H	351	40.43	-98.94

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.




RF Mode	TX WCDMA Band II	Channel	CH 9262 : 1852.4 MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3m

No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	31.41	-47.04	-13.00	-34.04	1.50 V	322	59.25	-106.29
2	65.14	-48.31	-13.00	-35.31	1.00 V	151	57.09	-105.40
3	98.88	-53.85	-13.00	-40.85	1.00 V	90	54.85	-108.70
4	297.10	-52.06	-13.00	-39.06	2.00 V	40	49.82	-101.88
5	363.17	-56.44	-13.00	-43.44	1.00 V	261	44.11	-100.55
6	429.25	-56.57	-13.00	-43.57	2.00 V	87	42.37	-98.94

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.




RF Mode	TX LTE Band II-1.4MHz	Channel	CH 18900 : 1880 MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	31.41	-41.64	-13.00	-28.64	1.49 H	86	64.65	-106.29
2	98.88	-53.38	-13.00	-40.38	1.99 H	307	55.32	-108.70
3	150.90	-54.27	-13.00	-41.27	1.49 H	166	49.50	-103.77
4	297.10	-57.34	-13.00	-44.34	1.00 H	112	44.54	-101.88
5	363.17	-55.83	-13.00	-42.83	1.00 H	242	44.72	-100.55
6	429.25	-56.71	-13.00	-43.71	1.49 H	163	42.23	-98.94

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.




RF Mode	TX LTE Band II-1.4MHz	Channel	CH 18900 : 1880 MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3m

No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	32.81	-42.52	-13.00	-29.52	1.99 V	110	63.62	-106.14
2	66.55	-45.84	-13.00	-32.84	1.00 V	12	59.68	-105.52
3	98.88	-52.12	-13.00	-39.12	1.00 V	92	56.58	-108.70
4	136.84	-53.79	-13.00	-40.79	1.00 V	99	50.76	-104.55
5	297.10	-50.18	-13.00	-37.18	1.00 V	55	51.70	-101.88
6	363.17	-52.56	-13.00	-39.56	1.51 V	190	47.99	-100.55

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.



ABOVE 1GHz

RF Mode	TX WCDMA Band II	Channel	CH 9262 : 1852.4 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3704.80	-49.70	-13.00	-36.70	1.77 H	350	43.50	-93.20
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3704.80	-48.50	-13.00	-35.50	1.68 V	29	44.70	-93.20

Remarks:

1. EIRP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + 20log(D) – 104.8
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	TX WCDMA Band II	Channel	CH 9400 : 1880 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-49.38	-13.00	-36.38	1.82 H	349	43.55	-92.93
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-48.18	-13.00	-35.18	1.67 V	33	44.75	-92.93

Remarks:

1. EIRP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + 20log(D) – 104.8
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	TX WCDMA Band II	Channel	CH 9538 : 1907.6 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	3815.20	-49.49	-13.00	-36.49	1.81 H	345	43.15	-92.64

Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	3815.20	-48.22	-13.00	-35.22	1.70 V	32	45.92	-94.14

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

RF Mode	TX LTE Band II-1.4MHz	Channel	CH 18607 : 1850.7 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3701.40	-50.00	-13.00	-37.00	2.06 H	38	43.25	-93.25

Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3701.40	-49.50	-13.00	-36.50	1.90 V	22	43.75	-93.25

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	TX LTE Band II-1.4MHz	Channel	CH 18900 : 1880 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-49.70	-13.00	-36.70	2.01 H	36	43.18	-92.88

Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-49.10	-13.00	-36.10	1.90 V	24	43.78	-92.88

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	TX LTE Band II-1.4MHz	Channel	CH 19193 : 1909.3 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	3818.60	-50.00	-13.00	-37.00	1.98 H	34	42.56	-92.56
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	3818.60	-49.20	-13.00	-36.20	1.85 V	22	43.36	-92.56

Remarks:

1. EIRP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + 20log(D) – 104.8
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	TX LTE Band II-5MHz	Channel	CH 18625 : 1852.5 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3705.00	-50.70	-13.00	-37.70	1.96 H	39	42.52	-93.22

Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3705.00	-49.80	-13.00	-36.80	1.86 V	26	43.42	-93.22

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

RF Mode	TX LTE Band II-5MHz	Channel	CH 18900 : 1880 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-50.36	-13.00	-37.36	2.05 H	35	42.52	-92.88

Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-49.46	-13.00	-36.46	1.89 V	27	43.42	-92.88

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

RF Mode	TX LTE Band II-5MHz	Channel	CH 19175 : 1907.5 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	3815.00	-50.20	-13.00	-37.20	2.05 H	33	42.37	-92.57

Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	3815.00	-49.40	-13.00	-36.40	1.94 V	27	43.17	-92.57

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

RF Mode	TX LTE Band II-20MHz	Channel	CH 18700 : 1860 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3720.00	-50.60	-13.00	-37.60	2.03 H	33	42.53	-93.13
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3720.00	-49.70	-13.00	-36.70	1.89 V	27	43.43	-93.13

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	TX LTE Band II-20MHz	Channel	CH 18900 : 1880 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-49.60	-13.00	-36.60	2.06 H	40	43.28	-92.88
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-49.10	-13.00	-36.10	1.94 V	24	43.78	-92.88

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	TX LTE Band II-20MHz	Channel	CH 19100 : 1900 MHz
Frequency Range	1GMHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	3800.00	-49.90	-13.00	-36.90	1.97 H	39	42.73	-92.63
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	3800.00	-49.50	-13.00	-36.50	1.92 V	27	43.13	-92.63

Remarks:

1. EIRP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + 20log(D) – 104.8
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---