



FCC ID: GKR436415  
Report No.: T210730W08-MF

Page 1 / 9  
Rev.: 00

**KDB 447498 D03**  
**47 C.F.R. Part 1, Subpart I, Section 1.1310**  
**47 C.F.R. Part 2, Subpart J, Section 2.1091**

## **RF EXPOSURE REPORT**

**For**

**Tablet**

**Model: MP27-ARGON2-C**

**Trade Name: ICON/iFit**

Issued to

**Compal Electronics Inc**  
**No.581 & 581-1, Ruiguang Rd., Neihu District, Taipei city, 11492 Taiwan**

Issued by

**Compliance Certification Services Inc.**  
**Wugu Laboratory**  
**No.11, Wugong 6th Rd., Wugu Dist.,**  
**New Taipei City, Taiwan. (R.O.C.)**  
**Issue Date: January 7, 2022**

**Note:** This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



**Report No.:** T210730W08-MF

Page 2 / 9

Rev.: 00

### Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	January 7, 2022	Initial Issue	ALL	Doris Chu



**Report No.:** T210730W08-MF

Page 3 / 9  
Rev.: 00

### TABLE OF CONTENTS

- 1. TEST RESULT CERTIFICATION .....4
- 2. LIMIT .....5
- 3. EUT SPECIFICATION .....6
- 4. TEST RESULTS .....8
- 5. MAXIMUM PERMISSIBLE EXPOSURE.....9

## 1. TEST RESULT CERTIFICATION

### We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091	No non-compliance noted
Statements of Conformity	
Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	

Approved by:




---

Kevin Tsai  
Deputy Manager  
Compliance Certification Services Inc.

Report No.: T210730W08-MF

## 2. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of the chapter.

**TABLE 1 - LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
<b>1,500-100,000</b>			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

Note 1 to Table 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

Note 2 to Table 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Report No.: T210730W08-MF

### 3. EUT SPECIFICATION

<b>EUT</b>	Tablet																																			
<b>Model</b>	MP27-ARGON2-C																																			
<b>Trade Name</b>	ICON/iFit																																			
<b>Model Discrepancy</b>	N/A																																			
<b>Received Date</b>	July 30, 2021																																			
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> Bluetooth: 2402MHz-2480MHz <input checked="" type="checkbox"/> 802.11b/g/n HT20: 2412MHz ~ 2462 MHz <input checked="" type="checkbox"/> 802.11a/n HT20: 5180MHz ~ 5240MHz / 5260 ~ 5320MHz / 5500 ~ 5700MHz / 5745MHz ~ 5825MHz <input type="checkbox"/> Others																																			
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others																																			
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )																																			
<b>Antenna Specification</b>	<p>PCB Antenna</p> <p>BT: Gain: 4.32 dBi</p> <p>WIFI 2.4GHz: Gain: 4.32 dBi</p> <p>WIFI 5GHz:</p> <p>5150~5250: Gain: 0.17 dBi</p> <p>5250~5350: Gain: 0.17 dBi</p> <p>5470~5725: Gain: 0.91 dBi</p> <p>5725~5850: Gain: 1.21 dBi</p> <table> <tr> <td>BT:</td> <td>Gain :</td> <td>4.32 dBi</td> <td>(Numeric gain: 2.70)</td> <td>Worst</td> </tr> <tr> <td>2.4GHz:</td> <td>Gain :</td> <td>4.32 dBi</td> <td>(Numeric gain: 2.70)</td> <td>Worst</td> </tr> <tr> <td>5GHz:</td> <td>Gain :</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>5150~5250: Gain:</td> <td>0.17 dBi</td> <td>(Numeric gain: 1.04)</td> <td>Worst</td> </tr> <tr> <td></td> <td>5250~5350: Gain:</td> <td>0.17 dBi</td> <td>(Numeric gain: 1.04)</td> <td>Worst</td> </tr> <tr> <td></td> <td>5470~5725: Gain:</td> <td>0.91 dBi</td> <td>(Numeric gain: 1.23)</td> <td>Worst</td> </tr> <tr> <td></td> <td>5725~5850: Gain:</td> <td>1.21 dBi</td> <td>(Numeric gain: 1.32)</td> <td>Worst</td> </tr> </table>	BT:	Gain :	4.32 dBi	(Numeric gain: 2.70)	Worst	2.4GHz:	Gain :	4.32 dBi	(Numeric gain: 2.70)	Worst	5GHz:	Gain :					5150~5250: Gain:	0.17 dBi	(Numeric gain: 1.04)	Worst		5250~5350: Gain:	0.17 dBi	(Numeric gain: 1.04)	Worst		5470~5725: Gain:	0.91 dBi	(Numeric gain: 1.23)	Worst		5725~5850: Gain:	1.21 dBi	(Numeric gain: 1.32)	Worst
BT:	Gain :	4.32 dBi	(Numeric gain: 2.70)	Worst																																
2.4GHz:	Gain :	4.32 dBi	(Numeric gain: 2.70)	Worst																																
5GHz:	Gain :																																			
	5150~5250: Gain:	0.17 dBi	(Numeric gain: 1.04)	Worst																																
	5250~5350: Gain:	0.17 dBi	(Numeric gain: 1.04)	Worst																																
	5470~5725: Gain:	0.91 dBi	(Numeric gain: 1.23)	Worst																																
	5725~5850: Gain:	1.21 dBi	(Numeric gain: 1.32)	Worst																																

Report No.: T210730W08-MF

<b>Maximum Measurement Average Power</b>	BT	3.38 dBm	(2.178 mW)
	2.4GHz		
	IEEE 802.11b Mode:	17.46 dBm	(55.719 mW)
	IEEE 802.11g Mode:	17.37 dBm	(54.576 mW)
	IEEE 802.11n HT 20 Mode:	17.09 dBm	(51.168 mW)
	5GHz		
	IEEE 802.11a Mode:	19.59 dBm	(90.991 mW)
	IEEE 802.11n HT 20 Mode:	19.85 dBm	(96.605 mW)
<b>Maximum tune up power</b>	BT	4.00 dBm	(2.512 mW)
	2.4GHz		
	IEEE 802.11b Mode:	18.00 dBm	(63.096 mW)
	IEEE 802.11g Mode:	18.00 dBm	(63.096 mW)
	IEEE 802.11n HT 20 Mode:	17.50 dBm	(56.234 mW)
	5GHz		
	IEEE 802.11a Mode:	20.00 dBm	(100.000 mW)
	IEEE 802.11n HT 20 Mode:	20.00 dBm	(100.000 mW)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A		

**Remark:**

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
3. The tune up power referred the AVG power of the test report T210730W08-RP1, T210730W08-RP2, T210730W08-RP3 and T210730W08-RP4 for RF Exposure assessment purpose.
4. For WIFI and BT could not be use as transmit/receive at the same time.

## 4. TEST RESULTS

**No non-compliance noted.**

### Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{377}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and

d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm<sup>2</sup>



Report No.: T210730W08-MF

## 5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where  $P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW / cm<sup>2</sup>

**BT:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
0	2402	2.512	2.70	20	0.0013	1

**IEEE 802.11b mode:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
1	2412	63.096	2.70	20	0.0339	1

**IEEE 802.11g mode:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
1	2412	63.096	2.70	20	0.0339	1

**IEEE 802.11n HT20 mode:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
6	2437	56.234	2.70	20	0.0302	1

**IEEE 802.11a mode:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
52	5260	100.000	1.04	20	0.0207	1

**IEEE 802.11n HT20 mode:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
64	5320	100.000	1.04	20	0.0207	1

--End of Report--