


# RF EXPOSURE EVALUATION REPORT

FCC ID : GKRAAN1FNC8  
Equipment : 5G Small Cell  
Brand Name : Compal  
Model Name : Cedar AAN1F-NC8  
Applicant : Compal Electronics, Inc.  
No.581 & 581-1, Ruiguang Rd.,  
Neihu District, Taipei, (114) Taiwan  
Manufacturer : Compal Electronics, Inc.  
No.581 & 581-1, Ruiguang Rd.,  
Neihu District, Taipei, (114) Taiwan  
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full



Approved by: Cona Huang / Deputy Manager



**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## **Table of Contents**

<b>1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....</b>	<b>4</b>
<b>2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS .....</b>	<b>4</b>
<b>3. RF EXPOSURE LIMIT INTRODUCTION .....</b>	<b>5</b>
<b>4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION .....</b>	<b>6</b>
4.1. Standalone Power Density Calculation .....	6



## History of this test report

Report No.	Version	Description	Issued Date
FA390524	Rev. 01	Initial issue of report	Dec. 21, 2023



**1. Description of Equipment Under Test (EUT)**

Product Feature & Specification	
EUT Type	5G Small Cell
Brand Name	Compal
Model Name	Cedar AAN1F-NC8
FCC ID	GKRAAN1FNC8
Wireless Technology and Frequency Range	5G NR n48 : 3550 MHz ~ 3700 MHz
Mode	5G NR: DFT-s-OFDM/CP-OFDM, Pi/2 BPSK/QPSK/16QAM/64QAM/256QAM
EUT Stage	Production Unit

**Reviewed by: Jason Wang**

**Report Producer: Carlie Tsai**

**2. Maximum RF average output power among production units**

Mode		Tune up (dBm)
FR1	n48	28

**Note:**

1. This device is equipped with 4 WWAN antennas, and the maximum combined output power of these four antennas is 28 dBm.



3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Table with 5 columns: Frequency range (MHz), Electric field strength (V/m), Magnetic field strength (A/m), Power density (mW/cm²), Averaging time (minutes). It is divided into two sections: (A) Limits for Occupational/Controlled Exposures and (B) Limits for General Population/Uncontrolled Exposure.

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

S = PG / (4πR²)

Where:

- S = Power Density
P = Output Power at Antenna Terminals
G = Gain of Transmit Antenna (linear gain)
R = Distance from Transmitting Antenna



**4. Radio Frequency Radiation Exposure Evaluation**

**4.1. Standalone Power Density Calculation**

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5G NR n48	7.5	28	35.5	3.55	3548.13	0.706	1

**Conclusion:**

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.