

Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 1 of 62

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 15 SUBPART C REQUIREMENT

OF

Product Name: NAZ10

Brand Name: N/A

Model Name: NAZ10, eLocity A7,AZ10

Model difference: For market segmentation

FCC ID: GKRNAZ10WB

Report No.: EH/2010/90009

Issue Date: Sep. 28, 2010

FCC Rule Part: §15.247, Cat: DSS

Prepared for: Compal Electronics, Inc.

No.581, Ruiguang Rd., Neihu District, Taipei

City 11492, Taiwan (R.O.C.)

Prepared by: SGS Taiwan Ltd.

Electronics & Communication Laboratory

No. 134, Wu Kung Rd., Wuku Industrial Zone,

Taipei County, Taiwan.





Testing Leboretory 0513 **Note:** This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. personnel only, and shall be noted in the revision section of the document.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 2 of 62

VERIFICATION OF COMPLIANCE

Applicant: Compal Electronics, Inc.

No.581, Ruiguang Rd., Neihu District, Taipei City 11492, Taiwan

(R.O.C.)

NAZ10 **Product Name:**

Brand Name: N/A

Model Name: NAZ10, eLocity A7, AZ10 **Model difference:** For market segmentation

FCC ID: **GKRNAZ10WB** EH/2010/90009 File Number:

Sep. 14, 2010 ~ Sep. 24, 2010 Date of test:

Sep. 14, 2010 **Date of EUT Received:**

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Test By:	Lazz Huang	Date:	Sep. 28, 2010	
Prepared By:	Jazz Huang / Engineer Gigi yek	Date:	Sep. 28, 2010	
Approved By:	Gigi Yeh/Clerk ALW HSieh Arno Hsieh/Asst Supervisor	Date:	Sep. 28, 2010	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 3 of 62

Version

Version No.	Date	Description
00	Sep. 28, 2010	Initial creation of document

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

***ACCESTANCE AND ACCESTANCE AND ACCESTANC



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 4 of 62

Table of Contents

1.	GEN	ERAL INFORMATION	6
	1.1.	Product Description	6
	1.2.	Related Submittal(s) / Grant (s)	8
	1.3.	Test Methodology	8
	1.4.	Test Facility	
	1.5.	Special Accessories	8
	1.6.	Equipment Modifications	
2.	SYST	ΓEM TEST CONFIGURATION	9
	2.1.	EUT Configuration	9
	2.2.	EUT Exercise	9
	2.3.	Test Procedure	9
	2.4.	Configuration of Tested System	10
3.	SUM	MARY OF TEST RESULTS	1
4.	DES	CRIPTION OF TEST MODES	1
5.	CON	DUCTED EMISSION TEST	12
	5.1.	Standard Applicable	12
	5.2.	EUT Setup.	12
	5.3.	Measurement Procedure	12
	5.4.	Measurement Equipment Used:	13
	5.5.	Measurement Result	13
6.	PEA:	K OUTPUT POWER MEASUREMENT	10
	6.1.	Standard Applicable	16
	6.2.	Measurement Equipment Used	16
	6.3.	Test Set-up:	16
	6.4.	Measurement Procedure:	17
	6.5.	Measurement Result.	17
7.	20dB	BAND WIDTH	22
	7.1.	Standard Applicable	22
	7.2.	Measurement Equipment Used	22
	7.3.	Test Set-up	22
	7.4.	Measurement Procedure:	22
	7.5.	Measurement Result:	23
8.	100K	Hz BANDWIDTH OF BAND EDGES MEASUREMENT	28
	8 1	Standard Applicable	2.8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

***ACCESTANCE AND ACCESTANCE AND ACCESTANC



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 5 of 62

	8.2.	Measurement Equipment Used	28
	8.3.	Test SET-UP:	29
	8.4.	Measurement Procedure	30
	8.5.	Field Strength Calculation	30
	8.6.	Measurement Result	30
9.	SPUR	RIOUS RADIATED EMISSION TEST	35
	9.1.	Standard Applicable	35
	9.2.	Measurement Equipment Used:	35
	9.3.	Test SET-UP:	35
	9.4.	Measurement Procedure:	35
	9.5.	Field Strength Calculation	36
	9.6.	Measurement Result:	36
10.	FRE(QUENCY SEPARATION	49
	10.1.	Standard Applicable	49
	10.2.	Measurement Equipment Used:	49
	10.3.	Test Set-up:	49
	10.4.	Measurement Procedure:	49
	10.5.	Measurement Result:	49
11.	NUM	BER OF HOPPING FREQUENCY	51
	11.1.	Standard Applicable	51
	11.2.	Measurement Equipment Used:	51
	11.3.	Test Set-up:	51
	11.4.	Measurement Procedure:	51
	11.5.	Measurement Result:	51
12.	TIME	E OF OCCUPANCY (DWELL TIME)	54
	12.1.	Standard Applicable	54
	12.2.	Measurement Equipment Used:	54
	12.3.	Test Set-up:	54
	12.4.	Measurement Procedure:	54
	12.5.	Measurement Result	55
13.	ANTI	ENNA REQUIREMENT	62
	13.1.	Standard Applicable	
	13.2.	Antenna Connected Construction	62



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 6 of 62

1. GENERAL INFORMATION

1.1. Product Description

General:

General.				
Product Name:	NAZ10			
Brand Name:	N/A	N/A		
Model Name:	NAZ10, eLocity	A7,AZ10		
Model Difference:	For market segm	nentation		
Hardware Version:	LA6621PR01			
Software Version:	NAZ1000.2.0078			
	7.4 Vdc re-charg	eable battery or 19Vdc by AC/DC power adapter		
	Battery:	Model No.:BATAZ10L2, Supplier: ATL		
Power Supply	Adapter 1:	Model: AD6113-1LF, Supplier: PI Technology Limited		
	Adapter 2:	Model: WA-30A19U, Supplier: ASIAN POWER DEVICES INC.		

GSM / WCDMA:

	Operating Frequency		
Cellular Phone Standards	GSM/GPRS 850 Class 10	824.2MHz-848.8MHz	33 dBm
Frequency Range and Power:	GSM/GPRS 1900 Class 10 1850.2MHz –1909.8MHz		30 dBm
10Wei.	EDGE 850 Class 10	824.2 MHz- 848.8 MHz	27 dBm
	EDGE 1900 Class 10	1850.2MHz –1909.8MHz	26 dBm
IMEI code	358826030020818		



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 7 of 62

Bluetooth:

Bluetooth Version:	$V2.1 + EDR (GFSK + \pi/4DQPSK + 8DPSK)$
Channel number:	79 channels
Modulation type:	Frequency Hopping Spread Spectrum
Rated Power:	1.32 dBm
Frequency Range:	2.402GHz – 2.480GHz
Dwell Time:	<= 0.4s
Operating Mode:	Point-to-Point
Antenna Designation:	Printed antenna, -3.34dBi

WLAN: 802.11 b/g:

Frequency Range:	2412 – 2462 MHz
Channel number:	11 channels
Transmit Power:	802.11 b: 16.00dBm (Peak) 802.11 g: 16.64dBm (Peak)
Modulation Technology:	DSSS, OFDM
Modulation type:	CCK, DQPSK, DBPSK for DSSS 64QAM. 16QAM, QPSK, BPSK for OFDM
Transition Rate:	802.11 b: 1/2/5.5/11 Mbps; 802.11 g: 6/9/12/18/24/36/48/54 Mbps
Antenna Designation:	Printed antenna, -3.34dBi

The EUT is compliance with Bluetooth 2.1 with EDR This report applies for Bluetooth.



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 8 of 62

1.2. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: GKRNAZ10WB filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.3. Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4: 2003. Radiated testing was performed at an antenna to EUT distance 3 meters.

Tested in accordance with FCC Public Notice DA 00-705

1.4. Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of SGS Taiwan Ltd. Electronics & Communication Laboratory No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003. FCC Registration Number are: 990257 and 236194, Canada Registration Number: 4620A-4

The 10 m Open Area Test Sites located on the address of SGS Taiwan Ltd. Electronics & Communication Laboratory No. 29, Pau-Tou-Tsuo Valley Chia-Pau Tsuen, Linkou Hsiang, Taipei county, which is constructed and calibrated to meet the CISPR 22/EN 55022 requirements. SGS Site No. 1(3 &10 meters) and FCC Registration Number: 94644.

1.5. Special Accessories

Not available for this EUT intended for grant.

1.6. Equipment Modifications

Not available for this EUT intended for grant.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 9 of 62

2. SYSTEM TEST CONFIGURATION

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

2.3. Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 7 and 13 of ANSI C63.4: 2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna, according to the requirements in Section 8 and 13 and Subclause 8.3.1.2 of ANSI C63.4: 2003 and DA 00-705.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 10 of 62

2.4. Configuration of Tested System

Fig. 2-1 AC Power line and Radiated Emission Configuration



Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model	Series No.	Data Cable	Power Cord
1	Bluetooth Test Set	Anritsu	MT8852B	N/A	N/A	Un-shielding

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Onless otherwise stated the results shown in this test report retier only to the sample(s) tested and such sample(s) test only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 11 of 62

3. SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.207(a)	Conducted Emission	Compliant
§15.247(b)(1)	Peak Output Power	Compliant
§15.247(a)	20dB Bandwidth	No Limit
§15.247(d)	100 KHz Bandwidth Of Fre-	Compliant
	quency Band Edges	
§15.247(d)	Spurious Emission	Compliant
§15.247(a)(1)	Frequency Separation	Compliant
§15.247(a)(1)(iii)	Number of hopping frequency	Compliant
§15.247(a)(1)(iii)	Time of Occupancy	Compliant
§15.247(e)	Peak Power Density	Compliant
§15.203,	Antenna Requirement	Compliant
§15.247(b)(4)(i)	_	

4. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting mode is programmed.

Channel low (2402MHz) · mid (2441MHz) and high (2480MHz) with highest data rate are chosen for full testing with EDR and to contrast with X, Y, Z axis, X axis which has Worst Case.

*Remark: Please be noted that the modular transmitter of this application does not $support\ simultaneous\ transmission\ (BT+WLAN)$

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 12 of 62

5. CONDUCTED EMISSION TEST

5.1. Standard Applicable

According to §15.207. frequency within 150KHz to 30MHz shall not exceed the limit table as below.

Engavanavana		mits
Frequency range	dB(uv)
MHz	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Note

- 1. The lower limit shall apply at the transition frequencies
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.2. EUT Setup

- 1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4: 2003.
- 2. The EUT was plug-in the AC/DC Power adapter. The host system was placed on the center of the back edge on the test table. The peripherals was placed on the side of the host PC system. The rear of the EUT and peripherals were placed flushed with the rear of the tabletop.
- 3. The spacing between the peripherals was 10 centimeters.
- 4. External I/O cables were draped along the edge of the test table and bundle when necessary.
- 5. The host system was connected with 120Vac/60Hz power source.

5.3. Measurement Procedure

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the control only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 13 of 62

5.4. Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.
TYPE		NUMBER	NUMBER	CAL.	
EMI Test Receiver	R&S	ESCS30	828985/004	09/16/2010	09/15/2011
LISN	Rolf-Heine	NNB-2/16Z	99012	02/02/2010	02/01/2011
LISN	FCC	FCC-LISN-50/250-25-2-01	04034	02/02/2010	02/01/2011
Coaxial Cables	N/A	WK CE Cable	N/A	10/30/2009	10/29/2010

5.5. Measurement Result

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Note: Refer to next page for measurement data and plots.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless otherwise stated the results snown in this test report refer only to the sample(s) lested and such sample(s) leste only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279




Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 14 of 62

AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode:	Bluetooth Mode	Test Date:	Sep. 23, 2010
		Test By:	Jazz



Site SGS CONDUCTED #1

Limit: FCC Class B Conduction(QP)

EUT: Notebook Computer

M/N: NAZ10

Note: WIFI +BT LINK MODE

Phase:	L1	remperature:	24 (
Power:	AC 120V/60Hz	Humidity:	55 %
Distance);	Air Pressure:	hpa

No.	Mk.	Freq.	Reading Level	Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1500	53.82	0.14	53.96	66.00	-12.04	peak	
2		0.1700	50.82	0.13	50.95	64.96	-14.01	peak	
3		0.4750	39.41	0.12	39.53	56.43	-16.90	peak	
4		1.0600	28.87	0.12	28.99	56.00	-27.01	peak	
5		6.1800	39.63	0.28	39.91	60.00	-20.09	peak	
6		9.8200	35.93	0.52	36.45	60.00	-23.55	peak	


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

55 %

Page: 15 of 62



Site SGS CONDUCTED#1

Limit: FCC Class B Conduction(QP)

EUT: Notebook Computer

M/N: NAZ10

Note: WIFI +BT LINK MODE

Phase:	N	remperature:
Power:	AC 120V/60Hz	Humidity:

Distance: Air Pressure: hpa

No.	Mk.	Freq.	Reading Level	Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1650	52.93	0.14	53.07	65.21	-12.14	peak	
2		0.2150	46.43	0.13	46.56	63.01	-16.45	peak	
3		0.2400	41.32	0.13	41.45	62.10	-20.65	peak	
4		1.0600	30.37	0.13	30.50	56.00	-25.50	peak	
5		5.9600	39.60	0.26	39.86	60.00	-20.14	peak	
6		9.5200	37.85	0.47	38.32	60.00	-21.68	peak	



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 16 of 62

PEAK OUTPUT POWER MEASUREMENT 6.


6.1. Standard Applicable

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850MHz band: 1Watt. For all other frequency hopping systems in the 2400 – 2483.5MHz band: 0.125 Watts.

Measurement Equipment Used

Conducted Emission Test Site							
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.		
TYPE		NUMBER	NUMBER	CAL.			
Power Sensor	Anritsu	MA2411B	917032	01/21/2010	01/20/2012		
Power Meter	Anritsu	ML2495A	1005007	02/17/2010	02/16/2012		
Spectrum Analyzer	Agilent	E4446A	MY43360126	04/19/2010	04/18/2012		
Spectrum Analyzer	Agilent	E4440A	MY45304525	01/25/2010	01/24/2011		
DC Block	Agilent	BLK-18	155452	07/05/2010	07/04/2011		
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA	N/A	01/05/2010	01/04/2011		
Attenuator	Mini-Circuit	BW-S6W5	001	07/05/2010	07/04/2011		
Attenuator	Mini-Circuit	BW-S10W5	001	07/05/2010	07/04/2011		
Attenuator	Mini-Circuit	BW-S20W5	001	07/05/2010	07/04/2011		
Splitter	Agilent	11636B	N/A	07/05/2010	07/04/2011		

6.3. Test Set-up:



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 17 of 62

6.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter or spectrum. (Max peak function, >20dB bandwidth, >=RBW)
- 3. Record the max. reading.
- 4. Repeat above procedures until all frequency measured were complete.

6.5. Measurement Result

BDR mode:

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
2402.00	-0.83	0.00	-0.83	0.00083	1
2441.00	0.65	0.00	0.65	0.00116	1
2480.00	0.14	0.00	0.14	0.00103	1

*Note: offset 6dB

EDR mode:

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
2402.00	-0.25	0.00	-0.25	0.00094	1
2441.00	1.32	0.00	1.32	0.00136	1
2480.00	0.52	0.00	0.52	0.00113	1

*Note: offset 6dB

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law




Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 18 of 62

Peak Power Output Data Plot (CH Low) (BDR mode)



Peak Power Output Data Plot (CH Mid) (BDR mode)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

She stated the States the State of the State of the State of States and States and States are stated and States are states and States and States are stat only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號


t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 19 of 62

Peak Power Output Data Plot (CH High) (BDR mode)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

She stated the States the State of the State of the State of States and States and States are stated and States are states and States and States are stat only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 t (886-2) 2299-3279




Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 20 of 62

Peak Power Output Data Plot (CH Low) (EDR mode)



Peak Power Output Data Plot (CH Mid) (EDR mode)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

She stated the States the State of the State of the State of States and States and States are stated and States are states and States and States are stat only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號


t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 21 of 62

Peak Power Output Data Plot (CH High) (EDR mode)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

She stated the States the State of the State of the State of States and States and States are stated and States are states and States and States are stat only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 22 of 62

7. 20dB BAND WIDTH

7.1. Standard Applicable

For frequency hopping systems operating in the 2400MHz-2483.5 MHz no limit for 20dB bandwidth.

7.2. Measurement Equipment Used

Refer to section 6.2 for details.

7.3. Test Set-up

Refer to section 6.3 for details.

7.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW=1 % of Bandwidth., Span= 3MHz, Sweep=auto
- 4. Mark the peak frequency and –20dB (upper and lower) frequency.
- 5. Repeat above procedures until all frequency measured were complete.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 23 of 62

7.5. Measurement Result:

20dB Bandwidth: BDR mode

uc				
СН	Bandwidth			
	(kHz)			
Lower	930.018			
Mid	924.768			
Higher	926.604			

20dB Bandwidth: EDR mode


СН	Bandwidth	2/3 Bandwidth
	(MHz)	(MHz)
Lower	1.317	0.878
Mid	1.265	0.843
Higher	1.27	0.847



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 24 of 62

20dB Band Width Test Data CH-Low (BDR mode)



20dB Band Width Test Data CH-Mid (BDR mode)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號


t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 25 of 62

20dB Band Width Test Data CH-High (BDR mode)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

She stated the States the State of the State of the State of States and States and States are stated and States are states and States and States are stat only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279


Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 26 of 62

20dB Band Width Test Data CH-Low (EDR mode)



20dB Band Width Test Data CH-Mid (EDR mode)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號


t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 27 of 62

20dB Band Width Test Data CH-High (EDR mode)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

She stated the States the State of the State of the State of States and States and States are stated and States are states and States and States are stat only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279

Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 28 of 62

100KHz BANDWIDTH OF BAND EDGES MEASUREMENT

8.1. Standard Applicable

According to §15.247(d), in any 100 KHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

8.2. Measurement Equipment Used

8.2.1. Conducted Emission at antenna port:

Refer to section 6.2 for details.

8.2.2. Radiated emission:

966 Chamber							
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.		
TYPE		NUMBER	NUMBER	CAL.			
Spectrum Analyzer	R&S	FSP 40	100034	02/12/2010	02/11/2011		
Bilog Antenna	SCHWAZBECK	VULB9160	3136	11/19/2009	11/18/2010		
Horn antenna	SCHWAZBECK	BBHA 9120D	9120D-673	03/09/2009	03/08/2011		
Pre-Amplifier	Agilent	8447D	1937A02834	11/28/2009	11/28/2010		
Pre-Amplifier	Agilent	8449B	3008A01973	01/05/2010	01/04/2011		
Radio Communication Analyzer	R & S	CMU200	102189	10/31/2008	10/30/2010		
DC Block	Agilent	BLK-18	155452	07/05/2010	07/04/2011		
Turn Table	HD	DT420	N/A	N.C.R	N.C.R		
Antenna Tower	HD	MA240-N	240/657	N.C.R	N.C.R		
Controller	HD	HD100	N/A	N.C.R	N.C.R		
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	01/05/2010	01/04/2011		
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	01/05/2010	01/04/2011		
3m Site	SGS	966 chamber	N/A	11/08/2009	11/09/2010		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 29 of 62


8.3. Test SET-UP:

8.3.1. Conducted Emission at antenna port:


Refer to section 6.3 for details.

8.3.2. Radiated emission:

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 30 of 62

8.4. Measurement Procedure

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = operating frequency.
- 4. Set the spectrum analyzer as RBW, VBW=100KHz, Span=25MHz, Sweep = auto
- 5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
- 6. Repeat above procedures until all frequency measured were complete.
- 7. Radiated Emission refer to section 9.

8.5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

8.6. Measurement Result

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279


f (886-2) 2298-0488 www.tw.sgs.com




Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 31 of 62

Conducted Emission: Test Data CH-Low (Worst: EDR mode)





Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號


t (886-2) 2299-3279




Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 32 of 62

Conducted Emission: Test Data CH-High





Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 33 of 62

Radiated Emission: (EDR mode)

Operation Mode TX CH Low Sep. 22, 2010 Test Date

Fundamental Frequency 2402 MHz Test By Jazz Temperature 25 °C Pol Ver.

Humidity 65 %

Freq. (MHz)	Peak Reading (dBuV)	AV Reading (dBuV)		Peak	al FS AV) (dBuV/m)	Peak Limit (dBuV/m)	AV Limit (dBuV/n	O	Remark
2390.00	43.89		-1.39	42.50		74.00	54.00	-11.50	Peak
Operation Mode TX CH Low Fundamental Frequency 2402 MHz Temperature 25 °C Humidity 65 %				Test Test Pol	Date By	Sep. 22, 20 Jazz Hor.)10		
	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq. (MHz)	Reading (dBuV)	Reading (dBuV)		Peak (dBuV/m)	AV) (dBuV/m)	Limit (dBuV/m)	Limit (dBuV/n	U	Remark
2390.00	43.04		-1.39	41.65		74.00	54.00	-12.35	Peak

Remark:

- (1) Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (2) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS columno
- (3) Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- (4) Spectrum AV Setting: 1GHz-26GHz, RBW=1MHz, VBW=10Hz, Sweep time=200 ms.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 34 of 62

Radiated Emission: (EDR mode)

Operation Mode TX CH High Sep. 22, 2010 Test Date

Fundamental Frequency 2480 MHz Test By Jazz **Temperature** 25 °C Pol Ver.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	ıal FS	Peak	\mathbf{AV}		
Freq. (MHz)	Reading (dBuV)	Reading (dBuV)			AV) (dBuV/m)	Limit (dBuV/m)(Limit (dBuV/n	O	Remark
2483.56	42.71		-0.92	41.79		74.00	54.00	-12.21	Peak
Operation Fundament Temperatu Humidity	tal Frequei					Test Test Pol	By	Sep. 22, 20 Jazz Hor.	010

		Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
	Freq.	Reading	Reading	Ant/CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
	(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
_	2483.56	46.95		-0.92	46.03		74.00	54.00	-7.97	Peak

Remark:

- (1) Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (2) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS columno
- (3) Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- (4) Spectrum AV Setting: 1GHz-26GHz, RBW=1MHz, VBW=10Hz, Sweep time=200 ms.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 35 of 62

9. SPURIOUS RADIATED EMISSION TEST

9.1. Standard Applicable

According to §15.247(c), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

9.2. Measurement Equipment Used:

9.2.1. Conducted Emission at antenna port:

Refer to section 6.2 for details.

9.2.2. Radiated emission:

Refer to section 8.2 for details.

9.3. Test **SET-UP**:

9.3.1. Conducted Emission at antenna port:

Refer to section 6.3 for details.

9.3.2. Radiated emission:

Refer to section 8.3 for details.

9.4. Measurement Procedure:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 7. Repeat above procedures until all frequency measured were complete.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 36 of 62

9.5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)				
	RA = Reading Amplitude	AG = Amplifier Gain				
	AF = Antenna Factor					

9.6. Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號


台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488 www.tw.sgs.com

Member of SGS Group


Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 37 of 62

Conducted Spurious Emission Measurement Result (Worst: EDR mode) Ch Low 30MHz - 3GHz



Ch Low 3GHz – 26.5GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號


t (886-2) 2299-3279




Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 38 of 62

Ch Mid 30MHz - 3GHz



Ch Mid 3GHz - 26.5GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

She stated the States the State of the State of the State of States and States and States are stated and States are states and States and States are stat only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan/台北縣五股工業區五工路 134 號 SGS Taiwan Ltd.


t (886-2) 2299-3279




Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 39 of 62

Ch High 30MHz – 3GHz



Ch High 3GHz – 26.5GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

She stated the States the State of the State of the State of States and States and States are stated and States are states and States and States are stat only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan/台北縣五股工業區五工路 134 號 SGS Taiwan Ltd.

t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 40 of 62

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode TX CH Low Sep. 23, 2010 Test Date

Fundamental Frequency 2402MHz Test By Jazz Temperature 25 °C Pol Ver./Hor.

Humidity 65 %

Freq.	Ant.Pol.	Detector Mode	Reading	Factor	Actual FS	Limit3m	Safe Margin
(MHz)	H/V	(PK/QP)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
61.04	V	Peak	47.71	-14.75	32.96	40.00	-7.04
201.69	V	Peak	49.41	-15.55	33.86	43.50	-9.64
230.79	V	Peak	48.24	-14.45	33.79	46.00	-12.21
293.84	V	Peak	44.62	-13.19	31.43	46.00	-14.57
385.99	V	Peak	42.18	-10.47	31.71	46.00	-14.29
446.13	V	Peak	40.10	-8.67	31.43	46.00	-14.57
37.76	Н	Peak	43.67	-14.24	29.43	40.00	-10.57
92.08	Н	Peak	49.34	-17.38	30.74	43.50	-12.76
261.83	Н	Peak	41.15	-13.63	27.52	46.00	-18.48
385.99	Н	Peak	39.45	-10.47	28.98	46.00	-17.02
417.03	Н	Peak	41.95	-9.46	31.28	46.00	-14.72
509.18	Н	Peak	38.11	-8.38	29.73	46.00	-16.27

Remark:

- 1 Measuring frequencies from 30 MHz to the 1GHz •
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 41 of 62

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode TX CH Mid Sep. 23, 2010 Test Date

Fundamental Frequency 2441MHz Test By Jazz Temperature 25 °C Pol Ver./Hor.

Humidity 65 %

Freq.	Ant.Pol.	Detector Mode	Reading	Factor	Actual FS	Limit3m	Safe Margin
(MHz)	H/V	(PK/QP)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
77.53	V	Peak	49.71	-17.46	32.25	40.00	-7.75
201.69	V	Peak	49.54	-15.55	33.99	43.50	-9.51
261.83	V	Peak	47.74	-13.63	34.11	46.00	-11.89
293.84	V	Peak	45.27	-13.19	32.08	46.00	-13.92
385.99	V	Peak	40.31	-10.47	29.84	46.00	-16.16
463.59	V	Peak	38.55	-8.55	30.00	46.00	-16.00
36.79	Н	Peak	45.06	-28.02	17.04	40.00	-22.96
92.08	Н	Peak	48.88	-29.03	19.85	43.50	-23.65
261.83	Н	Peak	44.25	-27.76	16.49	46.00	-29.51
385.99	Н	Peak	39.67	-24.89	14.78	46.00	-31.22
417.03	Н	Peak	39.09	-21.32	17.77	46.00	-28.23
478.14	Н	Peak	39.16	-18.39	20.77	46.00	-25.23

Remark:

- 1 Measuring frequencies from 30 MHz to the 1GHz •
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 42 of 62

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode TX CH High Sep. 23, 2010 Test Date

Fundamental Frequency 2480MHz Test By Jazz Temperature 25 °C Pol Ver./Hor.

Humidity 65 %

Freq.	Ant.Pol.	Detector Mode	Reading	Factor	Actual FS	Limit3m	Safe Margin
(MHz)	H/V	(PK/QP)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
58.13	V	Peak	47.60	-14.66	32.94	40.00	-7.06
92.08	V	Peak	50.44	-17.38	33.06	43.50	-10.44
201.69	V	Peak	49.86	-15.55	34.31	43.50	-9.19
230.79	V	Peak	50.05	-14.45	35.60	46.00	-10.40
261.83	V	Peak	45.14	-13.63	31.51	46.00	-14.49
417.03	V	Peak	40.04	-9.46	30.58	46.00	-15.42
77.53	Н	Peak	47.77	-28.02	19.75	40.00	-20.25
93.08	Н	Peak	49.38	-29.03	20.35	43.50	-23.15
201.69	Н	Peak	41.31	-27.76	13.55	43.50	-29.95
261.83	Н	Peak	43.05	-24.89	18.16	46.00	-27.84
400.54	Н	Peak	38.65	-21.32	17.33	46.00	-28.67
494.63	Н	Peak	37.33	-18.39	18.94	46.00	-27.06

Remark:

- 1 Measuring frequencies from 30 MHz to the 1GHz •
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 43 of 62

Radiated Spurious Emission Measurement Result (above 1GHz)

Sep. 23, 2010 Operation Mode TX CH Low Test Date

Fundamental Frequency 2402 MHz Test By Jazz Temperature 25 °C Pol Ver.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
4804.0	39.90		6.04	45.94		74.00	54.00	-8.06	Peak
7206.0						74.00	54.00		
9608.0						74.00	54.00		
12010.0						74.00	54.00		
14412.0						74.00	54.00		
16814.0						74.00	54.00		
19216.0						74.00	54.00		
21618.0						74.00	54.00		
24020.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- 5 Spectrum AV Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 44 of 62

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH Low Sep. 23, 2010 Test Date

Fundamental Frequency 2402 MHz Test By Jazz Temperature 25 °C Pol Hor.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
4804.0	39.92		6.04	45.96		74.00	54.00	-8.04	Peak
7206.0						74.00	54.00		
9608.0						74.00	54.00		
12010.0						74.00	54.00		
14412.0						74.00	54.00		
16814.0						74.00	54.00		
19216.0						74.00	54.00		
21618.0						74.00	54.00		
24020.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- 5 Spectrum AV Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 45 of 62

Radiated Spurious Emission Measurement Result (above 1GHz)

Sep. 23, 2010 Operation Mode TX CH Mid Test Date

Fundamental Frequency 2441 MHz Test By Jazz Temperature 25 °C Pol Ver.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
4882.0	39.65		6.17	45.82		74.00	54.00	-8.18	Peak
7323.0						74.00	54.00		
9764.0						74.00	54.00		
12205.0						74.00	54.00		
14646.0						74.00	54.00		
17087.0						74.00	54.00		
19528.0						74.00	54.00		
21969.0						74.00	54.00		
24410.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- 5 Spectrum AV Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 46 of 62

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH Mid Sep. 23, 2010 Test Date

Fundamental Frequency 2441 MHz Test By Jazz Temperature 25 °C Pol Hor.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
4882.0	39.78		6.17	45.95		74.00	54.00	-8.05	Peak
7323.0						74.00	54.00		
9764.0						74.00	54.00		
12205.0						74.00	54.00		
14646.0						74.00	54.00		
17087.0						74.00	54.00		
19528.0						74.00	54.00		
21969.0						74.00	54.00		
24410.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- 5 Spectrum AV Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 47 of 62

Radiated Spurious Emission Measurement Result (above 1GHz)

Sep. 23, 2010 Operation Mode TX CH High Test Date

Fundamental Frequency 2480 MHz Test By Jazz Temperature 25 °C Pol Ver.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
4960.0	39.86		6.36	46.22		74.00	54.00	-7.78	Peak
7440.0						74.00	54.00		
9920.0						74.00	54.00		
12400.0						74.00	54.00		
14880.0						74.00	54.00		
17360.0						74.00	54.00		
19840.0						74.00	54.00		
22320.0						74.00	54.00		
24800.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- 5 Spectrum AV Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 48 of 62

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH High Sep. 23, 2010 Test Date

Fundamental Frequency 2480 MHz Test By Jazz Temperature 25 °C Pol Hor.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
4960.0	39.55		6.36	45.91		74.00	54.00	-8.09	Peak
7440.0						74.00	54.00		
9920.0						74.00	54.00		
12400.0						74.00	54.00		
14880.0						74.00	54.00		
17360.0						74.00	54.00		
19840.0						74.00	54.00		
22320.0						74.00	54.00		
24800.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown " " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- 5 Spectrum AV Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 49 of 62

10. FREQUENCY SEPARATION

10.1. Standard Applicable

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 20dB bandwidth of the hopping channel, whichever is greater.

10.2. Measurement Equipment Used:

Refer to section 6.2 for details.

10.3. Test Set-up:

Refer to section 6.3 for details.

10.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = middle of hopping channel.
- 4. Set the spectrum analyzer as RBW, VBW=100KHz/100KHz, Adjust Span to 3.0 MHz, Sweep = auto.
- 5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

10.5. Measurement Result:

Channel separation (MHz)	Limit	Result
1	>=25KHz or 20dB bandwidth	PASS

Note: Refer to next page for plots.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 50 of 62

Frequency Separation Test Data



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

She stated the States the State of the State of the State of States and States and States are stated and States are states and States and States are stat only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 t (886-2) 2299-3279



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 51 of 62

11. NUMBER OF HOPPING FREQUENCY

11.1. Standard Applicable

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

11.2. Measurement Equipment Used:

Refer to section 6.2 for details.

11.3. Test Set-up:

Refer to section 6.3 for details.

11.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set spectrum analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = auto.
- 4. Set the spectrum analyzer as RBW, VBW=430KHz/1.3MHz,
- 5. Max hold, view and count how many channel in the band.

11.5. Measurement Result:

Note: Refer to next page for plots.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law






Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**


Page: 52 of 62

Channel Number

2.4 GHz - 2.441GHz



2.441 GHz - 2.4835GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

She stated the States the State of the State of the State of States and States and States are stated and States are states and States and States are stat only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279

f (886-2) 2298-0488


www.tw.sqs.com



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 53 of 62

AFH Mode



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless otherwise stated the results snown in this test report refer only to the sample(s) lested and such sample(s) are retained for so days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention. militation and piralicition issues defined interent. Any holder of this document is advised and information contained networn reference the Company's minings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 54 of 62

12. TIME OF OCCUPANCY (DWELL TIME)

12.1. Standard Applicable

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

12.2. Measurement Equipment Used:

Refer to section 6.2 for details.

12.3. Test Set-up:

Refer to section 6.3 for details.

12.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = operating frequency.
- 4. Set the spectrum analyzer as RBW, VBW=1MHz/1MHz, Span = 0Hz, Adjust Sweep = 2ms-5ms.
- 5. Repeat above procedures until all frequency measured were complete.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 55 of 62

12.5. Measurement Result

A period time = 0.4 (ms) * 79 = 31.6 (s)

CH Low DH1 time slot = 0.327 (ms) * (1600/2/79) * 31.6 = 104.64 (ms)

DH3 time slot = 1.540 (ms) * (1600/4/79) * 31.6 = 246.40 (ms)

DH5 time slot = 2.892 (ms) * (1600/6/79) * 31.6 = 308.48 (ms)

CH Mid DH1 time slot = 0.327 (ms) * (1600/2/79) * 31.6 = 104.64 (ms)

DH3 time slot = 1.540 (ms) * (1600/4/79) * 31.6 = 246.40 (ms)

DH5 time slot = 2.892 (ms) * (1600/6/79) * 31.6 = 308.48 (ms)

CH High DH1 time slot = 0.327 (ms) * (1600/2/79) * 31.6 = 104.64 (ms)

DH3 time slot = 1.540 (ms) * (1600/4/79) * 31.6 = 246.40 (ms)

DH5 time slot = 2.892 (ms) * (1600/6/79) * 31.6 = 308.48 (ms)

Note: Refer to next page for plots.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law




Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010


Page: 56 of 62

CH-Low

DH1



DH3



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan/台北縣五股工業區五工路 134 號 SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488


www.tw.sqs.com



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 57 of 62

DH5



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279




Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010


Page: 58 of 62

CH-Mid

DH1



DH3



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan/台北縣五股工業區五工路 134 號 SGS Taiwan Ltd.

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488


www.tw.sqs.com



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 59 of 62

DH5



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279






Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010


Page: 60 of 62

CH-High

DH1



DH3



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan/台北縣五股工業區五工路 134 號 SGS Taiwan Ltd.


t (886-2) 2299-3279



Report No.: EH/2010/90009 **Issue Date: Sep. 28, 2010**

Page: 61 of 62

DH5



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ships of the testing ships the testing ships the sample(s) testing and testing the testing ships the sample(s) testing and testing the sample(s) testing and testing the sample(s) testing and testin only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

t (886-2) 2299-3279



Report No.: EH/2010/90009 Issue Date: Sep. 28, 2010

Page: 62 of 62

13. ANTENNA REQUIREMENT

13.1. Standard Applicable

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than furnished by the responsible party shall be used with the device.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

13.2. Antenna Connected Construction

The directional gains of antenna used for transmitting is -3.34dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Please see EUT photo for details.