



FCC RADIO TEST REPORT

FCC ID : GKRRMLN1
Equipment : 5G LGA Module
Brand Name : COMPAL
Model Name : RML-N1
Marketing Name : 5G LGA Module
Applicant : Compal Electronics, Inc.
No.581 & 581-1, Ruiguang Rd., Neihu District,
Taipei, (114) Taiwan
Manufacturer : Compal Electronics, Inc.
No.581 & 581-1, Ruiguang Rd., Neihu District,
Taipei, (114) Taiwan
Standard : FCC 47 CFR Part 2, 96

The product was received on Jun. 13, 2023 and testing was performed from Jun. 28, 2023 to Jul. 26, 2023. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report..... 3

Summary of Test Result..... 4

1 General Description 5

 1.1 Product Feature of Equipment Under Test 5

 1.2 Modification of EUT 5

 1.3 Testing Location 6

 1.4 Applied Standards 7

2 Test Configuration of Equipment Under Test 8

 2.1 Test Mode..... 8

 2.2 Connection Diagram of Test System 9

 2.3 Support Unit used in test configuration 9

 2.4 Measurement Results Explanation Example 9

 2.5 Frequency List of Low/Middle/High Channels..... 10

3 Conducted Test Items..... 11

 3.1 Measuring Instruments..... 11

 3.2 Conducted Output Power 12

 3.3 Peak-to-Average Ratio 13

 3.4 EIRP 14

 3.5 Occupied Bandwidth 15

 3.6 Conducted Band Edge 16

 3.7 Conducted Spurious Emission 17

 3.8 Frequency Stability..... 18

4 Radiated Test Items 19

 4.1 Measuring Instruments..... 19

 4.2 Test Setup 19

 4.3 Test Result of Radiated Test..... 20

 4.4 Radiated Spurious Emission 21

5 List of Measuring Equipment..... 22

6 Measurement Uncertainty 23

Appendix A. Test Results of Conducted Test

Appendix B. Test Results of Radiated Test

Appendix C. Test Setup Photographs



History of this test report

Report No.	Version	Description	Issue Date
FG133040-05A	01	Initial issue of report	Aug. 10, 2023
FG133040-05A	02	Revise Section 1.1, Measurement Uncertainty and Appendix A This report is an updated version, replacing the report issued on Aug. 10, 2023.	Aug. 21, 2023



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046 RSS-192 8.6	Conducted Output Power	Reporting only	-
3.3	§96.41	Peak-to-Average Ratio	Pass	
3.4	§96.41	Effective Isotropic Radiated Power	Pass	-
3.5	§2.1049 §96.41	Occupied Bandwidth	Reporting only	-
3.6	§2.1051 §96.41	Conducted Band Edge Measurement	Pass	-
3.7	§2.1051 §96.41	Conducted Spurious Emission	Pass	
3.8	§2.1055	Frequency Stability for Temperature & Voltage	Pass	-
4.4	§2.1051 §96.41	Radiated Spurious Emission	Pass	10.04 dB under the limit at 10804.00 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Michelle Chen



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
<p>General Specs LTE/5G NR, and GNSS.</p> <p>Antenna Type WWAN: Monopole Antenna GPS / Glonass / BDS / Galileo: Monopole Antenna</p>

The following antenna was provided to the EUT.

	Band	Antenna Port	RF Exposure Max Antenna Gain(dBi)
5G NR	n48	ANT5	-2

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.



1.3 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH03-HY
Test Engineer	Sherry Wu and Luffy Lin
Temperature (°C)	20~24
Relative Humidity (%)	43~58

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH12-HY (TAF Code: 3786)
Test Engineer	Tim Lee and Wilson Wu
Temperature (°C)	20~25
Relative Humidity (%)	50~60
Remark	The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW3786



1.4 Applied Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ FCC 47 CFR Part 2, 96
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 940660 D01 Part 96 CBRS Eqpt v03
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.26 exploratory test procedures and only the worst case emissions were reported in this report.

Test Items	NR Band	Bandwidth (MHz)												Modulation					RB #			Test Channel		
		5	10	15	20	30	40	50	60	70	80	90	100	PI/2 BPSK	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	n48	v	v	v	v	-	v	v	v	-	v	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	n48				v	-				-				v	v	v	v	v			v		v	
26dB and 99% Bandwidth	n48	v	v	v	v	-	v	v	v	-	v	v	v	v	v	v	v	v			v		v	
Conducted Band Edge	n48	v	v	v	v	-	v	v	v	-	v	v	v	v	v	v	v	v	v		v	v	v	v
Conducted Spurious Emission	n48	v	v	v	v	-	v	v	v	-	v	v	v		v				v			v	v	v
Frequency Stability	n48				v	-				-				v							v		v	
E.I.R.P	n48	v	v	v	v	-	v	v	v	-	v	v	v	v	v	v	v	v	Max. Power					
Radiated Spurious Emission	n48	Worst Case																			v	v	v	
Remark	<ol style="list-style-type: none"> The mark "v" means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. For radiated measurement, pre-scanned in two modes, DFT-s OFDM and CP OFDM. The worst cases (DFT-s OFDM) were recorded in this report. One representative bandwidth is selected to perform PAR and frequency stability. Test combination are EN-DC 2A-n48A and EN-DC 66A-n48A. For 5G NR n48 BW:5 MHz only support SCS15kHz and test combination is CA 5G n5+n48. For 5G NR n48 BW:10/15/20/40/50MHz support SCS15 kHz&SCS30 kHz, after verified, the worst case is SCS30 kHz. Therefore, only performed the SCS30 kHz test results for Conducted test item in this report. 																							

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
3.	Adapter	Compal	F24L3-120200SPAU	N/A	N/A	Unshielded, 1 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

5G NR n48 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
100	Channel	640000	641666	643332
	Frequency	3600	3624.99	3649.98
90	Channel	639668	641666	643666
	Frequency	3595.02	3624.99	3654.99
80	Channel	639334	641666	644000
	Frequency	3590.01	3624.99	3660
60	Channel	638668	641666	644666
	Frequency	3580.02	3624.99	3669.99
50	Channel	638334	641666	645000
	Frequency	3575.01	3624.99	3675
40	Channel	638000	641666	645332
	Frequency	3570	3624.99	3679.98
20	Channel	637334	641666	646000
	Frequency	3560.01	3624.99	3690
15	Channel	637168	641666	646166
	Frequency	3557.52	3624.99	3692.49
10	Channel	637000	641666	646332
	Frequency	3555	3624.99	3694.98
5	Channel	636834	641667	646500
	Frequency	3552.51	3625.005	3697.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 EIRP, Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power

3.2.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio



3.4 EIRP

3.4.1 Description of the EIRP Measurement

The EIRP of mobile transmitters must not exceed 23 dBm /10 megahertz for 5G NR n48.

The testing follows ANSI C63.26-2015 Section 5.2.5.5

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - LC$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

Device	Maximum EIRP (dBm/10 MHz)	Maximum PSD (dBm/MHz)
End User Device	23	n/a

Remark: Total channel power is complied with EIRP limit 23dBm/10MHz.

3.4.2 Test Procedures

The testing follows procedure in Section 5.2 of ANSI C63.26-2015 and KDB 940660 D01 Part 96 CBRS Eqpt v03 Section 3.2(b)(2)

Determine the EIRP by adding the effective antenna gain to the measured average conducted power level.



3.5 Occupied Bandwidth

3.5.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.5.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.6 Conducted Band Edge

3.6.1 Description of Conducted Band Edge Measurement

The conducted power of any End User Device emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed -13 dBm/MHz within 0 to B megahertz (where B is the bandwidth in megahertz of the assigned channel or multiple contiguous channels of the End User Device) above the upper CBSD-assigned channel edge and within 0 to B megahertz below the lower CBSD-assigned channel edge. At all frequencies greater than B megahertz above the upper CBSD assigned channel edge and less than B megahertz below the lower CBSD-assigned channel edge, the conducted power of any End User Device emission shall not exceed -25 dBm/MHz. Notwithstanding the emission limits in this paragraph, the Adjacent Channel Leakage Ratio for End User Devices shall be at least 30 dB.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Adjacent Channel Leakage Ratio (ACLR) measurement,

1. The Adjacent Channel Leakage Ratio (ACLR) is the ratio of the average power in the assigned aggregated channel bandwidth to the average power over the equivalent adjacent channel bandwidth.
2. The option ACLR of spectrum analyzer is used and measures the ACLR ratio by setting equivalent channel bandwidth.
3. The measured ACLR ratio shall be at least 30 dB.



3.7 Conducted Spurious Emission

3.7.1 Description of Conducted Spurious Emission Measurement

96.41 (e)(2)

The conducted power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz.

3.7.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is -40dBm/MHz.



3.8 Frequency Stability

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency

3.8.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least -40dBm / MHz .
The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
 $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
 $ERP \text{ (dBm)} = EIRP - 2.15$
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
The limit line is -40dBm/MHz



5 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 20, 2022	Jun. 28, 2023~ Jun. 29, 2023	Sep. 19, 2023	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01 N-06	37059 & 01	30MHz~1GHz	Nov. 10, 2022	Jun. 28, 2023~ Jun. 29, 2023	Nov. 09, 2023	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-021 14	1GHz~18GHz	Aug. 09, 2022	Jun. 28, 2023~ Jun. 29, 2023	Aug. 08, 2023	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA9170	00993	18GHz~40GHz	Nov. 24, 2022	Jun. 28, 2023~ Jun. 29, 2023	Nov. 23, 2023	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Oct. 03, 2022	Jun. 28, 2023~ Jun. 29, 2023	Oct. 02, 2023	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A023 75	1GHz~26.5GHz	May 23, 2023	Jun. 28, 2023~ Jun. 29, 2023	May 22, 2024	Radiation (03CH12-HY)
Preamplifier	E-INSTRUME NT TECH LTD.	ERA-100M-18 G-56-01-A70	EC190024 9	1GHz-18GHz	Dec. 21, 2022	Jun. 28, 2023~ Jun. 29, 2023	Dec. 20, 2023	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 07, 2022	Jun. 28, 2023~ Jun. 29, 2023	Dec. 06, 2023	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Jan. 10, 2023	Jun. 28, 2023~ Jun. 29, 2023	Jan. 09, 2024	Radiation (03CH12-HY)
Filter	Wainwright	WHKX8-5872. 5-6750-18000 -40ST	SN2	6.75GHz High Pass Filter	Mar. 14, 2023	Jun. 28, 2023~ Jun. 29, 2023	Mar. 13, 2024	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 07, 2023	Jun. 28, 2023~ Jun. 29, 2023	Mar. 06, 2024	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 20, 2022	Jun. 28, 2023~ Jun. 29, 2023	Dec. 19, 2023	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Dec. 20, 2022	Jun. 28, 2023~ Jun. 29, 2023	Dec. 19, 2023	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803953/2	30MHz~40GHz	Dec. 20, 2022	Jun. 28, 2023~ Jun. 29, 2023	Dec. 19, 2023	Radiation (03CH12-HY)
Hygrometer	TECPEL	DTM-303B	TP210090	N/A	Oct. 03, 2022	Jun. 28, 2023~ Jun. 29, 2023	Oct. 02, 2023	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jun. 28, 2023~ Jun. 29, 2023	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1m~4m	N/A	Jun. 28, 2023~ Jun. 29, 2023	N/A	Radiation (03CH12-HY)
Base Station	Anritsu	8821C	626204465 7	N/A	Mar. 22, 2023	Jun. 28, 2023~ Jun. 29, 2023	Mar. 21, 2024	Radiation (03CH12-HY)
5G Wireless Test Platform	Anritsu	MT8000A	626194032 7	N/A	Dec. 09, 2022	Jun. 28, 2023~ Jun. 29, 2023	Dec. 08, 2023	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jun. 28, 2023~ Jun. 29, 2023	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-00098 9	N/A	N/A	Jun. 28, 2023~ Jun. 29, 2023	N/A	Radiation (03CH12-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	50Hz~60Hz	Sep. 29, 2022	Jul. 10, 2023~ Jul. 26, 2023	Sep. 28, 2023	Conducted (TH03-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101049	10Hz~44GHz	Oct. 07, 2022	Jul. 10, 2023~ Jul. 26, 2023	Oct. 06, 2023	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-40℃ ~90℃	Sep. 07, 2022	Jul. 10, 2023~ Jul. 26, 2023	Sep. 06, 2023	Conducted (TH03-HY)
5G Wireless Test Platform)	Keysight	E7515B	MY593218 26	FR1	Apr. 26, 2023	Jul. 10, 2023~ Jul. 26, 2023	Apr. 25, 2024	Conducted (TH03-HY)
Base Station (Measure)	Anritsu	MT8821C	626194032 7	LTE	Dec. 09, 2022	Jul. 10, 2023~ Jul. 26, 2023	Dec. 08, 2023	Conducted (TH03-HY)
Base Station (Measure)	Anritsu	MT8000A	626184901 5	FR1	Dec. 09, 2022	Jul. 10, 2023~ Jul. 26, 2023	Dec. 08, 2023	Conducted (TH03-HY)



6 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.31 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.25 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.81 dB
---	---------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power) and EIRP

<SCS15kHz>

NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)
5	1	1	PI/2 BPSK	23.42	23.62	23.42	21.78	0.1507
5	1	23		23.42	23.74	23.31		
5	12	6		23.43	23.78	23.42		
5	1	0		13.89	13.97	13.77		
5	1	24		13.85	14.06	13.68		
5	25	0		17.92	18.04	17.92		
5	1	1	QPSK	23.39	23.72	23.56	20.51	0.1125
5	1	23		23.38	23.63	23.54		
5	12	6		23.45	23.74	23.64		
5	1	0		13.46	13.49	13.35		
5	1	24		13.41	13.62	13.46		
5	25	0		18.92	19.19	19.10		
5	1	1	16-QAM	22.42	22.51	22.21	20.51	0.1125
5	1	1	64-QAM	20.86	21.07	21.11		
5	1	1	256-QAM	18.92	19.21	19.11		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)
10	1	1	PI/2 BPSK	23.16	23.83	23.64	21.96	0.157
10	1	50		23.46	23.84	23.56		
10	25	12		23.37	23.87	23.80		
10	1	0		13.58	14.30	14.16		
10	1	51		13.97	14.39	14.19		
10	50	0		17.86	18.42	18.26		
10	1	1	QPSK	23.20	23.83	23.64	20.70	0.1175
10	1	50		23.51	23.94	23.66		
10	25	12		23.33	23.96	23.74		
10	1	0		13.22	13.85	13.59		
10	1	51		13.43	13.95	13.72		
10	50	0		19.00	19.50	19.29		
10	1	1	16-QAM	22.11	22.69	22.70	20.70	0.1175
10	1	1	64-QAM	20.74	21.40	21.03		
10	1	1	256-QAM	18.75	19.51	19.32		
Limit	EIRP < 23dBm/10MHz			Result			Pass	



NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)		
15	1	1	PI/2 BPSK	23.10	23.69	23.63	21.95	0.1567		
15	1	77		23.39	23.83	23.59				
15	36	18		23.41	23.91	23.70				
15	1	0		13.55	14.18	14.18				
15	1	78		13.89	14.40	14.07				
15	75	0		17.98	18.49	18.28				
15	1	1	QPSK	23.08	23.70	23.60			20.75	0.1189
15	1	77		23.59	23.90	23.50				
15	36	18		23.47	23.95	23.80				
15	1	0		13.02	13.57	13.60				
15	1	78		13.57	13.79	13.58				
15	75	0		18.94	19.46	19.27				
15	1	1	16-QAM	22.34	22.75	22.69	20.75	0.1189		
15	1	1	64-QAM	20.47	21.12	20.92				
15	1	1	256-QAM	18.74	19.25	19.49				
Limit	EIRP < 23dBm/10MHz			Result			Pass			

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)		
20	1	1	PI/2 BPSK	23.29	23.76	23.66	21.97	0.1574		
20	1	104		23.61	23.92	23.61				
20	50	25		23.49	23.78	23.72				
20	1	0		13.71	14.23	14.11				
20	1	105		14.12	14.43	14.12				
20	100	0		17.93	18.38	18.23				
20	1	1	QPSK	23.25	23.77	23.62			20.74	0.1186
20	1	104		23.53	23.97	23.54				
20	50	25		23.51	23.96	23.63				
20	1	0		13.14	13.68	13.62				
20	1	105		13.51	13.96	13.68				
20	100	0		19.10	19.42	19.18				
20	1	1	16-QAM	22.40	22.73	22.74	20.74	0.1186		
20	1	1	64-QAM	20.62	21.12	21.12				
20	1	1	256-QAM	18.84	19.49	19.39				
Limit	EIRP < 23dBm/10MHz			Result			Pass			



NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)		
40	1	1	PI/2 BPSK	22.85	23.37	23.31	21.93	0.156		
40	1	214		23.24	23.52	23.33				
40	108	54		23.60	23.82	23.76				
40	1	0		13.50	13.86	13.89				
40	1	215		13.86	14.06	13.75				
40	216	0		17.93	18.22	18.05				
40	1	1	QPSK	22.91	23.24	23.26			20.30	0.1072
40	1	214		23.25	23.54	23.23				
40	108	54		23.51	23.93	23.83				
40	1	0		12.92	13.15	13.39				
40	1	215		13.12	13.48	13.22				
40	216	0		19.07	19.30	19.22				
40	1	1	16-QAM	21.92	22.17	22.30	20.30	0.1072		
40	1	1	64-QAM	20.29	20.77	20.70				
40	1	1	256-QAM	18.91	19.12	19.21				
Limit	EIRP < 23dBm/10MHz			Result			Pass			

NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)		
50	1	1	PI/2 BPSK	23.18	23.54	23.69	21.94	0.1563		
50	1	268		23.56	23.80	23.49				
50	135	67		23.56	23.94	23.85				
50	1	0		13.70	14.08	14.22				
50	1	269		14.13	14.41	13.98				
50	270	0		18.00	18.44	18.28				
50	1	1	QPSK	23.16	23.59	23.71			20.78	0.1197
50	1	268		23.56	23.87	23.43				
50	135	67		23.57	23.94	23.79				
50	1	0		13.17	13.58	13.78				
50	1	269		13.51	13.81	13.53				
50	270	0		19.09	19.45	19.42				
50	1	1	16-QAM	22.46	22.57	22.78	20.78	0.1197		
50	1	1	64-QAM	20.63	20.99	21.34				
50	1	1	256-QAM	18.92	18.98	19.16				
Limit	EIRP < 23dBm/10MHz			Result			Pass			

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



<SCS30kHz>

NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)
10	1	1	PI/2 BPSK	23.35	23.91	23.79	21.99	0.1581
10	1	22		23.41	23.95	23.73		
10	12	6		23.46	23.99	23.86		
10	1	0		13.99	14.42	14.33		
10	1	23		13.92	14.48	14.21		
10	24	0		17.98	18.56	18.38		
10	1	1	QPSK	23.49	23.99	23.83		
10	1	22		23.55	23.99	23.72		
10	12	6		23.49	23.95	23.91		
10	1	0		13.36	13.91	13.79		
10	1	23		13.44	14.00	13.71		
10	24	0		18.99	19.58	19.45		
10	1	1	16-QAM	22.36	22.75	22.78	20.78	0.1197
10	1	1	64-QAM	20.83	21.59	21.30		
10	1	1	256-QAM	18.82	19.57	19.48		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)
15	1	1	PI/2 BPSK	23.18	23.83	23.76	21.98	0.1578
15	1	36		23.49	23.92	23.66		
15	18	9		23.53	23.98	23.86		
15	1	0		13.85	14.41	14.26		
15	1	37		14.00	14.43	14.21		
15	36	0		18.07	18.51	18.45		
15	1	1	QPSK	23.22	23.87	23.76		
15	1	36		23.52	23.88	23.59		
15	18	9		23.58	23.95	23.85		
15	1	0		13.19	13.85	13.80		
15	1	37		13.33	13.93	13.66		
15	36	0		19.13	19.62	19.40		
15	1	1	16-QAM	22.50	22.81	22.94	20.94	0.1242
15	1	1	64-QAM	20.83	21.36	21.28		
15	1	1	256-QAM	18.96	19.52	19.38		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)
20	1	1	PI/2 BPSK	23.24	23.60	23.77	21.95	0.1567
20	1	49		23.41	23.91	23.61		
20	25	12		23.56	23.95	23.79		
20	1	0		13.78	14.29	14.26		
20	1	50		14.02	14.37	13.98		
20	50	0		17.99	18.40	18.23		
20	1	1	QPSK	23.30	23.86	23.70		
20	1	49		23.46	23.83	23.60		
20	25	12		23.74	23.91	23.77		
20	1	0		13.34	13.72	13.75		
20	1	50		13.49	13.82	13.53		
20	50	0		19.13	19.55	19.32		
20	1	1	16-QAM	22.44	22.66	22.69	20.69	0.1172
20	1	1	64-QAM	20.82	21.29	21.23		
20	1	1	256-QAM	18.84	19.44	19.46		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)
40	1	1	PI/2 BPSK	22.97	23.47	23.58	21.97	0.1574
40	1	104		23.44	23.71	23.42		
40	50	25		23.67	23.92	23.92		
40	1	0		13.54	13.94	14.05		
40	1	105		13.86	14.16	13.94		
40	100	0		18.09	18.44	18.32		
40	1	1	QPSK	22.97	23.37	23.49		
40	1	104		23.41	23.80	23.40		
40	50	25		23.71	23.94	23.97		
40	1	0		13.03	13.53	13.61		
40	1	105		13.39	13.59	13.42		
40	100	0		19.20	19.53	19.44		
40	1	1	16-QAM	22.12	22.30	22.51	20.51	0.1125
40	1	1	64-QAM	20.51	21.01	21.01		
40	1	1	256-QAM	18.49	19.18	19.18		
Limit	EIRP < 23dBm/10MHz			Result			Pass	



NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)
50	1	1	PI/2 BPSK	23.27	23.72	23.76	21.99	0.1581
50	1	131		23.60	23.90	23.59		
50	64	32		23.70	23.94	23.92		
50	1	0		13.77	14.22	14.41		
50	1	132		14.20	14.50	14.12		
50	128	0		18.17	18.43	18.42		
50	1	1	QPSK	23.27	23.67	23.75		
50	1	131		23.61	23.95	23.53		
50	64	32		23.72	23.99	23.96		
50	1	0		13.28	13.73	13.89		
50	1	132		13.68	13.94	13.65		
50	128	0		19.22	19.58	19.46		
50	1	1	16-QAM	22.42	22.83	22.44	20.83	0.1211
50	1	1	64-QAM	20.81	21.39	21.46		
50	1	1	256-QAM	18.97	19.34	19.39		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)
60	1	1	PI/2 BPSK	23.11	23.45	23.60	21.97	0.1574
60	1	160		23.61	23.72	23.49		
60	81	40		23.82	23.97	23.96		
60	1	0		13.69	14.05	14.17		
60	1	161		14.13	14.29	14.01		
60	162	0		18.25	18.47	18.37		
60	1	1	QPSK	23.08	23.46	23.60		
60	1	160		23.56	23.68	23.44		
60	81	40		23.81	23.96	23.96		
60	1	0		13.15	13.50	13.63		
60	1	161		13.64	13.78	13.52		
60	162	0		19.24	19.53	19.42		
60	1	1	16-QAM	22.27	22.38	22.55	20.55	0.1135
60	1	1	64-QAM	20.62	20.90	21.12		
60	1	1	256-QAM	18.82	19.07	19.22		
Limit	EIRP < 23dBm/10MHz			Result			Pass	



NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)		
80	1	1	PI/2 BPSK	22.73	23.01	23.28	21.94	0.1563		
80	1	215		23.29	23.44	23.22				
80	108	54		23.78	23.93	23.91				
80	1	0		13.40	13.70	13.94				
80	1	216		13.98	14.11	13.87				
80	216	0		18.21	18.46	18.39				
80	1	1	QPSK	22.72	23.06	23.30			20.26	0.1062
80	1	215		23.28	23.43	23.17				
80	108	54		23.83	23.94	23.94				
80	1	0		12.96	13.25	13.47				
80	1	216		13.53	13.62	13.43				
80	216	0		19.28	19.49	19.42				
80	1	1	16-QAM	21.80	22.02	22.26	20.26	0.1062		
80	1	1	64-QAM	20.41	20.64	20.97				
80	1	1	256-QAM	18.59	18.81	19.10				
Limit	EIRP < 23dBm/10MHz			Result			Pass			

NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)										
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)		
90	1	1	PI/2 BPSK	22.68	22.87	23.04	21.99	0.1581		
90	1	243		23.14	23.28	23.14				
90	120	60		23.75	23.96	23.99				
90	1	0		13.48	13.63	13.78				
90	1	244		13.92	14.05	13.93				
90	243	0		18.18	18.36	18.42				
90	1	1	QPSK	22.66	22.84	23.01			19.98	0.0995
90	1	243		23.13	23.28	23.12				
90	120	60		23.78	23.99	23.99				
90	1	0		12.97	13.10	13.30				
90	1	244		13.43	13.53	13.37				
90	243	0		19.23	19.42	19.43				
90	1	1	16-QAM	21.70	21.98	21.96	19.98	0.0995		
90	1	1	64-QAM	20.37	20.52	20.69				
90	1	1	256-QAM	18.46	18.73	18.83				
Limit	EIRP < 23dBm/10MHz			Result			Pass			

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



NR n48 Maximum Average Power [dBm] (GT - LC = -2 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP(W)
100	1	0	PI/2 BPSK	22.48	22.65	22.69	21.93	0.156
100	1	272		23.02	23.05	22.22		
100	270	0		23.78	23.93	23.29		
100	1	1		13.32	13.43	13.47		
100	1	1		13.84	13.81	13.02		
100	1	1		18.13	18.26	17.71		
100	0	0	QPSK	22.47	22.40	22.64		
100	0	0		22.99	22.32	22.15		
100	0	0		23.79	23.53	23.30		
100	0	0		12.81	12.90	12.93		
100	0	0		13.30	12.64	12.50		
100	0	0		19.20	18.92	18.75		
100	0	0		16-QAM	21.43	21.65	21.77	
100	0	0	64-QAM	20.13	20.24	20.49	19.77	0.0948
100	0	0	256-QAM	18.40	18.16	18.57		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



FR1 n48

Peak-to-Average Ratio



Mode	FR1 n48 / 20MHz / DFT-S OFDM				
Mod.	PI/2 BPSK	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Middle CH	7.56	5.82	6.46	6.52	PASS
Mode	FR1 n48 / 20MHz / DFT-S OFDM				
Mod.	256QAM				Limit: 13dB
RB Size	Full RB				Result
Middle CH	6.80				PASS



FR1 n48 / 20MHz / DFT-S OFDM / Middle Channel / Full RB



PI/2 BPSK

QPSK




16QAM

64QAM



256QAM





26dB Bandwidth


Mode	FR1 n48 : 26dB BW(MHz) / DFT-S OFDM							
BW	5MHz	10MHz	15MHz	20MHz	40MHz	50MHz	60MHz	80MHz
Mod.	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK
Middle CH	4.97	9.59	14.42	19.06	41.16	50.85	60.90	80.56
BW	90MHz	100MHz						
Mod.	PI/2 BPSK	PI/2 BPSK						
Middle CH	89.91	99.90						

Mode	FR1 n48 : 26dB BW(MHz) / CP OFDM							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	4.97	5.04	9.93	9.89	15.16	15.04	20.10	20.02
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM
Middle CH	4.88	4.88	9.97	9.99	15.13	15.04	20.06	20.10
BW	40MHz		50MHz		60MHz		80MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	41.40	41.08	50.85	51.05	60.66	60.66	80.88	81.20
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM
Middle CH	41.88	41.08	51.05	51.15	60.78	61.02	81.04	80.88
BW	90MHz		100MHz					
Mod.	QPSK	16QAM	QPSK	16QAM				
Middle CH	90.81	90.63	100.70	100.70				
Mod.	64QAM	256QAM	64QAM	256QAM				
Middle CH	90.81	90.99	101.30	100.70				




FR1 n48 /5MHz/ DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 5MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 10MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 10MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 15MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 15MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 20MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 20MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 40MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 40MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 50MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 50MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 60MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 60MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 80MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 80MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 90MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 90MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 100MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 100MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM



256QAM





Occupied Bandwidth


Mode	FR1 n48 : OB BW(MHz) / DFT-S OFDM							
BW	5MHz	10MHz	15MHz	20MHz	40MHz	50MHz	60MHz	80MHz
Mod.	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK
Middle CH	4.48	8.95	13.47	17.89	38.74	48.33	57.84	77.06
BW	90MHz	100MHz						
Mod.	PI/2 BPSK	PI/2 BPSK						
Middle CH	86.67	95.98						

Mode	FR1 n48 : OB BW(MHz) / CP OFDM							
BW	5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	4.50	4.49	9.28	9.27	14.14	14.13	18.93	18.99
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM
Middle CH	4.47	4.49	9.27	9.30	14.11	14.18	18.94	18.94
BW	40MHz		50MHz		60MHz		80MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	38.70	38.65	48.34	48.37	57.77	57.89	77.40	77.50
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM
Middle CH	38.75	38.65	48.39	48.49	57.85	57.87	77.47	77.37
BW	90MHz		100MHz					
Mod.	QPSK	16QAM	QPSK	16QAM				
Middle CH	87.24	87.39	97.10	96.97				
Mod.	64QAM	256QAM	64QAM	256QAM				
Middle CH	87.35	87.22	97.10	97.23				




FR1 n48 / 5MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 5MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 10MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 10MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 15MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 10MHz / CP OFDM / Middle Channel / Full RB


QPSK




16QAM



64QAM




256QAM






FR1 n48 / 20MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK




FR1 n48 / 20MHz / CP OFDM / Middle Channel / Full RB


QPSK



16QAM



64QAM



256QAM

