TABLE OF CONTENTS

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE136143

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST

PAGE 2.....TEST PROCEDURE

PAGE 3.....RADIATION INTERFERENCE TEST DATA

PAGE 4.....OCCUPIED BANDWIDTH TEST DATA

PAGE 5.....OCCUPIED BANDWIDTH PLOT

EXHIBITS CONTAINING:

EXHIBIT 1.....BLOCK DIAGRAM

EXHIBIT 2.....SCHEMATIC

EXHIBIT 3.....INSTRUCTION MANUAL

EXHIBIT 4.....SAMPLE OF FCC ID LABEL

EXHIBIT 5.....LOCATION OF FCC ID LABEL

EXHIBIT 6.....EXTERNAL PHOTO - FRONT SIDE

EXHIBIT 7.....EXTERNAL PHOTO - BACK SIDE

EXHIBIT 8......INTERNAL PHOTO - COMPONENT SIDE EXHIBIT 9.....INTERNAL PHOTO - COPPER SIDE

EXHIBIT 10.....TEST SET UP PHOTOGRAPHS

EXHIBIT 11.....CIRCUIT DESCRIPTION

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE136143

REPORT #: S\SUNCON\1155ZH1\1155ZH1RPT.doc

PAGE: TABLE OF CONTENTS LIST

TEST EQUIPMENT LIST

- 1._X_Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/
 preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter
 HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,
 S/N 3008A00372 Cal. 8/31/01 Due 8/31/02
- 3.__ Biconnical Antenna: Electro-Metrics Model BIA-25, S/N 1171 Cal. 4/26/01 Due 4/26/03
- 4.___ Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632 Char. 3/15/00 Due 3/15/01

- 7.__ Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180, 1-18 GHz, S/N 2319 Cal. 4/27/99 Due 4/27/00
- 8.__ 18-26.3GHz Systron Donner Standard Gain Horn #DBE-520-20 No Cal Required
- 9.__ Horn 40-60GHz: ATM Part #19-443-6R No Cal Required
- 10.__ Line Impedance Stabilization Network: Electro-Metrics Model EM-7820, w/NEMA Adapter S/N 2682 Cal. 3/16/01 Due 3/16/02
- 11.__ Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7 Char. 1/27/01 Due 1/27/02
- 12.__ Frequency Counter: HP Model 5385A, S/N 3242A07460 Char. 11/20/00 Due 11/20/01
- 13.__ Peak Power Meter: HP Model 8900C, S/N 2131A00545 Char. 1/26/01 Due 1/26/02
- 14._X_Open Area Test Site #1-3meters Cal. 12/22/99
- 15.__ Signal Generator: HP 8640B, S/N 2308A21464 Cal. 11/15/01 Due 11/15/02
- 16.__ Passive Loop Antenna: EMCO Model 6512, 9KHz to 30MHz, S/N 9706-1211 Char. 6/10/00 Due 6/10/01
- 17.__ Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153 Char. 11/24/00 Due 11/24/01
- 18.__ AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 10/9/01 Due 10/09/02
- 19._X_Digital Multimeter: Fluke Model 77, S/N 43850817 Cal. 11/16/00 Due 11/16/01
- 20.__ Oscilloscope: Tektronix Model 2230, S/N 300572 Char. 2/1/01 Due 2/1/02

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE136143

REPORT #: S\SUNCON\1155ZH1\1155ZH1RPT.doc

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was $100 \, \text{KHz}$ and the video bandwidth was $300 \, \text{KHz}$. The ambient temperature of the UUT was 64° with a humidity of 25%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS

33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE136143

REPORT #: S\SUNCON\1155ZH1\1155ZH1RPT.doc

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE136143

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.227

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.

OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz 40.0 dBuV/M MEASURED AT 3 METERS 88 - 216 MHz 43.5 dBuV/M 216 - 960 MHz 46.0 dBuV/M ABOVE 960 MHz 54.0 dBuV/M

TEST DATA:

Meter	Ant.	Coax		Field	
Reading	Polarity	Loss	Correction	Strength	Margin
dBuv		đВ	Factor	\mathtt{dBuv}/\mathtt{m}	đВ
			đВ		
66.8	v	0.31	11.78	78.89	1.11
14.8	v	0.84	9.60	25.24	14.76
7.4	v	1.23	9.30	17.93	25.57
8.7	v	1.34	13.73	23.77	19.73
9.3	v	1.50	16.78	27.58	15.92
11.2	v	1.72	14.23	27.15	16.35
13.9	v	1.87	11.39	27.16	18.84
12.2	v	1.98	11.82	26.00	20.00
9.5	v	2.09	13.75	25.34	20.66
	Reading dBuv 66.8 14.8 7.4 8.7 9.3 11.2 13.9	Reading dBuv 66.8 V 14.8 V 7.4 V 8.7 V 9.3 V 11.2 V 13.9 V 12.2 V	Reading dBuv dB 66.8 V 0.31 14.8 V 0.84 7.4 V 1.23 8.7 V 1.34 9.3 V 1.50 11.2 V 1.72 13.9 V 1.87 12.2 V 1.98	Reading dBuv Polarity dB Loss dB Correction dB 66.8 V 0.31 11.78 14.8 V 0.84 9.60 7.4 V 1.23 9.30 8.7 V 1.34 13.73 9.3 V 1.50 16.78 11.2 V 1.72 14.23 13.9 V 1.87 11.39 12.2 V 1.98 11.82	Reading dBuv Polarity dB Loss dB Correction dB Strength dBuv/m dB 66.8 V 0.31 11.78 78.89 14.8 V 0.84 9.60 25.24 7.4 V 1.23 9.30 17.93 8.7 V 1.34 13.73 23.77 9.3 V 1.50 16.78 27.58 11.2 V 1.72 14.23 27.15 13.9 V 1.87 11.39 27.16 12.2 V 1.98 11.82 26.00

SAMPLE CALCULATION: FSdBuV/m = MR(dBuV) + ACFdB.

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: JOSEPH SCOGLIO DATE: DECEMBER 21, 2001

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE136143

REPORT #: S\SUNCON\1155ZH1\1155ZH1RPT.doc

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE136143

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.227

REQUIREMENTS: The field strength of any emissions appearing

outside the 26.96-27.28 MHz band shall not exceed the general radiated emission limits in

(15.209).

THE GRAPH ON THE NEXT PAGE REPRESENTS THE WORSE CASE OCCUPPIED BANDWIDTH EMISSIONS FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to $-10~\mathrm{dBm}$ per division. The horizontal scale is set to $5~\mathrm{kHz}$ per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: JOSEPH SCOGLIO DATE: DECEMBER 21, 2001

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE136143

REPORT #: S\SUNCON\1155ZH1\1155ZH1RPT.doc

