

TABLE OF CONTENTS

APPLICANT: SUNCON TOYS INDUSTRY LTD

FCC ID: GLE32-0200DP

TEST REPORT CONTAINING:

PAGE 1-2....TEST PROCEDURE
PAGE 3.....CIRCUIT DESCRIPTION
PAGE 4.....49.86MHz Tx RADIATION INTERFERENCE TEST DATA
PAGE 5.....49.405MHz Tx RADIATION INTERFERENCE TEST DATA
PAGE 6.....OCCUPIED BANDWIDTH TEST DATA

EXHIBITS ATTACHMENTS:

EXHIBIT 1.....POWER OF ATTORNEY LETTER
EXHIBIT 2.....BLOCK DIAGRAM
EXHIBIT 3.....SCHEMATIC
EXHIBIT 4A-B-C.....PARTS LIST
EXHIBIT 5.....INSTRUCTION MANUAL
EXHIBIT 6.....FCC ID LABEL SAMPLE
EXHIBIT 7.....FCC ID LABEL LOCATION
EXHIBIT 8.....FRONT VIEW EXTERNAL PHOTOGRAPH
EXHIBIT 9.....REAR VIEW EXTERNAL PHOTOGRAPH
EXHIBIT 10.....INTERNAL COMPONENT SIDE PHOTOGRAPH
EXHIBIT 11.....INTERNAL COPPER SIDE PHOTOGRAPH
EXHIBIT 12.....OCCUPIED BANDWIDTH PLOT - TX/49.86
EXHIBIT 13.....OCCUPIED BANDWIDTH PLOT - TX/49.405
EXHIBIT 14.....OCCUPIED BANDWIDTH LOUD VOICE - TX/49.86
EXHIBIT 15.....OCCUPIED BANDWIDTH LOUD VOICE - TX/49.405
EXHIBIT 16.....OCCUPIED BANDWIDTH RINGER _ TX/49.86
EXHIBIT 17.....OCCUPIED BANDWIDTH RINGER _ TX/49.405

APPLICANT: SUNCON TOYS INDUSTRY LTD

FCC ID: GLE32-0200DP

REPORT #: F:\CUS\S\SUNCON\SUN242H8.RPT

TABLE OF CONTENTS PAGE

APPLICANT: SUNCON TOYS INDUSTRY LTD

FCC ID: GLE32-0200DP

TEST EQUIPMENT LIST

1. Spectrum Analyzer: Hewlett Packard 8566B - Opt 462, w/ preselector 85685A, & Quasi-Peak Adapter HP 85650A, & HP 8449B - OPT H02 Cal. 6/26/98
2. Signal Generator, Hewlett Packard 8640B, cal. 10/1/98
3. Eaton Biconnical Antenna Model 94455-1
20-200 MHz Serial No. 0997 Cal. 5/15/98
4. Electro-Metric Dipole Kit, 20-1000 MHz, Model TDA 25 cal. 5/15/97
5. Electro-Metric Horn 1-18 GHz, Model RGA-180, Cal. 8/15/98
6. Electro-Metric Antennas Model TDS-25-1, TDS-25-2, 5/15/97
7. Electro-Metric Line Impedance Stabilization Network Model No. EM-7821, Serial No. 101; 100KHz-30MHz 50uH. 12/3/97
8. Electro-Metric Line Impedance Stabilization Network Model No. EM-7820, Serial No. 2682; 10KHz-30MHz 50uH. 12/3/97

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was &temp& with a humidity of &humr&.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

APPLICANT: SUNCON TOYS INDUSTRY LTD

FCC ID: GLE32-0200DP

REPORT #: F:\CUS\S\SUNCON\SUN242H8.RPT

PAGE #: 1

TEST PROCEDURES CONTINUED

APPLICANT: SUNCON TOYS INDUSTRY LTD

FCC ID: GLE32-0200DP

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

APPLICANT: SUNCON TOYS INDUSTRY LTD

FCC ID: GLE32-0200DP

REPORT #: F:\CUS\S\SUNCON\SUN242H8.RPT

PAGE #: 2

APPLICANT: SUNCON TOYS INDUSTRY LTD

FCCID: GLE32-0200DP

CIRCUIT_DESCRIPTION:

When Unit A is turned on it transmits on 49.86MHz. This frequency is generated by oscillator Q1. The signal is coupled to the antenna by means of capacitor C1. This signal serves as a receiver local oscillator signal which heterodynes an incoming 49.405 MHz to a 455kHz IF frequency. The IF amplifier, detector, and receiver audio amplifier stages are all incorporated in integrated circuit - LC1600. When the ringer key is pressed the telephone sound IC -VM88 is activated and transmits.

When Unit B is turned on it transmits on 49.405 MHz. This frequency again serves as both the transmitter carrier and the receiver local oscillator. This signal provides low side injection to produce a 455 kHz IF from an 49.86 MHz signal.

ANTENNA_AND_GROUND_CIRCUITRY

This unit makes use of an 8" external antenna. The antenna is inductively coupled. The unit is powered from a 9.0 volt battery.

No ground connection is provided. The unit relies on the ground track of the printed circuit board.

APPLICANT: SUNCON TOYS INDUSTRY LTD

FCC ID: GLE32-0200DP

REPORT #: F:\CUS\S\SUNCON\SUN242H8.RPT

PAGE #: 3

APPLICANT: SUNCON TOYS INDUSTRY LTD

FCC ID: GLE32-0200DP

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.235

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz 40.0 dBuV/M MEASURED AT 3 METERS
88 - 216 MHz 43.5 dBuV/M
216 - 960 MHz 46.0 dBuV/M
ABOVE 960 MHz 54.0 dBuV/M
* Harmonics must be less than the fundamental.

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR dB	FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT. POL.
49.86	58.50	0.25	10.99	69.74	10.26	H
99.70	18.90	0.80	8.39	28.09	15.41	H
149.60	23.20	0.80	16.90	40.90	2.60	H
199.40	19.00	0.90	12.66	32.56	10.94	H
249.30	26.30	1.20	13.35	40.85	5.15	H
299.20	21.30	1.40	15.65	38.35	7.65	H
349.00	18.50	1.40	15.52	35.42	10.58	V
398.90	11.40	1.40	16.97	29.77	16.23	V
448.70	15.40	1.60	18.12	35.12	10.88	H
498.60	12.90	1.60	19.27	33.77	12.23	V
548.40	7.10	1.60	19.69	28.39	17.61	V
598.30	3.00	1.60	20.09	24.69	21.31	H
648.20	3.50	1.60	21.16	26.26	19.74	H

SAMPLE CALCULATION:

$FSdBuV/m = MR(dBuV) + ACFdB.$

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: _____ DATE: 23 SEPTEMBER 98
REPORT #: F:\CUS\S\SUNCON\SUN242H8.RPT
PAGE #: 4

APPLICANT:

FCC ID:

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.209

REQUIREMENTS: 1.705 to 30 MHz: 49.54 dBuV/m @ 3 METERS
30 to 88 MHz: 40.00 dBuV/M @ 3 METERS
88 to 216 MHz: 43.52 dBuV/M
216 to 960 MHz: 46.02 dBuV/M
ABOVE 960 MHz: 54.00 dBuV/M
* Harmonics must be less than the fundamental.

TEST RESULTS: A search was made of the spectrum from 25 to 1000 MHz and the measurements indicate that the unit DOES meet the FCC requirements.

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR dB	FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT. POL.
49.40	27.20	0.25	10.98	38.43	1.57	H
98.81	15.50	0.80	8.80	25.10	18.40	H
148.22	19.10	0.80	16.90	36.80	6.70	H
197.62	17.00	0.90	12.86	30.76	12.74	H
247.03	14.80	1.20	13.29	29.29	16.71	H
296.43	8.60	1.40	15.47	25.47	20.53	H
345.84	14.60	1.40	15.43	31.43	14.57	H
395.24	7.60	1.40	16.86	25.86	20.14	V
444.65	5.30	1.60	18.03	24.93	21.07	V
494.05	6.10	1.60	19.16	26.86	19.14	H
543.46	3.40	1.60	19.65	24.65	21.35	H
592.86	3.00	1.60	20.04	24.64	21.36	H

SAMPLE CALCULATION: FSdBuV/m = MR(dBuV) + ACFdB.

TEST PROCEDURE: ANSI STANDARD C63.4-1992 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Preselector, a Hewlett Packard Model 85650A Quasi-Peak adapter, Electro-Metric Dipole kits, models TDA, TDS-25-1, TDS-25-2, and an Eaton Model 94455-1 Biconical Antenna. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

PERFORMED BY: _____ DATE: 23 SEPTEMBER 98

REPORT #: F:\CUS\S\SUNCON\SUN242H8.RPT
PAGE #: 5

APPLICANT:

FCC ID:

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.235

REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPHS ON THE FOLLOWING PAGES REPRESENT THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the above photo was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: _____ 23 SEPTEMBER 98

APPLICANT:

FCC ID:

REPORT #: F:\CUS\S\SUNCON\SUN242H8.RPT

PAGE #: 6

