849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com

888.472.2424 F 352.472.2030 email: tei@timcoengr.com

Test Report

Product Name: WIRELESS RECEIVER

FCC ID: GLE60153R

Applicant:

SUNCON TOYS INDUSTRY LTD. 11/F, KAI TAK FACTORY BUILDING 99 KING FUK STREET SANPOKONG, KOWLOON HONG KONG

Date Receipt: 12/20/2006

Date Tested: 1/4/2007

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE60153R

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com

888.472.2424 F 352.472.2030 email: tei@timcoengr.com

TABLE OF CONTENTS LIST

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE60153R

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST PAGE 2.....TEST PROCEDURES

PAGE 3......RADIATION INTERFERENCE TEST DATA

EXHIBITS CONTAINING:

BLOCK DIAGRAM
SCHEMATIC
INSTRUCTION MANUAL
LABEL SAMPLE
LABEL LOCATION
EXTERNAL PHOTOGRAPHS
INTERNAL PHOTOGRAPHS
CIRCUIT DESCRIPTION
TEST SET UP PHOTOGRAPH

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE60153R

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com

888.472.2424 F 352.472.2030 email: tei@timcoengr.com

EMC Equipment List

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3/10-Meter OATS	TEI	N/A	N/A	Listed 3/27/04	3/26/07
3-Meter OATS	TEI	N/A	N/A	Listed 1/11/06	1/10/09
Antenna: Biconnical	Eaton	94455-1	1057	CAL 12/12/05	12/12/07
Antenna: Biconnical	Eaton	94455-1	1096	CAL 10/11/06	10/11/08
Antenna: Biconnical	Electro- Metrics	BIA-25	1171	CAL 4/29/05	4/29/07
Analyzer Blue Tower Quasi-Peak Adapter	HP	85650A	2811A01279	CAL 4/13/05	4/13/07
Analyzer Blue Tower RF Preselector	HP	85685A	2926A00983	CAL 9/5/05	9/5/07
Analyzer Blue Tower Spectrum Analyzer	HP	8568B	2928A04729 2848A18049	CAL 4/13/05	4/13/07
LISN	Electro- Metrics	ANS-25/2	2604	CAL 10/5/06	10/5/08
LISN	Electro- Metrics	EM-7820	2682	CAL 4/28/05	4/28/07
Antenna: Log- Periodic	Eaton	96005	1243	CAL 12/14/05	12/14/07

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE60153R

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: tei@timcoengr.com

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI standard C63.4-2003 using a spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was $100~\rm kHz$ with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was $100~\rm kHz$ and the video bandwidth was $300~\rm kHz$. The ambient temperature of the UUT was $80^{\circ}\rm F$ with a humidity of $70^{\circ}\rm k$.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + CL + ACF= FS 33 20 dBuV +1.2 + 10.36 dB = 31.56 dBuV/m @ 3m

ANSI STANDARD C63.4-2003 12.1.1.1 SUPERREGENERATIVE RECEIVER: A Signal Generator was set to the unit under test operating frequency. An un-Modulated continuous wave (CW) signal was radiated at the super-regenerative receiver operating frequency to cohere the characteristic broadband emissions from the receiver.

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE60153R

REPORT #: S\SUNCONGLE\3452HT6\3452HT6TestReport.doc

Page 2 of 4

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com

888.472.2424 F 352.472.2030 email: tei@timcoengr.com

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE60153R

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.109

REQUIREMENTS: 30 to 88 MHz: 40.0 dBuV/M @ 3 METERS

88 to 216 MHz: 43.5 dBuV/M 216 to 960 MHz: 46.0 dBuV/M ABOVE 960 MHz: 54.0 dBuV/M

TEST RESULTS: A search was made of the spectrum from 30 to 1000MHz and the measurements indicate that the unit DOES meet the FCC requirements.

TEST DATA:

Tuned	Emission	Meter	Ant.	Coax	Correction	Field	Margin
Frequency	Frequency	Reading	Polarity	Loss	Factor	Strength	đВ
MHz	MHz	dBuV		đВ	đВ	$\mathtt{dBuV/m}$	
49.9	47.78	21.6	v	0.95	11.04	33.59	6.41
49.9	47.82	17.0	H	0.95	12.02	29.97	10.03
49.9	49.05	21.7	v	0.96	10.79	33.45	6.55
49.9	50.50	18.1	H	0.98	11.33	30.41	9.59
49.9	50.80	19.8	v	0.98	10.39	31.17	8.83
49.9	51.90	18.0	v	0.99	10.11	29.10	10.90
49.9	52.66	19.2	v	0.99	9.91	30.10	9.90
49.9	53.56	18.0	v	1.00	9.67	28.67	11.33
49.9	54.16	18.6	v	1.01	9.52	29.13	10.87

SAMPLE CALCULATION: FSdBuV/m = MR (dBuV) + ACFdB.

Emissions attenuated more than $20~\mathrm{dB}$ below the permissible value are not reported.

PERFORMED BY: RICHARD BLOCK DATE: 1/4/2007

APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE60153R

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: tei@timcoengr.com



APPLICANT: SUNCON TOYS INDUSTRY LTD.

FCC ID: GLE60153R