


# ENGINEERING TEST REPORT



## ANNEX 1. WORKABOUT PRO G2 Handheld Computer Co-Location RFID and Bluetooth Model No.: 7527S

### Tested For

**Psion Teklogix Inc.**  
2100 Meadowvale Blvd.  
Mississauga, ON  
Canada, L5N 7J9

### In Accordance With

**SAR (Specific Absorption Rate) Requirements  
using guidelines established in IEEE Standard C95.1,  
FCC OET Bulletin 65 (Supplement C),  
Industry Canada RSS-102(Issue 2),  
EN 50360 (Council Recommendation 1999/519/EC) and  
ACA 2003 / ARPANSA Standard**

**UltraTech's File No.: TEK-596-SAR**

This Test report is Issued under the Authority of  
Tri M. Luu, Professional Engineer,  
Vice President of Engineering  
UltraTech Group of Labs



Date: July 16, 2007

Report Prepared by:  
JaeWook Choi

Tested by:  
Carolyn Luu

Issued Date:  
July 16, 2007

Test Dates:  
July 04, 2007

*The results in this Test Report apply only to the sample(s) tested, which has been randomly selected.*

## UltraTech

3000 Bristol Circle, Oakville, Ontario, Canada, L6H 6G4  
Telephone (905) 829-1570 Facsimile (905) 829-8050  
Website: [www.ultratech-labs.com](http://www.ultratech-labs.com) Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com)

## TABLE OF CONTENTS

<b>EXHIBIT 1. PERFORMANCE ASSESSMENT .....</b>	<b>3</b>
1.1. CLIENT AND MANUFACTURER INFORMATION .....	3
1.2. DEVICE UNDER TEST (D.U.T.) DESCRIPTION.....	3
1.3. GENERAL TEST CONFIGURATIONS .....	4
1.3.1. <i>Equipment Configuration</i> .....	4
1.3.2. <i>Exercising Equipment</i> .....	4
1.4. SPECIFIC OPERATING CONDITIONS.....	4
1.5. BLOCK DIAGRAM OF TEST SETUP .....	5
<b>EXHIBIT 2. SUMMARY OF TEST RESULTS.....</b>	<b>6</b>
2.1. LOCATION OF TESTS .....	6
2.2. APPLICABILITY & SUMMARY OF SAR RESULTS.....	6
2.2.1. <i>Maximum Peak Spatial-Average SAR for RFID</i> .....	6
2.2.2. <i>Maximum Peak Spatial-Average SAR for Bluetooth</i> .....	6
2.2.3. <i>Maximum Peak Spatial-Average SAR for Co-location RFID and Bluetooth</i> .....	7
<b>EXHIBIT 3. MEASUREMENTS, EXAMINATIONS &amp; TEST DATA .....</b>	<b>8</b>
3.1. TEST SETUP .....	8
3.2. PHOTOGRAPHS OF D.U.T. POSITION .....	9
3.2.1. <i>Body Configuration</i> .....	9
3.2.1.1. Top of DUT perpendicular to the phantom with spacing of 15 mm .....	9
<b>EXHIBIT 4. SAR MEASUREMENT .....</b>	<b>10</b>
4.1. BODY CONFIGURATION.....	10
4.1.1. <i>Body Worn</i> .....	10
4.1.1.1. Top of D.U.T. perpendicular to the phantom with spacing of 15 mm; #02 .....	11
<b>EXHIBIT 5. TISSUE DIELECTRIC PARAMETER CALIBRATION .....</b>	<b>12</b>
5.1. SIMULATED TISSUE AT 2450 MHZ .....	12
5.1.1. <i>2450 MHz Brain Tissue</i> .....	12
5.1.2. <i>2450 MHz Muscle Tissue</i> .....	12
<b>EXHIBIT 6. SAR SYSTEM CALIBRATION .....</b>	<b>13</b>
6.1. GENERAL INFORMATION OF THE PROBE .....	13
6.2. PROBE LINEARITY AND DYNAMIC RANGE .....	13
6.2.1. <i>Diode Compression Potential</i> .....	13
6.2.2. <i>Channel 1</i> .....	14
6.2.3. <i>Channel 2</i> .....	15
6.2.4. <i>Channel 3</i> .....	16
6.3. PROBE FREE SPACE CALIBRATION.....	17
6.3.1. <i>Calibration Setup at 2450 MHz</i> .....	17
6.3.2. <i>Amplifier Settings</i> .....	17
6.3.2.1. Freespace calibration at 2450 MHz .....	17
6.3.3. <i>Isotropic response</i> .....	18
6.4. CALCULABLE WAVEGUIDE CALIBRATION .....	19
6.4.1. <i>Calibration Setup</i> .....	19
6.4.1.1. Setup for 2400 MHz .....	19

**ULTRATECH GROUP OF LABS**

**File #: TEK-596-SAR  
July 16, 2007**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.4.2.	<i>Simulated Tissue</i> .....	20
6.4.2.1.	Brain Tissue at 2400 MHz .....	20
6.4.2.2.	Muscle Tissue at 2400 MHz .....	20
6.4.3.	<i>Conversion Factor</i> .....	21
6.4.3.1.	Calculable waveguide calibration at 2400 MHz for simulated brain tissue .....	21
6.4.3.2.	Calculable waveguide calibration at 2400 MHz for simulated muscle tissue .....	22
<b>EXHIBIT 7.</b>	<b>SAR SYSTEM VERIFICATION</b> .....	<b>23</b>
7.1.	VERIFICATION SETUP.....	23
7.1.1.	<i>Test setup at 2450 MHz using the dipole reference</i> .....	23
7.2.	SIMULATED TISSUE .....	24
7.2.1.	<i>Simulated brain tissue at 2450 MHz</i> .....	24
7.3.	VERIFICATION RESULT.....	25
7.3.1.	<i>Reference SAR values for simulated brain tissue at 2450 MHz</i> .....	25
7.3.2.	<i>Verification result at 2450 MHz</i> .....	25

**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA )
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 1. PERFORMANCE ASSESSMENT

### 1.1. CLIENT AND MANUFACTURER INFORMATION

<b>APPLICANT:</b>	
<b>Name:</b>	Psion Teklogix Inc.
<b>Address:</b>	2100 Meadowvale Blvd. Mississauga, ON Canada, L5N 7J9
<b>Contact Person:</b>	Mr. Sada Dharwarkar Phone #: +1.905.812.6200 ext. 3358 Fax #: +1.905.812.6301 Email Address: <a href="mailto:Sada.dharwarkar@psionteklogix.com">Sada.dharwarkar@psionteklogix.com</a>

<b>MANUFACTURER:</b>	
<b>Name:</b>	Psion Teklogix Inc.
<b>Address:</b>	2100 Meadowvale Blvd. Mississauga, ON Canada, L5N 7J9
<b>Contact Person:</b>	Mr. Sada Dharwarkar Phone #: +1.905.812.6200 ext. 3358 Fax #: +1.905.812.6301 Email Address: <a href="mailto:Sada.dharwarkar@psionteklogix.com">Sada.dharwarkar@psionteklogix.com</a>

### 1.2. DEVICE UNDER TEST (D.U.T.) DESCRIPTION

The following is the information provided by the applicant.

<b>Trade Name</b>	Psion Teklogix WORKABOUT PRO
<b>Product Description</b>	Handheld Computer
<b>Type/Model Number</b>	7527S (BTL040 Bluetooth module)
<b>Frequency of Operation</b>	2402 ~ 2480 MHz
<b>Rated RF Output Power</b>	0.59 dBm conducted
<b>Modulation Employed</b>	Bluetooth
<b>Antenna</b>	Type: Chip antenna Frequency Range: 2400 – 2483.5 MHz Gain: 4.1 dBi
<b>Power Supply</b>	Lithium Ion Rechargeable 3000 mAh Battery (3.7 V), Psion Teklogix Model No.: WA3006
<b>Primary User Functions of D.U.T.</b>	Provide data communication link through air

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### **1.3. GENERAL TEST CONFIGURATIONS**

#### **1.3.1. Equipment Configuration**

Power and signal distribution, grounding, interconnecting cabling and physical placement of equipment of a test system shall simulate the typical application and usage in so far as is practicable, and shall be in accordance with the relevant product specifications of the manufacturer.

The configuration that tends to maximize the D.U.T.'s emission or minimize its immunity is not usually intuitively obvious and in most instances selection will involve some trial and error testing. For example, interface cables may be moved or equipment re-orientated during initial stages of testing and the effects on the results observed.

Only configurations within the range of positions likely to occur in normal use need to be considered.

The configuration selected shall be fully detailed and documented in the test report, together with the justification for selecting that particular configuration.

#### **1.3.2. Exercising Equipment**

The exercising equipment and other auxiliary equipment shall be sufficiently decoupled from the D.U.T. so that the performance of such equipment does not significantly influence the test results.


### **1.4. SPECIFIC OPERATING CONDITIONS**

N/A

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- *All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

### 1.5. BLOCK DIAGRAM OF TEST SETUP

The D.U.T. was configured as normal intended use. The following block diagram shows a representative equipment arrangement during tests:



### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 2. SUMMARY OF TEST RESULTS

### 2.1. LOCATION OF TESTS

All of the measurements described in this report were performed at UltraTech Group of Labs located at:

3000 Bristol Circle, in the city of Oakville, Province of Ontario, Canada.

All measurements were performed in UltraTech’s shielded chamber, 24’ x 16’ x 8’.

### 2.2. APPLICABILITY & SUMMARY OF SAR RESULTS

Co-location of RFID and Bluetooth module (M/N: BTL040) in the 7527S had been addressed in this test report.

Since RFID and Bluetooth operates at the different frequency range, SAR evaluation was performed independently for each frequency using appropriate probe calibration and tissue dielectric parameter in the identical device positioning condition. The worst case measurement result was summed to verify and confirm the compliance of RF exposure safety requirement.

#### 2.2.1. Maximum Peak Spatial-Average SAR for RFID

#	Configuration	Device Test Positions	Antenna Position	Freq. [MHz]	Channel	MAX. SAR <sub>1g</sub> [W/Kg]
*	General Population/Uncontrolled Exposure Category Limit					1.6
02	Top of DUT perpendicular to the phantom with spacing of 15 mm	Body	Integrated	915.25	Middle	0.53

#### 2.2.2. Maximum Peak Spatial-Average SAR for Bluetooth

#	Configuration	Device Test Positions	Antenna Position	Freq. [MHz]	Channel	MAX. SAR <sub>1g</sub> [W/Kg]
*	General Population/Uncontrolled Exposure Category Limit					1.6
02	Top of DUT perpendicular to the phantom with spacing of 15 mm	Body	Integrated	2441	39	< 0.01

### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

File #: **TEK-596-SAR**  
 July 16, 2007

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**SPECIFIC ABSORPTION RATE (SAR)**

IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 2) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

**WORKABOUT PRO G2 Handheld Computer M/N: 7527S**

**FCC ID: GM37527SBTMPR6XXX**

### 2.2.3. Maximum Peak Spatial-Average SAR for Co-location RFID and Bluetooth

(Maximum Peak Spatial-Average SAR for RFID) + (Maximum Peak Spatial-Average SAR for Bluetooth)

$$= 0.53 + (\text{less than } 0.01) = 0.53$$

The maximum peak spatial - average SAR measured was found to be less than 0.53 W/Kg.

Exposure Category and SAR Limits	Test Requirements	Compliance (Yes/No)
<p><b>General population/Uncontrolled exposure</b> 0.08W/kg whole body average and <b>spatial peak SAR of 1.6W/kg</b>, averaged over 1gram of tissue Hands, wrist, feet and ankles have a peak SAR not to exceed 4 W/kg, averaged over 10 grams of tissue.</p>	<p>Requirements using guidelines established in IEEE C95.1-1991</p> <p>FCC OET Bulletin 65 (Supplement C Edition 01-01)</p> <p>Industry Canada RSS-102 (Issue 2).</p> <p>ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)</p>	<p>YES</p>
<p><b>Occupational/Controlled Exposure</b> 0.4W/kg whole body average and <b>spatial peak SAR of 8W/kg</b>, averaged over 1gram of tissue Hands, wrist, feet and ankles have a peak SAR not to exceed 20 W/kg, averaged over 10 grams of tissue.</p>	<p>Requirements using guidelines established in IEEE C95.1-1991</p> <p>FCC OET Bulletin 65 (Supplement C Edition 01-01),</p> <p>Industry Canada RSS-102 (Issue 2)</p> <p>ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)</p>	<p>N/A</p>

## ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

File #: **TEK-596-SAR**  
July 16, 2007

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



## EXHIBIT 3. MEASUREMENTS, EXAMINATIONS & TEST DATA

### 3.1. TEST SETUP

D.U.T. Information		Condition	
Product Name	WORKABOUT PRO G2 Handheld Computer (Bluetooth module)	Robot Type	6 Axis
Model Number	7527S (BTL040)	Scan Type	SAR – Area/Zoom/Att Vs Depth
Serial Number	N/A	Measured Field	E
Operating Frequency [MHz]	2400 ~ 2483.5	Phantom Type	2 <sub>mm</sub> base Flat Phantom
Frequency Tested [MHz]	2402, 2441, 2480	Phantom Position	Waist
Measured RF Output Power [dBm]	0.59 dBm conducted	Room Temperature [°C]	21.0 ± 1
Antenna Type	Chip, Gain: 4.1 dBi	Room Humidity [%]	40 ± 10
Modulation	FHSS	Tissue Temperature [°C]	21.0 ± 1
Worst Case Duty Cycle	100 %		
Duty Cycle Tested	100 %		
Source(or Usage)-based time-average	1		

Type of Tissue	Brain	Muscle
Test Frequency [MHz]	2450	2450
Measured Dielectric Constant	37.8 (-3.5 %)	50.1 (-4.9 %)
Target Dielectric Constant	39.2	52.7
Measured Conductivity [S/m]	1.72 (-4.6 %)	1.90 (-2.7 %)
Target Conductivity [S/m]	1.80	1.95
Penetration Depth (Plane Wave Excitation) [mm]	19.3	20.0
Probe Model Number	ET20	ET20
Probe Serial Number	03JUN-0028	03JUN-0028
Probe Orientation	Isotropic	Isotropic
Probe Offset [mm]	2.00	2.00
Probe Tip Diameter [mm]	4.00	4.00
Sensor Factor ( $\eta_{pd}$ ) [mV/(mW/cm <sup>2</sup> )]	10.8	10.8
Conversion Factor ( $\gamma$ )	4.566	3.691
Sensitivity ( $\zeta$ ) [W/Kg/mV]	1.315E-01	1.797E-01

### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### **3.2. PHOTOGRAPHS OF D.U.T. POSITION**

#### **3.2.1. Body Configuration**

##### **3.2.1.1. Top of DUT perpendicular to the phantom with spacing of 15 mm**



### **ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 4. SAR MEASUREMENT

### 4.1. BODY CONFIGURATION\*

#### 4.1.1. Body Worn

#	Configuration	Antenna Position	Frequency [MHz]	Channel	SAR <sub>local</sub> Before [W/Kg]	SAR <sub>local</sub> After [W/Kg]	MAX SAR <sub>1g</sub> [W/Kg]
* General Population/Uncontrolled Exposure Category Limit							1.6
01	Top of DUT perpendicular to the phantom with spacing of 15 mm	Integrated	2402	00			-
02		Integrated	2441	39	0.00	0.00	Less than 0.01
03		Integrated	2480	78			-

\* If the SAR measured at the middle channel for each test configuration is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

File #: **TEK-596-SAR**  
 July 16, 2007

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**SPECIFIC ABSORPTION RATE (SAR)**


IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 2) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

**WORKABOUT PRO G2 Handheld Computer M/N: 7527S**

**FCC ID: GM37527SBTMPR6XXX**

**4.1.1.1. Top of D.U.T. perpendicular to the phantom with spacing of 15 mm; #02**

Test date [MM/DD/YYYY]	07/04/2007
Test by	Carolyn Luu
Room temperature [°C]	21
Room humidity [%]	40
Simulated tissue temperature [°C]	21
Separation distance, d [mm]	15
Test frequency [MHz]	2441
E-field Probe	M/N: ET20, S/N:03JUN-0028, Sensor Offset: 2.0 mm
Sensor Factor ( $\eta_{Pd}$ ) [mV/(mW/cm <sup>2</sup> )]	10.8
Amplifier Settings (AS <sub>1</sub> , AS <sub>2</sub> , AS <sub>3</sub> )	0.0051459143, 0.0051393192, 0.0049804511
Tissue Type	Muscle
Measured conductivity [S/m]	1.90 (-2.7 %)
Measured dielectric constant	50.1 (-4.9 %)
Conversion Factor ( $\gamma$ )	3.691
Sensitivity ( $\zeta$ ) [W/Kg/mV]	1.797E-01
Source-(or Usage-)Based Time-Average Factor	1.0
Measurement Area Specification (X × Y)	90 mm × 60 mm; Resolution: 15 mm × 15 mm
Measurement Volume Specification (X × Y × Z)	7 pt × 7 pt × 7 pt; Resolution: 5 mm × 5 mm × 5 mm.
SAR <sub>1g</sub> [W/Kg]	Less than 0.01



**ULTRATECH GROUP OF LABS**

File #: **TEK-596-SAR**  
July 16, 2007

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 5. TISSUE DIELECTRIC PARAMETER CALIBRATION

### 5.1. SIMULATED TISSUE AT 2450 MHZ

<b>Tissue calibration type</b>	HP Dielectric Strength Probe System (M/N: 85070C)	
<b>Tissue calibration date</b> [MM/DD/YYYY]	07/04/2007	07/04/2007
<b>Tissue calibrated by</b>	Carolyn Luu	Carolyn Luu
<b>Room temperature</b> [°C]	21	21
<b>Room humidity</b> [%]	40	40
<b>Simulated tissue temperature</b> [°C]	21	21
<b>Tissue calibration frequency</b> [MHz]	2450	2450
<b>Tissue Type</b>	Brain	Muscle
<b>Target conductivity</b> [S/m]	1.80	1.95
<b>Target dielectric constant</b>	39.2	52.7
<b>Composition (by weight)</b> [%]	DI Water (59.70 %) DGBE (4.76 %) Triton X-100 (35.54 %)	DI Water (76.19 %) DGBE (9.52 %) Triton X-100 (14.29 %)
<b>Measured conductivity</b> [S/m]	1.73 (-4.2 %)	1.90 (-2.7 %)
<b>Measured dielectric constant</b>	37.8 (-3.5 %)	50.1 (-4.9 %)
<b>Penetration depth (plane wave excitation)</b> [mm]	19.3	20.0

#### 5.1.1. 2450 MHz Brain Tissue

Frequency [GHz]	Meas. after 5min			DI Water at 20°C			Init. Meas.		
	$\epsilon'$	$\epsilon''$	$\sigma$ [S/m]	$\epsilon'$	$\epsilon''$	$\sigma$ [S/m]	$\epsilon'$	$\epsilon''$	$\sigma$ [S/m]
2433.000	37.8392	13.1018	1.69	78.5591	10.7699	1.46	37.8636	13.2124	1.69
2450.000	37.8410	13.1514	1.73	78.5327	10.8405	1.48	37.8610	13.2490	1.73
2466.000	37.8249	13.1696	1.74	78.5271	10.9094	1.51	37.8302	13.2520	1.74

#### 5.1.2. 2450 MHz Muscle Tissue

Frequency [GHz]	Meas. after 5min			DI Water at 20°C			Init. Meas.		
	$\epsilon'$	$\epsilon''$	$\sigma$ [S/m]	$\epsilon'$	$\epsilon''$	$\sigma$ [S/m]	$\epsilon'$	$\epsilon''$	$\sigma$ [S/m]
2433.000	50.1739	14.8039	1.86	78.6123	10.9442	1.47	50.0895	14.8292	1.86
2450.000	50.1004	14.8414	1.90	78.6123	10.9442	1.49	50.0895	14.8292	1.90
2466.000	50.0141	14.9252	1.97	78.5928	11.0144	1.51	50.0126	14.9089	1.97

### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

File #: **TEK-596-SAR**  
 July 16, 2007

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 6. SAR SYSTEM CALIBRATION

### 6.1. GENERAL INFORMATION OF THE PROBE

Probe Type	E-Field Triangle, Isotropic
Model Number	ET20
Serial Number	03JUN-0028
Manufacturer	EMF Safety
Manufactured Date	JUNE 2003
Probe Length [mm]	270
Probe offset [mm]	2.0
Probe Tip diameter [mm]	4.0
Sensor Factor ( $\eta_{Pd}$ ) [ $mV/(mW/cm^2)$ ]	10.8
Sensor Factor ( $\eta_{E2}$ ) [ $mV/(V/m)^2$ ]	10.8 / 3770


### 6.2. PROBE LINEARITY AND DYNAMIC RANGE

#### 6.2.1. Diode Compression Potential

DCP <sub>1</sub>	66459
DCP <sub>2</sub>	67796
DCP <sub>3</sub>	69561

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.2.2. Channel 1




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

File #: TEK-596-SAR  
July 16, 2007

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.2.3. Channel 2



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

File #: TEK-596-SAR  
July 16, 2007

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



**6.2.4. Channel 3**



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**6.3. PROBE FREE SPACE CALIBRATION**

**6.3.1. Calibration Setup at 2450 MHz**

<b>Calibration cell type</b>	Waveguide
<b>Model Number</b>	13492
<b>Serial Number</b>	12463-1, 12463-2
<b>Manufacturer</b>	APOLLO
<b>Input Power / Power Density</b> [mW/(mW/cm <sup>2</sup> )]	24.7


**6.3.2. Amplifier Settings**

**6.3.2.1. Freespace calibration at 2450 MHz**

<b>Calibration Date</b> [MM/DD/YYYY]	07/24/2006
<b>Calibrated by</b>	Carolyn Luu
<b>Calibration Frequency</b> [MHz]	2450
<b>Room Temperature</b> [°C]	21
<b>Room Humidity</b> [%]	40
<b>φ</b> [°]	90
<b>Φ<sub>1</sub>, Φ<sub>2</sub>, Φ<sub>3</sub></b> [°]	54.7, 54.7, 54.7
<b>Pd</b> [mW/cm <sup>2</sup> ]	2.0
<b>SUM(U<sub>L,1</sub>(0°), ... ,U<sub>L,1</sub>(360°))</b>	32,913
<b>SUM(U<sub>L,2</sub>(0°), ... ,U<sub>L,2</sub>(360°))</b>	32,956
<b>SUM(U<sub>L,3</sub>(0°), ... ,U<sub>L,3</sub>(360°))</b>	34,007
<b>R<sub>ISO,1,1</sub></b>	1.0000000000
<b>R<sub>ISO,2,1</sub></b>	0.9987183739
<b>R<sub>ISO,3,1</sub></b>	0.9678457172
<b>AS<sub>1</sub></b>	0.0051459143
<b>AS<sub>2</sub></b>	0.0051393192
<b>AS<sub>3</sub></b>	0.0049804511

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.3.3. Isotropic response



Isotropy at 2450 MHz: ±0.08 dB

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**6.4. CALCULABLE WAVEGUIDE CALIBRATION**

**6.4.1. Calibration Setup**

**6.4.1.1. Setup for 2400 MHz**

<b>Calibration type</b>	Calculable waveguide calibration
<b>Waveguide Manufacturer</b>	APOLLO
<b>Waveguide dimension (a x b) [mm]</b>	109.2 x 54.7
<b>Dielectric Separator thickness [mm]</b>	12.6
<b>Dielectric Separator permittivity</b>	5.0
<b>Return Loss (at test frequency) [dB]</b>	Better than -20



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**6.4.2. Simulated Tissue**

**6.4.2.1. Brain Tissue at 2400 MHz**

<b>Tissue calibration type</b>	HP Dielectric Strength Probe System
<b>Tissue calibration date</b> [MM/DD/YYYY]	07/26/2006
<b>Tissue calibrated by</b>	Carolyn Luu
<b>Room temperature</b> [°C]	21
<b>Room humidity</b> [%]	40
<b>Simulated tissue temperature</b> [°C]	21
<b>Tissue calibration frequency</b> [MHz]	2400
<b>Tissue Type</b>	Brain
<b>Target conductivity</b> [S/m]	1.76
<b>Target dielectric constant</b>	39.3
<b>Measured conductivity</b> [S/m]	1.80 (+2.3 %)
<b>Measured dielectric constant</b>	39.1 (-0.5 %)
<b>Penetration depth (plane wave excitation)</b> [mm]	18.7

**6.4.2.2. Muscle Tissue at 2400 MHz**

<b>Tissue calibration type</b>	HP Dielectric Strength Probe System
<b>Tissue calibration date</b> [MM/DD/YYYY]	07/26/2006
<b>Tissue calibrated by</b>	JaeWook Choi
<b>Room temperature</b> [°C]	21
<b>Room humidity</b> [%]	40
<b>Simulated tissue temperature</b> [°C]	21
<b>Tissue calibration frequency</b> [MHz]	2400
<b>Tissue Type</b>	Muscle
<b>Target conductivity</b> [S/m]	1.90
<b>Target dielectric constant</b>	52.8
<b>Measured conductivity</b> [S/m]	1.97 (+3.7 %)
<b>Measured dielectric constant</b>	50.4 (-4.5 %)
<b>Penetration depth (plane wave excitation)</b> [mm]	19.3

**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com


**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**6.4.3. Conversion Factor**

**6.4.3.1. Calculable waveguide calibration at 2400 MHz for simulated brain tissue**

Calibration Date [MM/DD/YYYY]	07/26/2006
Calibration by	Carolyn Luu
Calibration Frequency [MHz]	2400
Room Temperature [°C]	21
Room Humidity [%]	40
Simulated Tissue Temperature [°C]	21
Input Power [mW]	204.80
Waveguide dimension (a × b) [mm]	0.1092 × 0.0547
Penetration Depth $\delta$ [m]	0.0186
Conversion Factor ( $\gamma$ )	4.566



**ULTRATECH GROUP OF LABS**


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

File #: TEK-596-SAR  
 July 16, 2007

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**6.4.3.2. Calculable waveguide calibration at 2400 MHz for simulated muscle tissue**

<b>Calibration Date</b> [MM/DD/YYYY]	07/26/2006
<b>Calibration by</b>	Carolyn Luu
<b>Calibration Frequency</b> [MHz]	2400
<b>Room Temperature</b> [°C]	21
<b>Room Humidity</b> [%]	40
<b>Simulated Tissue Temperature</b> [°C]	21
<b>Input Power</b> [mW]	212.73
<b>Waveguide dimension (a × b)</b> [mm]	0.1092 × 0.0547
<b>Penetration Depth <math>\delta</math></b> [m]	0.0191
<b>Conversion Factor (<math>\gamma</math>)</b>	3.691



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

File #: **TEK-596-SAR**  
 July 16, 2007


- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 7. SAR SYSTEM VERIFICATION

### 7.1. VERIFICATION SETUP

#### 7.1.1. Test setup at 2450 MHz using the dipole reference

<b>Flat phantom dimension (W × L × H) [mm]</b>	420 × 700 × 200
<b>Flat phantom shell thickness (d<sub>3</sub>) [mm]</b>	2.0
<b>Flat phantom shell permittivity</b>	2.98
<b>Reference dipole dimension (L × h × d) [mm]</b>	51.7 × 30.4 × 3.6
<b>Dipole-to-Phantom (d<sub>2</sub>) [mm]</b>	8.0
<b>Dipole-to-Liquid (d<sub>2</sub> + d<sub>3</sub>) [mm]</b>	10.0 (8.0 + 2.0)
<b>Return Loss (at test frequency) [dB]</b>	-20.0



### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



## 7.2. SIMULATED TISSUE

### 7.2.1. Simulated brain tissue at 2450 MHz

<b>Tissue calibration type</b>	HP Dielectric Strength Probe System
<b>Tissue calibration date</b> [MM/DD/YYYY]	07/04/2007
<b>Tissue calibrated by</b>	Carolyn Luu
<b>Room temperature</b> [°C]	21
<b>Room humidity</b> [%]	40
<b>Simulated tissue temperature</b> [°C]	21
<b>Tissue calibration frequency</b> [MHz]	2450
<b>Tissue Type</b>	Brain
<b>Target conductivity</b> [S/m]	1.80
<b>Target dielectric constant</b>	39.2
<b>Measured conductivity</b> [S/m]	1.73 (-4.2 %)
<b>Measured dielectric constant</b>	38.3 (-2.6 %)
<b>Penetration depth (plane wave excitation)</b> [mm]	19.3

## ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**7.3. VERIFICATION RESULT**

**7.3.1. Reference SAR values for simulated brain tissue at 2450 MHz\***

<b>Reference SAR<sub>Ig</sub></b> [W/Kg]	52.4
<b>Reference SAR<sub>s</sub></b> [W/Kg]	104.2
<b>Measured SAR<sub>Ig</sub></b> [W/Kg]	54.02
<b>Measured SAR<sub>s</sub></b> [W/Kg]	105.64

**7.3.2. Verification result at 2450 MHz**

<b>Test date</b> [MM/DD/YYYY]	07/04/2007
<b>Test by</b>	Carolyn Luu
<b>Room temperature</b> [°C]	21
<b>Room humidity</b> [%]	40
<b>Simulated tissue temperature</b> [°C]	21
<b>Test frequency</b> [MHz]	2450
<b>E-field Probe</b>	M/N: ET20, S/N: 03JUN-0028, Sensor Offset: 2.0 mm
<b>Sensor Factor (<math>\eta_{Pd}</math>)</b> [mV/(mW/cm <sup>2</sup> )]	10.8
<b>Amplifier Settings (AS<sub>1</sub>, AS<sub>2</sub>, AS<sub>3</sub>)</b>	0.0051459143, 0.0051393192, 0.0049804511
<b>Tissue Type</b>	Brain
<b>Measured conductivity</b> [S/m]	1.73 (-4.2 %)
<b>Measured dielectric constant</b>	37.8 (-3.5 %)
<b>Conversion Factor (<math>\gamma</math>)</b>	4.566
<b>Sensitivity (<math>\zeta</math>)</b> [W/Kg/mV]	1.315E-01
<b>Power</b> [mW]	500
<b>Measurement Volume Specification (X × Y × Z)</b>	7 <sub>pts</sub> × 7 <sub>pts</sub> × 7 <sub>pts</sub> , 30 <sub>mm</sub> × 30 <sub>mm</sub> × 30 <sub>mm</sub> ; Resolution: 5 <sub>mm</sub> × 5 <sub>mm</sub> × 5 <sub>mm</sub>
<b>SAR<sub>Ig</sub></b> [W/Kg]	27.01
<b>SAR<sub>s</sub></b> [W/Kg]	52.82

\* All SAR values in 7.3.1 are normalized to a forward power of 1 W.


- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**SPECIFIC ABSORPTION RATE (SAR)**

IEEE C95.1-1991, FCC OET Bulletin 65 (Supplement C), Industry Canada RSS-102(Issue 2) and ACA Radiocommunications (Electromagnetic Radiation – Human Exposure) Amendment Standard 2000 (No. 1)

**WORKABOUT PRO G2 Handheld Computer M/N: 7527S**

FCC ID: GM37527SBTMPR6XXX




**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

File #: TEK-596-SAR

July 16, 2007

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)




**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: http://www.ultratech-labs.com

**File #: TEK-596-SAR**  
**July 16, 2007**

- Assessed by ITI (UK) Competent Body, NVLAP (USA) Accreditation Body & ACA/AUSTEL (Australia), VCCI (Japan)
- Accredited by Industry Canada (Canada) under ACC-LAB (Europe/Canada MRA and APEC/Canada MRA)
- Recognized/Listed by FCC (USA)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)