



Psion
Parc de la Duranne
135 Rue René Descartes
BP 421000
13591 Aix en Provence Cedex 3
France
www.pSIONteklogix.com
Phone +33 (0)442 908 809
Fax +33 (0)442 908 88

07 April 2011

Timco Engineering, Inc.
849 NW State Road 45
P.O. Box 370
Newberry, Florida 32669

Re.: Acknowledgment of FCC Modular approval requirements

FCC ID: GM3HFAM1XT10

To Whom It May Concern:

The RFID Module HF-AM1-OMNII includes only 3 parts: The Multi ISO Reader, the interface board and one **permanently** attached antenna board. The HF Multi ISO Reader is a complete read/write radio transmitter with its buffered /modulation data input. The antenna is designed as a rectangle loop of 4 turns and his dimension are about 20X45 mm. The matching circuit is located on the interface Board. This module is only mounted in a dedicated generic pod and plugged on the 7545 terminal via an expansion port. The RFID Module HF-AM1-OMNII only uses the serial interface and the 5V power supply.

Modular approval requirement	Yes	No
i) The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly;		✓
ii) The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal;	✓	
iii) The module must contain power supply regulation on the module;		✓
iv) The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b);	✓	
v) The module must demonstrate compliance in a stand-alone configuration;	✓	
vi) The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labelling requirements);	✓	
vii) The module must comply with all specific rules applicable to the transmitter. The grantee must provide comprehensive instructions to explain compliance requirements;	✓	
viii) The module must comply with RF exposure requirements. For any transmitters intended for use in portable devices, SAR compliance must be demonstrated to be independent of the host device. See KDB Publication 447498 as a guide to determine if a transmitter can be tested without being limited to a host device. If SAR compliance can only be demonstrated in specific host types or platforms, then the module type must be "limited."	✓	

- i. The radio elements of OEM multi ISO aren't directly overlaid by a metal cover. The RFID module HF-AM 1-OMNII is plugged directly to the back of terminal using 4 screws.
- iii. The power supply regulation is provided directly by the 7545 terminal.

Sincerely,
Nicolas FORNIER
Psion