



RT041-09-100754-1A - OH / CHB

## TECHNICAL REPORT

Equipment under test:

**WORKABOUT PRO (7527C)  
+ WA9005 + BT + RA2041  
+ RFID Module UHF-CA3-A5  
FCC ID:GM3UHFCA3A5  
IC ID: 2739D-UHFCA3A5**


Company:

**PSION TEKLOGIX**

Diffusion: Mr BONNEFOY

(Company: PSION TEKLOGIX)

Number of pages: 6 without annex

Ed.	Date	Modified page(s)	Written by		Technical verification Quality approval	
			Name	Visa	Name	Visa
1	19-March-09	Creation	Régis GONZALEZ		Olivier HEYER	

*Duplication of this report is only permitted for an integral photographic facsimile. It includes the number of pages referenced above. This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole production of the item tested.*



*NAME OF THE EQUIPMENT UNDER TEST (E.U.T.)* : WORKABOUT PRO (7527C) + WA9005 +  
BT + RA2041 + RFID Module UHF-CA3-A5

*Serial number* : None

*Part number* : None

*Software Version* : None

*MANUFACTURER'S NAME* : PSION TEKLOGIX

*APPLICANT'S ADRESS:*

*Company* : PSION TEKLOGIX

*Adress* : 135 rue de la Duranne  
BP 421000  
13591 AIX EN PROVENCE CEDEX 3  
FRANCE

*Responsible* : Mr BONNEFOY

*DATE(S) OF STUDY* : March, the 16<sup>th</sup> of 2009

*EXPERT'S NAME* : Olivier HEYER

<b>CONTENTS</b>
-----------------

1. <i>INTRODUCTION</i> .....	4
2. <i>REFERENCE DOCUMENT(S)</i> .....	4
3. <i>EQUIPMENT UNDER TEST CONFIGURATION</i> .....	4
4. <i>RADIATED MEASUREMENTS</i> .....	5
5. <i>MAXIMUM PERMISSIBLE EXPOSURE CALCULATIONS</i> .....	5
6. <i>MAXIMUM PERMISSIBLE EXPOSURE LIMITS</i> .....	6
7. <i>MAXIMUM PERMISSIBLE EXPOSURE ESTIMATION</i> .....	6

### 1. INTRODUCTION

This document submits the results of Maximum Permissible Exposure (MPE) calculations performed on the equipment **WORKABOUT PRO (7527C) + WA9005 + BT + RA2041 + RFID Module UHF-CA3-A5**

### 2. REFERENCE DOCUMENT(S)

<b>Radio test report</b>	RC-032-GTC-09-100663-1-A Ed.0 from EMITECH Ile de France Laboratory
<b>OET Bulletin 65 (Aug 1997)</b>	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields
<b>FCC Part 1</b>	Practice and procedure
<b>RSS 210 Issue 7</b>	Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

### 3. EQUIPMENT UNDER TEST CONFIGURATION

<b><u>Product description:</u></b>	FCC ID: GM3UHFCA3A5 IC ID: 2739D-UHFCA3A5 Utilization: RFID TAG reader Antenna type: Incorporated antenna Antenna gain: Unknown Operating frequency range: 902MHz (Rfid), 2402MHz (Bluetooth), 2462MHz (Wifi) Power source: 5 Vdc (stand alone) or mains voltage (with docking) Power level and frequency range are not user adjustable
------------------------------------	--

#### 4. RADIATED MEASUREMENTS

These results come from EMITECH Ile de France radio test report RC-032-GTC-09-100663-1-A Ed.0. Please find below carrier radiated field strength (detail in test report):

**Measuring distance:** 3 m on Open Aera Test Site

##### Wifi radiated field strength:

Frequency (MHz)	Polarization	Measure (dB $\mu$ V/m)
2462.00	Vertical	101.00
2462.00	Horizontal	101.00

##### Bluetooth radiated field strength:

Frequency (MHz)	Polarization	Measure (dB $\mu$ V/m)
2402.00	Vertical	92.86
2402.00	Horizontal	85.80

#### 5. MAXIMUM PERMISSIBLE EXPOSURE CALCULATIONS

Equipment Under Test is always held farer than 20 cm from the body. Then we have estimate the power density at this distance using OET Bulletin 65 (Aug 1997).

For Wifi and Bluetooth:  $S = \frac{E^2}{3770}$  (1) of OET65

With S = power density (mW/cm<sup>2</sup>)  
E = electric field strength (V/m)

When E is measured at 3m, level in dB $\mu$ V/m must be increased by 23.52 dB when it is considered as far electric field ("plane wave" conditions) to be estimated at 20cm.

For information 1/d<sup>2</sup> propagation law results are specified (47.04 dB is then added)

## 6. MAXIMUM PERMISSIBLE EXPOSURE LIMITS

The limit for MPE estimation is (general population / uncontrolled exposure):

Frequency (MHz)	Limit for MPE (Power density in mW/cm <sup>2</sup> )
2402.00	1
2462.00	1

Combination of MPE must show that  $\sum (MPE/limit)$  is  $< 1$

## 7. MAXIMUM PERMISSIBLE EXPOSURE ESTIMATION

Using equations in §5, we can find following results:

### Wifi:

Frequency (MHz)	Polarization	MPE Calculation (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2462.00	Vertical	$7.51 \cdot 10^{-4}$	1
2462.00	Horizontal	$7.51 \cdot 10^{-4}$	1

For information using  $1/d^2$  propagation

Frequency (MHz)	Polarization	MPE Calculation (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2437.00	Vertical	0.17	1
2437.00	Horizontal	0.17	1

### Bluetooth:

Frequency (MHz)	Polarization	MPE Calculation (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2402.00	Vertical	$11.53 \cdot 10^{-5}$	1
2402.00	Horizontal	$2.27 \cdot 10^{-5}$	1

For information using  $1/d^2$  propagation

Frequency (MHz)	Polarization	MPE Calculation (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2402.00	Vertical	$10.00 \cdot 10^{-3}$	1
2402.00	Horizontal	$5.10 \cdot 10^{-3}$	1

### Maximum permissive exposure compared to limits

Polarization	$\sum MPE / Limit$	Limit
Vertical	$8.66 \cdot 10^{-4}$	1
Horizontal	$7.73 \cdot 10^{-4}$	1

□□□ End of report □□□