



R051-24-10-100197-2/A Ed. 0

<p>RADIO test report</p> <p>according to standard: FCC PART 15.247</p> <p>Equipment under test: INTEGRATED UHF RFID READER</p> <p>Company: PSION TEKLOGIX</p>
--

DISTRIBUTION: Mr BARRY

Company: PSION TEKLOGIX

Number of pages: 24 including 3 annexes

Ed.	Date	Modified pages	Written by		Technical Verification Quality Approval	
			Name	Visa	Name	Visa
0	16-Mar-10	Creation	L. BERTHAUD	LB		

Duplication of this document is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above.
 This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole manufactured products of the tested sample.



PRODUCT: INTEGRATED UHF RFID READER

Reference / model: UHF-CA3-AC5-GPRS

Serial number: not communicated

MANUFACTURER: PSION TEKLOGIX

COMPANY SUBMITTING THE PRODUCT:

Company: PSION TEKLOGIX

Address: 135 rue René Descartes
Parc de la Duranne
13591 AIX EN PROVENCE
FRANCE

Responsible: Mr BARRY

DATE(S) OF TEST: 09, 10 and 11 February 2010

TESTING LOCATION: EMITECH ATLANTIQUE laboratory at ANGERS (49) FRANCE
EMITECH ATLANTIQUE open area test site in LA POUEZE (49)
FRANCE
FCC Registration Number: 101696/FRN: 0006 6490 08

TESTED BY: L. BERTHAUD

CONTENTS

TITLE	PAGE
1. INTRODUCTION	4
2. PRODUCT DESCRIPTION	4
3. NORMATIVE REFERENCE	5
4. TEST METHODOLOGY	5
5. ADD ATTACHMENTS FILES	5
6. TESTS AND CONCLUSIONS	6
6.1 intentional radiator (subpart C)	6
6.2 unintentional radiator (subpart B)	7
7. RADIATED EMISSION LIMITS	8
8. MAXIMUM PEAK OUTPUT POWER	10
9. INTENTIONAL RADIATOR	12
10. BAND EDGE COMPLIANCE	14
CURVE N°: 1.....	15
CURVE N°: 2.....	16
CURVE N°: 3.....	17
CURVE N°: 4.....	18
ANNEX 1: PHOTOS OF THE EQUIPMENT UNDER TEST	19
ANNEX 2: TEST SET UP	21
ANNEX 3: OCCUPIED POWER BANDWIDTH	22

1. INTRODUCTION

This document presents the result of RADIO test carried out on the following equipment: INTEGRATED UHF RFID READER in accordance with normative reference.

2. PRODUCT DESCRIPTION

ITU Emission code: 500 KF7D

Class: B (residential environment)

Utilization: RFID reader

Antenna type: incorporated antenna

Operating frequency range: from 902.75 MHz to 927.25 MHz

Number of channels: 50

Channel spacing: 500 kHz

Frequency generation: SAW Resonator Crystal Synthesizer

Modulation: Amplitude Digital Frequency Phase

Power source: 115 Va.c charging dock + 3.7 Vd.c internal battery.

Power level, frequency range and channels characteristics are not user adjustable.

The details pictures of the product and the circuit boards are joined with this file.

3. NORMATIVE REFERENCE

The standards and testing methods related throughout this report are those listed below. They are applied on the whole test report even though the extensions (version, date and amendment) are not repeated.

FCC Part 15 (2008)	Code of Federal Regulations Title 47 – Telecommunication Chapter 1 – Federal Communications Commission Part 15 – Radio frequency devices Subpart C – Intentional Radiators
ANSI C63.10 (2009)	Methods of Measurement of Radio-Noise Emissions from Low-voltage Electrical and Electronics Equipment in the range of 9 kHz to 40 GHz.
Public Notice DA 00-705	Filing and Measurement Guideline for Frequency Hopping Spread Spectrum Systems.

4. TEST METHODOLOGY

Radio performance tests procedures given in part 15:

- Paragraph 33: frequency range of radiated measurements
- Paragraph 35: measurement detector functions and bandwidths
- Paragraph 107: conducted limits
- Paragraph 109: radiated emission limits
- Paragraph 111: antenna power conducted limits for receivers
- Paragraph 203: antenna requirement
- Paragraph 205: restricted bands of operation
- Paragraph 207: conducted limits
- Paragraph 209: radiated emission limits; general requirements
- Paragraph 247: operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz

5. ADD ATTACHMENTS FILES

- “Synoptic “***
- “Block diagram “***
- “External photos and Product labeling “***
- “Assembly of components “***
- “Internal photos “***
- “Layout pcb “***
- “Bil of materials “***
- “Schematics “***
- “Product description “***
- “User guide “***

6. TESTS AND CONCLUSIONS

6.1 intentional radiator (subpart C)

Test procedure	Description of test	Respected criteria?				Comment
		Yes	No	NAP	NAs	
FCC Part 15.203	ANTENNA REQUIREMENT	X				<i>Note 1</i>
FCC Part 15.205	RESTRICTED BANDS OF OPERATION	X				
FCC Part 15.207	CONDUCTED LIMITS				X	<i>Note 1</i>
FCC Part 15.209	RADIATED EMISSION LIMITS; general requirements	X				<i>Note 2</i>
FCC Part 15.247	OPERATION WITHIN THE BAND 902-928 MHZ, 2400-2483.5 MHz and 5725-5850 MHz					
	(a) (1) <i>hopping systems</i>				X	
	(a) (1) (i) 902 – 928 MHz				X	
	(a) (1) (ii) 5725 – 5850 MHz			X		
	(a) (1) (iii) 2400 – 2483.5 MHz			X		
	(a) (2) <i>digital modulation techniques</i>			X		
	(b) <i>maximum peak output power</i>	X				<i>Note 3</i>
	(c) <i>operation with directional antenna gains > 6 dBi</i>			X		
	(d) <i>intentional radiator</i>	X				
	(e) <i>peak power spectral density</i>			X		
	(f) <i>hybrid system</i>			X		
	(g)				X	
	(h)				X	
	(i) <i>RF exposure compliance</i>	X				<i>Note 4</i>
DA 00-705	BAND EDGE COMPLIANCE	X				

NAP: Not Applicable

NAs: Not Asked

Note 1: incorporated antenna.

Note 2: see FCC part 15.247 (d).

Note 3: conducted measurement is not possible (integral antenna), so we used the radiated method in open field.

Note 4: this type of equipment uses less than 0.5 W of output power with a high signal transmitting duty factor (section 3 from Oet 65c).

6.2 unintentional radiator (subpart B)

Test procedure	Description of test	Respected criteria?				Comment
		Yes	No	NAp	NAs	
FCC Part 15.107	CONDUCTED LIMITS				X	
FCC Part 15.109	RADIATED EMISSION LIMITS	X				
FCC Part 15.111	ANTENNA POWER CONDUCTED LIMITS FOR RECEIVER			X		

NAp: Not Applicable

NAs: Not Asked

7. RADIATED EMISSION LIMITS

Standard: FCC Part 15

Test procedure: paragraph 109

Limit class: Class B

Standard deviation: For $F > 1\text{GHz}$, the measurement is carried out at 3 m, instead of 10 m

Test equipments:

TYPE	BRAND	EMITECH NUMBER
Test receiver	Rohde & Schwarz ESVS 10	1219
Biconical antenna	Hewlett Packard 11966 C	728
Log periodic antenna	Rohde & Schwarz HL 223	1999
Double ridged guide antenna	Electrometrics EM 6961	1204
Spectrum analyzer	Rohde & Schwarz FSP40	4088
Open area test site	EMITECH	1274
Preamplifier 1 to 18 GHz	DBS Microwave DB97-1852	2648
High pass filter	Micro-tronics HPM11630	1673
Variac	Dereix R213	1419

Test set up:

The system is tested in an open area test site (OATS).

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuths correspond to the front of the equipment under test.

Frequency range: The highest frequency generated in the device is $f = 927.25\text{ MHz}$
According § 15.33 of the FCC Part 15 standard, the frequency range measured is indicated in the following table:

For unintentional radiator, including a digital device (Sec.15.33, §(b)(1) of the FCC Part 15 standard) :

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Detection mode: Quasi-peak (F < 1 GHz)
Average (F > 1 GHz)

Bandwidth: 120 kHz (F < 1 GHz)
1 MHz (F > 1 GHz)

Distance of antenna: 3 meters

Antenna height: 1 to 4 meters

Antenna polarization: vertical and horizontal (only the highest level is recorded)

Equipment under test operating condition:

The equipment is blocked in continuous reception mode.

Results:

Ambient temperature (°C):	18.5
Relative humidity (%):	48

Power source: 115 V.a.c through a variac + internal battery in charging mode.

Not any spurious has been detected.

Note: any spurious which has more than 20 dB of margin compared to the applicable limit is not necessarily reported.

Test conclusion:

RESPECTED STANDARD

8. MAXIMUM PEAK OUTPUT POWER

Standard: FCC Part 15

Test procedure: paragraph 15.247

Test equipments:

TYPE	BRAND	EMITECH NUMBER
Open site	EMITECH	1274
Power source E3610A	Hewlett Packard	4195
Multimeter 77-2	Fluke	0812
Meteo station	Oregon scientific	1539
Test receiver	Rohde & Schwarz ESVS10	1219
Log periodic antenna	Rohde & Schwarz HL223	1999
Variac	Dereix R213	1419

Test set up:

The system is tested in an open area test site (OATS).

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

We use for this measure outdoor test site. The measuring distance between the equipment and the test antenna is 3 m. The test antenna has been oriented in the two polarizations, we have recorded only the highest level.

A measurement of the electro-magnetic field is realized, with a resolution bandwidth of 120 kHz (detector quasi-peak).

Distance of antenna: 3 meters

Antenna height: 1 to 4 meters

Antenna polarization: vertical and horizontal

Equipment under test operating condition:

The equipment under test is blocked in continuous transmission mode, modulated by internal data signal, at the highest output power level which the transmitter is intended to operate.

Results:

Ambient temperature (°C): 18
Relative humidity (%): 46

Power source: 115 Va.c through a variac + internal battery in charging mode.

Sample n° 1 Low channel (902.75 MHz)

	Electro-magnetic field (dBμV/m):	P* (mW)	Limit (mW)
Normal test conditions	120.7	213.6	1000

Polarization of test antenna: horizontal (height: 300 cm)
Position of equipment: use position (azimuth: 165 degrees)

Sample n° 1 middle channel (915.25 MHz)

	Electro-magnetic field (dBμV/m):	P* (mW)	Limit (mW)
Normal test conditions	121.2	239.7	1000

Polarization of test antenna: horizontal (height: 300 cm)
Position of equipment: use position (azimuth: 170 degrees)

Sample n° 1 high channel (927.25 MHz)

	Electro-magnetic field (dBμV/m):	P* (mW)	Limit (mW)
Normal test conditions	122.1	294.9	1000

Polarization of test antenna: horizontal (height: 300 cm)
Position of equipment: use position (azimuth: 165 degrees)

* $P = (E \times d)^2 / (30 \times G_p)$ with $d = 3$ m and $G_p = 1.65$

Test conclusion:

RESPECTED STANDARD

9. INTENTIONAL RADIATOR

Standard: FCC Part 15

Test procedure: paragraph 15.205
 paragraph 15.209
 paragraph 15.247

Test equipments:

TYPE	BRAND	EMITECH NUMBER
Test receiver ESH3	Rohde & Schwarz	1058
Test receiver ESVS 10	Rohde & Schwarz	1219
Spectrum analyzer FSP 40	Rohde & Schwarz	4088
Loop antenna	EMCO	1406
Biconical antenna HP 11966C	Hewlett Packard	728
Log periodic antenna HL 223	Rohde & Schwarz	1999
Open site	Emitech	1274
Antenna RGA-60	Electrometrics	1204
Low-noise amplifier 2 to 18 GHz	Microwave DB	1922
High pass filter HP12/3200-5AA	Filtek	
Antenna WR42	IMC	1939
Low-noise amplifier 18 to 26 GHz	ALC	3036
Multimeter 77-2	Fluke	0812
Meteo station AB 888	Oregon scientific	1539
Variac R213	Dereix	1419

Test set up:

The system is tested in an open area test site (OATS).

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

Frequency range: from 9 kHz to harmonic 10 ($F_{\text{carrier}} \leq 10 \text{ GHz}$)

Bandwidth: 120 kHz ($F < 1 \text{ GHz}$) or 100 kHz, following 15.205 or 15.247
 1 MHz ($F > 1 \text{ GHz}$) or 100 kHz, following 15.205 or 15.247

Distance of antenna: between 30 m and 3 m according the frequencies and the limits.

Antenna height: 1 to 4 meters

Antenna polarization: vertical and horizontal, only the highest level is recorded.

Equipment under test operating condition:

The equipment under test is blocked in continuous transmission mode, modulated by internal data signal, at the highest output power level which the transmitter is intended to operate.

Results:

Ambient temperature (°C): 18.5
 Relative humidity (%): 48

Power source: 115 Va.c through a variac + internal battery in charging mode.

The polarity column refers to the antenna polarity at which the maximum emissions level is measured.

Low channel (902.75 MHz)

FREQUENCIES (MHz)	Detector P: Peak QP: Quasi-Peak Av: Average	Antenna height (cm)	Azimuth (degree)	resolution bandwidth (kHz)	Polarization H: Horizontal V: Vertical	Field strength (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
1805.5	P	155	225	100	V	74.6	102.1	27.5
2708.25	P	180	170	1000	V	53.3	74*	20.7
3611	P	175	200	1000	V	45	74*	29

Middle channel (915.25 MHz)

FREQUENCIES (MHz)	Detector P: Peak QP: Quasi-Peak Av: Average	Antenna height (cm)	Azimuth (degree)	resolution bandwidth (kHz)	Polarization H: Horizontal V: Vertical	Field strength (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
1830.5	P	160	220	100	V	74.1	102.1	28
2745.75	P	175	170	1000	V	53	74*	21
3661	P	170	205	1000	V	44.5	74*	29.5

High channel (927.25 MHz)

FREQUENCIES (MHz)	Detector P: Peak QP: Quasi-Peak Av: Average	Antenna height (cm)	Azimuth (degree)	resolution bandwidth (kHz)	Polarization H: Horizontal V: Vertical	Field strength (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
1854.5	P	160	220	100	V	74.8	102.1	27.3
2781.75	P	180	175	1000	V	53	74*	21
3709	P	175	205	1000	V	44.8	74*	29.2

* restricted bands of operation in 15.205, this limit corresponding at the 15.209 section. The peak levels measured are below the average measurements limit (54 dB μ V/m).

Note: any spurious which has more than 20 dB of margin compared to the applicable limit is not necessarily reported.

Applicable limits: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

The highest level recorded in a 100 kHz bandwidth is 122.1 dB μ V/m on high channel (927.25 MHz).

So the applicable limit is 102.1 dB μ V/m.

In addition, radiated emissions which fall in the restricted band, as defined in section 15.205 (a), must also comply with the radiated emission limits specified in section 15.209 (a) (see section 15.205 (c)).

Test conclusion:

RESPECTED STANDARD

10. BAND EDGE COMPLIANCE

Standard: FCC Part 15.247

Test procedure: Public Notice DA 00-705, Delta Marker method

Test equipments:

TYPE	MANUFACTURER	EMITECH NUMBER
Spectrum analyzer FSP 40	Rohde & Schwarz	4088
Multimeter 77-2	fluke	0812
Variac R213	Dereix	1419

Test set up:

Test realized in near field. All field strength measurements are correlated with the radiated maximum peak output power

Test operating condition of the equipment:

The equipment is blocked in frequency hopping mode.

Results:

Lower Band Edge: from 900 MHz to 902 MHz (curves n°1 and 2)

Upper Band Edge: from 928 MHz to 930 Mhz (curve n°3 and 4)

Sample n°1:

Fundamental frequency (MHz)	Field Strength Level of fundamental (dBµV/m)	Detector (Peak or Average)	Frequency of maximum Band-edges Emission (MHz)	Delta Marker (dB)*	Calculated Max Out of Band Emission Level (dBµV/m)**	Limit (dBµV/m)	Margin (dB)
902.75	120.7	Peak	901.98	-54.45	66.25	74	7.75
902.75	108.5	Average	901.05	-58.93	49.57	54	4.43
927.25	122.1	Peak	928.04	-55.16	66.94	74	7.06
927.25	109.8	Average	929.44	-56.58	53.22	54	0.78


* according to step 2 of Marker-Delta Method DA 00-705.

** according to step 3 of Marker-Delta Method:

$$\text{Calculated Emission Level} = \text{Field Strength Level} - \text{Delta Marker Level}$$


(1) the peak level is lower than the average limit (53.98 dBµV/m).

CURVE N°: 1.




Date: 11.FEB.2010 11:33:03

CURVE N°: 2.




Date: 11.FEB.2010 11:36:06

CURVE N°: 3.



Date: 11.FEB.2010 11:41:31

CURVE N°: 4.



Date: 11.FEB.2010 11:53:49

Test conclusion:

RESPECTED STANDARD


□□□ End of report, 3 annexes to be forwarded □□□

ANNEX 1: PHOTOS OF THE EQUIPMENT UNDER TEST

GENERAL VIEW




CHARGING DOCK



PDA



INTERNAL VIEW




ANNEX 2: TEST SET UP


RADIATED MEASUREMENTS




ANNEX 3: OCCUPIED POWER BANDWIDTH



Date: 11.FEB.2010 12:00:47



Date: 11.FEB.2010 11:59:17



Date: 11.FEB.2010 11:58:07