

**NOKIA**

NOKIA MOBILE PHONES

6000 Connection Drive

Irving, TX 75039

972 894 5000

972 894 4988

10 January, 2003


Federal Communications Commission,  
Authorization Et Evaluation Division,  
7435 Oakland Mills Road  
Columbia, MD. 21046

Attention: Equipment Authorization Branch

We hereby certify that the transceiver FCC ID: GMLNPM-10 complies with ANSI/IEEE C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

Compliance was determined by testing appropriate parameters according to standard.

NOKIA MOBILE PHONES

A handwritten signature in black ink, appearing to read 'Mike Linstrom', written in a cursive style.

Mike Linstrom  
Product Program Manager, Dallas

## • CERTIFICATION INFORMATION (SAR)

THIS MODEL PHONE MEETS THE GOVERNMENT'S REQUIREMENTS FOR EXPOSURE TO RADIO WAVES.

Your wireless phone is a radio transmitter and receiver. It is designed and manufactured not to exceed the emission limits for exposure to radio frequency (RF) energy set by the Federal Communications Commission of the U.S. Government. These limits are part of comprehensive guidelines and establish permitted levels of RF energy for the general population. The guidelines are based on standards that were developed by independent scientific organizations through periodic and thorough evaluation of scientific studies. The standards include a substantial safety margin designed to assure the safety of all persons, regardless of age and health.

The exposure standard for wireless mobile phones employs a unit of measurement known as the Specific Absorption Rate, or SAR. The SAR limit set by the FCC is 1.6W/kg.\* Tests for SAR are conducted using standard operating positions accepted by the FCC with the phone transmitting at its highest certified power level in all tested frequency bands. Although the SAR is determined at the highest certified power level, the actual SAR level of the phone while operating can be well below the maximum value. This is because the phone is designed to operate at multiple power levels so as to use only the power required to reach the network. In general, the closer you are to a wireless base station antenna, the lower the power output.

Before a phone model is available for sale to the public, it must be tested and certified to the FCC that it does not exceed the limit established by the government-adopted requirement for safe exposure. The tests are performed in positions and locations (for example, at the ear and worn on the body) as required by the FCC for each model. The highest SAR value for this model phone as reported to the FCC when tested for use at the ear is 1.08 W/kg, and when worn on the body, as described in this user guide, is 0.73 W/kg. (Body-worn measurements differ among phone models, depending upon available accessories and FCC requirements).

While there may be differences between the SAR levels of various phones and at various positions, they all meet the government requirement.

The FCC has granted an Equipment Authorization for this model phone with all reported SAR levels evaluated as in compliance with the FCC RF exposure guidelines. SAR information on this model phone is on file with the FCC and can be found under the Display Grant section of <http://www.fcc.gov/oet/fccid> after searching on FCC ID GMLNPM-10.


For body worn operation, this phone has been tested and meets the FCC RF exposure guidelines for use with an accessory that contains no metal and that positions the handset a minimum of 5/8 inch (1.5 cm) from the body. Use of other accessories may not ensure compliance with FCC RF exposure guidelines. If you do not use a body-worn accessory and are not holding the phone at the ear, position the handset a minimum of 5/8 inch (1.5 cm) from your body when the phone is switched on.

\*In the United States and Canada, the SAR limit for mobile phones used by the public is 1.6 watts/kilogram (W/kg) averaged over one gram of tissue. The standard incorporates a substantial margin of safety to give additional protection for the public and to account for any variations in measurements. SAR values may vary depending on national reporting requirements and the network band. For SAR information in other regions please look under product information at [www.nokia.com/us](http://www.nokia.com/us).

## SAR Compliance Test Report


<b>Test report no.:</b>	02-RF-0172	<b>Date of report:</b>	12 February, 2003
<b>Number of pages:</b>	19	<b>Contact person:</b>	Nerina Walton
		<b>Responsible test engineer:</b>	Nerina Walton
<b>Testing laboratory:</b>	Test Et Certification Center (TCC) Dallas Nokia Mobile Phones, Inc 6021 Connection Drive Irving TX 75039, USA Tel. +1 972 894 5000 Fax. +1 972 894 4988	<b>Client:</b>	Nokia Mobile Phones, Inc 6021 Connection Drive Irving TX 75039, USA Tel. +1 972 894 5000 Fax. +1 972 894 4988
<b>Tested devices:</b>	GMLNPM-10, Model 3595 BLC-2, HDE-2		
<b>Supplement reports:</b>	-		
<b>Testing has been carried out in accordance with:</b>	IEEE Std 1528-200X, Draft CBD 1.0 - April 4, 2002 Draft Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques FCC Supplement C Edition, 01-01 Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields		
<b>Documentation:</b>	The documentation of the testing performed on the tested devices is archived for 15 years at Test Et Certification Center (TCC) Dallas		
<b>Test results:</b>	<b>The tested device complies with the requirements in respect of all parameters subject to the test.</b>  The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		

**Date and signatures:**  
For the contents:



Alan C. Ewing  
TCC Line Manager

12 February, 2003



Nerina Walton  
Test Engineer

## CONTENTS

1. QUALITY SYSTEM.....	3
2. SUMMARY FOR SAR TEST REPORT .....	4
2.1 MAXIMUM RESULTS FOUND DURING SAR EVALUATION.....	4
3. DESCRIPTION OF TESTED DEVICE .....	5
3.1 PICTURE OF PHONE .....	5
3.2 DESCRIPTION OF THE ANTENNA.....	5
3.3 BATTERY OPTIONS.....	5
3.4 BODY WORN OPERATION.....	5
4. TEST CONDITIONS .....	6
4.1 AMBIENT CONDITIONS .....	6
4.2 RF CHARACTERISTICS OF THE TEST SITE .....	6
4.3 TEST SIGNAL, FREQUENCIES, AND OUTPUT POWER.....	6
5. DESCRIPTION OF THE TEST EQUIPMENT.....	7
5.1 SYSTEM ACCURACY VERIFICATION.....	8
5.2 TISSUE SIMULANTS.....	9
5.3 PHANTOMS.....	11
5.4 ISOTROPIC E-FIELD PROBE ET3DV6 .....	11
6. DESCRIPTION OF THE TEST PROCEDURE .....	12
6.1 TEST POSITIONS.....	12
6.2 SCAN PROCEDURES.....	14
6.3 SAR AVERAGING METHODS.....	14
7. MEASUREMENT UNCERTAINTY .....	15
7.1 DESCRIPTION OF INDIVIDUAL MEASUREMENT UNCERTAINTY .....	15
8. RESULTS.....	16
8.1 HEAD CONFIGURATION .....	16
8.2 BODY WORN CONFIGURATION.....	17

APPENDIX A: SCOPE OF ACCREDITATION FOR A2LA  
APPENDIX B: VALIDATION TEST PRINTOUTS  
APPENDIX C: SAR DISTRIBUTION PRINTOUTS  
APPENDIX D: CALIBRATION CERTIFICATE(S)

## 1. QUALITY SYSTEM

The quality system in place for TCC-Dallas conforms to ISO/IEC 17025 and has been audited to the standard by A2LA (American Association of Laboratory Accreditation). Appendix D of this report contains the scope of accreditation for A2LA. TCC – Dallas has also been audited using the ISO 9000 Quality System, as part of Nokia Mobile Phones, Inc., by ABS (American Bureau of Shipping) Quality Evaluations Inc.

TCC-Dallas is a recognized laboratory with the Federal Communications Commission in filing applications for Certification under Parts 15 and 18, Registration Number 100060, and Industry Canada, Registration Number IC 661.

## 2. SUMMARY FOR SAR TEST REPORT

Date of test	18, 19, 20 & 23 Dec-02 & 6-Jan-03
Contact person	Nerina Walton
Test plan referred to	-
FCC ID	GMLNPM-10
SN, HW, SW and Type of tested device	IMEI: 001004/50/098842/4, HW: Proto/4.0, SW: 3.0, Type: NPM-10
Accessories used in testing	BLC-2 Battery, HDE-2 Headset
Notes	-
Document code	02-RF-0172
Responsible test engineer	Nerina Walton
Measurement performed by	Elizabeth Parish

### 2.1 Maximum Results Found during SAR Evaluation

The equipment is deemed to fulfill the requirements if the measured values are less than or equal to the limit.

#### 2.1.1 Head Configuration

Mode	Ch / f (MHz)	EDRP (dBm) <sup>1</sup>	Position	Limit (mW/g)	Measured (mW/g)	Result
GSM 850	251 / 848.80	31.6	Left Touch Position	1.6	1.08	<b>PASSED</b>

Mode	Ch / f (MHz)	EIRP (dBm) <sup>1</sup>	Position	Limit (mW/g)	Measured (mW/g)	Result
GSM 1900	661 / 1880.00	29.5	Right Tilt Position	1.6	0.45	<b>PASSED</b>

Note 1: An FCC accredited laboratory, TCC Dallas, performed the EDRP and EIRP measurements.

#### 2.1.2 Body Worn Configuration

Mode	Ch / f (MHz)	EDRP (dBm) <sup>1</sup>	Position	Limit (mW/g)	Measured (mW/g)	Result
GSM 850	128 / 824.04	32.0	Flat Position with HDE-2 Headset	1.6	0.73	<b>PASSED</b>

Mode	Ch / f (MHz)	EIRP (dBm) <sup>1</sup>	Position	Limit (mW/g)	Measured (mW/g)	Result
GSM 1900	661 / 1880.00	29.5	Flat Position with HDE-2 Headset	1.6	0.47	<b>PASSED</b>

Note 1: An FCC accredited laboratory, TCC Dallas, performed the EDRP and EIRP measurements.

#### 2.1.3 Measurement Uncertainty

<b>Combined Standard Uncertainty</b>	<b>± 13.6%</b>
<b>Expanded Standard Uncertainty (k=2)</b>	<b>± 27.1%</b>

### 3. DESCRIPTION OF TESTED DEVICE

Device category	Portable device	
Exposure environment	Uncontrolled exposure	
Unit type	Prototype unit	
Case type	Fixed case	
Mode of Operation	GSM 850	GSM 1900
Modulation Mode	Gaussian Minimum Shift Keying (GMSK)	Gaussian Minimum Shift Keying (GMSK)
Duty Cycle	1/8	1/8
Transmitter Frequency Range (MHz)	824.20 – 848.80	1850.20 – 1909.80

#### 3.1 Picture of Phone

The tested device, GMLNPM-10 is shown below: -



#### 3.2 Description of the Antenna

Type	Internal Integrated Antenna
Location	Inside Back Cover, Near Top of the Device

#### 3.3 Battery Options

There is only one battery currently available for the tested device, a rechargeable Li-ion battery, BLC-2.

#### 3.4 Body Worn Operation

Body SAR was evaluated with a minimum separation distance of 15mm and with the HDE-2 headset connected.



## 4. TEST CONDITIONS

### 4.1 Ambient Conditions

Ambient temperature (°C)	22±2
Tissue simulating liquid temperature (°C)	20±2
Humidity (%)	39

### 4.2 RF characteristics of the test site

Tests were performed in a fully enclosed RF shielded environment.

### 4.3 Test Signal, Frequencies, and Output Power

The device was controlled by using a radio tester. Communication between the device and the tester was established by air link.

Measurements were performed on the lowest, middle and highest channels of the operating band.

The phone was set to maximum power level during all tests and at the beginning of each test the battery was fully charged.

The DASY3 system measures power drift during SAR testing by comparing e-field in the same location at the beginning and at the end of measurement. These records were used to monitor stability of power output.

## 5. DESCRIPTION OF THE TEST EQUIPMENT

The measurements were performed with an automated near-field scanning system, DASY3, manufactured by Schmid & Partner Engineering AG (SPEAG) in Switzerland.

Test Equipment	Model	NMP #	Serial Number	Due Date
DASY3, Data Acquisition	DAE V1	2292	389	07/03
E-field Probe	ET3DV6	2954	1504	07/03
Dipole Validation Kit	D835V2	3453	455	07/03
Dipole Validation Kit	D1900V2	3457	5D004	07/03

E-field probe and dipole validation kit calibration records are presented in Appendix D.

Additional equipment (required for validation).

Test Equipment	Model	NMP #	Serial Number	Due Date
Signal Generator	HP 8648C	0409	3836A04346	06/03
Amplifier	AR 5S1G4	0188	25583	-
Coupler	AR DC7144	2057	25304	-
Power Meter	Boonton 4232A	2996	64701	05/03
Power Sensor	Boonton 51015	2997	32187	05/03
Power Sensor	Boonton 51015	2998	32188	05/03
Thermometer	Omega CL27	3391	T-228450	03/03
Network Analyzer	HP 8720D	0455	US38431353	06/03
Dielectric Probe Kit	Agilent 85070C	3089	US99360172	-

The calibration interval on all items listed above can be obtained from the Engineering Services Group within NMP, Product Creation - Dallas. Where relevant, measuring equipment is subjected to in-service checks between testing. TCC - Dallas shall notify clients promptly, in writing, of identification of defective measuring equipment that casts doubt on the validity of results given in this report.

## 5.1 System Accuracy Verification

The manufacturer calibrates the probes annually. Dielectric parameters of the simulating liquids are measured using an Agilent 85070C dielectric probe kit and an HP 8720D network analyzer.

SAR measurements of the tested device were performed within 24 hours of system accuracy verification, which was done using the dipole validation kit.

The dipole antenna, which is manufactured by Schmid & Partner Engineering AG, is matched to be used near a flat phantom filled with tissue simulating solution. Length of the 835MHz dipole is 161mm with an overall height of 330mm; length of the 1900MHz dipole is 68mm with an overall height of 300mm. A specific distance holder is used in the positioning to ensure correct spacing between the phantom and the dipole.

A power level of 250 mW was supplied to the dipole antenna placed under the flat section of the SAM phantom. Validation results are in the table below and a print out of the validation tests are presented in Appendix B. All the measured parameters were within specification.

### 5.1.1 Head Tissue

Tissue	f (MHz)	Description	SAR (W/kg), 1g	Dielectric Parameters		Temp (°C)
				$\epsilon_r$	$\sigma$ (S/m)	
Head	835	Measured, 19-Dec-02	10.7	41.3	0.88	19.6
		Measured, 6-Jan-03	10.8	41.8	0.94	18.5
		Reference Result	9.8	42.5	0.90	N/A
Head	1900	Measured, 18-Dec-02	42.4	40.7	1.44	19.5
		Reference Result	44.0	39.8	1.46	N/A

### 5.1.2 Muscle Tissue

Tissue	f (MHz)	Description	SAR (W/kg), 1g	Dielectric Parameters		Temp (°C)
				$\epsilon_r$	$\sigma$ (S/m)	
Muscle	835	Measured, 20-Dec-02	10.4	54.8	0.92	19.7
		Reference Result	10.1	55.3	0.95	N/A
Muscle	1900	Measured, 23-Dec-02	44.8	53.0	1.60	19.5
		Reference Result	44.0	54.4	1.57	N/A

## 5.2 Tissue Simulants

All dielectric parameters of tissue simulants were measured within 24 hours of SAR measurements. The depth of the tissue simulant in the ear reference point of the phantom was 15cm ± 5mm during all tests. Volume for each tissue simulant was 26 litres.

### 5.2.1 Head Tissue Simulant

The composition of the brain tissue simulating liquid for 835 MHz is: -

51.07%	De-Ionized Water
47.31%	Sugar
1.15%	Salt
0.23%	HEC
0.24%	Bactericide

<i>f</i> (MHz)	Description	Dielectric Parameters		Temp (°C)
		$\epsilon_r$	$\sigma$ (S/m)	
836.52	Measured, 19-Dec-02	41.3	0.88	19.6
	Measured, 6-Jan-03	41.8	0.94	18.5
	Recommended Values	41.5	0.90	N/A

The composition of the brain tissue simulating liquid for 1900 MHz is: -

44.91%	2-(2-butoxyethoxy) Ethanol
54.88%	De-Ionized Water
0.21%	Salt

<i>f</i> (MHz)	Description	Dielectric Parameters		Temp (°C)
		$\epsilon_r$	$\sigma$ (S/m)	
1880	Measured, 18-Dec-02	40.8	1.42	19.5
	Recommended Values	40.0	1.40	N/A

Recommended values are adopted from OET Bulletin 65 (97-01) Supplement C (01-01).

## 5.2.2 Muscle Tissue Simulant

The composition of the muscle tissue simulating liquid for 835 MHz is: -

65.45% De-Ionized Water  
 34.31% Sugar  
 0.62% Salt  
 0.10% Bactericide

$f$ (MHz)	Description	Dielectric Parameters		Temp (°C)
		$\epsilon_r$	$\sigma$ (S/m)	
836.52	Measured, 20-Dec-02	54.7	0.92	19.7
	Recommended Values	55.2	0.97	N/A

The composition of the muscle tissue simulating liquid for 1900 MHz is: -

69.02% De-Ionized Water  
 30.76% Diethylene Glycol Monobutyl Ether  
 0.22% Salt

$f$ (MHz)	Description	Dielectric Parameters		Temp (°C)
		$\epsilon_r$	$\sigma$ (S/m)	
1880	Measured, 23-Dec-02	53.1	1.58	19.5
	Recommended Values	53.3	1.52	N/A

Recommended values are adopted from OET Bulletin 65 (97-01) Supplement C (01-01).

### 5.3 Phantoms

"SAM v4.0" phantom", manufactured by SPEAG, was used during the measurement. It has a fiberglass shell integrated into a wooden table. The shape of the shell corresponds to the phantom defined by SCC34-SC2. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. Reference markings on the phantom allow the complete set-up of all predefined phantom positions and measurement grids by manually teaching three points in the robot.



The thickness of phantom shell is 2 mm except for the ear, where an integrated ear spacer provides a 6 mm spacing from the tissue boundary. Manufacturer reports tolerance in shell thickness to be  $\pm 0.1$ mm.

### 5.4 Isotropic E-Field Probe ET3DV6

<b>Construction</b>	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycol ether)
<b>Calibration</b>	Calibration certificate in Appendix D
<b>Frequency</b>	10 MHz to 3 GHz (dosimetry); Linearity: $\pm 0.2$ dB (30 MHz to 3 GHz)
<b>Optical Surface Detection</b>	$\pm 0.2$ mm repeatability in air and clear liquids over diffuse reflecting surfaces
<b>Directivity</b>	$\pm 0.2$ dB in HSL (rotation around probe axis) $\pm 0.4$ dB in HSL (rotation normal to probe axis)
<b>Dynamic Range</b>	5 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB
<b>Dimensions</b>	Overall length: 330 mm Tip length: 16 mm Body diameter: 12 mm Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm
<b>Application</b>	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms



## 6. DESCRIPTION OF THE TEST PROCEDURE

### 6.1 Test Positions

The device was placed into a holder using a special positioning tool, which aligns the bottom of the device with the holder and ensures that holder contacts only to the sides of the device. After positioning is done, tool is removed. This method provides standard positioning and separation, and also ensures free space for antenna.

Device holder was provided by SPEAG together with DASY3.



#### 6.1.1 Against Phantom Head

Measurements were made on both the "left hand" and "right hand" side of the phantom.

The device was positioned against phantom according to OET Bulletin 65 (97-01) Supplement C (01-01). Definitions of terms used in aligning the device to a head phantom are available in IEEE Draft Standard P1528-2001 "Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"

##### 6.1.1.1 Initial Ear Position

The device was initially positioned with the earpiece region pressed against the ear spacer of a head phantom parallel to the "Neck-Front" line defined along the base of the ear spacer that contains the "ear reference point". The "test device reference point" is aligned to the "ear reference point" on the head phantom and the "vertical centerline" is aligned to the "phantom reference plane".

##### 6.1.1.2 Touch Position

"Initial ear position" alignments are maintained and the device is brought toward the mouth of the head phantom by pivoting along the "Neck-Front" line until any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom or when any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

The following picture shows the tested device in the left touch position:



### 6.1.1.3 Tilt Position

In the "Touch Position", if the earpiece of the device is not in full contact with the phantom's ear spacer and the peak SAR location for the "touch position" is located at the ear spacer region or corresponds to the earpiece region of the handset, the device is returned to the "initial ear position" by rotating it away from the mouth until the earpiece is in full contact with the ear spacer. Otherwise, the device is moved away from the cheek perpendicular to the line passes through both "ear reference points" for approximate 2-3 cm. While it is in this position, the device is tilted away from the mouth with respect to the "test device reference point" by 15°. After the tilt, it is then moved back toward the head perpendicular to the line passes through both "ear reference points" until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process is repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously.

The following picture shows the tested device in the left tilt position:






## 6.1.2 Body Worn Configuration

Body SAR measurements were performed with the antenna facing towards the flat part of the phantom, with a separation distance of 15mm with the HDE-2 headset connected.

The following picture shows the tested device in the body test position: -



Note: the 15mm spacer was removed during the SAR measurement.

## 6.2 Scan Procedures

First coarse scans are used for quick determination of the field distribution. Next a cube scan, 5x5x7 points; spacing between each point 8x8x5 mm, is performed around the highest E-field value to determine the averaged SAR-distribution over 1g.

## 6.3 SAR Averaging Methods

The maximum SAR value is averaged over its volume using interpolation and extrapolation.

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot" -condition [W. Gander, Computermathematik, p. 141-150] (x, y and z -directions) [Numerical Recipes in C, Second Edition, p 123].

The extrapolation is based on least square algorithm [W. Gander, Computermathematik, p.168-180]. Through the points in the first 30 mm in all z-axis, polynomials of order four are calculated. This polynomial is then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1mm from one another.



## 7. MEASUREMENT UNCERTAINTY

### 7.1 Description of Individual Measurement Uncertainty

#### 7.1.1 Assessment Uncertainty

Uncertainty description	Uncert. value %	Probability distribution	Div.	$C_i$	Stand. uncert (1g) %	$v_i$ or $v_{eff}$
<b>Measurement System</b>						
Probe calibration	± 4.4	normal	1	1	± 4.4	∞
Axial isotropy of the probe	± 4.7	rectangular	√3	$(1-c_p)^{1/2}$	± 1.9	∞
Sph. Isotropy of the probe	± 9.6	rectangular	√3	$(c_p)^{1/2}$	± 3.9	∞
Spatial resolution	± 0.0	rectangular	√3	1	± 0.0	∞
Boundary effects	± 5.5	rectangular	√3	1	± 3.2	∞
Probe linearity	± 4.7	rectangular	√3	1	± 2.7	∞
Detection limit	± 1.0	rectangular	√3	1	± 0.6	∞
Readout electronics	± 1.0	normal	1	1	± 1.0	∞
Response time	± 0.8	rectangular	√3	1	± 0.5	∞
Integration time	± 1.4	rectangular	√3	1	± 0.8	∞
RF ambient conditions	± 3.0	rectangular	√3	1	± 1.7	∞
Mech. constrains of robot	± 0.4	rectangular	√3	1	± 0.2	∞
Probe positioning	± 2.9	rectangular	√3	1	± 1.7	∞
Extrap. and integration	± 3.9	rectangular	√3	1	± 2.3	∞
<b>Test Sample Related</b>						
Device positioning	± 6.0	normal	0.89	1	± 6.7	12
Device holder uncertainty	± 5.0	normal	0.84	1	± 5.9	8
Power drift	± 5.0	rectangular	√3	1	± 2.9	∞
<b>Phantom and Setup</b>						
Phantom uncertainty	± 4.0	rectangular	√3	1	± 2.3	∞
Liquid conductivity (target)	± 5.0	rectangular	√3	0.6	± 1.7	∞
Liquid conductivity (meas.)	± 10.0	rectangular	√3	0.6	± 3.5	∞
Liquid permittivity (target)	± 5.0	rectangular	√3	0.6	± 1.7	∞
Liquid permittivity (meas.)	± 5.0	rectangular	√3	0.6	± 1.7	∞
<b>Combined Standard Uncertainty</b>					± 13.6	
<b>Expanded Standard Uncertainty (k=2)</b>					± 27.1	

## 8. RESULTS

Corresponding SAR distribution print outs of maximum results in every operating mode and position are shown in Appendix C; it also includes Z-plots of maximum measurement results in head and body worn configurations. The SAR distributions are substantially similar or equivalent to the plots submitted regardless of used channel in each mode and position, unless otherwise presented.

### 8.1 Head Configuration

Mode	Channel/ f (MHz)	EDRP (dBm) <sup>1</sup>	SAR, averaged over 1g (mW/g)			
			Left-hand		Right-hand	
			Touch	Tilt	Touch	Tilt
GSM 850	128 / 824.04	32.0	0.91	0.49	0.86	0.58
	190 / 836.60	32.1	1.00	0.53	0.89	0.57
	251 / 848.80	31.6	1.08	0.57	0.96	0.61

Mode	Channel/ f (MHz)	EIRP (dBm) <sup>1</sup>	SAR, averaged over 1g (mW/g)			
			Left-hand		Right-hand	
			Touch	Tilt	Touch	Tilt
GSM 1900	512 / 1850.20	30.0	-	-	-	-
	661 / 1880.00	29.5	0.39	0.43	0.38	0.45
	810 / 1909.80	29.6	-	-	-	-

Note 1: An FCC accredited laboratory, TCC Dallas, performed the EDRP and EIRP measurements.

## 8.2 Body Worn Configuration

Body SAR measurements were performed with the HDE-2 headset connected.

Mode	Channel/ <i>f</i> (MHz)	EDRP (dBm) <sup>1</sup>	SAR, averaged over 1g (mW/g)
			HDE-2
GSM 850	128 / 824.04	32.0	0.73
	190 / 836.60	32.1	0.63
	251 / 848.80	31.6	0.56


Mode	Channel/ <i>f</i> (MHz)	EIRP (dBm) <sup>1</sup>	SAR, averaged over 1g (mW/g)
			HDE-2
GSM 1900	512 / 1850.20	30.0	-
	661 / 1880.00	29.5	0.47
	810 / 1909.80	29.6	-

Note 1: An FCC accredited laboratory, TCC Dallas, performed the EDRP and EIRP measurements.

## APPENDIX A: SCOPE OF ACCREDITATION FOR A2LA

TCC-Dallas is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below:





“This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined to be in accordance with the laboratory's terms of accreditation unless stated otherwise in the report.”

Should this report contain any data for tests for which we are not accredited, such data would not be covered by this laboratory's A2LA accreditation.

## APPENDIX B: VALIDATION TEST PRINTOUTS

## Dipole 835 MHz, Head Validation

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Brain Tissue:  $\sigma = 0.88$  mho/m  $\epsilon_r = 41.3$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cubes (2): SAR (1g): 2.68 mW/g  $\pm$  0.05 dB, SAR (10g): 1.71 mW/g  $\pm$  0.05 dB, (Worst-case extrapolation)

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: -0.03 dB

Liquid Temperature (°C):19.6





## Dipole 835 MHz, Head Validation

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Brain Tissue:  $\sigma = 0.94$  mho/m  $\epsilon_r = 41.8$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cubes (2): SAR (1g): 2.69 mW/g  $\pm$  0.06 dB, SAR (10g): 1.70 mW/g  $\pm$  0.06 dB, (Worst-case extrapolation)

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: -0.04 dB

Liquid Temperature (°C):18.5



## Dipole 1900 MHz, Head Validation

SAM 3 (PCS - Brain / Muscle Tissue) Phantom

Frequency: 1900 MHz; Crest factor: 1.0

Validation 1900MHz - Brain Tissue:  $\sigma = 1.44$  mho/m  $\epsilon_r = 40.7$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(5.40,5.40,5.40)

Cubes (2): SAR (1g): 10.6 mW/g  $\pm 0.05$  dB, SAR (10g): 5.47 mW/g  $\pm 0.04$  dB, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 12.0

Powerdrift: 0.14 dB

Liquid Temperature (°C):19.5



## Dipole 835 MHz, Body Validation

SAM 2 (Cellular - Muscle Tissue) Phantom

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Muscle Tissue:  $\sigma = 0.92$  mho/m  $\epsilon_r = 54.8$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cubes (2): SAR (1g): 2.61 mW/g  $\pm$  0.05 dB, SAR (10g): 1.69 mW/g  $\pm$  0.05 dB, (Worst-case extrapolation)

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: -0.06 dB

Liquid Temperature (°C):19.7



## Dipole 1900 MHz, Body Validation

SAM 3 (PCS - Brain / Muscle Tissue) Phantom

Frequency: 1900 MHz; Crest factor: 1.0

Validation 1900MHz - Muscle Tissue:  $\sigma = 1.60$  mho/m  $\epsilon_r = 53.0$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(5.00,5.00,5.00)

Cubes (2): SAR (1g): 11.2 mW/g  $\pm 0.04$  dB, SAR (10g): 5.76 mW/g  $\pm 0.04$  dB, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 12.0

Powerdrift: -0.03 dB

Liquid Temperature (°C):19.5



## APPENDIX C: SAR DISTRIBUTION PRINTOUTS

## GMLNPM-10, GSM 850, Channel 251, Left Touch Position

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 849 MHz; Crest factor: 8.0

Cellular Band - Brain Tissue:  $\sigma = 0.94$  mho/m  $\epsilon_r = 41.8$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 1.08 mW/g, SAR (10g): 0.743 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.22 dB

Liquid Temperature (°C):18.5



## GMLNPM-10, GSM 850, Channel 251, Left Tilt Position

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 849 MHz; Crest factor: 8.0

Cellular Band - Brain Tissue:  $\sigma = 0.94$  mho/m  $\epsilon_r = 41.8$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 0.569 mW/g, SAR (10g): 0.389 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.12 dB

Liquid Temperature (°C):18.5



## GMLNPM-10, GSM 850, Channel 251, Right Touch Position

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 849 MHz; Crest factor: 8.0

Cellular Band - Brain Tissue:  $\sigma = 0.88$  mho/m  $\epsilon_r = 41.3$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 0.955 mW/g, SAR (10g): 0.665 mW/g, (Worst-case extrapolation)

Coarse: Dx = 19.0, Dy = 14.0, Dz = 10.0

Powerdrift: -0.05 dB

Liquid Temperature (°C):19.6





## GMLNPM-10, GSM 850, Channel 251, Right Tilt Position

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 849 MHz; Crest factor: 8.0

Cellular Band - Brain Tissue:  $\sigma = 0.88$  mho/m  $\epsilon_r = 41.3$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cubes (2): SAR (1g): 0.611 mW/g  $\pm$  0.01 dB, SAR (10g): 0.422 mW/g  $\pm$  0.00 dB, (Worst-case extrapolation)

Coarse: Dx = 19.0, Dy = 14.0, Dz = 10.0

Powerdrift: -0.12 dB

Liquid Temperature (°C):19.6



## GMLNPM-10, GSM 850, Channel 128, Flat Position - Back of Phone with 15mm Spacer and HDE-2 Headset

SAM 2 (Cellular - Muscle Tissue) Phantom

Frequency: 824 MHz; Crest factor: 8.0

Cellular Band - Muscle Tissue:  $\sigma = 0.92$  mho/m  $\epsilon_r = 54.7$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 0.725 mW/g, SAR (10g): 0.505 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 12.0

Powerdrift: -0.03 dB

Liquid Temperature (°C):19.7



## GMLNPM-10, GSM 1900, Channel 661, Left Touch Position

SAM 3 (PCS - Brain / Muscle Tissue) Phantom

Frequency: 1880 MHz; Crest factor: 8.0

PCS Band - Brain Tissue:  $\sigma = 1.42$  mho/m  $\epsilon_r = 40.8$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(5.40,5.40,5.40)

Cube 5x5x7: SAR (1g): 0.390 mW/g, SAR (10g): 0.215 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.26 dB

Liquid Temperature (°C):19.5



## GMLNPM-10, GSM 1900, Channel 661, Left Tilt Position

SAM 3 (PCS - Brain / Muscle Tissue) Phantom

Frequency: 1880 MHz; Crest factor: 8.0

PCS Band - Brain Tissue:  $\sigma = 1.42$  mho/m  $\epsilon_r = 40.8$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(5.40,5.40,5.40)

Cube 5x5x7: SAR (1g): 0.434 mW/g, SAR (10g): 0.251 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.10 dB

Liquid Temperature (°C):19.5



## GMLNPM-10, GSM 1900, Channel 661, Right Touch Position

SAM 3 (PCS - Brain / Muscle Tissue) Phantom

Frequency: 1880 MHz; Crest factor: 8.0

PCS Band - Brain Tissue:  $\sigma = 1.42$  mho/m  $\epsilon_r = 40.8$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(5.40,5.40,5.40)

Cube 5x5x7: SAR (1g): 0.375 mW/g, SAR (10g): 0.201 mW/g, (Worst-case extrapolation)

Coarse: Dx = 19.0, Dy = 14.0, Dz = 10.0

Powerdrift: -0.33 dB

Liquid Temperature (°C):19.5



## GMLNPM-10, GSM 1900, Channel 661, Right Tilt Position

SAM 3 (PCS - Brain / Muscle Tissue) Phantom

Frequency: 1880 MHz; Crest factor: 8.0

PCS Band - Brain Tissue:  $\sigma = 1.42$  mho/m  $\epsilon_r = 40.8$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(5.40,5.40,5.40)

Cube 5x5x7: SAR (1g): 0.453 mW/g, SAR (10g): 0.256 mW/g, (Worst-case extrapolation)

Coarse: Dx = 19.0, Dy = 14.0, Dz = 10.0

Powerdrift: 0.38 dB

Liquid Temperature (°C):19.5



## GMLNPM-10, GSM 1900, Channel 661, Flat Position - Back of Phone with 15mm Spacer and HDE-2 Headset

SAM 3 (PCS - Brain / Muscle Tissue) Phantom

Frequency: 1880 MHz; Crest factor: 8.0

PCS Band - Muscle Tissue:  $\sigma = 1.58$  mho/m  $\epsilon_r = 53.1$   $\rho = 1.00$  g/cm<sup>3</sup>


Probe: ET3DV6 - SN1504; ConvF(5.00,5.00,5.00)

Cube 5x5x7: SAR (1g): 0.474 mW/g, SAR (10g): 0.279 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 12.0

Powerdrift: -0.09 dB

Liquid Temperature (°C):19.5



## GMLNPM-10, GSM 850, Channel 251, Left Touch Position

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 849 MHz; Crest factor: 8.0


Cellular Band - Brain Tissue:  $\sigma = 0.94$  mho/m  $\epsilon_r = 41.8$   $\rho = 1.00$  g/cm<sup>3</sup>

Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 1.08 mW/g, SAR (10g): 0.743 mW/g, (Worst-case extrapolation)

Cube 5x5x7: Dx = 8.0, Dy = 8.0, Dz = 5.0

Liquid Temperature (°C):18.5





## GMLNPM-10, GSM 850, Channel 128, Flat Position - Back of Phone with 15mm Spacer and HDE-2 Headset

SAM 2 (Cellular - Muscle Tissue) Phantom

Frequency: 824 MHz; Crest factor: 8.0


Cellular Band - Muscle Tissue:  $\sigma = 0.92$  mho/m  $\epsilon_r = 54.7$   $\rho = 1.00$  g/cm<sup>3</sup>

Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 0.725 mW/g, SAR (10g): 0.505 mW/g, (Worst-case extrapolation)

Cube 5x5x7: Dx = 8.0, Dy = 8.0, Dz = 5.0

Liquid Temperature (°C):19.7



## GMLNPM-10, GSM 1900, Channel 661, Right Tilt Position

SAM 3 (PCS - Brain / Muscle Tissue) Phantom

Frequency: 1880 MHz; Crest factor: 8.0


PCS Band - Brain Tissue:  $\sigma = 1.42$  mho/m  $\epsilon_r = 40.8$   $\rho = 1.00$  g/cm<sup>3</sup>

Probe: ET3DV6 - SN1504; ConvF(5.40,5.40,5.40)

Cube 5x5x7: SAR (1g): 0.453 mW/g, SAR (10g): 0.256 mW/g, (Worst-case extrapolation)

Cube 5x5x7: Dx = 8.0, Dy = 8.0, Dz = 5.0

Liquid Temperature (°C):19.5



## GMLNPM-10, GSM 1900, Channel 661, Flat Position - Back of Phone with 15mm Spacer and HDE-2 Headset

SAM 3 (PCS - Brain / Muscle Tissue) Phantom

Frequency: 1880 MHz; Crest factor: 8.0


PCS Band - Muscle Tissue:  $\sigma = 1.58$  mho/m  $\epsilon_r = 53.1$   $\rho = 1.00$  g/cm<sup>3</sup>

Probe: ET3DV6 - SN1504; ConvF(5.00,5.00,5.00)

Cube 5x5x7: SAR (1g): 0.474 mW/g, SAR (10g): 0.279 mW/g, (Worst-case extrapolation)

Cube 5x5x7: Dx = 8.0, Dy = 8.0, Dz = 5.0

Liquid Temperature (°C):19.5



**APPENDIX D: CALIBRATION CERTIFICATES**

# Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

## Calibration Certificate

### Dosimetric E-Field Probe

Type:

**ET3DV6**

Serial Number:

**1504**

Place of Calibration:

**Zurich**

Date of Calibration:

**July 26, 2002**

Calibration Interval:

**12 months**

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:

*U. Vella*

Approved by:

*Adrian Katz*

# Probe ET3DV6

## SN:1504

Manufactured:	October 24, 1999
Last calibration:	January 10, 2002
Recalibrated:	July 26, 2002

Calibrated for System DASY3

## DASY3 - Parameters of Probe: ET3DV6 SN:1504

### Sensitivity in Free Space

NormX	<b>2.02</b> $\mu\text{V}/(\text{V}/\text{m})^2$
NormY	<b>1.78</b> $\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	<b>1.73</b> $\mu\text{V}/(\text{V}/\text{m})^2$

### Diode Compression

DCP X	<b>95</b>	mV
DCP Y	<b>95</b>	mV
DCP Z	<b>95</b>	mV

### Sensitivity in Tissue Simulating Liquid

Head	<b>835 MHz</b>	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.90 \pm 5\%$ mho/m
Head	<b>900 MHz</b>	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.97 \pm 5\%$ mho/m
ConvF X	<b>6.5</b> $\pm 9.5\%$ (k=2)	Boundary effect:	
ConvF Y	<b>6.5</b> $\pm 9.5\%$ (k=2)	Alpha	<b>0.39</b>
ConvF Z	<b>6.5</b> $\pm 9.5\%$ (k=2)	Depth	<b>2.42</b>
Head	<b>1880 MHz</b>	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\%$ mho/m
Head	<b>1800 MHz</b>	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\%$ mho/m
ConvF X	<b>5.4</b> $\pm 9.5\%$ (k=2)	Boundary effect:	
ConvF Y	<b>5.4</b> $\pm 9.5\%$ (k=2)	Alpha	<b>0.53</b>
ConvF Z	<b>5.4</b> $\pm 9.5\%$ (k=2)	Depth	<b>2.44</b>

### Boundary Effect



Head	<b>835 MHz</b>	<b>Typical SAR gradient: 5 % per mm</b>	
Probe Tip to Boundary		<b>1 mm</b>	<b>2 mm</b>
SAR <sub>be</sub> [%]	Without Correction Algorithm	9.6	5.3
SAR <sub>be</sub> [%]	With Correction Algorithm	0.3	0.5
Head	<b>1880 MHz</b>	<b>Typical SAR gradient: 10 % per mm</b>	
Probe Tip to Boundary		<b>1 mm</b>	<b>2 mm</b>
SAR <sub>be</sub> [%]	Without Correction Algorithm	13.0	8.5
SAR <sub>be</sub> [%]	With Correction Algorithm	0.2	0.2

### Sensor Offset



Probe Tip to Sensor Center	<b>2.7</b>	mm
Optical Surface Detection	<b>1.4 <math>\pm</math> 0.2</b>	mm

### Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$



**f = 30 MHz, TEM cell ifi110**





**f = 100 MHz, TEM cell ifi110**





**f = 300 MHz, TEM cell ifi110**




**f = 900 MHz, TEM cell ifi110**








### Isotropy Error ( $\phi$ ), $\theta = 0^\circ$





# Frequency Response of E-Field



( TEM-Cell:ifi110, Waveguide R22)



### Dynamic Range f(SAR<sub>brain</sub>) ( Waveguide R22 )





## Conversion Factor Assessment



Head	835 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.90 \pm 5\%$ mho/m
Head	900 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.97 \pm 5\%$ mho/m
	ConvF X	<b>6.5</b> $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	<b>6.5</b> $\pm 9.5\%$ (k=2)	Alpha <b>0.39</b>
	ConvF Z	<b>6.5</b> $\pm 9.5\%$ (k=2)	Depth <b>2.42</b>
Head	1880 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\%$ mho/m
Head	1800 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\%$ mho/m
	ConvF X	<b>5.4</b> $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	<b>5.4</b> $\pm 9.5\%$ (k=2)	Alpha <b>0.53</b>
	ConvF Z	<b>5.4</b> $\pm 9.5\%$ (k=2)	Depth <b>2.44</b>


## Conversion Factor Assessment



<b>Body</b>	<b>835 MHz</b>	$\epsilon_r = 55.2 \pm 5\%$	$\sigma = 0.97 \pm 5\% \text{ mho/m}$
<b>Body</b>	<b>900 MHz</b>	$\epsilon_r = 55.0 \pm 5\%$	$\sigma = 1.05 \pm 5\% \text{ mho/m}$
	ConvF X	<b>6.5</b> $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	<b>6.5</b> $\pm 9.5\%$ (k=2)	Alpha <b>0.42</b>
	ConvF Z	<b>6.5</b> $\pm 9.5\%$ (k=2)	Depth <b>2.38</b>
<b>Body</b>	<b>1880 MHz</b>	$\epsilon_r = 53.3 \pm 5\%$	$\sigma = 1.52 \pm 5\% \text{ mho/m}$
<b>Body</b>	<b>1800 MHz</b>	$\epsilon_r = 53.3 \pm 5\%$	$\sigma = 1.52 \pm 5\% \text{ mho/m}$
	ConvF X	<b>5.0</b> $\pm 9.5\%$ (k=2)	Boundary effect:
	ConvF Y	<b>5.0</b> $\pm 9.5\%$ (k=2)	Alpha <b>0.74</b>
	ConvF Z	<b>5.0</b> $\pm 9.5\%$ (k=2)	Depth <b>2.06</b>

# Deviation from Isotropy in HSL

Error ( $\theta, \phi$ ),  $f = 900$  MHz



## Calibration Certificate

### 835 MHz System Validation Dipole

Type:

**D835V2**

Serial Number:

**455**

Place of Calibration:

**Zurich**

Date of Calibration:

**July 16, 2002**

Calibration Interval:

**24 months**

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:

*N. Vetter*

Approved by:

*Alconio Klatza*

# DASY

## Dipole Validation Kit

Type: D835V2

Serial: 455

Manufactured: January 31, 2002  
Calibrated: July 16, 2002



## 1. Measurement Conditions

The measurements were performed in the flat section of the new generic twin phantom filled with head simulating solution of the following electrical parameters at 835 MHz:

Relative Dielectricity	<b>42.5</b>	$\pm 5\%$
Conductivity	<b>0.90 mho/m</b>	$\pm 5\%$

The DASY3 System (Software version 3.1d) with a dosimetric E-field probe ET3DV6 (SN:1507, Conversion factor 6.6 at 835 MHz) was used for the measurements.

The dipole was mounted on the small tripod so that the dipole feedpoint was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15mm from dipole center to the solution surface. The included distance holder was used during measurements for accurate distance positioning.

The coarse grid with a grid spacing of 20mm was aligned with the dipole. The 5x5x7 fine cube was chosen for cube integration. Probe isotropy errors were cancelled by measuring the SAR with normal and 90° turned probe orientations and averaging.

The dipole input power (forward power) was 250mW  $\pm 3\%$ . The results are normalized to 1W input power.

### 2.1. SAR Measurement with DASY3 System

Standard SAR-measurements were performed according to the measurement conditions described in section 1. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the worst-case extrapolation are:

averaged over 1 cm <sup>3</sup> (1 g) of tissue:	<b>9.84 mW/g</b>
averaged over 10 cm <sup>3</sup> (10 g) of tissue:	<b>6.32 mW/g</b>

### 2.2 SAR Measurement with DASY4 System

Standard SAR-measurements were performed according to the measurement conditions described in section 1. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the advanced extrapolation are:

averaged over 1 cm <sup>3</sup> (1 g) of tissue:	<b>9.20 mW/g</b>
averaged over 10 cm <sup>3</sup> (10 g) of tissue:	<b>6.08 mW/g</b>

### 3. Dipole Impedance and Return Loss

The impedance was measured at the SMA-connector with a network analyzer and numerically transformed to the dipole feedpoint. The transformation parameters from the SMA-connector to the dipole feedpoint are:

Electrical delay:	<b>1.375 ns</b>	(one direction)
Transmission factor:	<b>0.992</b>	(voltage transmission, one direction)

The dipole was positioned at the flat phantom sections according to section 1 and the distance holder was in place during impedance measurements.

Feedpoint impedance at 835 MHz:	$\text{Re}\{Z\} = 49.6 \Omega$
	$\text{Im}\{Z\} = -1.8 \Omega$
Return Loss at 835 MHz	<b>-34.7 dB</b>

### 4. Measurement Conditions

The measurements were performed in the flat section of the new generic twin phantom filled with body simulating solution of the following electrical parameters at 835 MHz:

Relative Dielectricity	<b>55.3</b>	$\pm 5\%$
Conductivity	<b>0.95 mho/m</b>	$\pm 5\%$

The DASY3 System (Software version 3.1d) with a dosimetric E-field probe ET3DV6 (SN:1507, Conversion factor 6.2 at 835 MHz) was used for the measurements.

The dipole was mounted on the small tripod so that the dipole feedpoint was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15mm from dipole center to the solution surface. The included distance holder was used during measurements for accurate distance positioning.

The coarse grid with a grid spacing of 20mm was aligned with the dipole. The 5x5x7 fine cube was chosen for cube integration. Probe isotropy errors were cancelled by measuring the SAR with normal and 90° turned probe orientations and averaging.

The dipole input power (forward power) was 250mW  $\pm 3\%$ . The results are normalized to 1W input power.

### **5.1. SAR Measurement with DASYS System**

Standard SAR-measurements were performed according to the measurement conditions described in section 4. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the worst-case extrapolation are:

averaged over 1 cm<sup>3</sup> (1 g) of tissue:      **10.1 mW/g**

averaged over 10 cm<sup>3</sup> (10 g) of tissue:      **6.60 mW/g**

### **5.2 SAR Measurement with DASYS System**

Standard SAR-measurements were performed according to the measurement conditions described in section 4. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the advanced extrapolation are:

averaged over 1 cm<sup>3</sup> (1 g) of tissue:      **9.24 mW/g**

averaged over 10 cm<sup>3</sup> (10 g) of tissue:      **6.20 mW/g**

### **6. Dipole Impedance and Return Loss**

The dipole was positioned at the flat phantom sections according to section 4 and the distance holder was in place during impedance measurements.

Feedpoint impedance at 835 MHz:      **Re{Z} = 45.6 Ω**

**Im {Z} = -4.3 Ω**

Return Loss at 835 MHz      **-23.7 dB**

#### **4. Handling**

Do not apply excessive force to the dipole arms, because they might bend. Bending of the dipole arms stresses the soldered connections near the feedpoint leading to a damage of the dipole.

#### **5. Design**

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.



#### **6. Power Test**

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

## Validation Dipole D835V2 SN455, d = 15 mm



Frequency: 835 MHz; Antenna Input Power: 250 [mW]  
 1 Phantom; Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0  
 Case: ET3DV6 - SN1507; ConvF(6.60,6.60,6.60) at 835 MHz; IEEE1528 835 MHz:  $\sigma = 0.90 \text{ mho/m}$ ,  $\epsilon_r = 42.5$ ,  $\rho = 1.00 \text{ g/cm}^3$   
 Cases (2): Peak: 3.84 mW/g  $\pm$  0.02 dB, SAR (1g): 2.46 mW/g  $\pm$  0.02 dB, SAR (10g): 1.58 mW/g  $\pm$  0.01 dB, (Worst-case extrapolation)  
 Extrapolation depth: 12.1 (11.1, 13.5) [mm]  
 Reverberation: 0.00 dB

SAR<sub>Tot</sub> [mW/g]




## Validation Dipole D835V2 SN455, d = 15 mm

Frequency: 835 MHz; Antenna Input Power: 250 [mW]  
 Phantom: Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0  
 Case: ET3DV6 - SN1507; ConvF(6.60,6.60) at 835 MHz; IEEE1528 835 MHz:  $\sigma = 0.90$  mho/m  $\epsilon_r = 42.5$   $\rho = 1.00$  g/cm<sup>3</sup>  
 Losses (2): Peak: 3.40 mW/g  $\pm 0.02$  dB, SAR (1g): 2.30 mW/g  $\pm 0.02$  dB, SAR (10g): 1.52 mW/g  $\pm 0.01$  dB, (Advanced extrapolation)  
 Stratification depth: 13.1 (12.8, 13.6) [mm]  
 Error drift: 0.00 dB




CH1 S11 1 U FS 1: 49.559  $\Omega$  -1.7637  $\Omega$  100.07 pF 835.000 000 MHz

Del  
PRM  
Cor  
Avg  
16  
↑





CH2 S11 LOG 5 dB/REF 0 dB 1:-34.735 dB 835.000 000 MHz



PRM  
Cor  
↑

## Validation Dipole D835V2 SN455, d = 15 mm

Frequency: 835 MHz; Antenna Input Power: 250 [mW]  
 Phantom: Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0  
 Case: ET3DV6 - SN1507; ConvF(6.20,6.20,6.20) at 835 MHz; IEEE1528 835 MHz:  $\sigma = 0.95$  mho/m  $\epsilon_r = 55.3$   $\rho = 1.00$  g/cm<sup>3</sup>  
 Losses (2): Peak: 3.91 mW/g  $\pm 0.01$  dB, SAR (1g): 2.53 mW/g  $\pm 0.01$  dB, SAR (10g): 1.65 mW/g  $\pm 0.01$  dB, (Worst-case extrapolation)  
 Penetration depth: 12.7 (11.6, 14.2) [mm]  
 Reverberation: 0.01 dB







## Validation Dipole D835V2 SN455, d = 15 mm

Frequency: 835 MHz; Antenna Input Power: 250 [mW]  
 Phantom: Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0  
 Model: ET3DV6 - SN1507; ConvF(6.20,6.20,6.20) at 835 MHz; IEEE1528 835 MHz;  $\sigma = 0.95$  mho/m  $\epsilon_r = 55.3$   $\rho = 1.00$  g/cm<sup>3</sup>  
 Losses (2): Peak: 3.30 mW/g  $\pm$  0.01 dB, SAR (1g): 2.31 mW/g  $\pm$  0.01 dB, SAR (10g): 1.55 mW/g  $\pm$  0.01 dB, (Advanced extrapolation)  
 Stratification depth: 14.3 (14.2, 14.5) [mm]  
 Reverberation: 0.01 dB


SAR<sub>Tot</sub> [mW/g]




CH1 S11 1 U FS 1: 45.561  $\Omega$  -4.3477  $\Omega$  43.841 pF 835.000 000 MHz

235 Meade

Del  
PRM  
Cor  
Avg  
16  
↑



CH2 S11 LOG 5 dB/REF 0 dB 1: -23.713 dB 835.000 000 MHz



PRM  
Cor  
↑

START 635.000 000 MHz

STOP 1 035.000 000 MHz

## Calibration Certificate

### 1900 MHz System Validation Dipole

Type:

**D1900V2**

Serial Number:

**5d004**

Place of Calibration:

**Zurich**

Date of Calibration:

**July 17, 2002**

Calibration Interval:

**24 months**

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:

*D. Velled*

Approved by:

*Polovic Katya*

# DASY3

## Dipole Validation Kit

Type: D1900V2

Serial: 5d004

Manufactured: February 14, 2002

Calibrated: July 17, 2002

## 1. Measurement Conditions

The measurements were performed in the flat section of the new SAM twin phantom filled with head simulating solution of the following electrical parameters at 1900 MHz:

Relative permittivity	<b>39.8</b>	$\pm 5\%$
Conductivity	<b>1.46 mho/m</b>	$\pm 10\%$

The DASY3 System (Software version 3.1d) with a dosimetric E-field probe ET3DV6 (SN:1507, conversion factor 5.2 at 1900 MHz) was used for the measurements.

The dipole feedpoint was positioned below the center marking and oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10mm from dipole center to the solution surface. The included distance holder was used during measurements for accurate distance positioning.

The coarse grid with a grid spacing of 20mm was aligned with the dipole. The 5x5x7 fine cube was chosen for cube integration. Probe isotropy errors were cancelled by measuring the SAR with normal and 90° turned probe orientations and averaging.

The dipole input power (forward power) was 250mW  $\pm 3\%$ . The results are normalized to 1W input power.

### 2.1. SAR Measurement with DASY3 System

Standard SAR-measurements were performed according to the measurement conditions described in section 1. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the worst-case extrapolation are:

averaged over 1 cm <sup>3</sup> (1 g) of tissue:	<b>44.0 mW/g</b>
averaged over 10 cm <sup>3</sup> (10 g) of tissue:	<b>22.7 mW/g</b>

### 2.2 SAR Measurement with DASY4 System



Standard SAR-measurements were performed according to the measurement conditions described in section 1. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the advanced extrapolation are:

averaged over 1 cm <sup>3</sup> (1 g) of tissue:	<b>40.4 mW/g</b>
averaged over 10 cm <sup>3</sup> (10 g) of tissue:	<b>21.3 mW/g</b>

## Validation Dipole D1900V2 SN5d004, d = 10 mm



Frequency: 1900 MHz; Antenna Input Power: 250 [mW]  
 SAM Phantom; Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0  
 Probe: ET3DV6 - SN1507; ConvF(5.20,5.20,5.20) at 1900 MHz; IEEE1528 1900 MHz:  $\sigma = 1.46$  mho/m  $\epsilon_r = 39.8$   $\rho = 1.00$  g/cm<sup>3</sup>  
 Cubes (2): Peak: 20.5 mW/g  $\pm 0.01$  dB, SAR (1g): 11.0 mW/g  $\pm 0.01$  dB, SAR (10g): 5.68 mW/g  $\pm 0.01$  dB, (Worst-case extrapolation)  
 Penetration depth: 8.1 (7.8, 8.8) [mm]  
 Powerdrift: -0.01 dB

SAR<sub>Tot</sub> [mW/g]



### Validation Dipole D1900V2 SN5d004, d = 10 mm

Frequency: 1900 MHz; Antenna Input Power: 250 [mW]  
 SAM Phantom; Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0  
 Probe: ET3DV6 - SN1507; ConvF(5.20,5.20,5.20) at 1900 MHz; IEEE1528 1900 MHz;  $\sigma = 1.46$  mho/m  $\epsilon_r = 39.8$   $\rho = 1.00$  g/cm<sup>3</sup>  
 Cubes (2): Peak: 17.7 mW/g  $\pm$  0.01 dB, SAR (1g): 10.1 mW/g  $\pm$  0.01 dB, SAR (10g): 5.32 mW/g  $\pm$  0.01 dB, (Advanced extrapolation)  
 Penetration depth: 8.7 (8.6, 8.9) [mm]  
 Powerdrift: -0.01 dB



CH1 S11 1 U FS 1: 50.549  $\Omega$  3.5332  $\Omega$  295.96  $\mu$ H 1 900.000 000 MHz

↑

Del


PRM

Cor

Avg

16

↑




CH2 S11 LOG 5 dB/REF 0 dB 1:-29.069 dB 1 900.000 000 MHz

PRM

Cor

↑



START 1 700.000 000 MHz

STOP 2 100.000 000 MHz



### 3. Dipole Impedance and Return Loss

The impedance was measured at the SMA-connector with a network analyzer and numerically transformed to the dipole feedpoint. The transformation parameters from the SMA-connector to the dipole feedpoint are:

Electrical delay:	<b>1.179 ns</b>	(one direction)
Transmission factor:	<b>0.989</b>	(voltage transmission, one direction)

The dipole was positioned at the flat phantom sections according to section 1 and the distance holder was in place during impedance measurements.

Feedpoint impedance at 1900 MHz:	$\text{Re}\{Z\} = 50.5 \Omega$
	$\text{Im}\{Z\} = 3.5 \Omega$
Return Loss at 1900 MHz	<b>- 29.1 dB</b>

### 4. Measurement Conditions

The measurements were performed in the flat section of the new SAM twin phantom filled with body simulating solution of the following electrical parameters at 1900 MHz:

Relative permittivity	<b>54.4</b>	$\pm 5\%$
Conductivity	<b>1.57 mho/m</b>	$\pm 10\%$

The DASY3 System (Software version 3.1d) with a dosimetric E-field probe ET3DV6 (SN:1507, conversion factor 4.9 at 1900 MHz) was used for the measurements.

The dipole feedpoint was positioned below the center marking and oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10mm from dipole center to the solution surface. The included distance holder was used during measurements for accurate distance positioning.

The coarse grid with a grid spacing of 20mm was aligned with the dipole. The 5x5x7 fine cube was chosen for cube integration. Probe isotropy errors were cancelled by measuring the SAR with normal and 90° turned probe orientations and averaging.

The dipole input power (forward power) was 250mW  $\pm 3\%$ . The results are normalized to 1W input power.



## **7. Handling**

Do not apply excessive force to the dipole arms, because they might bend. Bending of the dipole arms stresses the soldered connections near the feedpoint leading to a damage of the dipole.

## **8. Design**

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.



Small end caps have been added to the dipole arms in order to improve matching when loaded according to the position as explained in Section 1. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

## **9. Power Test**

After long term use with 40W radiated power, only a slight warming of the dipole near the feedpoint can be measured.



**Validation Dipole D1900V2 SN5d004, d = 10 mm**

Frequency: 1900 MHz; Antenna Input Power: 250 [mW]  
 SAM Phantom; Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0  
 Probe: ET3DV6 - SN1507; ConvF(4.90,4.90,4.90) at 1900 MHz; IEEE1528 1900 MHz:  $\sigma = 1.57$  mho/m  $\epsilon_r = 54.4$   $\rho = 1.00$  g/cm<sup>3</sup>  
 Cubes (2): Peak: 20.4 mW/g  $\pm$  0.00 dB, SAR (1g): 11.0 mW/g  $\pm$  0.01 dB, SAR (10g): 5.73 mW/g  $\pm$  0.02 dB, (Worst-case extrapolation)  
 Penetration depth: 8.5 (8.0, 9.5) [mm]  
 Powerdrift: 0.00 dB



### Validation Dipole D1900V2 SN5d004, d = 10 mm


Frequency: 1900 MHz; Antenna Input Power: 250 [mW]  
SAM Phantom; Flat Section; Grid Spacing: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Probe: ET3DV6 - SNI507; ConvF(4.90,4.90,4.90) at 1900 MHz; IEEE1528 1900 MHz;  $\sigma = 1.57$  mho/m  $\epsilon_r = 54.4$   $\rho = 1.00$  g/cm<sup>3</sup>  
Cubes (2): Peak: 17.5 mW/g  $\pm$  0.00 dB, SAR (1g): 10.1 mW/g  $\pm$  0.01 dB, SAR (10g): 5.36 mW/g  $\pm$  0.02 dB, (Advanced extrapolation)  
Penetration depth: 9.3 (9.1, 9.6) [mm]  
Powerdrift: 0.00 dB




CH1 S11 1 U FS 1: 45.686  $\Omega$  3.6289  $\Omega$  303.98  $\mu$ H 1 900.000 000 MHz

Mosde

Del  
PRM  
Cor  
Avg  
16  
↑



CH2 S11 LOG 5 dB/REF 0 dB 1:-25.882 dB 1 900.000 000 MHz



PRM  
Cor  
↑

START 1 700.000 000 MHz

STOP 2 100.000 000 MHz