



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Orchestra of Lights-Lightshow Tree and Speaker

Model: 113341

Brand: Gemmy

Test Report Number:

C180509Z09-RP1-2

Issued for

GEMMY INDUSTRIES (HK)LIMITED BVI

**No.301 on 3rd Floor, East Ocean Centre, No.98 Granville Road, Kowloon,
Hong Kong**

Issued by:

COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.

**No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd.,
Guan Lan Town, Baoan District, Shenzhen China**

TEL: 86-755-28055000

FAX: 86-755-28055221

E-Mail: service@ccssz.com

Issued Date: June 12, 2018



Certificate Number: 2861.01

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST, CNAS or any government agencies. The test result of this report relate only to the tested sample identified in this report.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	June 12, 2018	Initial Issue	ALL	Amzula Chen



TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION..... 4

2 TEST RESULT SUMMARY 5

3 EUT DESCRIPTION 6

4 TEST METHODOLOGY 7

 4.1. DESCRIPTION OF TEST MODES 7

5 SETUP OF EQUIPMENT UNDER TEST 8

 5.1. SETUP CONFIGURATION OF EUT 8

 5.2. SUPPORT EQUIPMENT 8

 5.3. TEST INSTRUMENTS..... 9

6 FACILITIES AND ACCREDITATIONS..... 11

 6.1. FACILITIES 11

 6.2. ACCREDITATIONS..... 11

 6.3. MEASUREMENT UNCERTAINTY 11

7 FCC PART 15.247 REQUIREMENTS 12

 7.1. 20DB BANDWIDTH 12

 7.2. ANTENNA GAIN 16

 7.3. PEAK POWER..... 17

 7.4. PEAK POWER SPECTRAL DENSITY 19

 7.5. BAND EDGES MEASUREMENT 20

 7.6. FREQUENCY SEPARATION 29

 7.7. NUMBER OF HOPPING FREQUENCY 32

 7.8. TIME OF OCCUPANCY (DWELL TIME) 34

 7.9. PURIOUS EMISSIONS 41

 7.10. POWERLINE CONDUCTED EMISSIONS 64



1 TEST RESULT CERTIFICATION

Product	Orchestra of Lights-Lightshow Tree and Speaker
Model	113341
Brand	Gemmy
Tested	May 9~June 11, 2018
Applicant	GEMMY INDUSTRIES (HK) LIMITED BVI No.301 on 3rd Floor, East Ocean Centre, No.98 Granville Road, Kowloon, Hong Kong
Manufacturer	ZAIXING ELECTRONIC (SHENZHEN) CO., LTD. 3#, 1st Road Yang Yong, Shapu Community, Songgang, Baoan District, Shenzhen City, Guangdong Province, China. DynaTech Co. Ltd 259-261 Xincheng Road, Qiaotou Town, Dongguan, Guangdong, China

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.10: 2013** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Eve Wang
Supervisor of EMC Dept.
Compliance Certification Services (Shenzhen) Inc.

Nancy Fu
Supervisor of Report Dept.
Compliance Certification Services (Shenzhen) Inc.



2 TEST RESULT SUMMARY

APPLICABLE STANDARDS			
Standard	Test Type	Result	Remark
15.247(a)(1)	20dB Bandwidth Measurement	Pass	Meet the requirement of limit.
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.
15.247(a)(1)	Frequency Separation	Pass	Meet the requirement of limit.
15.247(a)(1)(ii)	Number Of Hopping Frequency	Pass	Meet the requirement of limit.
15.247(a)(1)(iii)	Time Of Occupancy (Dwell Time)	Pass	Meet the requirement of limit.
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.
15.247(d)	<ul style="list-style-type: none">● Spurious Emissions● Conducted Measurement● Radiated Emissions	Pass	Meet the requirement of limit.
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.

Note:

1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.
2. The information of measurement uncertainty is available upon the customer's request.



3 EUT DESCRIPTION

Product	Orchestra of Lights-Lightshow Tree and Speaker
Model Number	113341
Brand	Gemmy
Model Discrepancy	N/A
Identify Number	C180509Z09-RP1-2
Received Date	May 9, 2018
Power Supply	DC12V Supply by the adapter
Adapter Model & Manufacturer	TS-36W12V AC Input: AC120V~60Hz, 0.64A DC Output: DC12V, 3A DC Output Cable: Unshielded 1.70m
Frequency Range	2402 ~ 2480 MHz
Transmit Power	GFSK: -1.10dBm $\pi/4$ -DQPSK: 0.11dBm
Modulation Technique	FHSS (GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps)
Number of Channels	79 Channels
Antenna Specification	Internal Antenna with 0dBi gain(MAX)
Temperature Range	-20°C ~ +70°C
Hardware Version	113341-USA(V1)
Software Version	113341-USA(V1)

Note: This submittal(s) (test report) is intended for FCC ID: 2AGG8113341 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



4 TEST METHODOLOGY

4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. FCCAssist 1.5.exe

Used the “FCCAssist 1.5.exe” software to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Test Item	Test mode	Worse mode
Conducted Emission	Mode 1: Normal	<input type="checkbox"/>
	Mode 2: Woking by WiFi	<input type="checkbox"/>
	Mode 3: Woking by BT	<input checked="" type="checkbox"/>
Radiated Emission	Mode 1: TX	<input checked="" type="checkbox"/>

Note:

1. Channel Low (2402MHz) and Mid (2441MHz) were chosen for pre-testing for GFSK and $\pi/4$ -DQPSK, GFSK were the worse case and print in the report.
2. Radiated band edges were tested with both fixed and hopping mode, the fixed mode was the worse case and recorded in the report.



5 SETUP OF EQUIPMENT UNDER TEST

5.1. SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

5.2. SUPPORT EQUIPMENT

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Orchestra of Lights-Indoor Hub	114357	N/A	DoC	Gemmy	DoC	Unshielded 1.80m
2	WiFi Router	WR7502	WR7502162100 045	DoC	MTC	N/A	Unshielded 1.50m
3	Smartphone	MLA-AL10	N/A	DoC	HUAWEI	N/A	N/A
5	Notebook	E335	R9-WN1EF	DoC	Thinkpad	Unshielded 3.00m	Unshielded 1.50m (AC Cable) Shielded 1.60m (DC Cable)

Notes:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



5.3. TEST INSTRUMENTS

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	01/27/2018	01/26/2019
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	01/27/2018	01/26/2019
LISN	EMCO	3825/2	8901-1459	01/27/2018	01/26/2019
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	01/29/2018	01/28/2019
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

Radiated Emission Test Site 966 (2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	01/27/2018	01/26/2019
Amplifier	EMEC	EM330	060661	01/27/2018	01/26/2019
High Noise Amplifier	Agilent	8449B	3008A01838	01/27/2018	01/26/2019
Loop Antenna	COM-POWER	AL-130	121044	01/30/2018	01/29/2019
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2018	02/20/2019
Horn Antenna	SCHWARZBECK	BBHA9120	D286	01/27/2018	01/26/2019
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	01/24/2018	01/23/2019
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	01/29/2018	01/28/2019
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

20dB Bandwidth					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Peak Output Power					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Power Meter	Anritsu	ML2495A	1204003	01/27/2018	01/26/2019
Power Sensor	Anritsu	MA2411B	1126150	01/27/2018	01/26/2019



Frequency Separation					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Number Of Hopping Frequency					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Time Of Occupancy (Dwell Time)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Band edges					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Antenna Conducted Spurious Emission					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.



6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at

- No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China**

The sites are constructed in conformance with the requirements of ANSI C63.10:2013, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA	A2LA
China	CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA	FCC
Japan	VCCI(C-4815, R-4320, T-2317, G-10624)
Canada	INDUSTRY CANADA

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccssz.com>

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.9211dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.9037dB
Radiated Emission, 1 to 8 GHz	+/-5.3516dB
Radiated Emission, 8 to 18 GHz	+/-5.3894dB
Conducted Emissions	+/-4.1742dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.




7 FCC PART 15.247 REQUIREMENTS

7.1. 20DB BANDWIDTH

No limits

Remark: Each piece of equipment is scheduled for calibration once a year.

7.1.1. TEST CONFIGURATION



7.1.2. TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT, and then connect a low loss RF cable from antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=30 kHz, VBW=100 kHz, Span=3MHz, Sweep = auto.
4. Mark the peak frequency and 20dB (upper and lower) frequency.
5. Repeat until all the test channels are investigated.

7.1.3. TEST RESULTS

No non-compliance noted

GFSK

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
Low	2402	0.8593
Mid	2441	0.8582
High	2480	0.8586

$\pi/4$ -DQPSK


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
Low	2402	1.2260
Mid	2441	1.2290
High	2480	1.2270




Test plot

GFSK

20dB Bandwidth(CH Low)




20dB Bandwidth (CH Mid)






20dB Bandwidth (CH High)




$\pi/4$ -DQPSK

20dB Bandwidth (CH Low)






20dB Bandwidth (CH Mid)



20dB Bandwidth (CH High)





7.2. ANTENNA GAIN

7.2.1. MEASUREMENT

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal BT devices, the GFSK mode is used.

7.2.2. MEASUREMENT PARAMETERS

Measurement parameter	
Detector	Peak
Sweep time	Auto
Resolution bandwidth	3 MHz
Video bandwidth	3 MHz
Trace-Mode	Max hold

7.2.3. LIMITS

FCC	IC
Antenna Gain	
6 dBi	

7.2.4. TEST RESULTS

GFSK

T _{nom}	V _{nom}	Lowest channel 2402MHz	Middle channel 2441MHz	Highest channel 2480MHz
Conducted power [dBm] Measured with GFSK modulation		-1.11	-1.23	-1.56
Radiated power [dBm] Measured with GFSK modulation		-1.24	-1.37	-1.83
Gain [dBi] Calculated		-0.13	-0.14	-0.47
Measurement uncertainty		± 1.5 dB (cond.) / ± 3 dB (rad.)		

π/4-DQPSK

T _{nom}	V _{nom}	Lowest channel 2402MHz	Middle channel 2441MHz	Highest channel 2480MHz
Conducted power [dBm] Measured with GFSK modulation		-1.14	0.11	-0.18
Radiated power [dBm] Measured with GFSK modulation		-1.35	0.07	-0.83
Gain [dBi] Calculated		-0.21	-0.04	-0.65
Measurement uncertainty		± 1.5 dB (cond.) / ± 3 dB (rad.)		




7.3. PEAK POWER

7.3.1. LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.
3. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.3.2. TEST CONFIGURATION



7.3.3. TEST PROCEDURE

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.



7.3.4. TEST RESULTS

No non-compliance noted

Test Data

GFSK

Channel	Frequency (MHz)	Reading Power (dBm)	Cable loss (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Peak /AVG	Result
Low	2402	-4.60	3.50	-1.10	0.00078	0.125	peak	PASS
Mid	2441	-4.73	3.50	-1.23	0.00075			PASS
High	2480	-5.06	3.50	-1.56	0.00070			PASS
Low	2402	-5.39	3.50	-1.89	0.00065	0.125	AVG	PASS
Mid	2441	-5.43	3.50	-1.93	0.00064			PASS
High	2480	-5.61	3.50	-2.11	0.00062			PASS

$\pi/4$ -DQPSK

Channel	Frequency (MHz)	Reading Power (dBm)	Cable loss (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Peak /AVG	Result
Low	2402	-4.64	3.50	-1.14	0.00077	0.125	peak	PASS
Mid	2441	-3.39	3.50	0.11	0.00103			PASS
High	2480	-3.68	3.50	-0.18	0.00096			PASS
Low	2402	-6.18	3.50	-2.68	0.00054	0.125	AVG	PASS
Mid	2441	-5.82	3.50	-2.32	0.00059			PASS
High	2480	-6.09	3.50	-2.59	0.00055			PASS




7.4. PEAK POWER SPECTRAL DENSITY

7.4.1. LIMIT

1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

7.4.2. TEST CONFIGURATION



7.4.3. TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.4.4. TEST RESULTS

Not applicable. Since EUT is the Bluetooth device.




7.5. BAND EDGES MEASUREMENT

7.5.1. LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

7.5.2. TEST CONFIGURATION



7.5.3. TEST PROCEDURE


1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz / VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=1/T / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.



7.5.4. TEST RESULTS

Refer to attach spectrum analyzer data chart.




Test Data (GFSK)







No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2390.000	53.95	-2.86	51.09	74.00	-22.91	Peak	Horizontal
2	2402.300	93.09	-2.80	90.29	---	---	Peak	Horizontal
1	2390.000	42.11	-2.86	39.25	54.00	-14.75	Average	Horizontal
2	2402.200	92.57	-2.80	89.77	---	---	Average	Horizontal



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2480.325	84.71	-2.37	82.34	---	---	Peak	Vertical
2	2483.500	53.54	-2.35	51.19	74.00	-22.81	Peak	Vertical
1	2480.125	83.49	-2.37	81.12	---	---	Average	Vertical
2	2483.500	42.31	-2.35	39.96	54.00	-14.04	Average	Vertical



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2480.325	95.37	-2.37	93.00	---	---	Peak	Horizontal
2	2483.500	55.90	-2.35	53.55	74.00	-20.45	Peak	Horizontal
1	2480.150	94.43	-2.37	92.06	---	---	Average	Horizontal
2	2483.500	46.66	-2.35	44.31	54.00	-9.69	Average	Horizontal




$\pi/4$ -DQPSK

Band Edges (CH Low)


Detector mode: Peak

Polarity: Vertical





Detector mode: Average


Polarity: Vertical





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2390.000	53.47	-2.86	50.61	74.00	-23.39	Peak	Vertical
2	2402.200	83.03	-2.80	80.23	---	---	Peak	Vertical
1	2390.000	41.93	-2.86	39.07	54.00	-14.93	Average	Vertical
2	2402.100	78.98	-2.80	76.18	---	---	Average	Vertical



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2390.000	53.92	-2.86	51.06	74.00	-22.94	Peak	Horizontal
2	2402.100	93.19	-2.80	90.39	---	---	Peak	Horizontal
1	2390.000	42.52	-2.86	39.66	54.00	-14.34	Average	Horizontal
2	2402.100	89.16	-2.80	86.36	---	---	Average	Horizontal



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2480.175	83.40	-2.37	81.03	---	---	Peak	Vertical
2	2483.500	50.99	-2.35	48.64	74.00	-25.36	Peak	Vertical
1	2480.125	80.57	-2.37	78.20	---	---	Average	Vertical
2	2483.500	42.16	-2.35	39.81	54.00	-14.19	Average	Vertical



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2480.250	95.67	-2.37	93.30	---	---	Peak	Horizontal
2	2483.500	56.19	-2.35	53.84	74.00	-20.16	Peak	Horizontal
1	2480.150	91.75	-2.37	89.38	---	---	Average	Horizontal
2	2483.500	45.78	-2.35	43.43	54.00	-10.57	Average	Horizontal




7.6. FREQUENCY SEPARATION

7.6.1. LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

7.6.2. TEST CONFIGURATION



7.6.3. TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW=30kHz, VBW=30kHz, Adjust Span to 4 MHz, Sweep = auto.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

7.6.4. TEST RESULTS

No non-compliance noted


Test Data


GFSK

Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	572.867	> Two-thirds of the 20 dB Bandwidth	Pass

$\pi/4$ -DQPSK

Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	819.333	> Two-thirds of the 20 dB Bandwidth	Pass








7.7. NUMBER OF HOPPING FREQUENCY

7.7.1. LIMIT

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

7.7.2. TEST CONFIGURATION



7.7.3. TEST PROCEDURE

- Place the EUT on the table and set it in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- Set spectrum analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = 1ms.
- Set the spectrum analyzer as RBW, VBW=300kHz,
- Max hold, view and count how many channel in the band.

7.7.4. TEST RESULTS

No non-compliance noted


Test Data

Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS



Test Plot

Channel Number






7.8. TIME OF OCCUPANCY (DWELL TIME)

7.8.1. LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4s multiplied by the number of hopping channels employed.

7.8.2. TEST CONFIGURATION



7.8.3. TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.



7.8.4. TEST RESULTS

No non-compliance noted

Test Data

GFSK

DH 1

CH Mid: $0.416 * (1600/2)/79 * 31.6 = 133.1200(\text{ms})$

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.416	133.120	31.60	400.00	PASS

DH 3

CH Mid: $1.675 * (1600/4)/79 * 31.6 = 268.000 (\text{ms})$

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.675	268.000	31.60	400.00	PASS

DH 5

CH Mid: $2.940 * (1600/6)/79 * 31.6 = 313.600 (\text{ms})$

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	2.940	313.600	31.60	400.00	PASS



$\pi/4$ -DQPSK

2DH 1

CH Mid: $0.426 * (1600/2)/79 * 31.6 = 136.320(\text{ms})$

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.426	136.320	31.60	400.00	PASS

2DH 3

CH Mid: $1.682 * (1600/4)/79 * 31.6 = 269.1200 (\text{ms})$

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.682	269.120	31.60	400.00	PASS

2DH 5

CH Mid: $2.932 * (1600/6)/79 * 31.6 = 312.747(\text{ms})$

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	2.932	312.747	31.60	400.00	PASS




Test Plot

GFSK


DH 1


CH Mid





DH 3

CH Mid












7.9. SPURIOUS EMISSIONS

7.9.1. CONDUCTED MEASUREMENT

7.9.1.1. LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

7.9.1.2. TEST CONFIGURATION



7.9.1.3. TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 9 kHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels, and highest channels. No emission found between lowest internal used/generated frequency to 10MHz , it is only recorded 10MHz to 26GHz.


7.9.1.4. TEST RESULTS


No non-compliance noted

Remark: *The hopping on mode and hopping off mode were chosen for pre-test and the hopping off mode was the worse case and print in the report.*




Hopping Off








CH High (10MHz ~26.5GHz)




CH High (2.475GHz ~ 2.5GHz)






$\pi/4$ -DQPSK

CH Low (10MHz ~26.5GHz)




CH Low (2.31GHz ~2.41GHz)








CH High (10MHz ~26.5GHz)



CH High (2.475GHz ~ 2.5GHz)






Hopping On


GFSK

CH Low (2.31GHz ~2.5GHz)



$\pi/4$ -DQPSK

CH Low (2.31GHz ~2.5GHz)





7.9.2. RADIATED EMISSIONS MEASUREMENT

7.9.1.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength ($\mu\text{V}/\text{m}$ at 3-meter)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$ at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54




7.9.1.2. TEST CONFIGURATION

Below 30MHz




Below 1 GHz





Above 1 GHz



7.9.1.3. MEASURING SETTING

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/T for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/T for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP



7.9.1.4. TEST PROCEDURE

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Pre measurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the pre measurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on



the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Pre measurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.



--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Pre measurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height scan range is 1 meter to 2.5 meter.

--- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.

--- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.



--- The measurement distance is 1 meter.

--- The EUT was set into operation.

Pre measurement:

--- The antenna is moved spherical over the EUT in different polarisations of the antenna.

Final measurement:

--- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.

--- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.



7.9.1.5. TEST RESULTS

Below 1 GHz

Test Mode: TX / GFSK(CH Low)

Tested by: Darry Wu

Ambient temperature: 24°C **Relative humidity:** 52% RH

Date: June 8, 2018


Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
34.8500	37.89	-14.50	23.39	40.00	-16.61	V	QP
41.6400	41.58	-17.37	24.21	40.00	-15.79	V	QP
64.9200	43.76	-24.82	18.94	40.00	-21.06	V	QP
133.7900	40.67	-20.94	19.73	43.50	-23.77	V	QP
879.7200	29.40	-9.98	19.42	46.00	-26.58	V	QP
980.6000	30.90	-9.21	21.69	54.00	-32.31	V	QP
31.9400	32.46	-12.80	19.66	40.00	-20.34	H	QP
108.5700	45.67	-22.09	23.58	43.50	-19.92	H	QP
138.6400	43.29	-21.18	22.11	43.50	-21.39	H	QP
340.4000	34.03	-18.13	15.90	46.00	-30.10	H	QP
407.3300	31.96	-15.74	16.22	46.00	-29.78	H	QP
872.9300	30.14	-10.20	19.94	46.00	-26.06	H	QP

Notes:

1. No emission found between lowest internal used/generated frequency to 30MHz.
2. Pre-scan all mode and recorded the worst case results in this report (TX (Low Channel))

Remark:

1. Radiated emissions measured in frequency range from 9 kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
2. Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. The IF bandwidth of Receiver between 30MHz to 1GHz was 120 kHz.
4. Frequency (MHz). = Emission frequency in MHz
 Reading (dBuV/m) = Receiver reading
 Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
 Limit (dBuV/m) = Limit stated in standard
 Margin (dB) = Measured (dBuV/m) – Limits (dBuV/m)
 Antenna Pole (H/V) = Current carrying line of reading





Above 1 GHz

GFSK

Test Mode: TX(CH Low)

Tested by: Darry Wu

Ambient temperature: 24°C **Relative humidity:** 52% RH

Date: June 25, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1900.000	47.53	-5.63	41.90	74.00	-32.10	V	peak
2494.000	46.33	-2.29	44.04	74.00	-29.96	V	peak
3394.000	43.59	-0.70	42.89	74.00	-31.11	V	peak
4078.000	44.73	1.86	46.59	74.00	-27.41	V	peak
5104.000	42.63	5.17	47.80	74.00	-26.20	V	peak
5761.000	42.75	5.98	48.73	74.00	-25.27	V	peak
2539.000	46.32	-2.19	44.13	74.00	-29.87	H	Peak
3376.000	44.17	-0.73	43.44	74.00	-30.56	H	Peak
4123.000	43.26	2.02	45.28	74.00	-28.72	H	Peak
4798.000	45.27	4.32	49.59	74.00	-24.41	H	peak
5140.000	41.44	5.23	46.67	74.00	-27.33	H	peak
5617.000	42.04	5.92	47.96	74.00	-26.04	H	peak

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- Spectrum setting:
 - Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 3MHz, Sweep time = auto.
 - AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.
- | | |
|------------------------|--|
| Frequency (MHz) | = Emission frequency in MHz |
| Reading (dBμV/m) | = Uncorrected Analyzer / Receiver Reading |
| Correction Factor (dB) | = Antenna factor + Cable loss – Amplifier gain |
| Limit (dBμV/m) | = Limit stated in standard |
| Margin (dB) | = Result (dBμV/m)- Limit (dBμV/m) |
| Peak | =Peak Reading |
| AVG. | =Average Reading |
| Remark | = Mark Peak Reading or Average Reading |



Test Mode: TX(CH Mid)

Tested by: Darry Wu

Ambient temperature: 24°C

Relative humidity: 52% RH

Date: June 25, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2566.000	45.89	-2.14	43.75	74.00	-30.25	V	peak
3799.000	43.73	0.74	44.47	74.00	-29.53	V	peak
4519.000	42.10	3.41	45.51	74.00	-28.49	V	peak
5320.000	41.53	5.55	47.08	74.00	-26.92	V	peak
5761.000	42.42	5.98	48.40	74.00	-25.60	V	peak
6481.000	41.54	6.86	48.40	74.00	-25.60	V	peak
2530.000	46.98	-2.21	44.77	74.00	-29.23	H	Peak
3853.000	43.29	0.97	44.26	74.00	-29.74	H	Peak
4780.000	42.41	4.26	46.67	74.00	-27.33	H	Peak
4879.000	42.59	4.59	47.18	74.00	-26.82	H	peak
5383.000	41.72	5.66	47.38	74.00	-26.62	H	peak
5950.000	41.60	6.06	47.66	74.00	-26.34	H	peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 3MHz, Sweep time = auto.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.
5. Frequency (MHz). = Emission frequency in MHz
 Reading (dBuV/m) = Uncorrected Analyzer / Receiver Reading
 Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
 Limit (dBuV/m) = Limit stated in standard
 Margin (dB) = Result (dBuV/m)- Limit (dBuV/m)
 Peak =Peak Reading
 AVG. =Average Reading
 Remark = Mark Peak Reading or Average Reading



Test Mode: TX(CH High)

Tested by: Darry Wu

Ambient temperature: 24°C

Relative humidity: 52% RH

Date: June 25, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3772.000	44.20	0.63	44.83	74.00	-29.17	V	peak
4213.000	43.21	2.34	45.55	74.00	-28.45	V	peak
4960.000	42.54	4.85	47.39	74.00	-26.61	V	peak
5626.000	41.56	5.92	47.48	74.00	-26.52	V	peak
5761.000	42.69	5.98	48.67	74.00	-25.33	V	peak
6013.000	42.28	6.10	48.38	74.00	-25.62	V	peak
2521.000	46.00	-2.22	43.78	74.00	-30.22	H	Peak
4330.000	43.80	2.75	46.55	74.00	-27.45	H	Peak
4690.000	43.14	3.97	47.11	74.00	-26.89	H	Peak
4960.000	45.66	4.85	50.51	74.00	-23.49	H	peak
5626.000	42.06	5.92	47.98	74.00	-26.02	H	peak
6481.000	41.39	6.86	48.25	74.00	-25.75	H	peak

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- Spectrum setting:
 - Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 3MHz, Sweep time = auto.
 - AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.
- | | |
|------------------------|--|
| Frequency (MHz) | = Emission frequency in MHz |
| Reading (dBμV/m) | = Uncorrected Analyzer / Receiver Reading |
| Correction Factor (dB) | = Antenna factor + Cable loss – Amplifier gain |
| Limit (dBμV/m) | = Limit stated in standard |
| Margin (dB) | = Result (dBμV/m)- Limit (dBμV/m) |
| Peak | =Peak Reading |
| AVG. | =Average Reading |
| Remark | = Mark Peak Reading or Average Reading |



$\pi/4$ -DQPSK

Test Mode: TX(CH Low)

Tested by: Darry Wu

Ambient temperature: 24°C

Relative humidity: 52% RH

Date: June 25, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2521.000	46.70	-2.22	44.48	74.00	-29.52	V	peak
3088.000	44.98	-1.21	43.77	74.00	-30.23	V	peak
4177.000	43.77	2.21	45.98	74.00	-28.02	V	peak
4690.000	42.41	3.97	46.38	74.00	-27.62	V	peak
5167.000	41.54	5.28	46.82	74.00	-27.18	V	peak
5761.000	43.09	5.98	49.07	74.00	-24.93	V	peak
2611.000	46.39	-2.06	44.33	74.00	-29.67	H	Peak
4222.000	41.93	2.37	44.30	74.00	-29.70	H	Peak
4798.000	45.36	4.32	49.68	74.00	-24.32	H	Peak
5491.000	41.10	5.85	46.95	74.00	-27.05	H	peak
6112.000	41.71	6.26	47.97	74.00	-26.03	H	peak
6841.000	41.68	7.44	49.12	74.00	-24.88	H	peak

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- Spectrum setting:
 - Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 3MHz, Sweep time = auto.
 - AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.
- | | |
|------------------------|--|
| Frequency (MHz). | = Emission frequency in MHz |
| Reading (dBμV/m) | = Uncorrected Analyzer / Receiver Reading |
| Correction Factor (dB) | = Antenna factor + Cable loss – Amplifier gain |
| Limit (dBμV/m) | = Limit stated in standard |
| Margin (dB) | = Result (dBμV/m)- Limit (dBμV/m) |
| Peak | =Peak Reading |
| AVG. | =Average Reading |
| Remark | = Mark Peak Reading or Average Reading |



Test Mode: TX(CH Mid)

Tested by: Darry Wu

Ambient temperature: 24°C Relative humidity: 52% RH

Date: June 25, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3745.000	44.34	0.51	44.85	74.00	-29.15	V	peak
4330.000	42.53	2.75	45.28	74.00	-28.72	V	peak
4879.000	43.33	4.59	47.92	74.00	-26.08	V	peak
5131.000	43.04	5.21	48.25	74.00	-25.75	V	peak
5707.000	41.91	5.96	47.87	74.00	-26.13	V	peak
6328.000	41.69	6.61	48.30	74.00	-25.70	V	peak
2521.000	47.12	-2.22	44.90	74.00	-29.10	H	Peak
3079.000	45.56	-1.23	44.33	74.00	-29.67	H	Peak
3700.000	43.97	0.32	44.29	74.00	-29.71	H	Peak
4735.000	42.95	4.12	47.07	74.00	-26.93	H	peak
4879.000	46.30	4.59	50.89	74.00	-23.11	H	peak
5707.000	41.78	5.96	47.74	74.00	-26.26	H	peak

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- Spectrum setting:
 - Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 3MHz, Sweep time = auto.
 - AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.
- | | |
|------------------------|--|
| Frequency (MHz) | = Emission frequency in MHz |
| Reading (dBμV/m) | = Uncorrected Analyzer / Receiver Reading |
| Correction Factor (dB) | = Antenna factor + Cable loss – Amplifier gain |
| Limit (dBμV/m) | = Limit stated in standard |
| Margin (dB) | = Result (dBμV/m)- Limit (dBμV/m) |
| Peak | =Peak Reading |
| AVG. | =Average Reading |
| Remark | = Mark Peak Reading or Average Reading |



Test Mode: TX(CH High)

Tested by: Darry Wu

Ambient temperature: 24°C

Relative humidity: 52% RH

Date: June 25, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2539.000	47.06	-2.19	44.87	74.00	-29.13	V	peak
3367.000	45.81	-0.74	45.07	74.00	-28.93	V	peak
4294.000	43.41	2.62	46.03	74.00	-27.97	V	peak
4762.000	43.07	4.20	47.27	74.00	-26.73	V	peak
5140.000	42.15	5.23	47.38	74.00	-26.62	V	peak
6013.000	41.81	6.10	47.91	74.00	-26.09	V	peak
1909.000	47.84	-5.58	42.26	74.00	-31.74	H	Peak
2242.000	45.65	-3.67	41.98	74.00	-32.02	H	Peak
2512.000	47.02	-2.24	44.78	74.00	-29.22	H	Peak
4348.000	43.55	2.81	46.36	74.00	-27.64	H	peak
4960.000	45.96	4.85	50.81	74.00	-23.19	H	peak
5266.000	42.54	5.45	47.99	74.00	-26.01	H	peak

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- Spectrum setting:
 - Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 3MHz, Sweep time = auto.
 - AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.
- | | |
|------------------------|--|
| Frequency (MHz). | = Emission frequency in MHz |
| Reading (dBuV/m) | = Uncorrected Analyzer / Receiver Reading |
| Correction Factor (dB) | = Antenna factor + Cable loss – Amplifier gain |
| Limit (dBuV/m) | = Limit stated in standard |
| Margin (dB) | = Result (dBuV/m)- Limit (dBuV/m) |
| Peak | =Peak Reading |
| AVG. | =Average Reading |
| Remark | = Mark Peak Reading or Average Reading |



7.10. POWERLINE CONDUCTED EMISSIONS


7.10.1. LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

7.10.2. TEST CONFIGURATION



See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.



7.10.3. TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.


7.10.4. TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.



7.10.5. TEST DATA

Model No.	113341	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 3
Tested by	Evan Ai	Line	L
Test Date	June 2, 2018	Test Voltage	AC120V/60Hz




Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.4620	35.02	22.53	19.54	54.56	42.07	56.66	46.66	-2.10	-4.59	Pass
0.5740	24.52	9.52	19.56	44.08	29.08	56.00	46.00	-11.92	-16.92	Pass
1.3980	23.39	10.53	19.62	43.01	30.15	56.00	46.00	-12.99	-15.85	Pass
1.9740	21.28	9.01	19.72	41.00	28.73	56.00	46.00	-15.00	-17.27	Pass
3.3740	21.02	10.68	19.72	40.74	30.40	56.00	46.00	-15.26	-15.60	Pass
12.1380	32.07	14.96	20.09	52.16	35.05	60.00	50.00	-7.84	-14.95	Pass

REMARKS: L = Line One (Live Line)



Model No.	113341	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 3
Tested by	Evan Ai	Line	N
Test Date	June 2, 2018	Test Voltage	AC120V/60Hz



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.3420	31.18	19.55	19.54	50.72	39.09	59.15	49.15	-8.43	-10.06	Pass
0.4580	31.66	16.01	19.53	51.19	35.54	56.73	46.73	-5.54	-11.19	Pass
0.7700	22.25	7.37	19.60	41.85	26.97	56.00	46.00	-14.15	-19.03	Pass
0.9540	21.69	10.37	19.56	41.25	29.93	56.00	46.00	-14.75	-16.07	Pass
3.3740	20.38	10.62	19.77	40.15	30.39	56.00	46.00	-15.85	-15.61	Pass
12.0820	32.17	19.05	20.09	52.26	39.14	60.00	50.00	-7.74	-10.86	Pass

REMARKS: N = Line Two (Neutral Line)