

April 4, 2008

TEE
 24175 Research Dr.
 Farmington Hills, MI 48335-2642
 Tel 248.478.7210
 Fax 248.478.7241

RE: Certification for Honda MY09 FSK Highline TPM Sensor

Model #: 217652-112
 FCC ID: GQ4-37T
 Canada IC: 1470A-18T

GENERAL DESCRIPTION

This transmitter is a transmitter device with tire valve, which is mounted in the valve hole of the wheel rim and transmits the pressure and temperature inside the tire, the battery voltage of the transmitter, and the tire identification code (ID) at normal and abnormal condition with the radio wave (RF) that conforms to the used area. Also this device has a countermeasure function such as the random delay of transmission time so that the RF signal from each tire will not interfere due to the simultaneous transmission. The transmitter device also has a Low Frequency (LF) receiver. This receiver supports Low Frequency (LF) magnetic field communications allowing the changing of measurement/monitoring states of the transmitter by commands sent via the TPM diagnostic tool. The RF signal operates at 315MHz and uses FSK Manchester code modulation. 217652-112 transmits 5 RF packets every 1 minute.

Description of Operations

P/N	Consumer's Use Mode	Mfg. Modes	Mode of Operation	Explanation	Frequency of Transmission
217652-112	X		Storage Mode	No transmission. Measures temperature and pressure.	5 words whenever LF activation occurs
217652-112	X		Normal Mode	Measures temperature and pressure. Transmits periodically. Enters this mode from storage when a LF command has been sent.	5 words every 1 minute, 5 words LF activation occurs
217652-112	X		Alert Mode	Transmits when: a) significant pressure delta detected b) high temperature is detected	10 words every 4 seconds for 1 minute
217652-112		X	Mfg. Mode	Used to test soldering on LF coils.	5 words whenever LF activation occurs