

Testing and certification of, consultancy and research concerning, electronic and electric appliances, systems, installations and telecommunication systems

TEST REPORT CONCERNING THE COMPLIANCE OF A RECEIVER FOR A REMOTE KEYLESS ENTRY SYSTEM (RKE), BRAND TRW, MODEL 41R, WITH 47 CFR PART 15 (2006-08-14).

FCC listed: 90828Industry Canada: IC3501VCCI registered: R-1518, C-1598

TNO Electronic Products & Services (EPS) B.V. P.O. Box 15 9822 ZG Niekerk (NL) Smidshornerweg 18 9822 TL Niekerk (NL)

Telephone: +31 594 505005 Telefax: +31 594 504804

E-mail: info@tno-eps.com

Project number: 07052303.FCC2amd1



MEASUREMENT/TECHNICAL REPORT

TRW Automotive

Model: 41R

FCC ID: GQ4-41R

May 29, 2007

This report concerns:	Original grant/certification Cl	ass 2 change –	Verification	
Equipment type:	Receiver for a Remote Keyless	Entry System (RKE)	
Deferred grant requested	per 47 CFR 0.457(d)(1)(ii) ?	Yes	No	n.a.
Report prepared by:	Name Company name Address Postal code/city Mailing address Postal code/city Country Telephone number Telefax number E-mail	: O.H. Hoe : TNO Elec : Smidshor : 9822 TL : P.O. Box : 9822 ZG : The Neth : + 31 594 : + 31 594 : info@tno	ctronic Products & nerweg 18 Niekerk 15 Niekerk erlands 505 005 504 804	& Services (EPS) B.V.

The data taken for this test and report herein was done in accordance with 47 CFR Part 15 and the measurement procedures of ANSI C63.4-2003. TNO Electronic Products & Services (EPS) B.V. at Niekerk, The Netherlands, certifies that the data is accurate and contains a true representation of the emission profile of the Equipment Under Test (EUT) on the date of the test as noted in the test report. I have reviewed the test report and find it to be an accurate description of the test(s) performed and the EUT so tested.

Date: May 29, 2007



Signature:

diens

H.J. Pieters Project Manager TNO Electronic Products & Services (EPS) B.V.



Description of test item

Test item	:	Receiver for a Remote Keyless Entry System (RKE)
Manufacturer	:	TRW Automotive
Brand	:	TRW
Model	:	41R
Serial number(s)	:	-
Revision	:	Rev. A
Receipt date	:	May 25, 2007
Applicant information		
Applicant's representative	:	Mr. M. Koskella
Company	:	TRW Automotive
Address	:	24175 Research Drive
Destal and		MI 49225 2642

Address	:	241/5 Research Drive
Postal code	:	MI 48335-2642
City	:	Farmington Hills
PO-box	:	-
Postal code	:	-
City	:	-
Country	:	United States of America
Telephone number	:	+1 248 442 5304
Telefax number	:	+1 248 478 7241

Test(s) performed

Location Test(s) started Test(s) completed Purpose of test(s)	:	Niekerk May 29, 2007 May 29, 2007 Equipment Authorisatio	n (Certification).
Test specification(s)	:	47 CFR Part 15 (2006-0	8-14)
Test engineers	:	O.H. Hoekstra	(Y) Neelshi
Report written by	:	O.H. Hoekstra	UPI Plotonic
Report date	:	May 29 , 2007	

This report is in conformity with NEN-EN-ISO/IEC 17025: 2000. This report shall not be reproduced, except in full, without the written permission of TNO Electronic Products & Services (EPS) B.V. The test results relate only to the item(s) tested.



Table of contents

1 General information.	5
1.1 Product description	5
1.1.1 Introduction.	
1.2 Related submittal(s) and/or Grant(s).	5
1.3 Tested system details.	
1.3.1 Description of input and output ports.	6
1.4 Test methodology	6
1.5 Test facility	6
1.6 Test conditions.	
2 System test configuration.	7
2.1 Justification.	
2.2 EUT mode of operation.	
2.3 Special accessories.	
2.4 Equipment modifications	7
2.5 Block diagram of the EUT.	
2.6 Schematics of the EUT.	
2.7 Part list of the EUT	7
3 Radiated emission data	
3.1 Radiated field strength measurements (30 MHz – 4000 MHz, E-field).	8
3.1.1 Average and Quasi peak values of the emissions	
3.1.2 Peak values of the emissions	9
4 List of utilized test equipment.	



1 General information.

1.1 Product description.

1.1.1 Introduction.

The EUT is a receiver for a Radio Frequency (RF) Remote Keyless Entry System (RKE) that allows the driver to remotely control the door locking and unlocking of his vehicle.

1.2 Related submittal(s) and/or Grant(s).

Not applicable.

1.3 Tested system details.

Details and an overview of the system and all of its components, as it has been tested, may be found below.

EUT	:	Receiver for a Remote Keyless Entry System (RKE)
Manufacturer	:	TRW Automotive
Brand	:	TRW
Model	:	41R
Serial number	:	-
Voltage input rating	:	12 VDC
Current input rating	:	
Frequency	:	315 MHz (314.5 MHz to 315.5 MHz)
Antenna	:	internal
Remarks	:	none



Receiver, brand TRW, model 41R



1.3.1 Description of input and output ports.

The EUT is operated from a 12 VDC car battery. The EUT has an open collector output for a serial data link.

1.4 Test methodology.

The test methodology used is based on the requirements of 47 CFR Part 15 (2006-08-14), sections 15.109.

The test methods, which have been used, are based on ANSI C63.4: 2003.

Radiated emission tests above 30 MHz were performed at a measurement distance of 3 meters.

Radiated emission tests below 30 MHz were performed at a measurement distance of 3 meters and if necessary at 10 and 30 meters. To calculate the field strength level from these results to the appropriate distance at which the limit is specified, the computation method in appendix 1 has been applied.

1.5 Test facility.

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at TNO Electronic Products & Services (EPS) B.V., located in Niekerk, 9822 TL Smidshornerweg 18, The Netherlands, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 2, section 2.948.

The description of the test facilities has been filed at the Office of the Federal Communications Commission under registration number 90828. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at http://www.fcc.gov.

1.6 Test conditions.

Normal test conditions.

Temperature (*)	: +15°C to +35°C
Relative humidity(*)	: 20 % to 75 %
Supply voltage	: not applicable, the equipment under test is battery operated
Air pressure	: 950 – 1050 hPa

* When is was impracticable to carry out the tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests are stated separately.



2 System test configuration.

2.1 Justification.

The justification and manipulation of cables and equipment in order to simulate a worst-case behavior of the test setup has been carried out as prescribed in ANSI C63.4: 2003.

2.2 EUT mode of operation.

The EUT has been tested in receive mode.

All test set ups have been documented in pictures in the documentation package which will be submitted to the Commission

2.3 Special accessories.

No special accessories are used and/or needed to achieve compliance with the applicable sections of 47 CFR Part 15.

2.4 Equipment modifications.

No modifications have been made to the equipment in order to achieve compliance with the appropriate sections of 47 CFR Part 15.

2.5 Block diagram of the EUT.

The block diagram is available in the technical documentation package which will be submitted to the Commission.

2.6 Schematics of the EUT.

The schematics are available in the technical documentation package which will be submitted to the Commission.

2.7 Part list of the EUT.

The part list is available in the technical documentation package which will be submitted to the Commission.



3 Radiated emission data.

3.1 Radiated field strength measurements (30 MHz – 4000 MHz, E-field).

3.1.1 Average and Quasi peak values of the emissions

Frequency (MHz)	Measurement results $dB(\mu V)/m$ @ 3 metres		Detector dB(µV)	Limits dB(µV)/m @ 3 metres	Margin (dB)		Result
	Vertical	Horizontal			Vertical	Horizontal	
30-1000	< 20.0	< 20.0	QP	40.0-54	< -20.0	< -20.0	PASS
1000-4000	< 30.0	< 30.0	AV	54	< -24.0	< -24.0	PASS

Table 1: Radiated emissions of the EUT, Average and Quasi peak values.

The results of the radiated emission tests, carried out in accordance with 47 CFR Part 15, section 15.109, are depicted in table 1.

Notes:

- 1. (AV) average detector
- 2. (QP) quasi peak detector
- 3. The reported field strength values are the worst case values at the indicated frequency, obtained by rotation of the EUT and orientation of the antenna.

Test engineer

Signature

: (If Hubbe

Name

: O.H. Hoekstra

Date : May 29, 2007



3.1.2 Peak values of the emissions

Frequency (MHz)		$\begin{array}{c} Measurement\ results\\ dB(\mu V)/m\ @\ 3\ metres \end{array} \ Detector \end{array}$		Limits dB(µV)/m @ 3 metres	Margin (dB)		Result
	Vertical	Horizontal		w 5 metres	Vertical	Horizontal	
1000-4000	< 30.0	< 30.0	PK	74	< -44.0	< -44.0	PASS

Table 2: Radiated emissions of the EUT, Peak values.

The results of the radiated emission tests, carried out in accordance with 47 CFR Part 15, section 15.35, are depicted in table 2.

Notes:

- 1. (PK) peak detector.
- 2. Only for frequencies where average radiated emission measurements are specified.
- 3. The reported field strength values are the worst case values at the indicated frequency, obtained by rotation of the EUT and orientation of the antenna.

Test engineer

signature

. (M Hubh

Name

: O.H. Hoekstra

Date : May 29, 2007



4 List of utilized test equipment.

Inventory Description number		Brand	Brand Model		Next cal.	
12476	Antenna mast	EMCO	TR3	-	-	
12477	Antenna mast 1-4 mtr	Poelstra		-	-	
12482	Loop antenna	EMCO	6507	04/2007	04/2008	
12483	Guidehorn	EMCO	3115	03/2007	03/2008	
12484	Guidehorn	EMCO	3115	03/2007	03/2008	
12533	Signalgenerator	MARCONI	2032	03/2007	03/2008	
12605	Calibrated dipole 28MHz-1GHz	EMCO	3121c	09/2002	09/2007	
12640	Temperature chamber	Heraeus	VEM03/500	01/2007	01/2008	
13664	Spectrum analyzer	HP	HP8593E	08/2006	08/2007	
13886	Open Area testsite	Comtest		07/2005	07/2007	
14051	Anechoic room	Comtest		-	-	
15633	Biconilog Testantenna	Chase	CBL 6111B	02/2007	02/2008	
15667	Measuring receiver	R&S	ESCS 30	04/2007	04/2008	
99596	Preamplifier 0.5 GHz - 18 GHz	Miteq	AMF-5D-005180-28-13p	07/2006	07/2007	