

May 6, 2011

TEE  
24175 Research Dr.  
Farmington Hills, MI 48335-2642  
Tel 248.478.7210  
Fax 248.699.4241

RE: Certification for FSK 315MHz Low Line Transmitter  
Model #: 225816106, 225816108  
FCC ID: GQ4-46T  
Canada IC: 1470A-27T

**GENERAL DESCRIPTION**

This transmitter is a transmitter device with tire valve, which is mounted in the valve hole of the wheel rim and transmits the pressure and temperature inside the tire, the battery voltage of the transmitter, and the tire identification code (ID) at normal and abnormal condition with the radio wave (RF) that conforms to the used area. Also this device has a countermeasure function such as the random delay of transmission time so that the RF signal from each tire will not interfere due to the simultaneous transmission. The transmitter device also has a Low Frequency (LF) receiver. This receiver supports Low Frequency (LF) magnetic field communications allowing the changing of measurement/monitoring states of the transmitter by commands sent via the TPM diagnostic tool. The RF signal operates at 315MHz and uses FSK Manchester code modulation. The EUT transmits 4 RF packets every 210 seconds.

**Description of Operations**

<b>Mode of Operation</b>	<b>Explanation</b>	<b>Frequency of Transmission</b>
Storage Mode	No transmission. Measures temperature & pressure	4 words when activation occurs with TPM diagnostic tool
Normal Mode	Measures temperature and pressure. Transmits periodically. Enters this mode from storage when pressure goes above threshold.	<ul style="list-style-type: none"><li>• 4 words every 210 seconds</li><li>• 4 words when activation occurs with TPM diagnostic tool</li></ul>
Alert Mode	Transmits when: a) significant pressure delta detected b) high temperature is detected	8 words every 4 seconds for 1 minute