

August 9, 2013

OSS Electronics
24175 Research Dr.
Farmington Hills, MI 48335-2642
Tel 248.478.7210
Fax 248.478.7241

RE: Certification for Honda 315MHz ASK AA Svc. Sensor Long Valve & Short Valve

FCC ID: GQ4-67T
Canada IC: 1470A-48T
Model #: 209624-125, -126

GENERAL DESCRIPTION

This transmitter is a transmitter device with tire valve, which is mounted in the valve hole of the wheel rim and transmits the pressure and temperature inside the tire, the battery voltage of the transmitter, and the tire identification code (ID) at normal and abnormal condition with the radio wave (RF) that conforms to the used area. Also this device has a countermeasure function such as the random delay of transmission time so that the RF signal from each tire will not interfere such as due to the simultaneous transmission.

Description of Operations

P/N	Consumer's Use Mode	Mfg. Modes	Mode of Operation	Explanation	Frequency of Transmission
209624-125 209624-126	X		Storage Mode	No transmission. Measures temperature.	4 words whenever LF activation occurs
209624-125 209624-126	X		Normal Mode Stationary	No transmission. Measures temperature and pressure. Enters this mode from storage after a valid LF activation occurs.	4 words whenever LF activation occurs
209624-125 209624-126	X		Normal Mode rolling	Measures temperature and pressure. Transmits periodically. Enters this mode from Normal Mode Stationary when acceleration goes above threshold.	4 words every 1 minute, 4 words LF activation occurs
209624-125 209624-126	X		Alert Mode	Transmits when: a) significant pressure delta detected b) high temperature is detected	8 words every 4 seconds for 1 minute