

<b>APPLICANT</b> <b>Visonic, Inc.</b> <b>10 Northwood Drive</b> <b>Bloomfield, CT 06002</b>	<b>MANUFACTURER</b> <b>Visonic, Inc.</b> <b>10 Northwood Drive</b> <b>Bloomfield, CT 06002</b>
--	---

**TEST SPECIFICATION:** ~~FCC Rules and Regulations Part 15, Subpart C, Para. 15.231~~

**TEST PROCEDURE:** **ANSI C63.4:2000**

**TEST SAMPLE DESCRIPTION**

**BRANDNAME:** **Visonic, Inc.** **MODEL:** **MCT-302 3V**

**TYPE:** **Pulsed Transmitter**

**POWER REQUIREMENTS:** **3 Volt Lithium, Type CR2 Battery**

**FREQUENCY OF OPERATION:** **315 MHz**

**TESTS PERFORMED**

**Para. 15.231(b), Radiated Emissions, Fundamental and Harmonics**

**Para. 15.231(b), Radiated Emissions, Spurious Case**

**Para. 15.35, Duty Cycle Determination**

**Para. 15.231(c), Occupied Bandwidth**

**REPORT OF MEASUREMENTS**

**Applicant:** **Visonic, Inc.**

**Device:** **Pulsed Transmitter**

**FCC ID:** **GSAMCT3023V**

**Power Requirements:** **3 Volt Lithium, Type CR2 Battery**

Test Report No. R-9666-1  
FCC ID: GSAMCT3023V

**Applicable Rule Section: Part 15, Subpart C, Section 15.231**

Test Report No. R-9666-1  
FCC ID: GSAMCT3023V

## REPORT OF MEASUREMENTS (continued)

### TEST RESULTS

- 15.231 (a): This device is used as a security transmitter.
- 15.231 (a)(1) & 15.231(a)(2): The transmitter is automatically operated and ceases transmission within 5 seconds after deactivation.
- 15.231 (a)(3): The transmitter does perform periodic transmissions once every 60 minutes for a duration of 580 milliseconds.
- 15.231 (b): The fundamental field strength did not exceed 6040  $\mu\text{V/M}$  (Average) at a test distance of 3 meters. In addition, the requirements of section 15.35 for averaging pulsed emissions and for limiting peak emissions were met.
- The field strength of harmonic and spurious emissions did not exceed 604  $\mu\text{V/M}$  (AVERAGE).

### DETERMINATION OF FIELD STRENGTH LIMITS

The field strength limits shown below are found in Section 15.231.

Frequency				Limit	
F1	=	260	3750	=	L1
Fo	=	315			Lo
F2	=	470	12500	=	L2

The formula below was utilized to determine the limits:

$$\text{Limit} = L1 + [(Fo-F1)(L2-L1)/(F2-F1)]$$

Solving yields:

$$\text{Fundamental Limit} = 6040 \mu\text{V/M (AVERAGE) @ 3 Meters}$$

$$\text{Harmonic Limit} = 604 \mu\text{V/M (AVERAGE) @ 3 Meters}$$

## **REPORT OF MEASUREMENTS (continued)**

### **DUTY CYCLE DETERMINATION**

The unit's RF output was directly coupled to the input of the spectrum analyzer. The analyzer was set for a frequency span of 0Hz. The sweep time was then adjusted in order to display one full pulse train. The transmitter on time was then summed and compared to the time for one full cycle in order to obtain the duty cycle.( See plots for additional information)

Transmitter On Time = 21.05 milliseconds (maximum)

Transmitter Cycle Time = 48 milliseconds

Transmitter Duty Cycle = 43.8 %

#### **CALCULATION:**

1 Large Pulse = 14.4 milliseconds

19 x 350  $\mu$ s (small pulse) = 6.65 milliseconds

14.4 + 6.65 = 21.05 milliseconds

Duty Cycle (21.05/48) = 43.8 %

Correction Factor =  $20 \log(0.438)$  = -7.2 dB

### **SPECTRUM ANALYZER DESENSITIZATION CONSIDERATIONS**

Due to the nature of the emissions being measured, care was taken to ensure that the resolution bandwidth of the spectrum analyzer was adequate to provide accurate measurements. The following formula was utilized:

Setting pulse desensitization equal to zero and utilizing the minimum observed pulse width of 350 $\mu$ s yields a minimum required bandwidth of 1904.8 Hz. FCC specified bandwidths of 100kHz and 1MHz were utilized below and above 1GHz, respectively.

## **GENERAL NOTES**

All readings were taken utilizing a peak detector function at a test distance of 3 meters.

The duty cycle was applied to the peak readings in order to determine the average value of the emissions.

The frequency range was scanned from 30 MHz to 3.2 GHz. All emissions not reported were more than 20 dB below the specified limit.

## EQUIPMENT LIST

### FCC15.231 Compliance Testing

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
067	Open Area Test Site	Retlif	3 Meter	RNY	09/20/2000	09/20/2003
128	Double Ridged Guide	Electro-Mechanics	1 GHz - 18 GHz	3105	06/07/2002	06/07/2003
133	Broadband Pre-Amplifier	Electro-Metrics	10 kHz - 1 GHz, 26dB	BPA-1000	06/11/2002	06/11/2003
141	Spectrum Analyzer	Hewlett Packard	100 Hz - 40 GHz	8566B	07/17/2002	01/17/2003
141A	Graphics Plotter	Hewlett Packard	N/A	7470A	03/05/2002	03/05/2003
141B	Quasi-Peak Adaptor	Hewlett Packard	100 Hz - 1 GHz	85650A	07/16/2002	01/16/2003
206B	6.0 dB Attenuator	Texscan	0 - 1.0 GHz	FP-50 - 6 dB	06/11/2002	06/11/2003
543	Preamplifier	Hewlett Packard	1.0 GHz - 26.5 GHz	8449B	07/11/2002	07/11/2003
617	Interference Analyzer	Electro-Metrics	10 kHz - 1 GHz	EMC-30	08/23/2002	08/23/2003
767	Biconilog	EMCO	26 - 2000 MHz	3142B	09/03/2002	09/03/2003

FCC 15.231(b)  
RADIATED EMISSIONS, FUNDAMENTAL & SPURIOUS CASE

Test Report No. R-9132-1  
FCC ID:GSAMCT3023V

FCC 15.231(c)  
OCCUPIED BANDWIDTH



FCC 15.35  
DUTY CYCLE

Test Setup Photograph

Test Report No. R-9666-1  
FCC ID:GSAMCT3023V