

FCC ID: GSS-VSD242

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

BT:

Operation Frequency: 2402MHz~2480MHz

Power density limited: $1\text{mW}/\text{cm}^2$

Antenna Type: Cable Antenna

WIFI antenna gain: 2.0dBi;

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

antenna gain Numeric= $10^{(\text{dBi}/10)}=10^{(1/10)}=1.58$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm	(mW/cm ²)
				(dBm)	(mW)	Numeric		
2402	GFSK	1.76	1.5±1	2.5	1.778279	1.58	0.00056	1
2441		2.29	1.5±1	2.5	1.778279	1.58	0.00056	1
2480		0.92	1.5±1	2.5	1.778279	1.58	0.00056	1
2402	π/4-DQPSK,	2.38	2.0±1	3	1.995262	1.58	0.00063	1
2441		2.82	2.0±1	3	1.995262	1.58	0.00063	1
2480		1.66	2.0±1	3	1.995262	1.58	0.00063	1
2402	8DPSK	3.09	2.5±1	3.5	2.238721	1.58	0.00070	1
2441		3.50	2.5±1	3.5	2.238721	1.58	0.00070	1
2480		2.15	2.5±1	3.5	2.238721	1.58	0.00070	1
2402	BLE(GFSK)	6.21	6±1	7	5.011872	1.58	0.00158	1
2441		6.84	6±1	7	5.011872	1.58	0.00158	1
2480		5.66	6±1	7	5.011872	1.58	0.00158	1

2.4G WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

Power density limited: $1\text{mW}/\text{cm}^2$

Antenna Type: FPCB Antenna

WIFI antenna gain: 2.0dBi;

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

antenna gain Numeric= $10^{(\text{dBi}/10)}=10^{(1/10)}=1.58$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm	(mW/cm ²)
				(dBm)	(mW)	Numeric		
2412	802.11b	13.4	13.0±1	14	25.11886	1.58	0.00790	1
2437		13.7	13.0±1	14	25.11886	1.58	0.00790	1
2462		13.9	13.0±1	14	25.11886	1.58	0.00790	1
2412	802.11g	13	13.0±1	14	25.11886	1.58	0.00790	1
2437		13.3	13.0±1	14	25.11886	1.58	0.00790	1
2462		13.5	13.0±1	14	25.11886	1.58	0.00790	1
2412	802.11n H20	12.6	12.5±1	13.5	22.38721	1.58	0.00704	1
2437		13	12.5±1	13.5	22.38721	1.58	0.00704	1
2462		13.1	12.5±1	13.5	22.38721	1.58	0.00704	1

5G WIFI:

Operation Frequency: WIFI 802.11a/n(HT20)/ac20: 5180-5240MHz;5745-5825MHz

WIFI 802.11n(HT40)/ac40: 5190-5230MHz;5755-5795MHz

WIFI 802.11ac80: 5210MHz; 5775MHz

Power density limited: 1mW/ cm

Antenna Type: FPCB Antenna

WIFI antenna gain: 2.0dBi;

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(2/10)}=1.58$

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna Gain Numeric	Evaluation result at 20cm Power density(mW/cm)	Power density Limits (mW/cm ²)
				tune-up power				
				(dBm)	(mW)			
5180	802.11a	12.6	11.6±1	12.6	18.19701	1.58	0.00572	1
5200		12.2	11.6±1	12.6	18.19701	1.58	0.00572	1
5240		10.6	11.6±1	12.6	18.19701	1.58	0.00572	1
5745		9.2	9±1	10	10	1.58	0.00314	1
5785		7.4	9±1	10	10	1.58	0.00314	1
5825		8.3	9±1	10	10	1.58	0.00314	1
5180	802.11n H20	12	11.0±1	12	15.84893	1.58	0.00498	1
5200		11.8	11.0±1	12	15.84893	1.58	0.00498	1
5240		10	11.0±1	12	15.84893	1.58	0.00498	1
5745		9	9±1	10	10	1.58	0.00314	1
5785		7.2	9±1	10	10	1.58	0.00314	1
5825		8.1	9±1	10	10	1.58	0.00314	1
5190	802.11n H40	11.2	10.5±1	11.5	14.12538	1.58	0.00444	1
5230		9.7	10.5±1	11.5	14.12538	1.58	0.00444	1
5755		7.7	7±1	8	6.309573	1.58	0.00198	1
5795		6.3	7±1	8	6.309573	1.58	0.00198	1
5180	802.11n ac20	12.3	11.5±1	12.5	17.78279	1.58	0.00559	1
5200		11.9	11.5±1	12.5	17.78279	1.58	0.00559	1
5240		10.1	11.5±1	12.5	17.78279	1.58	0.00559	1
5745		8.9	8±1	9	7.943282	1.58	0.00250	1
5785		7.1	8±1	9	7.943282	1.58	0.00250	1
5825		8	8±1	9	7.943282	1.58	0.00250	1
5190	802.11 ac40	11.2	10.5±1	11.5	14.12538	1.58	0.00444	1
5230		9.7	10.5±1	11.5	14.12538	1.58	0.00444	1
5755		7.7	7±1	8	6.309573	1.58	0.00198	1
5795		6.3	7±1	8	6.309573	1.58	0.00198	1
5210	802.11ac80	10.1	10.0±1	11	12.58925	1.58	0.00396	1
5775		6.4	6±1	7	5.011872	1.58	0.00158	1

Conclusion:

For the max result : $0.00790 \leq 1.0$ for Max Power Density, compliance RF exposure..

Jason chen

Signature:

Date: 2018-08-13

NAME AND TITLE (Please print or type): Jason Chen/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E,
Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R.
China