RF Exposure / SAR Statement

No.: 33CE0139-SH-02

Applicant : SMK Corporation

Type of Equipment: ZigBee RF4CE-compatible RF receiver

Model No. : SSR-RFNANO FCC ID : GT3FC017

SMK Corporation declares that Model: ZigBee RF4CE-compatible RF receiver complies with FCC radiation exposure requirement specified in the FCC Rules 2.1093.

The "SSR-RFNANO" has 1.26 mW of conducted Peak Output power and 2.25 mW of EIRP. This kind of equipment is complied to "(maximum EIRP [mW]) / (minimum test separation [mm]) $x (\sqrt{f(GHz)}) \leq 3.0$ (for 1g-SAR) or ≤ 7.5 (for 10g extremity SAR) (from KDB 447498, 4.3.1 1))", so that SAR testing is excluded. The Following calculation is the reference data for 5mm minimum distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "SSR-RFNANO" as calculated value from FCC KDB 447498 D01 General RF Exposure Guidance v05 clause 4.3.1 1). This calculation is based on the highest EIRP possible from the system, considering caliculation value a less than 3.0, exposure limit. The formula used was:

[caliculation]: $S = [(max. power [mW])/(min. test separation distance[mm])] x [<math>\sqrt{f(GHz)}]$ Where

For: SSR-RFNANO S= 0.7

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 Facsimile: +81 463 50 6401