

FCC TEST REPORT  
FOR

Shenzhen Linpa Technology Co.,Ltd

Bluetooth Speaker

Model No.: PBT616

Additional Model No.: LBS31, SBT616

Prepared for : Shenzhen Linpa Technology Co.,Ltd  
Address : 114,C8, Flavor Commercial Street, Vanke Dream Town , Longgang District,Shenzhen City, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : July 01, 2015  
Number of tested samples : 1  
Serial number : Prototype  
Date of Test : July 01, 2015 – July 15, 2015  
Date of Report : July 15, 2015

FCC TEST REPORT

FCC CFR 47 PART 15 C(15.247): 2014

Report Reference No. .... : LCS1506301766E

Date of Issue ..... : July 15, 2015

Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address ..... : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure..... : Full application of Harmonised standards [X]
Partial application of Harmonised standards [ ]
Other standard testing method [ ]

Applicant's Name ..... : Shenzhen Linpa Technology Co.,Ltd

Address ..... : 114,C8, Flavor Commercial Street, Vanke Dream Town , Longgang District,Shenzhen City, China

Test Specification

Standard..... : FCC CFR 47 PART 15 C(15.247): 2014

Test Report Form No..... : LCSEMC-1.0

TRF Originator ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description. .... : Bluetooth Speaker

Trade Mark ..... : Linpa World/Sharper Image/Polaroid

Model/ Type reference..... : PBT616

Ratings ..... : DC 5V by battery (1200mAh);
Recharge Voltage: DC 5.0V 0.8A

Result ..... : Positive

Compiled by:

Dick Su

Supervised by:

Glin Lu

Approved by:

Gavin Liang

Dick Su / File administrators

Glin Lu/ Technique principal

Gavin Liang/ Manager

# FCC -- TEST REPORT

<b>Test Report No. : LCS1506301766E</b>	<u>July 15, 2015</u> Date of issue
-----------------------------------------	---------------------------------------

Type / Model..... : PBT616  EUT..... : Bluetooth Speaker
<b>Applicant..... : Shenzhen Linpa Technology Co.,Ltd</b> Address..... : 114,C8, Flavor Commercial Street, Vanke Dream Town , Longgang District,Shenzhen City, China Telephone..... : / Fax..... : /
<b>Manufacturer..... : LINPA WORLD., Ltd</b> Address..... : 4 Floor B2 building Huaxing industrial park,Buxin village ,Yantian district Fenggang Town Dongguan City GD Province, China Telephone..... : / Fax..... : /
<b>Factory..... : LINPA WORLD., Ltd</b> Address..... : 4 Floor B2 building Huaxing industrial park,Buxin : village ,Yantian district Fenggang Town Dongguan City GD Province, China Telephone..... : / Fax..... : /

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.  
 It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION</b> .....	<b>5</b>
<b>1.1 Description of Device (EUT)</b> .....	5
1.2 Support equipment List .....	5
1.3 External I/O Cable .....	5
1.4 Description of Test Facility .....	6
1.5 Statement of The Measurement Uncertainty .....	6
1.6 Measurement Uncertainty .....	6
1.7 Description Of Test Modes .....	7
<b>2. TEST METHODOLOGY</b> .....	<b>8</b>
2.1 EUT Configuration .....	8
2.2 EUT Exercise .....	8
2.3 General Test Procedures .....	8
<b>3. SYSTEM TEST CONFIGURATION</b> .....	<b>9</b>
3.1 Justification .....	9
3.2 EUT Exercise Software .....	9
3.3 Special Accessories .....	9
3.4 Block Diagram/Schematics .....	9
3.5 Equipment Modifications .....	9
3.6 Test Setup .....	9
<b>4. SUMMARY OF TEST RESULTS</b> .....	<b>10</b>
<b>5. SUMMARY OF TEST EQUIPMENT</b> .....	<b>11</b>
<b>6. ANTENNA PORT MEASUREMENT</b> .....	<b>12</b>
6.1 Peak Power .....	12
6.2 Frequency Separation And 20 dB Bandwidth .....	13
6.3 Number Of Hopping Frequency .....	18
6.4 Time Of Occupancy (Dwell Time) .....	20
6.5 Conducted Spurious Emissions and Band Edges Test .....	23
<b>7. RADIATED MEASUREMENT</b> .....	<b>30</b>
7.1 Block Diagram of Test Setup .....	30
7.2 Radiated Emission Limit .....	31
7.3 Instruments Setting .....	32
7.4 Test Procedures .....	33
7.5 Results for Radiated Emissions .....	33
7.6 Results for Band edge Testing (Radiated) .....	36
7.7. Power line conducted emissions .....	37
<b>8. ANTENNA REQUIREMENT</b> .....	<b>39</b>
8.1 Standard Applicable .....	39
8.2 Antenna Connected Construction .....	39

# 1. GENERAL INFORMATION

## 1.1 Description of Device (EUT)

EUT	: Bluetooth Speaker
Model No.	: PBT616
Frequency Range	: 2.402-2.480GHz
Channel Number	: 79 channels for Bluetooth
Channel frequency	: 2402.00-2480.00MHz (Channel Frequency=2402+1(K-1), K=1, 2, 3 .....79);
Channel Spacing	: 1MHz for Bluetooth
Modulation Type	: GFSK, $\pi/4$ -DQPSK
Bluetooth Version	: V2.1+EDR
Antenna Gain	: Internal antenna,0dBi(Max.)
Input Voltage	: DC 5V by battery (1200mAh) Recharge Voltage: DC 5.0V 0.8A

## 1.2 Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
Lenovo	PC	B470	--	DOC

## 1.3 External I/O Cable

I/O Port Description	Quantity	Cable
USB Port	1	N/A
DC IN	1	N/A

## 1.4 Description of Test Facility

### Site Description

EMC Lab. : CNAS Registration Number. is L4595.  
 FCC Registration Number. is 899208.  
 Industry Canada Registration Number. is 9642A-1.  
 VCCI Registration Number. is C-4260 and R-3804.  
 ESMD Registration Number. is ARCB0108.  
 UL Registration Number. is 100571-492.  
 TUV SUD Registration Number. is SCN1081.  
 TUV RH Registration Number. is UA 50296516-001

## 1.5 Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 1.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	3.10dB	(1)
	30MHz~200MHz	2.96dB	(1)
	200MHz~1000MHz	3.10dB	(1)
	1GHz~26.5GHz	3.80dB	(1)
	26.5GHz~40GHz	3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	1.63dB	(1)
Power disturbance	30MHz~300MHz	1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 1.7 Description Of Test Modes

Bluetooth operates in the unlicensed ISM Band at 2.4GHz. With the introduction of the enhanced data rate (EDR) feature, the data rates can be up to 3 Mb/s. An increase in the peak data rate beyond the basic rate of 1 Mb/s is achieved by modulating the RF carrier using GFSK techniques, resulting in an increase of two to three times the number of bits per symbol. The 2 Mb/s EDR packets use a  $\pi/4$ -DQPSK modulation and the 3 Mb/s EDR packets use 8DPSK modulation. X, Y, Z position have been tested. The following operating modes were applied for the related test items. All test modes were tested, only the result of the worst case was recorded in the report.

Mode of Operations	Frequency Range (MHz)	Data Rate (Mbps)
GFSK	2402	1
	2441	1
	2480	1
$\pi/4$ DQPSK	2402	2
	2441	2
	2480	2
For Conducted Emission		
Test Mode	TX Mode	
For Radiated Emission		
Test Mode	TX Mode	

Worst-case mode and channel used for 150kHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, that was determined to be TX(1Mbps-Hopping Mode).

Worst-case mode and channel used for 9kHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be TX(1Mbps---High Channel).

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, RSS-210, FCC CFR PART 15C 15.207, 15.209, 15.247 and DA 00-705.

### 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2 EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209, 15.247 under the FCC Rules Part 15 Subpart C and RSS-210.

### 2.3 General Test Procedures

#### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table 0.8 meter above ground for below 1GHz and 1.5m for above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013



### **3. SYSTEM TEST CONFIGURATION**

#### **3.1 Justification**

The system was configured for testing in a continuous transmit condition.

#### **3.2 EUT Exercise Software**

N/A.

#### **3.3 Special Accessories**

N/A.

#### **3.4 Block Diagram/Schematics**

Please refer to the related document.

#### **3.5 Equipment Modifications**

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### **3.6 Test Setup**

Please refer to the test setup photo.

## 4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart C		
FCC Rules	Description of Test	Result
§15.247(a)	Maximum Conducted Output Power	Compliant
§15.247(c)	Frequency Separation And 20 dB Bandwidth	Compliant
§15.247(a)(1)(ii)	Number Of Hopping Frequency	Compliant
§15.247(a)(1)(iii)	Time Of Occupancy (Dwell Time)	Compliant
§15.209, §15.205	Conducted Spurious Emissions and Band Edges Test	Compliant
§15.209, §15.247(d)	Radiated and Conducted Spurious Emissions	Compliant
§15.205	Emissions at Restricted Band	Compliant
§15.207(a)	Conducted Emissions	Compliant
§15.203	Antenna Requirements	Compliant
§15.247(i) §2.1093	RF Exposure	Compliant


## 5. SUMMARY OF TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Power Sensor	R&S	NRV-Z51	100458	2015-06-18	2016-06-17
2	Power Sensor	R&S	NRV-Z32	10057	2015-06-18	2016-06-17
3	Power Meter	R&S	NRVS	100444	2015-06-18	2016-06-17
4	DC Filter	MPE	23872C	N/A	2015-06-18	2016-06-17
5	RF Cable	Harbour Industries	1452	N/A	2015-06-18	2016-06-17
6	SMA Connector	Harbour Industries	9625	N/A	2015-06-18	2016-06-17
7	Spectrum Analyzer	Agilent	N9020A	MY50510140	2014-10-27	2015-10-26
8	Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	2015-06-16	2016-06-15
9	RF Cable	Hubersuhne	Sucoflex104	FP2RX2	2015-06-18	2016-06-17
10	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2015-06-18	2016-06-17
11	Amplifier	SCHAFFNER	COA9231A	18667	2015-06-18	2016-06-17
12	Amplifier	Agilent	8449B	3008A02120	2015-06-16	2016-06-15
13	Amplifier	MITEQ	AMF-6F-260400	9121372	2015-06-16	2016-06-15
14	Loop Antenna	R&S	HFH2-Z2	860004/001	2015-06-18	2016-06-17
15	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2015-06-10	2016-06-09
16	Horn Antenna	EMCO	3115	6741	2015-06-10	2016-06-09
17	Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	2015-06-10	2016-06-09
18	RF Cable-R03m	Jye Bao	RG142	CB021	2015-06-18	2016-06-17
19	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2015-06-18	2016-06-17
20	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	101142	2015-06-18	2016-06-17
21	EMI Test Receiver	ROHDE & SCHWARZ	ESPI	101840	2015-06-18	2016-06-17
22	Artificial Mains	ROHDE & SCHWARZ	ENV216	101288	2015-06-18	2016-06-17
23	EMI Test Software	AUDIX	E3	N/A	2015-06-18	2016-06-17

## 6. ANTENNA PORT MEASUREMENT

### 6.1 Peak Power

#### 6.1.1 Block Diagram of Test Setup



#### 6.1.2 Limit

According to §15.247(a)(1) or A8.4 (2), For frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW..

#### 6.1.3 Test Procedure

The transmitter output is connected to the Power Meter.

#### 6.1.4 Test Results


Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit (mW)	Result
GFSK	2402	1.78	1.507	125	Pass
	2441	1.88	1.542	125	Pass
	2480	1.57	1.436	125	Pass
$\pi$ / 4-DQPSK	2402	1.26	1.337	125	Pass
	2441	1.41	1.384	125	Pass
	2480	1.28	1.343	125	Pass

## 6.2 Frequency Separation And 20 dB Bandwidth

### 6.2.1 Limit

According to §15.247(c) or A8.1(a), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 6.2.2 Block Diagram of Test Setup



### 6.2.3 Test Procedure

Frequency separation test procedure:

- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set center frequency of Spectrum Analyzer = middle of hopping channel.
- D. Set the Spectrum Analyzer as RBW = 100kHz, VBW = 300kHz, Span = wide enough to capture the peaks of two adjacent channels, Sweep = auto.
- E. Max hold, mark 2 peaks of hopping channel and record the 2 peaks frequency.

20dB bandwidth test procedure:

- A. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel.
- B.  $RBW \geq 1\%$  of the 20 dB bandwidth,  $VBW \geq RBW$ .
- C. Detector function = peak.
- D. Trace = max hold.


**6.2.4 Test Results**

<b>The Measurement Result With 1Mbps For GFSK Modulation</b>				
<b>Channel</b>	<b>20dB Bandwidth (KHz)</b>	<b>Channel Separation (MHz)</b>	<b>Limit (MHz)</b>	<b>Result</b>
Low	854.840	1.000	$\geq 25$ KHz or $\frac{2}{3}$ 20 dB BW	Pass
Middle	852.693		$\geq 25$ KHz or $\frac{2}{3}$ 20 dB BW	Pass
High	857.521		$\geq 25$ KHz or $\frac{2}{3}$ 20 dB BW	Pass


<b>The Measurement Result With 2Mbps For <math>\pi/4</math> DQPSK Modulation</b>				
<b>Channel</b>	<b>20dB Bandwidth (MHz)</b>	<b>Channel Separation (MHz)</b>	<b>Limit (MHz)</b>	<b>Result</b>
Low	1.228	1.000	$\geq 25$ KHz or $\frac{2}{3}$ 20 dB BW	Pass
Middle	1.229		$\geq 25$ KHz or $\frac{2}{3}$ 20 dB BW	Pass
High	1.231		$\geq 25$ KHz or $\frac{2}{3}$ 20 dB BW	Pass

*The test data refer to the following page.*

### Test Plot Of Frequency Separation (1Mbps)




### Test Plot Of Frequency Separation (2Mbps)




**Measurement of 20dB Bandwidth**


**Test frequency: 2402MHz(1Mbps)**



**Test frequency: 2441MHz(1Mbps)**




**Test frequency: 2480MHz(1Mbps)**







**Test frequency: 2402MHz(2Mbps)**



**Test frequency: 2441MHz(2Mbps)**



**Test frequency: 2480MHz(2Mbps)**




### 6.3 Number Of Hopping Frequency

#### 6.3.1 Limit

According to §15.247(a)(1)(ii) or A8.1 (d), Frequency hopping systems operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels.

#### 6.3.2 Block Diagram of Test Setup



#### 6.3.3 Test Procedure



- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set Spectrum Analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = auto.
- D. Set the Spectrum Analyzer as RBW, VBW=1MHz.
- E. Max hold, view and count how many channel in the band.

#### 6.3.4 Test Results

The Measurement Result With The Worst Case of 1Mbps For GFSK Modulation			
Total No. of Hopping Channel	Measurement Result (No. of Ch)	Limit (MHz)	Result
	79	≥ 15	Pass

The test data refer to the following page.

**Test Plot- Number of Hopping Channel**




## 6.4 Time Of Occupancy (Dwell Time)

### 6.4.1 Limit

According to §15.247(a)(1)(iii) or A8.1 (d), Frequency hopping systems operating in the 2400MHz- 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

### 6.4.2 Block Diagram of Test Setup



### 6.4.3 Test Procedure

- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set center frequency of Spectrum Analyzer = operating frequency.
- D. Set the Spectrum Analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
- E. Repeat above procedures until all frequency measured were complete.

**6.4.4 Test Results**

The Measurement Result With The Worst Case of 1Mbps For GFSK Modulation				
Channel	Time of Pulse for DH5 (ms)	Period Time (s)	Sweep Time (ms)	Limit (ms)
Low	2.85	31.6	304.0	400
Middle	2.885	31.6	304.0	400
High	2.885	31.6	304.0	400

**Low Channel**

$2.85 * (1600 / 6) / 79 * 31.6 = 304.0 \text{ms}$

**Middle Channel**


$2.85 * (1600 / 6) / 79 * 31.6 = 304.0 \text{ms}$

**High Channel**


$2.85 * (1600 / 6) / 79 * 31.6 = 304.0 \text{ms}$

The test data refer to the following:


**Low Channel**



### Middle Channel



### High Channel




## 6.5 Conducted Spurious Emissions and Band Edges Test

### 6.5.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 6.5.2 Block Diagram of Test Setup



### 6.5.3 Test Procedure

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 300 KHz.


Measurements are made over the 9kHz to 25GHz range with the transmitter set to the lowest, middle, and highest channels

### 6.5.4 Test Results of Conducted Spurious Emissions


No non-compliance noted. Only record the worst test result (TX-GFSK) in this report. The test data refer to the following page.

**Test Plot**

**9KHz-25GHz Low Channel(GFSK)**




**9KHz-25GHz Middle Channel(GFSK)**





**9KHz-25GHz High Channel(GFSK)**





### 6.5.5 Test Results of Band Edges Test



No non-compliance noted. Only record the worst test result in this report. The test data refer to the following page.

#### Test Plot



##### Hopping On - (GFSK)





**Hopping Off - (GFSK)**



**Hopping On - ( $\pi/4$  DQPSK)**




**Hopping Off - ( $\pi/4$  DQPSK)**




## 7. RADIATED MEASUREMENT

### 7.1 Block Diagram of Test Setup




Below 30MHz

Below 30MHz



Below 1GHz



Above 1GHz

Above 1 GHz

### 7.2 Radiated Emission Limit

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293.	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

Part 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector.

Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

Part 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

### 7.3 Instruments Setting

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP



## 7.4 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground for below 1GHz and 1.5m for above 1GHz. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.


## 7.5 Results for Radiated Emissions

### **PASS.**

*Only record the worst test result in this report.*

*The test data please refer to following page:*


**Below 1GHz (High Channel)**



Env./Ins: 24°C/56%  
 EUT: Bluetooth Speaker  
 M/N: PBT616  
 Power Rating: DC 3.7V  
 Test Mode: TX-High Channel  
 Operator: Dick  
 Memo:  
 pol: HORIZONTAL

	Freq MHz	Reading dBuV	CabLos dB	Antfac dB/m	Measured dBuV/m	Limit dBuV/m	Over dB	Remark
1	48.43	4.61	0.35	13.34	18.30	40.00	-21.70	QP
2	98.87	3.46	0.61	13.09	17.16	43.50	-26.34	QP
3	239.52	26.41	1.01	12.07	39.49	46.00	-6.51	QP
4	359.80	17.63	1.18	14.43	33.24	46.00	-12.76	QP
5	480.08	23.95	1.31	16.07	41.33	46.00	-4.67	QP
6	600.36	15.10	1.43	18.45	34.98	46.00	-11.02	QP

Note: 1. All readings are Quasi-peak values.  
 2. Measured= Reading + Antenna Factor + Cable Loss  
 3. The emission that are 20db below the official limit are not reported



Env./Ins: 24°C/56%  
 EUT: Bluetooth Speaker  
 M/N: PBT616  
 Power Rating: DC 3.7V  
 Test Mode: TX-High Channel  
 Operator: Dick  
 Memo:  
 pol: VERTICAL

	Freq MHz	Reading dBuV	CabLos dB	Antfac dB/m	Measured dBuV/m	Limit dBuV/m	Over dB	Remark
1	43.58	4.51	0.41	13.56	18.48	40.00	-21.52	QP
2	99.84	3.92	0.60	13.15	17.67	43.50	-25.83	QP
3	239.52	19.91	1.01	12.07	32.99	46.00	-13.01	QP
4	480.08	16.00	1.31	16.07	33.38	46.00	-12.62	QP
5	600.36	15.85	1.43	18.45	35.73	46.00	-10.27	QP
6	826.37	3.97	1.80	20.33	26.10	46.00	-19.90	QP

Note: 1. All readings are Quasi-peak values.  
 2. Measured= Reading + Antenna Factor + Cable Loss  
 3. The emission that are 20db below the official limit are not reported

**Above 1GHz**

The worst test result for GFSK, Tx-Low Channel:

Freq. MHz	Reading dBuv	Ant. Fac dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4804.00	54.34	33.06	35.04	3.94	56.30	74	-17.70	Peak	Horizontal
4804.00	38.39	33.06	35.04	3.94	40.35	54	-13.65	Average	Horizontal
4804.00	54.42	33.06	35.04	3.94	56.38	74	-17.62	Peak	Vertical
4804.00	38.60	33.06	35.04	3.94	40.56	54	-13.44	Average	Vertical

The worst test result for GFSK, Tx-Middle Channel:

Freq. MHz	Reading Dbuv	Ant. Fac dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4882.00	56.52	33.16	35.15	3.96	58.49	74	-15.51	Peak	Horizontal
4882.00	37.77	33.16	35.15	3.96	39.74	54	-14.26	Average	Horizontal
4882.00	52.36	33.16	35.15	3.96	54.33	74	-19.67	Peak	Vertical
4882.00	37.37	33.16	35.15	3.96	39.34	54	-14.66	Average	Vertical

The worst test result for GFSK, Tx-High Channel:

Freq. MHz	Reading DBuv	Ant. Fac dB/m	Pre. Fac. dB	Cab. Los dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4960.00	56.59	33.26	35.14	3.98	58.69	74	-15.31	Peak	Horizontal
4960.00	37.94	33.26	35.14	3.98	40.04	54	-13.96	Average	Horizontal
4960.00	52.93	33.26	35.14	3.98	55.03	74	-18.97	Peak	Vertical
4960.00	35.95	33.26	35.14	3.98	38.05	54	-15.95	Average	Vertical

**Notes:**

1. Measuring frequencies from 9k~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30 MHz.
2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
3. 18~25GHz at least have 20dB margin. No recording in the test report.

## 7.6 Results for Band edge Testing (Radiated)

Only record the worst test case (Tx, GFSK, Non-hopping) as following:

Tx-2402, GFSK, Non-hopping

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2385.00	51.57	32.89	35.16	3.51	52.81	74	-21.19	Peak	Horizontal
2385.00	38.53	32.89	35.16	3.51	39.78	54	-14.22	Average	Horizontal
2400.00	53.29	32.92	35.16	3.54	54.59	74	-19.41	Peak	Horizontal
2400.00	36.66	32.92	35.16	3.54	37.96	54	-16.04	Average	Horizontal
2385.00	49.67	32.89	35.16	3.51	50.91	74	-23.09	Peak	Vertical
2385.00	36.05	32.89	35.16	3.51	37.30	54	-16.70	Average	Vertical
2400.00	47.94	32.92	35.16	3.54	49.24	74	-24.76	Peak	Vertical
2400.00	35.85	32.92	35.16	3.54	37.15	54	-16.85	Average	Vertical

Tx-2480, GFSK, Non-hopping

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2483.50	50.85	33.06	35.18	3.60	52.33	74	-21.67	Peak	Horizontal
2483.50	37.96	33.06	35.18	3.60	39.44	54	-14.56	Average	Horizontal
2483.50	50.55	33.06	35.18	3.60	52.03	74	-21.97	Peak	Vertical
2483.50	36.67	33.06	35.18	3.60	38.15	54	-15.85	Average	Vertical


### 7.7. Power line conducted emissions

#### 7.7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

#### 7.7.2 Block Diagram of Test Setup




#### 7.7.3 Test Results

PASS.

The test data please refer to following page.


Test result for GFSK (High Chanel)



Trace: 140  
 Env. Ins: 24\*/56%  
 EUT: Bluetooth Speaker  
 M/N: PBT616  
 Power Rating: AC 120V/60Hz  
 Test Mode: TX-High Channel  
 Operator: Dick  
 Memo:  
 Pol: LINE

Freq	Reading	LisnFac	CabLos	Atten_Fac	Measured	Limit	Over	Remark
MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1 0.15816	30.87	9.58	0.02	10.00	50.47	65.56	-15.09	QP
2 0.15826	18.39	9.58	0.02	10.00	37.99	55.55	-17.56	Average
3 0.21392	13.92	9.63	0.03	10.00	33.58	63.05	-29.47	QP
4 0.21402	-0.92	9.63	0.03	10.00	18.74	53.05	-34.31	Average
5 0.49673	12.34	9.62	0.04	10.00	32.00	56.05	-24.05	QP
6 0.49683	0.33	9.62	0.04	10.00	19.99	46.05	-26.06	Average
7 1.68020	11.52	9.64	0.05	10.00	31.21	56.00	-24.79	QP
8 1.68120	2.02	9.64	0.05	10.00	21.71	46.00	-24.29	Average
9 8.14832	9.91	9.68	0.07	10.00	29.66	60.00	-30.34	QP
10 8.14932	-1.09	9.68	0.07	10.00	18.66	50.00	-31.34	Average
1126.55813	18.46	9.71	0.13	10.00	38.30	60.00	-21.70	QP
1226.55913	8.43	9.71	0.13	10.00	28.27	50.00	-21.73	Average

Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss+Atten\_Fac.  
 2. The emission levels that are 20dB below the official limit are not reported.



Trace: 142  
 Env. Ins: 24\*/56%  
 EUT: Bluetooth Speaker  
 M/N: PBT616  
 Power Rating: AC 120V/60Hz  
 Test Mode: TX-High Channel  
 Operator: Dick  
 Memo:  
 Pol: NEUTRAL

Freq	Reading	LisnFac	CabLos	Atten_Fac	Measured	Limit	Over	Remark
MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1 0.15000	33.64	9.70	0.02	10.00	53.36	66.00	-12.64	QP
2 0.15010	16.70	9.70	0.02	10.00	36.42	55.99	-19.57	Average
3 0.20181	18.72	9.59	0.02	10.00	38.33	63.54	-25.21	QP
4 0.20191	-2.46	9.59	0.02	10.00	17.15	53.53	-36.38	Average
5 0.48632	10.76	9.62	0.04	10.00	30.42	56.23	-25.81	QP
6 0.48642	-0.16	9.62	0.04	10.00	19.50	46.23	-26.73	Average
7 1.99065	17.23	9.63	0.05	10.00	36.91	56.00	-19.09	QP
8 1.99165	6.16	9.63	0.05	10.00	25.84	46.00	-20.16	Average
9 9.20442	-1.37	9.71	0.08	10.00	18.42	50.00	-31.58	Average
10 9.20432	11.44	9.71	0.08	10.00	31.23	60.00	-28.77	QP
1126.98365	18.58	9.83	0.13	10.00	38.54	60.00	-21.46	QP
1226.98465	9.03	9.83	0.13	10.00	28.99	50.00	-21.01	Average

Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss+Atten\_Fac.  
 2. The emission levels that are 20dB below the official limit are not reported.

## 8. ANTENNA REQUIREMENT

### 8.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### 8.2 Antenna Connected Construction

#### 8.2.1. Standard Applicable

According to § 15.203 & RSS-Gen, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 8.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 0dBi, and the antenna is connect to PCB board and no consideration of replacement. Please see EUT photo for details.

#### 8.2.3. Results: Compliance.

**Measurement parameters:**

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	3 MHz
Video bandwidth:	3 MHz
Trace-Mode:	Max hold

Note: The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal Bluetooth devices, the GFSK mode is used.

**Limits:**

FCC	IC
Antenna Gain	
6.0dBi	

Tnom	Vnom	lowest channel 2402 MHz	middle channel 2440 MHz	highest channel 2480 MHz
Conducted power [dBm] Measured with GFSK modulation		1.78	1.88	1.57
Radiated power [dBm] Measured with GFSK modulation		1.55	1.69	1.41
Gain [dBi] Calculated		-0.23	-0.19	-0.16
Measurement uncertainty			± 1.5 dB (cond.) / ± 3.0 dB (rad.)	

**Result: -/-**

-----THE END OF TEST REPORT-----