8. RADIO FREQUENCY EXPOSURE

8.1. Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

Table: Limits for General Population/Uncontrolled Exposure

Frequency Range	Power Density (S)	
(MHz)	(mW/cm2)	
0.3–1.34	*(100)	
1.34-30	*(180/f ²)	
30–300	0.2	
300-1500	f/1500	
1500–100,000	1.0	

F = frequency in MHz

Maximum Permissible Exposure

The MPE was calculated at 20cm to show compliance with the power density limit.

 $S = PG/4\pi R^2$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna.

Note:

- 1. Manufacturer declared that the maximum antenna gain is 2dBi(Max.).
- 2. Manufacturer declared that the nearest distance between human and the EUT is 20cm.
- 3. Only record worst case data.

Conducted Power Results

^{* =} Plane-wave equivalent power density

Mode	Channel	Channel Frequency (MHz) Conducted Output Power (dBm)		Tolerance ±(dB)
GFSK	00	2402	0.871	0 ± 1.0
	39	2441	-1.258	-1.0 ± 1.0
	78	2480	-3.236	-3.0 ± 1.0
π/4DQPSK	00	2402	-0.464	0 ± 1.0
	39	2441	-2.169	-2.0 ± 1.0
	78	2480	-3.911	-3.0 ± 1.0
8-DPSK	00	2402	-0.337	0 ± 1.0
	39	2441	-2.065	-2.0 ± 1.0
	78	2480	-3.846	-3.0 ± 1.0

Test Mode	Channel	Max. Tune Up Power (dBm)	Max. Tune Up Power (mW)	MPE (mW/cm²)	Limit (mW/cm²)
GFSK	Low	1.0	1.26	0.0004	1.0
	Middle	0	1.0 0	0.0003	1.0
	High	-2.0	0.63	0.0002	1.0
π/4DQPSK	Low	1.0	1.26	0.0004	1.0
	Middle	-1.0	0.79	0.0002	1.0
	High	-2.0	0.63	0.0002	1.0
8-DPSK	Low	1.0	1.26	0.0004	1.0
	Middle	-1.0	0.79	0.0002	1.0
	High	-2.0	0.63	0.0002	1.0

Antenna Gain (typical): 2dBi, 1.58(numeric)

Prediction distance: >=20cm

The power density level worst case at 20 cm is below the uncontrolled exposure limit.

-----THE END OF REPORT-----