

# RF TEST REPORT

ISSUED BY  
Shenzhen BALUN Technology Co., Ltd.




FOR

## Air Purifier

ISSUED TO  
ACCO Brands, Inc.

1500 Fashion Island Blvd., 3rd Floor, San Mateo, CA, United States



Report No.:	BL-SZ2180090-603
EUT Name:	Air Purifier
Model Name:	Z-3500 (refer section 2.4)
Brand Name:	TruSens
Test Standard:	47 CFR Part 15 Subpart C
FCC ID:	GV3-20Z3X00A
Test Conclusion:	Pass
Test Date:	Aug. 17, 2021 ~ Aug. 26, 2021
Date of Issue:	Sep. 29, 2021

**NOTE:** This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

**Revision History**

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Sep. 22, 2021</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Sep. 28, 2021</u>	<u>Change model name.</u> <u>Correction modulation technology in section 2.5 and test setup in section 4.3.</u>
<u>Rev. 03</u>	<u>Sep. 29, 2021</u>	<u>Correction test setup in section 4.3.</u>

**TABLE OF CONTENTS**

1	ADMINISTRATIVE DATA (GENERAL INFORMATION) .....	5
1.1	Identification of the Testing Laboratory .....	5
1.2	Identification of the Responsible Testing Location .....	5
1.3	Laboratory Condition .....	5
1.4	Announce .....	5
2	PRODUCT INFORMATION .....	6
2.1	Applicant Information.....	6
2.2	Manufacturer Information .....	6
2.3	Factory Information .....	6
2.4	General Description for Equipment under Test (EUT) .....	6
2.5	Technical Information.....	7
3	SUMMARY OF TEST RESULTS.....	8
3.1	Test Standards.....	8
3.2	Verdict .....	8
4	GENERAL TEST CONFIGURATIONS .....	9
4.1	Test Environments .....	9
4.2	Test Equipment List.....	9
4.3	Description of Test Setup .....	10
4.3.1	For Antenna Port Test .....	10
4.3.2	For AC Power Supply Port Test .....	10
4.3.3	For Radiated Test (Below 30 MHz) .....	11
4.3.4	For Radiated Test (30 MHz-1 GHz) .....	11
4.3.5	For Radiated Test (Above 1 GHz).....	12
4.4	Measurement Results Explanation Example.....	13
4.4.1	For conducted test items: .....	13

4.4.2	For radiated band edges and spurious emission test:	13
5	TEST ITEMS	14
5.1	Antenna Requirements	14
5.1.1	Relevant Standards	14
5.1.2	Antenna Anti-Replacement Construction	14
5.1.3	Antenna Gain	14
5.2	Number of Hopping Frequency	15
5.2.1	Limit	15
5.2.2	Test Setup	15
5.2.3	Test Procedure	15
5.2.4	Test Result	15
5.3	Peak Output Power	16
5.3.1	Test Limit	16
5.3.2	Test Setup	16
5.3.3	Test Procedure	16
5.3.4	Test Result	16
5.4	Occupied Bandwidth	17
5.4.1	Limit	17
5.4.2	Test Setup	17
5.4.3	Test Procedure	17
5.4.4	Test Result	17
5.5	Carrier Frequency Separation	18
5.5.1	Limit	18
5.5.2	Test Setup	18
5.5.3	Test Procedure	18
5.5.4	Test Result	18
5.6	Time of Occupancy (Dwell time)	19
5.6.1	Limit	19
5.6.2	Test Setup	19
5.6.3	Test Procedure	19
5.6.4	Test Result	19
5.7	Conducted Spurious Emission & Authorized-band band-edge	20

5.7.1	Limit.....	20
5.7.2	Test Setup .....	20
5.7.3	Test Procedure.....	20
5.7.4	Test Result .....	20
5.8	Conducted Emission .....	21
5.8.1	Limit.....	21
5.8.2	Test Setup .....	21
5.8.3	Test Procedure.....	21
5.8.4	Test Result .....	21
5.9	Radiated Spurious Emission .....	22
5.9.1	Limit.....	22
5.9.2	Test Setup .....	22
5.9.3	Test Procedure.....	22
5.9.4	Test Result .....	23
5.10	Band Edge (Restricted-band band-edge).....	24
5.10.1	Limit.....	24
5.10.2	Test Setup .....	24
5.10.3	Test Procedure.....	24
5.10.4	Test Result .....	24
ANNEX A	TEST RESULT .....	25
A.1	Number of Hopping Frequency .....	25
A.2	Peak Output Power .....	26
A.3	6 dB and 99% bandwidth .....	28
A.4	Hopping Frequency Separation.....	30
A.5	Average Time of Occupancy .....	30
A.6	Conducted Spurious Emissions & Authorized-band band-edge .....	31
A.7	Conducted Emissions.....	35
A.8	Radiated Emission .....	37
A.9	Band Edge (Restricted-band band-edge).....	45
ANNEX B	TEST SETUP PHOTOS .....	47
ANNEX C	EUT EXTERNAL PHOTOS .....	47
ANNEX D	EUT INTERNAL PHOTOS .....	47

# 1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

## 1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

## 1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

## 1.3 Laboratory Condition

Ambient Temperature	20°C to 25°C
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

## 1.4 Announce

- (1) The test report reference to the report template version v2.2.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

Applicant	ACCO Brands, Inc.
Address	1500 Fashion Island Blvd., 3rd Floor, San Mateo, CA, United States

### 2.2 Manufacturer Information

Manufacturer	ACCO Brands, Inc.
Address	1500 Fashion Island Blvd., 3rd Floor, San Mateo, CA, United States

### 2.3 Factory Information

Factory	N/A
Address	N/A

### 2.4 General Description for Equipment under Test (EUT)

EUT Name	Air Purifier
Model Name Under Test	Z-3500
Series Model Name	Z-2500
Description of Model name differentiation	differ only in the scale of the enclosure.
Hardware Version	Z3500_v1.1, Z2500_v1.1
Software Version	Z3500_v1.1, Z2500_v1.1
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

## 2.5 Technical Information

Network and Wireless connectivity	Bluetooth BLE WIFI 802.11b, 802.11g, 802.11n 2.4G ISM Band (GFSK modulation)
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	DTS
Modulation Type	GFSK
Product Type	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Transfer Rate	2Mbps
Frequency Range	The frequency range used is 2467 MHz – 2481 MHz; The frequency block is 2400 MHz to 2483.5 MHz.
Number of channel	7
Tested Channel	Low (2468 MHz), Middle (2470 MHz), High (2480 MHz)
Antenna Type	PCB Antenna
Antenna Gain	2.0 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
Adaptive or non-adaptive	non-adaptive
The Max RF Output power	-8.82 dBm

Test Case	Test Conditions			
	Modulation Technology	Modulation Type	Date rate	Channel
Peak Output Power	DTS	GFSK	2Mbps	Low/Middle/High
Occupied Bandwidth	DTS	GFSK	2Mbps	Low/Middle/High
Conducted Spurious Emission	DTS	GFSK	2Mbps	Low/Middle/High
Conducted Emission	DTS	GFSK	2Mbps	Low/Middle/High
Radiated Emission	DTS	GFSK	2Mbps	Low/Middle/High
Band Edge	DTS	GFSK	2Mbps	Low/High

All channel list:

Channel	Frequency
1	2468MHz
2	2470MHz
3	2472MHz
4	2474MHz
5	2476MHz
6	2478MHz
7	2480MHz

### 3 SUMMARY OF TEST RESULTS

#### 3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

#### 3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	--	Pass <sup>Note 1</sup>
2	Number of Hopping Frequency	15.247(a)	ANNEX A.1	N/A
3	Peak Output Power	15.247(b)	ANNEX A.2	Pass
4	Occupied Bandwidth	15.247(a)	ANNEX A.3	Pass
5	Carrier Frequency Separation	15.247(a)	ANNEX A.4	N/A
6	Time of Occupancy (Dwell time)	15.247(a)	ANNEX A.5	N/A
7	Conducted Spurious Emission& Authorized-band band-edge	15.247(d)	ANNEX A.6	Pass
8	Conducted Emission	15.207	ANNEX A.7	Pass
9	Radiated Spurious Emission	15.209 15.247(d)	ANNEX A.8	Pass
10	Band Edge (Restricted-band band-edge)	15.209 15.247(d)	ANNEX A.9	Pass
11	Receiver Spurious Emissions	--	--	N/A <sup>Note 2</sup>

Note <sup>1</sup>: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note <sup>2</sup>: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

## 4 GENERAL TEST CONFIGURATIONS

### 4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%		
Atmospheric Pressure	100 kPa to 102 kPa		
Temperature	NT (Normal Temperature)		20°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)		110 V

### 4.2 Test Equipment List


Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-40	101544	2021.04.01	2022.03.31
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2021.06.01	2022.05.31
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2021.06.01	2022.05.31
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2021.06.01	2022.05.31
LISN	SCHWARZBECK	NSLK 8127	8127-687	2021.06.01	2022.05.31
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2019.10.29	2021.10.28
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2019.07.02	2022.07.01
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1917	2019.07.02	2022.07.01
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2021.01.05	2023.01.04
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2022.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60 *7.35m	N/A	2019.08.08	2022.08.07
Shielded Enclosure	ChangNing	CN-130701	130703	--	--

## 4.3 Description of Test Setup


### 4.3.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:  
Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm



### 4.3.2 For AC Power Supply Port Test




#### 4.3.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

#### 4.3.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

#### 4.3.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

## 4.4 Measurement Results Explanation Example

### 4.4.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

### 4.4.2 For radiated band edges and spurious emission test:

Per part 15.35(c), the EUT Bluetooth average emission level could be determined by the peak emission level applying duty cycle correction factor, to represent averaging over the whole pulse train.

The average level is derived from the peak level corrected with "Duty cycle correction factor".

Average Emission Level (dB<sub>V/m</sub>) = Peak Emission Level (dB<sub>V/m</sub>) + Duty cycle correction factor (dB)

Duty cycle correction factor (dB) =  $20 * \log (\text{Duty cycle})$ .

Duty cycle = on time / 100 milliseconds

On time = dwell time \* hopping number in 100 ms

For example: bluetooth with dwell time 2.9 ms and 3 hops in 100 ms, then

Duty cycle correction factor (dB) =  $20 * \log ((2.9 * 3) / 100) = -21.21 \text{ dB}$

Following shows an average computation example with duty cycle correction factor = -21.21 dB, and the peak emission level is 45.61 dB<sub>V/m</sub>.

Example:

Average Emission Level (dB<sub>V/m</sub>) = Peak Emission Level (dB<sub>V/m</sub>) + duty cycle correction factor (dB)  
= 45.61 + (-21.21) = 24.4 (dB<sub>V/m</sub>)

## 5 TEST ITEMS

### 5.1 Antenna Requirements

#### 5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

#### 5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	The antenna is welded on the mainboard, can't be replaced by the consumer

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

#### 5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 5.2 Number of Hopping Frequency

### 5.2.1 Limit

FCC §15.247(a) (1) (iii); RSS-247, 5.1 (4)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

### 5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.2.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW  $\geq$  1% of the span

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

### 5.2.4 Test Result

Please refer to ANNEX A.1.

## 5.3 Peak Output Power

### 5.3.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

RSS-247, 5.4 (2)

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels (see Section 5.4(5) for exceptions).

### 5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.3.3 Test Procedure

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

### 5.3.4 Test Result

Please refer to ANNEX A.2.

## 5.4 Occupied Bandwidth

### 5.4.1 Limit

FCC §15.247(a); RSS-247, 5.1 (1)

Measurement of the 20dB bandwidth of the modulated signal.

### 5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.4.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  1% of the 20 dB bandwidth

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

### 5.4.4 Test Result

Please refer to ANNEX A.3.

## 5.5 Carrier Frequency Separation

### 5.5.1 Limit

FCC §15.247(a); RSS-247, 5.1 (2)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span

Video (or Average) Bandwidth (VBW)  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

### 5.5.4 Test Result

Please refer to ANNEX A.4.

## 5.6 Time of Occupancy (Dwell time)

### 5.6.1 Limit

FCC §15.247(a); RSS-247, 5.1 (4)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 5.6.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.6.3 Test Procedure

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

### 5.6.4 Test Result

Please refer to ANNEX A.5

## 5.7 Conducted Spurious Emission & Authorized-band band-edge

### 5.7.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 5.7.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

### 5.7.4 Test Result

Please refer to ANNEX A.6.

## 5.8 Conducted Emission

### 5.8.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

### 5.8.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

### 5.8.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

### 5.8.4 Test Result

Please refer to ANNEX A.7.

## 5.9 Radiated Spurious Emission

### 5.9.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength ( $\text{dB}\mu\text{V}/\text{m}$ ) =  $20*\log[\text{Field Strength } (\mu\text{V}/\text{m})]$ .
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dB $\mu$ V/m@3m (AV) and 74dB $\mu$ V/m@3m (PK).

### 5.9.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.9.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

#### 5.9.4 Test Result

Please refer to ANNEX A.8.

## 5.10 Band Edge (Restricted-band band-edge)

### 5.10.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

### 5.10.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

### 5.10.4 Test Result

Please refer to ANNEX A.9.

## ANNEX A TEST RESULT

### A.1 Number of Hopping Frequency

Note: Not applicable.


## A.2 Peak Output Power

### Peak Power Test Data


Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	-9.26	0.12	30	1000	Pass
Middle	-9.16	0.12			Pass
High	-8.82	0.13			Pass

### Test plots

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL




### Duty Cycle Test Data

Band	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)
GFSK	0.2077	0.5413	38.37

### Test plots

GFSK



### A.3 6 dB and 99% bandwidth


#### Test Data

Test Mode	GFSK		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	700.000	1383.200	≥500
Middle Channel	675.000	1397.100	≥500
High Channel	675.000	1350.700	≥500


#### Test plots

##### 6 dB Bandwidth


GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



99% Bandwidth


### GFSK LOW CHANNEL



### GFSK MIDDLE CHANNEL



### GFSK HIGH CHANNEL



## A.4 Hopping Frequency Separation

Note: Not applicable.

## A.5 Average Time of Occupancy

Note: Not applicable.

## A.6 Conducted Spurious Emissions & Authorized-band band-edge

### Test Data

GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-44.87	-9.46	-29.46	Pass
Middle	-44.93	-9.21	-29.21	Pass
High	-46.68	-8.84	-28.84	Pass


GFSK				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-52.41	-9.46	-29.46	Pass
High	-58.04	-8.84	-28.84	Pass

## Test Plots


### GFSK LOW CHANNEL, CARRIER LEVEL



### GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




### GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




### GFSK MIDDLE CHANNEL, CARRIER LEVEL



### GFSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




### GFSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




### GFSK HIGH CHANNEL, CARRIER LEVEL




### GFSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




### GFSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




### LOW CHANNEL, Reference level




### LOW CHANNEL, Band Edge



### HIGH CHANNEL, Reference level



### HIGH CHANNEL, Band Edge



## A.7 Conducted Emissions


Note<sup>1</sup>: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Note<sup>2</sup>: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz ) shown here.

Note<sup>3</sup>: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)


### Test Data and Plots

#### PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.154	46.10	10.41	65.78	-19.68	Peak	L	Pass
1**	0.154	30.72	10.41	55.78	-25.06	AV	L	Pass
2	0.242	43.27	10.34	62.03	-18.76	Peak	L	Pass
2**	0.242	29.76	10.34	52.03	-22.27	AV	L	Pass
3	0.402	34.15	10.31	57.81	-23.66	Peak	L	Pass
3**	0.402	28.45	10.31	47.81	-19.36	AV	L	Pass
4	0.566	37.50	10.28	56.00	-18.50	Peak	L	Pass
4**	0.566	30.98	10.28	46.00	-15.02	AV	L	Pass
5	0.612	37.39	10.28	56.00	-18.61	Peak	L	Pass
5**	0.612	29.47	10.28	46.00	-16.53	AV	L	Pass
6	2.858	31.10	10.28	56.00	-24.90	Peak	L	Pass
6**	2.858	17.13	10.28	46.00	-28.87	AV	L	Pass

## PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.164	48.50	10.40	65.26	-16.76	Peak	N	Pass
1**	0.164	30.98	10.40	55.26	-24.28	AV	N	Pass
2	0.186	45.78	10.39	64.21	-18.43	Peak	N	Pass
2**	0.186	33.12	10.39	54.21	-21.09	AV	N	Pass
3	0.354	37.26	10.31	58.87	-21.61	Peak	N	Pass
3**	0.354	26.27	10.31	48.87	-22.60	AV	N	Pass
4	0.620	37.27	10.28	56.00	-18.73	Peak	N	Pass
4**	0.620	27.85	10.28	46.00	-18.15	AV	N	Pass
5	2.074	33.26	10.26	56.00	-22.74	Peak	N	Pass
5**	2.074	23.30	10.26	46.00	-22.70	AV	N	Pass
6	10.450	32.20	10.37	60.00	-27.80	Peak	N	Pass
6**	10.450	22.08	10.37	50.00	-27.92	AV	N	Pass

## A.8 Radiated Emission

### Test Data and Plots

Note <sup>1</sup>: The symbol of “--” in the table which means not application.


Note <sup>2</sup>: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note <sup>3</sup>: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and DH5-Hopping mode is the worst.

Note <sup>4</sup>: Results (dB<sub>UV</sub>/m) = Original reading level of Spectrum Analyzer (dB<sub>UV</sub>/m) + Factor (dB)


The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

#### 30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dB <sub>UV</sub> /m)	Factor (dB)	Limit (dB <sub>UV</sub> /m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.430	14.12	-24.23	40.0	-25.88	Peak	341.10	100	Horizontal	Pass
2	74.523	14.19	-27.74	40.0	-25.81	Peak	274.20	100	Horizontal	Pass
3	103.041	16.28	-26.97	43.5	-27.22	Peak	134.10	100	Horizontal	Pass
4	122.005	17.97	-24.53	43.5	-25.53	Peak	90.30	200	Horizontal	Pass
5	221.333	21.30	-24.96	46.0	-24.70	Peak	246.10	200	Horizontal	Pass
6	315.228	20.16	-21.28	46.0	-25.84	Peak	307.90	100	Horizontal	Pass

## 30 MHz to 1 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.042	26.77	-24.31	40.0	-13.23	Peak	158.20	100	Vertical	Pass
2	53.474	27.79	-24.74	40.0	-12.21	Peak	116.00	100	Vertical	Pass
3	68.800	29.73	-26.76	40.0	-10.27	Peak	107.70	100	Vertical	Pass
4	74.620	29.88	-27.73	40.0	-10.12	Peak	145.70	100	Vertical	Pass
5	118.949	32.63	-25.05	43.5	-10.87	Peak	128.80	100	Vertical	Pass
6	128.600	30.52	-24.32	43.5	-12.98	Peak	99.10	100	Vertical	Pass

### Test Data and Plots (1 GHz ~ 10th Harmonic)

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.


#### GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1920.100	41.74	-15.88	74.0	-32.26	Peak	23.00	100	Horizontal	Pass
1**	1920.100	35.61	-15.88	54.0	-18.39	AV	23.00	100	Horizontal	Pass
2	2467.500	86.42	-12.26	74.0	12.42	Peak	117.00	100	Horizontal	N/A
2**	2467.500	85.83	-12.26	54.0	31.83	AV	117.00	100	Horizontal	N/A
3	4935.500	52.77	-1.39	74.0	-21.23	Peak	231.00	100	Horizontal	Pass
3**	4935.500	50.83	-1.39	54.0	-3.17	AV	231.00	100	Horizontal	Pass
4	7355.000	54.67	1.61	74.0	-19.33	Peak	62.00	100	Horizontal	Pass
4**	7355.000	45.39	1.61	54.0	-8.61	AV	62.00	100	Horizontal	Pass
5	9287.999	49.03	-1.57	74.0	-24.97	Peak	0.00	100	Horizontal	Pass
5**	9287.999	40.02	-1.57	54.0	-13.98	AV	0.00	100	Horizontal	Pass
6	15343.000	53.87	1.46	74.0	-20.13	Peak	11.00	100	Horizontal	Pass
6**	15343.000	44.55	1.46	54.0	-9.45	AV	11.00	100	Horizontal	Pass

## GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1919.600	41.33	-15.87	74.0	-32.67	Peak	13.00	100	Vertical	Pass
1**	1919.600	34.72	-15.87	54.0	-19.28	AV	13.00	100	Vertical	Pass
2	2467.600	84.27	-12.27	74.0	10.27	Peak	187.00	100	Vertical	N/A
2**	2467.600	83.78	-12.27	54.0	29.78	AV	187.00	100	Vertical	N/A
3	4936.000	55.94	-1.33	74.0	-18.06	Peak	360.00	100	Vertical	Pass
3**	4936.000	54.49	-1.33	54.0	0.49	AV	360.00	100	Vertical	N/A
3*	4936.000	49.439	-1.33	54.0	-4.561	AV	360.00	100	Vertical	Pass
4	7510.250	54.23	1.40	74.0	-19.77	Peak	30.00	100	Vertical	Pass
4**	7510.250	44.13	1.40	54.0	-9.87	AV	30.00	100	Vertical	Pass
5	9058.500	49.06	-3.21	74.0	-24.94	Peak	0.00	100	Vertical	Pass
5**	9058.500	39.74	-3.21	54.0	-14.26	AV	0.00	100	Vertical	Pass
6	15084.500	52.37	0.93	74.0	-21.63	Peak	0.00	100	Vertical	Pass
6**	15084.500	42.55	0.93	54.0	-11.45	AV	0.00	100	Vertical	Pass

## GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1920.000	39.63	-15.88	74.0	-34.37	Peak	8.00	100	Horizontal	Pass
1**	1920.000	34.61	-15.88	54.0	-19.39	AV	8.00	100	Horizontal	Pass
2	2473.600	77.31	-12.60	74.0	3.31	Peak	2.00	100	Horizontal	N/A
2**	2473.600	76.74	-12.60	54.0	22.74	AV	2.00	100	Horizontal	N/A
3	4948.000	52.06	-1.51	74.0	-21.94	Peak	4.00	100	Horizontal	Pass
3**	4948.000	47.88	-1.51	54.0	-6.12	AV	4.00	100	Horizontal	Pass
4	7376.000	53.85	0.84	74.0	-20.15	Peak	5.00	100	Horizontal	Pass
4**	7376.000	44.86	0.84	54.0	-9.14	AV	5.00	100	Horizontal	Pass
5	9287.500	48.92	-1.61	74.0	-25.08	Peak	6.00	100	Horizontal	Pass
5**	9287.500	40.04	-1.61	54.0	-13.96	AV	6.00	100	Horizontal	Pass
6	15329.500	52.06	1.36	74.0	-21.94	Peak	5.00	100	Horizontal	Pass
6**	15329.500	43.36	1.36	54.0	-10.64	AV	5.00	100	Horizontal	Pass

## GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1920.200	40.20	-15.89	74.0	-33.80	Peak	146.00	100	Vertical	Pass
1**	1920.200	34.10	-15.89	54.0	-19.90	AV	146.00	100	Vertical	Pass
2	2473.600	84.09	-12.60	74.0	10.09	Peak	0.00	100	Vertical	N/A
2**	2473.600	83.76	-12.60	54.0	29.76	AV	0.00	100	Vertical	N/A
3	4947.500	55.72	-1.56	74.0	-18.28	Peak	360.00	100	Vertical	Pass
3**	4947.500	53.59	-1.56	54.0	-0.41	AV	360.00	100	Vertical	N/A
3*	4947.500	49.384	-1.56	54.0	-4.616	AV	360.00	100	Vertical	Pass
4	7484.750	54.61	1.40	74.0	-19.39	Peak	158.00	100	Vertical	Pass
4**	7484.750	45.21	1.40	54.0	-8.79	AV	158.00	100	Vertical	Pass
5	8812.500	49.08	-2.80	74.0	-24.92	Peak	26.00	100	Vertical	Pass
5**	8812.500	39.36	-2.80	54.0	-14.64	AV	26.00	100	Vertical	Pass
6	16455.999	52.13	1.45	74.0	-21.87	Peak	290.00	100	Vertical	Pass
6**	16455.999	42.27	1.45	54.0	-11.73	AV	290.00	100	Vertical	Pass

## GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1920.300	41.17	-15.89	74.0	-32.83	Peak	70.00	100	Horizontal	Pass
1**	1920.300	33.52	-15.89	54.0	-20.48	AV	70.00	100	Horizontal	Pass
2	2480.000	86.77	-12.61	74.0	12.77	Peak	300.00	100	Horizontal	N/A
2**	2480.000	86.74	-12.61	54.0	32.74	AV	300.00	100	Horizontal	N/A
3	4959.500	52.73	-2.09	74.0	-21.27	Peak	278.00	100	Horizontal	Pass
3**	4959.500	50.45	-2.09	54.0	-3.55	AV	278.00	100	Horizontal	Pass
4	7427.500	54.63	1.07	74.0	-19.37	Peak	42.00	100	Horizontal	Pass
4**	7427.500	44.94	1.07	54.0	-9.06	AV	42.00	100	Horizontal	Pass
5	9328.500	49.08	-2.46	74.0	-24.92	Peak	98.00	100	Horizontal	Pass
5**	9328.500	39.98	-2.46	54.0	-14.02	AV	98.00	100	Horizontal	Pass
6	15229.500	52.18	0.58	74.0	-21.82	Peak	113.00	100	Horizontal	Pass
6**	15229.500	43.66	0.58	54.0	-10.34	AV	113.00	100	Horizontal	Pass

## GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1920.000	40.50	-15.88	74.0	-33.50	Peak	191.00	100	Vertical	Pass
1**	1920.000	35.08	-15.88	54.0	-18.92	AV	191.00	100	Vertical	Pass
2	2479.700	84.64	-12.61	74.0	10.64	Peak	19.00	100	Vertical	N/A
2**	2479.700	84.57	-12.61	54.0	30.57	AV	19.00	100	Vertical	N/A
3	4959.500	54.90	-2.09	74.0	-19.10	Peak	0.00	100	Vertical	Pass
3**	4959.500	52.30	-2.09	54.0	-1.70	AV	0.00	100	Vertical	N/A
3*	4959.500	48.215	-2.09	54.0	-5.785	AV	0.00	100	Vertical	Pass
4	7533.000	54.11	1.55	74.0	-19.89	Peak	138.00	100	Vertical	Pass
4**	7533.000	45.57	1.55	54.0	-8.43	AV	138.00	100	Vertical	Pass
5	9304.001	50.07	-1.05	74.0	-23.93	Peak	247.00	100	Vertical	Pass
5**	9304.001	40.81	-1.05	54.0	-13.19	AV	247.00	100	Vertical	Pass
6	16496.500	51.83	2.03	74.0	-22.17	Peak	126.00	100	Vertical	Pass
6**	16496.500	43.13	2.03	54.0	-10.87	AV	126.00	100	Vertical	Pass

## A.9 Band Edge (Restricted-band band-edge)

Note <sup>1</sup>: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.


Note <sup>2</sup>: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note <sup>3</sup>: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note <sup>4</sup>: The Level (dB<sub>UV</sub>/m) has been corrected by factor.


### Test Data

#### GFSK LOW CHANNEL



No.	Frequency (MHz)	Results (dB <sub>UV</sub> /m)	Factor (dB)	Limit (dB <sub>UV</sub> /m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	54.10	0.70	74.0	-19.90	Peak	88.00	100	Horizontal	Pass
1**	2390.000	43.07	0.70	54.0	-10.93	AV	88.00	100	Horizontal	Pass
2	2318.333	55.30	1.05	74.0	-18.70	Peak	98.00	100	Horizontal	Pass
2**	2318.333	43.76	1.05	54.0	-10.24	AV	98.00	100	Horizontal	Pass

## GFSK HIGH CHANNEL,



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	63.69	0.86	74.0	-10.31	Peak	295.00	100	Horizontal	Pass
1**	2483.500	43.77	0.86	54.0	-10.23	AV	295.00	100	Horizontal	Pass

## ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ2180090-AR.PDF".

## ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ2180090-AW.PDF".

## ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ2180090-AI.PDF".

--END OF REPORT--