

APPLICATION CERTIFICATION

On Behalf of  
ACCO Brands, Inc.

KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Model No.: M01147

FCC ID: GV3-M01147

Prepared for : ACCO Brands, Inc.  
Address : 333 Twin Dolphin Drive, 6th Floor, Redwood Shores,  
California, United States

Prepared by : ACCURATE TECHNOLOGY CO. LTD  
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.  
Science & Industry Park, Nanshan, Shenzhen, Guangdong  
P.R. China

Tel: (0755) 26503290  
Fax: (0755) 26503396

Report Number : ATE20120132  
Date of Test : February 9-21, 2012  
Date of Report : February 21, 2012

# TABLE OF CONTENTS

Description	Page
Test Report Certification	
<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. Description of Device (EUT).....	5
1.2. Accessory and Auxiliary Equipment .....	5
1.3. Description of Test Facility .....	6
1.4. Measurement Uncertainty.....	6
<b>2. MEASURING DEVICE AND TEST EQUIPMENT .....</b>	<b>7</b>
<b>3. OPERATION OF EUT DURING TESTING .....</b>	<b>8</b>
3.1. Operating Mode .....	8
3.2. Configuration and peripherals .....	8
<b>4. TEST PROCEDURES AND RESULTS .....</b>	<b>9</b>
<b>5. 20DB BANDWIDTH TEST.....</b>	<b>10</b>
5.1. Block Diagram of Test Setup.....	10
5.2. The Requirement For Section 15.247(a)(1).....	10
5.3. EUT Configuration on Measurement .....	10
5.4. Operating Condition of EUT .....	10
5.5. Test Procedure .....	11
5.6. Test Result .....	11
<b>6. CARRIER FREQUENCY SEPARATION TEST.....</b>	<b>15</b>
6.1. Block Diagram of Test Setup.....	15
6.2. The Requirement For Section 15.247(a)(1).....	15
6.3. EUT Configuration on Measurement .....	15
6.4. Operating Condition of EUT .....	15
6.5. Test Procedure .....	16
6.6. Test Result .....	16
<b>7. NUMBER OF HOPPING FREQUENCY TEST .....</b>	<b>20</b>
7.1. Block Diagram of Test Setup.....	20
7.2. The Requirement For Section 15.247(a)(1)(iii).....	20
7.3. EUT Configuration on Measurement .....	20
7.4. Operating Condition of EUT .....	20
7.5. Test Procedure .....	21
7.6. Test Result .....	21
<b>8. DWELL TIME TEST .....</b>	<b>25</b>
8.1. Block Diagram of Test Setup.....	25
8.2. The Requirement For Section 15.247(a)(1)(iii).....	25
8.3. EUT Configuration on Measurement .....	25
8.4. Operating Condition of EUT .....	25
8.5. Test Procedure .....	26
8.6. Test Result .....	26
<b>9. MAXIMUM PEAK OUTPUT POWER TEST .....</b>	<b>30</b>
9.1. Block Diagram of Test Setup.....	30
9.2. The Requirement For Section 15.247(b)(1).....	30
9.3. EUT Configuration on Measurement .....	30
9.4. Operating Condition of EUT .....	30

9.5.	Test Procedure .....	31
9.6.	Test Result .....	31
<b>10.</b>	<b>BAND EDGE COMPLIANCE TEST .....</b>	<b>35</b>
10.1.	Block Diagram of Test Setup.....	35
10.2.	The Requirement For Section 15.247(d) .....	35
10.3.	EUT Configuration on Measurement .....	35
10.4.	Operating Condition of EUT .....	36
10.5.	Test Procedure .....	36
10.6.	Test Result .....	37
<b>11.</b>	<b>RADIATED SPURIOUS EMISSION TEST .....</b>	<b>48</b>
11.1.	Block Diagram of Test Setup.....	48
11.2.	The Limit For Section 15.247(d) .....	48
11.3.	Restricted bands of operation .....	49
11.4.	Configuration of EUT on Measurement .....	49
11.5.	Operating Condition of EUT .....	50
11.6.	Test Procedure .....	50
11.7.	The Field Strength of Radiation Emission Measurement Results .....	51
<b>12.</b>	<b>CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST .....</b>	<b>72</b>
12.1.	Block Diagram of Test Setup.....	72
12.2.	The Requirement For Section 15.247(d) .....	72
12.3.	EUT Configuration on Measurement .....	72
12.4.	Operating Condition of EUT .....	73
12.5.	Test Procedure .....	73
12.6.	Test Result .....	73
<b>13.</b>	<b>AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) ..</b>	<b>77</b>
13.1.	Block Diagram of Test Setup.....	77
13.2.	The Emission Limit .....	77
13.3.	Configuration of EUT on Measurement .....	78
13.4.	Operating Condition of EUT .....	78
13.5.	Test Procedure .....	78
13.6.	Power Line Conducted Emission Measurement Results .....	79
<b>14.</b>	<b>ANTENNA REQUIREMENT.....</b>	<b>82</b>
14.1.	The Requirement .....	82
14.2.	Antenna Construction .....	82

## Test Report Certification

Applicant : ACCO Brands, Inc.  
Manufacturer : Shenzhen Doking Electronic Technology Co., Ltd.  
EUT Description : KEYFOLIO EXPERT BLUETOOTH KEYBOARD  
(A) MODEL NO.: M01147  
(B) SERIAL NO.: N/A  
(C) POWER SUPPLY: DC 3.7V(Li-ion battery 1x)

Measurement Procedure Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.247**  
**ANSI C63.4: 2003**

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.


Date of Test : February 9-21, 2012

Prepared by :



(Engineer)

Approved & Authorized Signer :



(Manager)

# 1. GENERAL INFORMATION

## 1.1. Description of Device (EUT)

EUT	:	KEYFOLIO EXPERT BLUETOOTH KEYBOARD
Model Number	:	M01147
Frequency Band	:	2402MHz-2480MHz
Number of Channels	:	79
Antenna Gain	:	0dBi
Power Supply	:	DC 3.7V(Li-ion battery 1×)
Applicant	:	ACCO Brands, Inc.
Address	:	333 Twin Dolphin Drive, 6th Floor, Redwood Shores, California, United States
Manufacturer	:	Shenzhen Doking Electronic Technology Co., Ltd.
Address	:	Dingfeng Hi-tech Estate, Shapu, Songgang Town, Baoan District, Shenzhen, Guangdong, China
Date of sample received	:	February 9, 2012
Date of Test	:	February 9-21, 2012

## 1.2. Accessory and Auxiliary Equipment

PC (CE, FCC: DOC, VCCI)	Manufacturer: DELL M/N: DMC S/N: HZXLM1
LCD Monitor (CE, FCC: DOC, VCCI)	: Manufacturer: DELL M/N: 1704FPTt

### 1.3. Description of Test Facility

EMC Lab	:	<p>Accredited by TUV Rheinland Shenzhen</p> <p>Listed by FCC The Registration Number is 752051</p> <p>Listed by Industry Canada The Registration Number is 5077A-2</p> <p>Accredited by China National Accreditation Committee for Laboratories The Certificate Registration Number is L3193</p>
Name of Firm	:	ACCURATE TECHNOLOGY CO. LTD
Site Location	:	<p>F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science &amp; Industry Park, Nanshan, Shenzhen, Guangdong P.R. China</p>

### 1.4. Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty (Above 1GHz)	=	4.06dB, k=2

## 2. MEASURING DEVICE AND TEST EQUIPMENT

**Table 1: List of Test and Measurement Equipment**

Kind of equipment	Manufacturer	Type	S/N	Calibrated date	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 7, 2012	Jan. 7, 2013
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 7, 2012	Jan. 7, 2013
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 7, 2012	Jan. 7, 2013
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 7, 2012	Jan. 7, 2013
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 7, 2012	Jan. 7, 2013
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 7, 2012	Jan. 7, 2013
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 7, 2012	Jan. 7, 2013
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 7, 2012	Jan. 7, 2013
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 7, 2012	Jan. 7, 2013
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 7, 2012	Jan. 7, 2013

### 3. OPERATION OF EUT DURING TESTING

#### 3.1.Operating Mode

The mode is used: Transmitting mode

Low Channel: 2402MHz

Middle Channel: 2441MHz

High Channel: 2480MHz

Hopping

Charging (Connect to PC)

#### 3.2.Configuration and peripherals




Figure 1 Setup: Transmitting mode




## 4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.247(d) Section 15.209	Radiated Spurious Emission Test	Compliant
Section 15.247(d)	Conducted Spurious Emission Test	Compliant
Section 15.207	AC Power Line Conducted Emission Test	Compliant
Section 15.203	Antenna Requirement	Compliant

## 5. 20DB BANDWIDTH TEST

### 5.1. Block Diagram of Test Setup



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

### 5.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

### 5.3. EUT Configuration on Measurement

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 5.3.1. KEYFOLIO EXPERT BLUETOOTH KEYBOARD (EUT)

Model Number	:	M01147
Serial Number	:	N/A
Manufacturer	:	Shenzhen Doking Electronic Technology Co., Ltd.

### 5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX(Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, 2480MHz TX frequency to transmit.

## 5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2. Set RBW of spectrum analyzer to 30kHz and VBW to 100kHz.

5.5.3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

## 5.6. Test Result

**PASS.**

Date of Test:	<u>February 14, 2012</u>	Temperature:	<u>25°C</u>
EUT:	<u>KEYFOLIO EXPERT</u>	Humidity:	<u>50%</u>
Model No.:	<u>M01147</u>	Power Supply:	<u>DC 3.7V</u>
Test Mode:	<u>TX</u>	Test Engineer:	<u>Kai</u>


Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
Low	2402	0.858	N/A
Middle	2441	0.852	N/A
High	2480	0.846	N/A


Note: N/A: 1) The 20 dB bandwidth of the hopping channel is not limit.

2) The data of 20 dB bandwidth of the hopping channel is limit of carrier frequencies separated

The spectrum analyzer plots are attached as below.


"Spectrum analyzer" is R/S








1 PR  
MAXH



## 6. CARRIER FREQUENCY SEPARATION TEST

### 6.1. Block Diagram of Test Setup



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

### 6.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### 6.3. EUT Configuration on Measurement

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 6.3.1. KEYFOLIO EXPERT BLUETOOTH KEYBOARD (EUT)

Model Number : M01147  
 Serial Number : N/A  
 Manufacturer : Shenzhen Doking Electronic Technology Co., Ltd.

### 6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, 2480MHz TX frequency to transmit.

## 6.5. Test Procedure

6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz. Adjust Span to 3 MHz.

6.5.3. Set the adjacent channel of the EUT maxhold another trace.

6.5.4. Measurement the channel separation

## 6.6. Test Result

**PASS.**


Date of Test:	February 14, 2012	Temperature:	25°C
EUT:	KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Humidity:	50%
Model No.:	M01147	Power Supply:	DC 3.7V
Test Mode:	Hopping	Test Engineer:	Kai

Channel	Channel Frequency (MHz)	Channel separation (MHz)	Limit
Low	2402	1.002	> the 20dB Bandwidth or 25kHz (whichever is greater)
Middle	2441	1.002	> the 20dB Bandwidth or 25kHz (whichever is greater)
High	2480	1.002	> the 20dB Bandwidth or 25kHz (whichever is greater)

The spectrum analyzer plots are attached as below.




Spectrum analyzer" is R/S






1 PK  
MAXH






1 PK  
MAXH



## 7. NUMBER OF HOPPING FREQUENCY TEST

### 7.1. Block Diagram of Test Setup



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

### 7.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 7.3. EUT Configuration on Measurement

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 7.3.1. KEYFOLIO EXPERT BLUETOOTH KEYBOARD (EUT)

Model Number	:	M01147
Serial Number	:	N/A
Manufacturer	:	Shenzhen Doking Electronic Technology Co., Ltd.

### 7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it.

## 7.5. Test Procedure

7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2. Set the spectrum analyzer as Span=30MHz, RBW=300kHz, VBW=300kHz.

7.5.3. Max hold, view and count how many channel in the band.

## 7.6. Test Result


**PASS.**


Date of Test:	<u>February 14, 2012</u>	Temperature:	<u>25°C</u>
	<u>KEYFOLIO EXPERT</u>		
EUT:	<u>BLUETOOTH KEYBOARD</u>	Humidity:	<u>50%</u>
Model No.:	<u>M01147</u>	Power Supply:	<u>DC 3.7V</u>
Test Mode:	<u>Hopping</u>	Test Engineer:	<u>Kai</u>


Total number of hopping channel	Measurement result (CH)	Limit (CH)
	79	>15

The spectrum analyzer plots are attached as below.

Spectrum analyzer" is R/S










## 8. DWELL TIME TEST

### 8.1. Block Diagram of Test Setup



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

### 8.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 8.3. EUT Configuration on Measurement

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 8.3.1. KEYFOLIO EXPERT BLUETOOTH KEYBOARD (EUT)

Model Number	: M01147
Serial Number	: N/A
Manufacturer	: Shenzhen Doking Electronic Technology Co., Ltd.

### 8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, 2480MHz TX frequency to transmit.

## 8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Set center frequency of spectrum analyzer = operating frequency.

8.5.3. Set the spectrum analyzer as RBW=100kHz, VBW=300kHz, Span=0Hz, Adjust Sweep=1s. Get the burst (in 1 sec.).

8.5.4. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz, Adjust Sweep=2ms. Get the pulse time.

8.5.5. Repeat above procedures until all frequency measured were complete.

## 8.6. Test Result

**PASS.**

Date of Test:	<u>February 14, 2012</u>	Temperature:	<u>25°C</u>
	<u>KEYFOLIO EXPERT</u>		
EUT:	<u>BLUETOOTH KEYBOARD</u>	Humidity:	<u>50%</u>
Model No.:	<u>M01147</u>	Power Supply:	<u>DC 3.7V</u>
Test Mode:	<u>Hopping</u>	Test Engineer:	<u>Kai</u>



A period transmit time =  $0.4 \times 79 = 31.6$



Dwell time = pulse time  $\times$  burst (in 1 sec.)  $\times 31.6$



Channel	Channel Frequency (MHz)	Pulse Time (ms)	Burst (in 1 sec.)	Dwell Time (ms)	Limit (ms)
Low	2402	0.384	10	121.3	400
Middle	2441	0.384	10	121.3	400
High	2480	0.384	10	121.3	400

The spectrum analyzer plots are attached as below.

"Spectrum analyzer" is R/S








## 9. MAXIMUM PEAK OUTPUT POWER TEST

### 9.1. Block Diagram of Test Setup



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

### 9.2. The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 9.3. EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 9.3.1. KEYFOLIO EXPERT BLUETOOTH KEYBOARD (EUT)

Model Number	:	M01147
Serial Number	:	N/A
Manufacturer	:	Shenzhen Doking Electronic Technology Co., Ltd.

### 9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, 2480MHz TX frequency to transmit.

## 9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz.

9.5.3. Measurement the maximum peak output power.

## 9.6. Test Result


**PASS.**

Date of Test:	<u>February 14, 2012</u>	Temperature:	<u>25°C</u>
	<u>KEYFOLIO EXPERT</u>		
EUT:	<u>BLUETOOTH KEYBOARD</u>	Humidity:	<u>50%</u>
Model No.:	<u>M01147</u>	Power Supply:	<u>DC 3.7V</u>
Test Mode:	<u>TX</u>	Test Engineer:	<u>Kai</u>

Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2402	-3.02	0.499	30 dBm / 1 W
Middle	2441	-3.21	0.478	30 dBm / 1 W
High	2480	-3.47	0.450	30 dBm / 1 W

The spectrum analyzer plots are attached as below.


"Spectrum analyzer" is R/S








1 PK  
MAXH






1 PK  
MAXH



## 10.BAND EDGE COMPLIANCE TEST

### 10.1.Block Diagram of Test Setup



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

### 10.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

### 10.3.EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 10.3.1.KEYFOLIO EXPERT BLUETOOTH KEYBOARD (EUT)

Model Number	:	M01147
Serial Number	:	N/A
Manufacturer	:	Shenzhen Doking Electronic Technology Co., Ltd.

## 10.4. Operating Condition of EUT

10.4.1. Setup the EUT and simulator as shown as Section 10.1.

10.4.2. Turn on the power of all equipment.

10.4.3. Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

## 10.5. Test Procedure

### Conducted Band Edge:

10.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

10.5.2. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz.

### Radiate Band Edge:

10.5.3. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.

10.5.4. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

10.5.5. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

10.5.6. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

RBW=1MHz, VBW=1MHz

10.5.7. The band edges was measured and recorded.

## 10.6.Test Result

**Pass****Conducted test**

Date of Test:	February 14, 2012	Temperature:	25°C
	KEYFOLIO EXPERT		
EUT:	BLUETOOTH KEYBOARD	Humidity:	50%
Model No.:	M01147	Power Supply:	DC 3.7V
Test Mode:	TX (Hopping off)	Test Engineer:	Kai

**Conducted test**

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2402	37.41	> 20dBc
2480	42.53	> 20dBc


Date of Test:	February 14, 2012	Temperature:	25°C
	KEYFOLIO EXPERT		
EUT:	BLUETOOTH KEYBOARD	Humidity:	50%
Model No.:	M01147	Power Supply:	DC 3.7V
Test Mode:	TX (Hopping on)	Test Engineer:	Kai

**Conducted test**

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2402	38.63	> 20dBc
2480	43.41	> 20dBc




1 PK  
MAXH






1 PK  
MAXH






1 PK  
MAXH







1 PK  
MAXH



**Radiated Band Edge Result**

Date of Test:	February 14, 2012	Temperature:	25°C
EUT:	KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Humidity:	50%
Model No.:	M01147	Power Supply:	DC 3.7V
Test Mode:	TX (2402MHz)	Test Engineer:	Kai

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

**Note:**

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:  

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$
3. Display the measurement of peak values.

Date of Test:	February 14, 2012	Temperature:	25°C
EUT:	KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Humidity:	50%
Model No.:	M01147	Power Supply:	DC 3.7V
Test Mode:	TX (2480MHz)	Test Engineer:	Kai

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

## Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:  
Result = Reading + Corrected Factor
3. Display the measurement of peak values.




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 988 chamber  
Tel:+86-0755-26503290  
Fax:+86-0755-26503396

Job No.: Bob #1034	Polarization: Horizontal
Standard: FCC Part 15 PEAK 2.4G	Power Source: DC 3.7V
Test item: Radiation Test	Date: 12/02/14/
Temp.( C)/Hum.(%) 24 C / 48 %	Time: 9/52/32
EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Engineer Signature:
Mode: TX 2402	Distance: 3m
Model: M01147	
Manufacturer: Doking	

Note: Report NO.:ATE20120132




**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 988 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1036	Polarization: Vertical
Standard: FCC Part 15 PEAK 2.4G	Power Source: DC 3.7V
Test item: Radiation Test	Date: 12/02/14/
Temp.( C)/Hum.(%) 24 C / 48 %	Time: 9/56/21
EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Engineer Signature:
Mode: TX 2402	Distance: 3m
Model: M01147	
Manufacturer: Doking	

Note: Report NO.:ATE20120132




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503398

Job No.: Bob #1038	Polarization: Horizontal
Standard: FCC Part 15 PEAK 2.4G	Power Source: DC 3.7V
Test item: Radiation Test	Date: 12/02/14/
Temp.( C)/Hum.(%) 24 C / 48 %	Time: 10/02/59
EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Engineer Signature:
Mode: TX 2480	Distance: 3m
Model: M01147	
Manufacturer: Doking	

Note: Report NO.:ATE20120132




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1037  
Standard: FCC Part 15 PEAK 2.4G  
Test item: Radiation Test  
Temp.( C)/Hum.(%) 24 C / 48 %  
EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD  
Mode: TX 2480  
Model: M01147  
Manufacturer: Doking

Polarization: Vertical  
Power Source: DC 3.7V  
Date: 12/02/14/  
Time: 9/58/36  
Engineer Signature:  
Distance: 3m


Note: Report NO.:ATE20120132



# 11.RADIATED SPURIOUS EMISSION TEST


## 11.1.Block Diagram of Test Setup

### 11.1.1.Block diagram of connection between the EUT and simulators



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

### 11.1.2.Semi-Anechoic Chamber Test Setup Diagram



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

## 11.2.The Limit For Section 15.247(d)



Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

### 11.3.Restricted bands of operation

#### 11.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

<sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510

<sup>2</sup>Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

### 11.4.Configuration of EUT on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 11.4.1.KEYFOLIO EXPERT BLUETOOTH KEYBOARD (EUT)

Model Number : M01147  
 Serial Number : N/A  
 Manufacturer : Shenzhen Doking Electronic Technology Co., Ltd.

### 11.5.Operating Condition of EUT

11.5.1.Setup the EUT and simulator as shown as Section 11.1.

11.5.2.Turn on the power of all equipment.

11.5.3.Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, 2480MHz TX frequency to transmit.

### 11.6.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver (R&S ESI26) is set at 120kHz in 30-1000MHz. and set at 1MHz in above 1000MHz.

The frequency range from 30MHz to 25000MHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

The field strength is calculated by adding the antenna factor, and cable loss, and subtracting the amplifier gain from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

## 11.7. The Field Strength of Radiation Emission Measurement Results

### PASS.

Date of Test:	February 11-14, 2012	Temperature:	25°C
EUT:	KEYFOLIO EXPERT BLUETOOTH	Humidity:	50%
Model No.:	M01147	Power Supply:	DC 3.7V
Test Mode:	TX (2402MHz)	Test Engineer:	Kai

#### For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
143.7760	14.30	14.48	28.78	43.50	-14.72	Vertical
189.1076	14.89	46.00	30.89	43.50	-12.61	
236.7928	16.23	16.54	32.77	46.00	-13.23	
143.7760	22.66	14.48	37.14	43.50	-6.36	Horizontal
236.7928	22.56	16.80	39.36	46.0	-6.64	
285.2611	16.11	18.46	34.57	46.00	-11.43	

#### For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2402.000	57.43	70.18	-7.45	49.98	62.73	-	-	-	-	Vertical
2402.000	55.66	66.66	-7.45	48.21	59.21	-	-	-	-	Horizontal

**Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**

**2. \*: Denotes restricted band of operation.**

Date of Test:	February 11-14, 2012	Temperature:	25°C
EUT:	KEYFOLIO EXPERT BLUETOOTH	Humidity:	50%
Model No.:	M01147	Power Supply:	DC 3.7V
Test Mode:	TX (2441MHz)	Test Engineer:	Kai

**For 30MHz-1000MHz**

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
143.7760	15.89	14.48	30.37	43.50	-13.13	Vertical
189.1076	14.75	16.00	30.75	43.50	-12.75	
236.7928	17.12	16.54	33.66	46.00	-12.34	
143.7760	22.02	14.48	36.50	43.50	-7.00	Horizontal
236.7928	22.30	16.80	39.10	46.00	-6.90	
285.2611	15.63	18.46	34.09	46.00	-11.91	

**For 1GHz-25GHz**

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2441.000	55.41	66.37	-7.35	48.06	59.02	-	-	-	-	Vertical
2441.000	58.37	72.03	-7.35	51.02	64.68	-	-	-	-	Horizontal

**Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.****2. \*: Denotes restricted band of operation.**

Date of Test:	February 11-14, 2012	Temperature:	25°C
EUT:	KEYFOLIO EXPERT BLUETOOTH	Humidity:	50%
Model No.:	M01147	Power Supply:	DC 3.7V
Test Mode:	TX (2480MHz)	Test Engineer:	Kai

**For 30MHz-1000MHz**

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
143.7760	15.98	14.48	30.46	43.50	-13.04	Vertical
189.1076	14.19	16.00	30.19	43.50	-13.31	
236.7928	16.18	16.54	32.72	46.00	-13.28	
143.7760	20.30	14.48	34.78	43.50	-8.72	Horizontal
189.1076	19.19	16.06	35.25	43.50	-8.25	
236.7928	18.70	16.80	35.50	46.00	-10.50	

**For 1GHz-25GHz**

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2480.000	57.48	69.06	-7.37	50.11	61.69	-	-	-	-	Vertical
2480.000	58.34	71.54	-7.37	50.97	64.17	-	-	-	-	Horizontal

**Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.****2. \*: Denotes restricted band of operation.**


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1022	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 12/02/14/
Temp.( C)/Hum.(%) 24 C / 48 %	Time: 9/06/21
EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Engineer Signature:
Mode: TX 2402	Distance: 3m
Model: M01147	
Manufacturer: Doking	

Note: Report NO.:ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	143.7780	22.66	14.48	37.14	43.50	-6.36	QP			
2	236.7928	22.56	16.80	39.36	46.00	-6.64	QP			
3	285.2611	16.11	18.46	34.57	46.00	-11.43	QP			


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 968 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1023

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2402

Model: M01147

Manufacturer: Doking

Polarization: Vertical

Power Source: DC 3.7V


Date: 12/02/14/

Time: 9/09/12

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	143.7760	14.30	14.48	28.78	43.50	-14.72	QP			
2	189.1076	14.89	16.00	30.89	43.50	-12.61	QP			
3	236.7928	16.23	16.54	32.77	46.00	-13.23	QP			



**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: Bob #986	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2012/02/13
Temp.( C)/Hum.(%) 24 C / 48 %	Time: 12:52:17
EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Engineer Signature:
Mode: TX 2402	Distance: 3m
Model: M01147	
Manufacturer: Doking	

Note: Report NO.:ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	66.66	-7.45	59.21	—	—	peak			
2	2402.000	55.66	-7.45	48.21	—	—	AVG			




**ACCURATE TECHNOLOGY CO., LTD.**

 F1.Bldg.A, Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park, Nanshan Shenzhen, P.R.China

Site: 968 chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: Bob #987

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2402

Model: M01147

Manufacturer: Doking

Polarization: Vertical

Power Source: DC 3.7V


Date: 2012/02/13

Time: 12:56:05

Engineer Signature:

Distance: 3m

Note: Report NO.: ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	70.18	-7.45	62.73	--	--	peak			
2	2402.000	57.43	-7.45	49.98	--	--	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1238

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2402MHz

Model: M01147

Manufacturer: Doking

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2012/2/11

Time: 5/47/15

Engineer Signature: Bob

Distance:

Note: Report No.: ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1239

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2402MHz

Model: M01147

Manufacturer: Doking

Polarization: Vertical

Power Source: DC 3.7V


Date: 2012/2/11

Time: 5/49/05

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1025

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2441

Model: M01147

Manufacturer: Doking

Polarization: Horizontal

Power Source: DC 3.7V


Date: 12/02/14/

Time: 9/16/50

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20120132






**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1024

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2441

Model: M01147

Manufacturer: Doking

Polarization: Vertical

Power Source: DC 3.7V


Date: 12/02/14/

Time: 9/13/10

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	143.7760	15.89	14.48	30.37	43.50	-13.13	QP			
2	189.1076	14.75	16.00	30.75	43.50	-12.75	QP			
3	238.7928	17.12	16.54	33.66	46.00	-12.34	QP			


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #992	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2012/02/13
Temp.( C)/Hum.(%) 24 C / 48 %	Time: 13:07:52
EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Engineer Signature:
Mode: TX 2441	Distance: 3m
Model: M01147	
Manufacturer: Doking	

Note: Report NO.:ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.000	72.03	-7.35	64.68	—	—	peak			
2	2441.000	58.37	-7.35	51.02	—	—	AVG			


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #991  
 Standard: FCC Class B 3M Radiated  
 Test item: Radiation Test  
 Temp.( C)/Hum.(%) 24 C / 48 %  
 EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD  
 Mode: TX 2441  
 Model: M01147  
 Manufacturer: Doking

Polarization: Vertical  
 Power Source: DC 3.7V  
 Date: 2012/02/13  
 Time: 13:05:27  
 Engineer Signature:  
 Distance: 3m

Note: Report NO.:ATE20120132




**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1241

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2441MHz

Model: M01147

Manufacturer: Doking

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2012/2/11

Time: 5/53/01

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------




**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1240

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2441MHz

Model: M01147

Manufacturer: Doking

Polarization: Vertical

Power Source: DC 3.7V


Date: 2012/2/11

Time: 5/51/02

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**


 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 968 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1026	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 12/02/14/
Temp.( C)/Hum.(%) 24 C / 48 %	Time: 9/21/29
EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Engineer Signature:
Mode: TX 2480	Distance: 3m
Model: M01147	
Manufacturer: Doking	
Note: Report NO.:ATE20120132	




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	143.7760	20.30	14.48	34.78	43.50	-8.72	QP			
2	189.1078	19.19	16.06	35.25	43.50	-8.25	QP			
3	236.7928	18.70	16.80	35.50	46.00	-10.50	QP			


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: Bob #1027	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 12/02/14/
Temp.( C)/Hum.(%) 24 C / 48 %	Time: 9/24/11
EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD	Engineer Signature:
Mode: TX 2480	Distance: 3m
Model: M01147	
Manufacturer: Doking	
Note: Report NO.:ATE20120132	



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	143.7760	15.98	14.48	30.46	43.50	-13.04	QP			
2	189.1076	14.19	16.00	30.19	43.50	-13.31	QP			
3	236.7928	16.18	16.54	32.72	46.00	-13.28	QP			


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #995

Polarization: Horizontal

Standard: FCC Class B 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 2012/02/13

Temp.( C)/Hum.(%) 24 C / 48 %

Time: 13:14:50

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Engineer Signature:


Mode: TX 2480

Distance: 3m

Model: M01147

Manufacturer: Doking

Note: Report NO.: ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	71.54	-7.37	64.17	—	—	peak			
2	2480.000	58.34	-7.37	50.97	—	—	AVG			




**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg.A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 986 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503398

Job No.: Bob #996

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2480

Model: M01147

Manufacturer: Doking

Polarization: Vertical

Power Source: DC 3.7V


Date: 2012/02/13

Time: 13:19:24

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20120132




**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #1242

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2480MHz

Model: M01147

Manufacturer: Doking

Polarization: Horizontal

Power Source: DC 3.7V


Date: 2012/2/11

Time: 5/55/57

Engineer Signature: Bob

Distance:

Note: Report No.:ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: Bob #1243

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 24 C / 48 %

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD

Mode: TX 2480MHz

Model: M01147

Manufacturer: Doking

Polarization: Vertical

Power Source: DC 3.7V


Date: 2012/2/11

Time: 5/57/43

Engineer Signature: Bob

Distance:


Note: Report No.: ATE20120132



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------

## 12.CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST

### 12.1.Block Diagram of Test Setup



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

### 12.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

### 12.3.EUT Configuration on Measurement

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 12.3.1.KEYFOLIO EXPERT BLUETOOTH KEYBOARD (EUT)

Model Number	:	M01147
Serial Number	:	N/A
Manufacturer	:	Shenzhen Doking Electronic Technology Co., Ltd.



## 12.4.Operating Condition of EUT

12.4.1.Setup the EUT and simulator as shown as Section 12.1.

12.4.2.Turn on the power of all equipment.

12.4.3.Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, 2480MHz TX frequency to transmit.

## 12.5.Test Procedure

12.5.1.The transmitter output was connected to the spectrum analyzer via a low loss cable.

12.5.2.Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz (below 1GHz).

Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz (above 1GHz).


12.5.3.The Conducted Spurious Emission was measured and recorded.

## 12.6.Test Result


**Pass.**

The spectrum analyzer plots are attached as below.


"Spectrum analyzer" is [Agilent](#)  
TX 2402GHz (30MHz-1GHz)




TX 2402GHz (1GHz-25GHz)




TX 2441GHz (30MHz-1GHz)




TX 2441GHz (1GHz-25GHz)



TX 2480GHz (30MHz-1GHz)



TX 2480GHz (1GHz-25GHz)




## 13.AC POWER LINE CONDUCTED EMISSION FOR FCC PART

### 15 SECTION 15.207(A)


#### 13.1.Block Diagram of Test Setup

##### 13.1.1.Block diagram of connection between the EUT and simulators



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

##### 13.1.2.Shielding Room Test Setup Diagram



(EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD)

#### 13.2.The Emission Limit

##### 13.2.1.Conducted Emission Measurement Limits According to Section 15.207(a)

Frequency (MHz)	Limit dB(μV)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

\* Decreases with the logarithm of the frequency.

### 13.3.Configuration of EUT on Measurement

The following equipment are installed on the Conducted Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 13.3.1.KEYFOLIO EXPERT BLUETOOTH KEYBOARD (EUT)

Model Number : M01147  
Serial Number : N/A  
Manufacturer : Shenzhen Doking Electronic Technology Co., Ltd.

### 13.4.Operating Condition of EUT

13.4.1.Setup the EUT and simulator as shown as Section 13.1.

13.4.2.Turn on the power of all equipment.

13.4.3.Let the EUT work in (Charging) mode measure it.

### 13.5.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2003 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

### 13.6.Power Line Conducted Emission Measurement Results

**PASS.**

The frequency range from 150kHz to 30MHz is checked.

Date of Test:	<u>February 11, 2012</u>	Temperature:	<u>25°C</u>
	<u>KEYFOLIO EXPERT</u>		
EUT:	<u>BLUETOOTH KEYBOARD</u>	Humidity:	<u>50%</u>
Model No.:	<u>M01147</u>	Power Supply:	<u>AC 120V/ 60Hz</u>
Test Mode:	<u>Charging</u>	Test Engineer:	<u>Kai</u>

Frequency (MHz)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector	Line
0.154868	49.70	65.7	-16.0	QP	Neutral
0.195997	46.60	63.8	-17.2	QP	
0.451436	41.40	56.8	-15.4	QP	
0.154868	33.30	55.7	-22.4	AV	
0.196781	29.40	53.7	-24.3	AV	
0.438995	23.60	47.1	-23.5	AV	
0.157990	48.10	65.6	-17.5	QP	Live
0.194439	45.40	63.8	-18.4	QP	
0.423503	38.50	57.4	-18.9	QP	
0.156109	31.70	55.7	-24.0	AV	
0.195216	29.60	53.8	-24.2	AV	
0.432041	24.20	47.2	-23.0	AV	

Emissions attenuated more than 20 dB below the permissible value are not reported.  
The spectral diagrams are attached as below.


# ACCURATE TECHNOLOGY CO., LTD

## CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD M/N:M01147  
 Manufacturer: Doking  
 Operating Condition: On  
 Test Site: 1#Shielding Room  
 Operator: Bob  
 Test Specification: N AC 120V/60Hz  
 Comment: Mains port  
 Reprot NO.: ATE20120132

### SCAN TABLE: "V 150K-30MHz fin"

Short Description: \_SUB\_STD\_VTERM2 1.70  
 Start Stop Step Detector Meas. IF Transducer  
 Frequency Frequency Width Time Bandw.  
 150.0 kHz 30.0 MHz 0.8 % QuasiPeak 1.0 s 9 kHz NSLK8126 2008  
 Average



### MEASUREMENT RESULT: "B-0203-04\_fin"

2/11/2012 10:56AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.154868	49.70	11.0	65.7	16.0	QP	N	GND
0.195997	46.60	11.2	63.8	17.2	QP	N	GND
0.451436	41.40	11.9	56.8	15.4	QP	N	GND

### MEASUREMENT RESULT: "B-0203-04\_fin2"

2/11/2012 10:56AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.154868	33.30	11.0	55.7	22.4	AV	N	GND
0.196781	29.40	11.2	53.7	24.3	AV	N	GND
0.438995	23.60	11.9	47.1	23.5	AV	N	GND




**ACCURATE TECHNOLOGY CO., LTD****CONDUCTED EMISSION STANDARD FCC PART 15B**

EUT: KEYFOLIO EXPERT BLUETOOTH KEYBOARD M/N:M01147  
 Manufacturer: Doking  
 Operating Condition: On  
 Test Site: 1#Shielding Room  
 Operator: Bob  
 Test Specification: L AC 120V/60Hz  
 Comment: Mains port  
 Reprot NO.: ATE20120132

**SCAN TABLE: "V 150K-30MHz fin"**

Short Description: \_SUB\_STD\_VTERM2 1.70  

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency	Width				
150.0 kHz	30.0 MHz	0.8 %	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			

**MEASUREMENT RESULT: "B-0203-03\_fin"**

2/11/2012 10:52AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.157990	48.10	11.0	65.6	17.5	QP	L1	GND
0.194439	45.40	11.2	63.8	18.4	QP	L1	GND
0.423503	38.50	11.9	57.4	18.9	QP	L1	GND

**MEASUREMENT RESULT: "B-0203-03\_fin2"**

2/11/2012 10:52AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.156109	31.70	11.0	55.7	24.0	AV	L1	GND
0.195216	29.60	11.2	53.8	24.2	AV	L1	GND
0.432041	24.20	11.9	47.2	23.0	AV	L1	GND


## 14.ANTENNA REQUIREMENT

### 14.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 14.2.Antenna Construction

Antenna is formed by a copper trace on the PCB. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna