



# FCC TEST REPORT

**REPORT NO. :** RF931220A08

**MODEL NO. :** 64379

**RECEIVED :** Dec. 20, 2004

**TESTED :** Dec. 21, 2004

**ISSUED:** Dec. 30, 2004

**APPLICANT :** ACCO Brands Inc.

**ADDRESS :** 2000 Alameda de las Pulgas 2nd Floor, San Mateo,  
CA 94403, United States

**ISSUED BY :** Advance Data Technology Corporation

**LAB ADDRESS :** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang  
244, Taipei Hsien, Taiwan, R.O.C.

**TEST LOCATION :** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang  
244, Taipei Hsien, Taiwan, R.O.C.

This test report consists of 15 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agency. The test results in the report only apply to the tested sample.





## Table of Contents

|       |  |    |
|-------|--|----|
| 1     | CERTIFICATION .....                            | 3  |
| 2     | SUMMARY OF TEST RESULTS.....                   | 4  |
| 2.1   | MEASUREMENT UNCERTAINTY .....                  | 4  |
| 3     | GENERAL INFORMATION .....                      | 5  |
| 3.1   | GENERAL DESCRIPTION OF EUT.....                | 5  |
| 3.2   | DESCRIPTION OF TEST MODES.....                 | 6  |
| 3.3   | GENERAL DESCRIPTION OF APPLIED STANDARDS ..... | 6  |
| 3.4   | DESCRIPTION OF SUPPORT UNITS.....              | 7  |
| 3.5   | CONFIGURATION OF SYSTEM UNDER TEST .....       | 7  |
| 4     | TEST PROCEDURE AND RESULT .....                | 8  |
| 4.1   | CONDUCTED EMISSION MEASUREMENT .....           | 8  |
| 4.2   | RADIATED EMISSION MEASUREMENT .....            | 8  |
| 4.2.1 | LIMITS OF RADIATED EMISSION MEASUREMENT.....   | 8  |
| 4.2.2 | TEST INSTRUMENT.....                           | 9  |
| 4.2.3 | TEST PROCEDURE .....                           | 10 |
| 4.2.4 | DEVIATION FROM TEST STANDARD .....             | 10 |
| 4.2.5 | TEST SETUP .....                               | 11 |
| 4.2.6 | EUT OPERATING CONDITION .....                  | 11 |
| 4.2.7 | TEST RESULTS.....                              | 12 |
| 5     | PHOTOGRAPHS OF THE TEST CONFIGURATION.....     | 14 |
| 6     | INFORMATION ON THE TESTING LABORATORIES.....   | 15 |



## 1 CERTIFICATION

**PRODUCT NAME :** Pilotboard Wireless Desktop

**BRAND NAME:** Kensington, ACCO

**MODEL NO. :** 64379

**APPLICANT :** ACCO Brands Inc.

**TESTED :** Dec. 21, 2004

**TEST SAMPLE :** ENGINEERING SAMPLE

**STANDARDS :** FCC Part 15, Subpart C (15.227)

ANSI C63.4-2003

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** Annie Chang, **DATE:** Dec. 30, 2004  
(Annie Chang)

**TECHNICAL**  
**ACCEPTANCE :** Arthur Lin, **DATE:** Dec. 30, 2004  
Responsible for EMI (Arthur Lin)

**APPROVED BY :** Cody Chang, **DATE:** Dec. 30, 2004  
(Cody Chang, Deputy Manager)

## 2 SUMMARY OF TEST RESULTS

After estimating all the combination of every test mode and channel, the result shown as below is the worst case.

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 15, Subpart C |                         |        |   |
|--|-------------------------|--------|---|
| STANDARD PARAGRAPH                       | TEST TYPE               | RESULT | REMARK  |
| 15.207                                   | Conducted Emission Test | NA     | Power supply is 1.5Vdc * 2 battery              |
| 15.227<br>15.209                         | Radiated Emission Test  | PASS   | Minimum passing margin is -7.53 dB at 39.72 MHz |

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

| MEASUREMENT        | UNCERTAINTY |
|--------------------|-------------|
| Radiated emissions | 3.86 dB     |

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|  |                                    |
|--|------------------------------------|
| <b>PRODUCT</b>                           | PilotBoard Wireless Desktop        |
| <b>MODEL NO</b>                          | 64379                              |
| <b>POWER SUPPLY</b>                      | 1.5Vdc * 2 battery for transmitter |
| <b>MODULATION TYPE</b>                   | FSK                                |
| <b>CARRIER FREQUENCY OF EACH CHANNEL</b> | 27.145 MHz                         |
| <b>MAXIMUM FIELD STRENGTH</b>            | 0.257 mV/m @ 3m                    |
| <b>NUMBER OF CHANNEL</b>                 | 1                                  |
| <b>ANTENNA TYPE</b>                      | Loop antenna                       |
| <b>DATA CABLE</b>                        | NA                                 |
| <b>I/O PORTS</b>                         | NA                                 |

**NOTE:**

1. The EUT is a wireless Keyboard.
2. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

One channel was provided to this EUT.

| Channel | Frequency |
|---------|-----------|
| 1       | 27.145MHz |

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is the transmitter part of a PilotBoard Wireless Desktop. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.227)**

**ANSI C63.4-2003**

All test items have been performed and recorded as per the above standards.



### 3.4 DESCRIPTION OF SUPPORT UNITS

NA

### 3.5 CONFIGURATION OF SYSTEM UNDER TEST

|             |
|-------------|
| EUT<br>(Tx) |
| *Test Table |

## 4 TEST PROCEDURE AND RESULT

### 4.1 CONDUCTED EMISSION MEASUREMENT

NA

### 4.2 RADIATED EMISSION MEASUREMENT

#### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

According to 15.227 the field strength of Emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

| Fundamental Frequency (MHz) | Field Strength of Fundamental (dBuV/m) |         |
|-----------------------------|--|---------|
|                             | Peak                                   | Average |
| 26.96~27.28                 | 100                                    | 80      |

Field strength limits are at the distance of 3 meters, Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

| Frequencies (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009-0.490       | 2400/F(kHz)                       | 300                           |
| 0.490-1.705       | 24000/F(kHz)                      | 30                            |
| 1.705-30.0        | 30                                | 30                            |
| 30-88             | 100                               | 3                             |
| 88-216            | 150                               | 3                             |
| 216-960           | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any Emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 4.2.2 TEST INSTRUMENT

| DESCRIPTION & MANUFACTURER         | MODEL NO.           | SERIAL NO.   | CALIBRATED UNTIL |
|------------------------------------|---------------------|--------------|------------------|
| * HP Preamplifier                  | 8447D               | 2432A03504   | Jun. 3, 2005     |
| * HP Preamplifier                  | 8449B               | 3008A01924   | Sep. 19, 2005    |
| * HP Preamplifier                  | 8449B               | 3008A01638   | Sep. 30, 2005    |
| SCHWARZBECK Tunable Dipole Antenna | VHA 9103            | NA           | Oct. 29, 2005    |
| SCHWARZBECK Tunable Dipole Antenna | UHA 9105            | 977          |                  |
| * ROHDE & SCHWARZ TEST RECEIVER    | ESI7                | 836697/012   | Nov. 05, 2005    |
| Schwarzbeck Antenna                | VULB 9168           | 137          | Feb. 27, 2005    |
| R&S Loop Antenna                   | HFH2-Z2             | 100070       | June 6, 2005     |
| * EMCO Horn Antenna                | 3115                | 6714         | Oct. 28, 2005    |
| * EMCO Horn Antenna                | 3115                | 9312-4192    | Feb. 28, 2005    |
| ADT. Turn Table                    | TT100               | 0306         | NA               |
| ADT. Tower                         | AT100               | 0306         | NA               |
| Software                           | ADT_Radiated_V<br>6 | NA           | NA               |
| TIMES RF cable                     | LL142               | CABLE-CH6-01 | Apr. 16, 2005    |

- NOTE:**
1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
  2. "\*" = These equipment are used for the final measurement.
  3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  4. The test was performed in ADT Chamber No. 6.
  5. The Industry Canada Reference No. IC 3789-6.



#### 4.2.3 TEST PROCEDURE


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected Emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the Emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the Emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item in this test report - Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITION

Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.

## 4.2.7 TEST RESULTS

|                                 |                             |                          |                |
|---------------------------------|-----------------------------|--------------------------|----------------|
| <b>EUT</b>                      | PilotBoard Wireless Desktop | <b>MODEL</b>             | 64379          |
| <b>INPUT POWER</b>              | 3 Vdc                       | <b>FREQUENCY RANGE</b>   | Below 1000MHz  |
| <b>ENVIRONMENTAL CONDITIONS</b> | 23 deg. C, 73% RH, 1007 hPa | <b>DETECTOR FUNCTION</b> | Peak / Average |
| <b>TESTED BY</b>                | Jamison Chan                |                          |                |

**ANTENNA POLARITY & TEST DISTANCE AT 3 M**

| No. | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|----------------------|------------------|--------------------------|
| 1   | *27.14      | 52.67 PK                | 100.00         | -47.33      | 360                  | 45.27            | 7.40                     |
| 2   | *27.14      | 48.21 AV                | 80.00          | -31.79      | 360                  | 40.81            | 7.40                     |

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB /m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other Emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. "\*"= Fundamental frequency.



|                                 |                             |                          |               |
|---------------------------------|-----------------------------|--------------------------|---------------|
| <b>EUT</b>                      | PilotBoard Wireless Desktop | <b>MODEL</b>             | 64379         |
| <b>INPUT POWER</b>              | 3 Vdc                       | <b>FREQUENCY RANGE</b>   | Below 1000MHz |
| <b>ENVIRONMENTAL CONDITIONS</b> | 23 deg. C, 73% RH, 1007 hPa | <b>DETECTOR FUNCTION</b> | Quasi-Peak    |
| <b>TESTED BY</b>                | Jamison Chan                |                          |               |

| <b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b> |             |                         |                |             |                    |                      |                  |                          |
|--|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No.  | Freq. (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1  | 45.55       | 13.42 QP                | 40.00          | -26.58      | 4.00 H             | 253                  | 5.86             | 7.56                     |
| 2  | 107.76      | 27.25 QP                | 43.50          | -16.25      | 1.75 H             | 220                  | 19.45            | 7.80                     |
| 3  | 206.89      | 24.17 QP                | 43.50          | -19.33      | 1.25 H             | 208                  | 16.07            | 8.09                     |
| 4  | 255.49      | 20.19 QP                | 46.00          | -25.81      | 1.25 H             | 184                  | 11.95            | 8.23                     |
| 5  | 362.40      | 18.05 QP                | 46.00          | -27.95      | 1.25 H             | 112                  | 9.48             | 8.57                     |
| 6  | 663.71      | 22.62 QP                | 46.00          | -23.38      | 2.00 H             | 301                  | 13.51            | 9.11                     |

| <b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b> |              |                         |                |              |                    |                      |                  |                          |
|--|--------------|-------------------------|----------------|--------------|--------------------|----------------------|------------------|--------------------------|
| No.  | Freq. (MHz)  | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB)  | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| <b>1</b>   | <b>39.72</b> | <b>32.47 QP</b>         | <b>40.00</b>   | <b>-7.53</b> | <b>1.25 V</b>      | <b>133</b>           | <b>25.07</b>     | <b>7.40</b>              |
| 2  | 72.77        | 30.29 QP                | 40.00          | -9.71        | 3.00 V             | 115                  | 22.72            | 7.57                     |
| 3  | 107.76       | 28.14 QP                | 43.50          | -15.36       | 1.50 V             | 187                  | 20.34            | 7.80                     |
| 4  | 193.29       | 30.21 QP                | 43.50          | -13.29       | 1.75 V             | 319                  | 22.14            | 8.07                     |
| 5  | 634.55       | 29.40 QP                | 46.00          | -16.60       | 1.00 V             | 187                  | 20.33            | 9.07                     |
| 6  | 786.17       | 29.64 QP                | 46.00          | -16.36       | 1.50 V             | 334                  | 20.24            | 9.40                     |

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

### RADIATED EMISSION TEST





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:

|                    |                       |
|--------------------|-----------------------|
| <b>USA</b>         | FCC, NVLAP, UL, A2LA  |
| <b>Germany</b>     | TUV Rheinland         |
| <b>Japan</b>       | VCCI                  |
| <b>Norway</b>      | NEMKO                 |
| <b>Canada</b>      | INDUSTRY CANADA , CSA |
| <b>R.O.C.</b>      | CNLA, BSMI, DGT       |
| <b>Netherlands</b> | Telefication          |
| <b>Singapore</b>   | PSB , GOST-ASIA(MOU)  |
| <b>Russia</b>      | CERTIS(MOU)           |

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180  
Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab**

Tel: 886-3-3183232  
Fax: 886-3-3185050

**Email:** [service@adt.com.tw](mailto:service@adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.