

RF EXPOSURE REPORT

REPORT NO.: SA120510D16

MODEL NO.: M01154

FCC ID: GV3M01154

RECEIVED: May 10, 2012

TESTED: May 14 ~ 16, 2012

ISSUED: May 22, 2012

APPLICANT: ACCO Brands, Inc.

ADDRESS: 333 Twin Dolphin Drive, 6th Floor, Redwood Shores, CA,

94065, U.S.A.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB LOCATION: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New

Taipei City, Taiwan (R.O.C.)

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.

Reference No.: 120522D01

Report No: SA120510D16 1 Report Format Version 4.0.0



TABLE OF CONTENTS

RELEAS	RELEASE CONTROL RECORD			
1.	CERTIFICATION	4		
2.	CONCLUSION	5		

Report No: SA120510D16 Reference No.: 120522D01



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA120510D16	Original release	May 22, 2012

Report No: SA120510D16 Reference No.: 120522D01



1. CERTIFICATION

PRODUCT: Kensington Presentair(TM)

BRAND NAME: Kensington

MODEL NO.: M01154

APPLICANT: ACCO Brands, Inc.

TESTED: May 14 ~ 16, 2012

TEST ITEM: ENGINEERING SAMPLE

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY:

Jessica Cheng / Specialist)

DATE: May 22, 2012

APPROVED BY :

, DATE: May 22. 20/1

(Ken Liu / Manager)



2. CONCLUSION

No Evaluation Required if power is below this threshold:

F(C	SHz)	mW	
Low	2.402	24.58	
High	2.480	24.50	

Maximum measured transmitter power:

Pout (dBm	Pout (mW)	
Conducted Power	-2.5	0.6
EIRP Power	1.4	1.4

*Note: The antenna is Printed antenna with 3.85dBi gain

Threshold for no SAR evaluation is 24.58mW Transmitter power is 1.4mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---

Report No: SA120510D16 Reference No.: 120522D01