APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

Date of Issue: October 26, 2009

EUT Specification

EUT	Nobo Kapture USB Receiver
Frequency band (Operating)	 WLAN: 2.412GHz ~ 2.462GHz WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz WLAN: 5.745GHz ~ 5.825GHz
Device category	 ✓ Others: Bluetooth: 2.402GHz ~ 2.480GHz ✓ Portable (<20cm separation) ✓ Mobile (>20cm separation) ✓ Others
Exposure classification	Occupational/Controlled exposure $(S = 5mW/cm^2)$ Seneral Population/Uncontrolled exposure $(S=1mW/cm^2)$
Antenna diversity	 Single antenna Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	3.69dBm (0.0023mW)
Antenna gain (Max)	-2 dBi (Numeric gain: 0.631)
Evaluation applied	 MPE Evaluation SAR Evaluation N/A*
Remark:	
1. The maximum output power is <u>3.69dBm (0.0023mW) at 2402MHz</u> (with <u>0.631 numeric</u> antenna gain.)	
	routine RF evaluation; MPE estimate is used to justify the
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm ² even if the calculation indicates that the power density would be larger.	

TEST RESULTS

No non-compliance noted.

(SAR evaluation is not required for the PORTABLE device while its maximum output power is lower than the general population low threshold: $60/f_{(GHz)}=60/2.441=24.58$ mW)

Page 74 Rev. 00