

47 CFR PART 15 SUBPART C TEST REPORT

for

Outdoor Pet-Immune PIR Motion Sensor

Model No.: EIR-32

FCC ID: GX9EIR32F1919

of

Applicant: CLIMAX TECHNOLOGY CO., LTD.

**Address: No. 258, Sinhu 2nd Rd., Neihu District, Taipei City 114,
Taiwan (R.O.C.)**

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1477, TW0020, TW1072

Industry Canada filed test laboratory Reg. No. 20037

A2LA Accredited No.: 2732.01



Report No.: W6M22009-20261-C-1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



TABLE OF CONTENTS

| | | |
|----------|--|-----------|
| 1 | GENERAL INFORMATION..... | 2 |
| 1.1 | NOTES | 2 |
| 1.2 | TESTING LABORATORY | 3 |
| 1.2.1 | Location | 3 |
| 1.2.2 | Details of accreditation status | 3 |
| 1.3 | DETAILS OF APPROVAL HOLDER | 3 |
| 1.4 | APPLICATION DETAILS..... | 4 |
| 1.5 | GENERAL INFORMATION OF TEST ITEM..... | 4 |
| 1.6 | TEST STANDARDS | 5 |
| 2 | TECHNICAL TEST..... | 6 |
| 2.1 | SUMMARY OF TEST RESULTS..... | 6 |
| 2.2 | TEST ENVIRONMENT | 6 |
| 2.3 | TEST EQUIPMENT LIST..... | 7 |
| 2.4 | GENERAL TEST PROCEDURE..... | 10 |
| 3 | TEST RESULTS (ENCLOSURE)..... | 12 |
| 3.1 | PEAK OUTPUT POWER (TRANSMITTER)..... | 13 |
| 3.2 | EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)..... | 16 |
| 3.3 | EXEMPTION LIMITS FOR ROUTINE EVALUATION ACCORDING TO 1647 CFR FCC PART 2 SUBPART J, SECTION 2.109116 | |
| 3.4 | TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS..... | 18 |
| 3.5 | SPURIOUS EMISSIONS (TX) | 19 |
| 3.6 | CARRIER FREQUENCY SEPARATION..... | 21 |
| 3.7 | NUMBER OF HOPPING FREQUENCIES | 24 |
| 3.8 | TIME OF OCCUPANCY (DWELL TIME) | 26 |
| 3.9 | 20dB BANDWIDTH | 30 |
| 3.10 | BAND-EDGE COMPLIANCE OF RF EMISSIONS | 33 |
| 3.11 | RADIATED EMISSIONS FROM RECEIVER PART | 36 |
| 3.12 | POWER LINE CONDUCTED EMISSION | 37 |



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.


The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.

Tester:

| | | | |
|------------------|----------|--|-----------|
| October 07, 2020 | Kent Lin |  | |
| Date | WTS-Lab. | Name | Signature |

Technical responsibility for area of testing:

| | | | |
|------------------|------------|--|-----------|
| October 07, 2020 | Kevin Wang |  | |
| Date | WTS | Name | Signature |



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1

FCC ID: GX9EIR32F1919

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Lishui, Shuang Sing Village,
Wanli Dist., New Taipei City 207,
Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228

FAX:886-2-2791-5046

Company

Worldwide Testing Services(Taiwan) Co., Ltd.

6F, NO. 58, LANE 188, RUEY-KUANG RD.

NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. TW1477, TW0020, TW1072

Industry Canada filed test laboratory Reg. No. 20037

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.

Accredited number: ./.

Street: ./.

Town: ./.

Country: ./.

Telephone: ./.

Fax: ./.

1.3 Details of approval holder

Name: CLIMAX TECHNOLOGY CO., LTD.

Street: No. 258, Sinhu 2nd Rd., Neihu District,

Town: Taipei City 114,

Country: Taiwan (R.O.C.)

Telephone: +886-2-2794-0001

Fax: +886-2-2792-6618



Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

1.4 Application details

Date of receipt of test item: September 28, 2020
Date of test: from September 29, 2020 to October 05, 2020

1.5 General information of Test item

Type of test item: Outdoor Pet-Immune PIR Motion Sensor
Model Number: EIR-32
Multi-listing model number: ./.
Photos: see Annex

Technical data

Frequency band: 918.0375-924.48 MHz
Frequency (Ch 1): 918.0375 MHz
Frequency (Ch 25): 921.98 MHz
Frequency (Ch 50): 924.48 MHz

Transmitter


Power (Ch 1): Conducted: 11.71 dBm
Power (Ch 25): Conducted: 11.51 dBm
Power (Ch 50): Conducted: 11.36 dBm

Unom

Power supply: Battery 1.5Vd.c.*2
Operation modes: Half-duplex
Modulation Type: FSK
Antenna Type: PCB antenna
Antenna gain: 0.04 dBi
Host device: none

Classification:

| | |
|--|-------------------------------------|
| Fixed Device | <input checked="" type="checkbox"/> |
| Mobile Device (Human Body distance > 20cm) | <input type="checkbox"/> |
| Portable Device (Human Body distance < 20cm) | <input type="checkbox"/> |
| Modular Radio Device | <input type="checkbox"/> |



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1


FCC ID: GX9EIR32F1919

Manufacturer: (if applicable)

Name: ./.
Street: ./.
Town: ./.
Country: ./.

1.6 Test standards

Technical standard : 47 CFR PART 15 SUBPART C § 15.247 (2019-10)



Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations were ascertained in the course of the tests performed.

2.2 Test environment

Relative humidity content: 20 ... 75 %


Air pressure: 86 ... 103 kPa

Details of power supply: Battery 1.5Vd.c.*2

Extreme conditions parameters: test voltage : -- extreme
min : -- V
max : -- V

| Test item Name | Uncertainty |
|---|---|
| Estimation Result of Uncertainty of Conducted Emission | Expanded Uncertainty: AMN: 1.06 dB Voltage probe: 1.12 dB |
| Estimation Result of Uncertainty of Radiated Emission(3M) | Expanded Uncertainty: 0.009-30 MHz: 1.88 dB 30-1000 MHz: 2.79 dB 1-18 GHz: 2.36 dB 18-40 GHz: 1.55 dB |
| Estimation Result of Uncertainty of Bandwidth Measurement 20 dB Bandwidth, Occupied bandwidth, Channel bandwidth, Necessary Bandwidth | Expanded Uncertainty: 0.45 kHz |
| Estimation Result of Uncertainty of Conducted Output Power Measurement Output power | Expanded Uncertainty: 1.14 dB |
| Estimation Result of Uncertainty of Band Edge Measurement | Expanded Uncertainty: 1.01 dBc |
| Estimation Result of Uncertainty of Frequency Separation Measurement Hopping channel separation | Expanded Uncertainty: 554.14 Hz |
| Estimation Result of Uncertainty of Duty Cycle Measurement Dwell time | Expanded Uncertainty: 0.1 ms |

Measurement uncertainty is not included in the calculation of test results.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

2.3 Test Equipment List

| No. | Test equipment | Type | Serial No. | Manufacturer | Cal. Date | Next Cal. Date |
|--------------|---|-----------------|-------------|--------------|---------------|----------------|
| ETSTW-CE 001 | EMI TEST RECEIVER | ESHS10 | 842121/013 | R&S | 2020/6/11 | 2021/6/10 |
| ETSTW-CE 003 | AC POWER SOURCE | APS-9102 | D161137 | GW | Function Test | |
| ETSTW-CE 004 | ZWEILEITER-V-NETZACHBILDUNG TWO-LINE V-NETWORK | ESH3-Z5 | 840731/011 | R&S | 2019/11/1 | 2020/10/31 |
| ETSTW-CE 006 | IMPULSBEGRENZER PULSE LIMITER | ESH3-Z2 | 100226 | R&S | 2020/9/22 | 2021/9/21 |
| ETSTW-CE 008 | HF-EICHLITUNG RF STEP ATTENUATOR 139dB DPSP | 334.6010.02 | 844581/024 | R&S | Function Test | |
| ETSTW-CE 009 | TEMP.&HUMIDITY CHAMBER | GTH-225-40-1P-U | MAA0305-009 | GIANT FORCE | 2020/7/22 | 2021/7/21 |
| ETSTW-CE 016 | TWO-LINE V-NETWORK | ENV216 | 100050 | R&S | 2020/9/22 | 2021/9/21 |
| ETSTW-CE 028 | MXE EMI Receiver | N9038A | MY53220110 | Agilent | 2020/7/29 | 2021/7/28 |
| ETSTW-RE 003 | EMI TEST RECEIVER | ESI 26 | 831438/001 | R&S | 2020/6/12 | 2021/6/11 |
| ETSTW-RE 004 | EMI TEST RECEIVER | ESI 40 | 832427/004 | R&S | 2020/7/16 | 2021/7/15 |
| ETSTW-RE 012 | TUNABLE BANDREJECT FILTER | D.C 0309 | 146 | K&L | Function Test | |
| ETSTW-RE 013 | TUNABLE BANDREJECT FILTER | D.C 0336 | 397 | K&L | Function Test | |
| ETSTW-RE 018 | MICROWAVE HORN ANTENNA | AT4560 | 27212 | AR | 2020/7/30 | 2021/7/29 |
| ETSTW-RE 027 | Passive Loop Antenna | 6512 | 00034563 | ETS-Lindgren | 2020/7/8 | 2021/7/7 |
| ETSTW-RE 030 | Double-Ridged Guide Horn Antenna | 3117 | 00035224 | ETS-Lindgren | 2020/4/22 | 2021/4/21 |
| ETSTW-RE 042 | Biconical Antenna | HK116 | 100172 | R&S | 2020/2/18 | 2021/2/17 |
| ETSTW-RE 043 | Log-Periodic Dipole Antenna | HL223 | 100166 | R&S | 2020/5/8 | 2021/5/7 |
| ETSTW-RE 044 | Log-Periodic Antenna | HL050 | 100094 | R&S | 2020/8/3 | 2021/8/2 |
| ETSTW-RE 045 | ESA-E SERIES SPECTRUM ANALYZER | E4404B | MY45111242 | Agilent | Pre-test Use | |
| ETSTW-RE 050 | Attenuator 10dB | 50HF-010-1 | None | JFW | 2020/2/20 | 2021/2/19 |
| ETSTW-RE 051 | Attenuator 6dB | 50HF-006-1 | None | JFW | 2020/2/20 | 2021/2/19 |
| ETSTW-RE 053 | Attenuator 3dB | 50HF-003-1 | None | JFW | 2020/2/20 | 2021/2/19 |
| ETSTW-RE 055 | SPECTRUM ANALYZER | FSU 26 | 200074 | R&S | 2020/3/6 | 2021/3/5 |
| ETSTW-RE 060 | Attenuator 30dB | 5015-30 | F651012z-01 | ATM | 2020/2/20 | 2021/2/19 |
| ETSTW-RE 062 | Amplifier Module | CHC 2 | None | KMIC | 2020/5/15 | 2021/5/14 |
| ETSTW-RE 064 | Bluetooth Test Set | MT8852B-042 | 6K00005709 | Anritsu | Function Test | |
| ETSTW-RE 069 | Double-Ridged Guide Horn Antenna | 3117 | 00069377 | ETS-Lindgren | Function Test | |
| ETSTW-RE 072 | CELL SITE TEST SET | 8921A | 3339A00375 | HP | 2020/9/22 | 2021/9/21 |
| ETSTW-RE 088 | SOLID STATE AMPLIFIER | KMA180265A01 | 99057 | KMIC | 2020/9/8 | 2021/9/7 |
| ETSTW-RE 091 | Match Pad | MDCS1500 | None | WOKEN | 2020/5/22 | 2021/5/21 |
| ETSTW-RE 099 | DC Block | 50DB-007-1 | None | JFW | 2020/2/20 | 2021/2/19 |
| ETSTW-RE 112 | AC POWER SOURCE | TFC-1005 | T-0A023536 | T-Power | Function test | |



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

| | | | | | | |
|-----------------|--------------------------------------|--|-----------------|--------------------|------------------|------------|
| ETSTW-RE 115 | 2.4GHz Notch Filter | N0124411 | 473874 | MICROWAVE CIRCUITS | 2020/1/13 | 2021/1/12 |
| ETSTW-RE 120 | RF Player | MP9200 | MP9210-111022 | ADIVIC | Function test | |
| ETSTW-RE 122 | SIGNAL GENERATOR | SMF100A | 102149 | R&S | 2020/6/11 | 2021/6/10 |
| ETSTW-RE 125 | 5GHz Notch filter | 5NSL11-5200/E221.3-O/O | 1 | K&L Microwave | 2020/8/7 | 2021/8/6 |
| ETSTW-RE 126 | 5GHz Notch filter | 5NSL12-5800/E221.3-O/O | 1 | K&L Microwave | 2020/8/7 | 2021/8/6 |
| ETSTW-RE 127 | RF Switch Box | RFS-01 | None | WTS | 2020/2/20 | 2021/2/19 |
| ETSTW-RE 128 | 5.3GHz Notch filter | N0153001 | SN487233 | Microwave Circuits | 2020/8/7 | 2021/8/6 |
| ETSTW-RE 129 | 5.5GHz Notch filter | N0555984 | SN487234 | Microwave Circuits | 2020/8/7 | 2021/8/6 |
| ETSTW-RE 130 | Handheld RF Spectrum Analyzer | N9340A | CN0147000204 | Agilent | Pre-test Use | |
| ETSTW-RE 142 | Amplifier | 8447D | 2805A03378 | Agilent | 2020/5/15 | 2021/5/14 |
| ETSTW-RE 146 | Preamplifier | JPA-10M1G | 15090004 | JPT | 2020/6/5 | 2021/6/4 |
| ETSTW-RE 147 | Bi-log Hybrid Antenna | MCTD 2786B | BLB16M04005 | ETC | 2020/4/9 | 2021/4/8 |
| ETSTW-RE 148 | Bi-log Hybrid Antenna | MCTD 2786B | BLB16M04006 | ETC | 2020/7/9 | 2021/7/8 |
| ETSTW-RF 002 | Electromagnetic field probe | LF-30 | K-0007 | STT | 2020/6/9 | 2021/6/8 |
| ETSTW-EMI 011 | USB Compact Modulator | SFC-U | 101689 | R&S | 2020/5/21 | 2021/5/20 |
| ETSTW-GSM 002 | Universal Radio Communication Tester | CMU 200 | 109439 | R&S | 2020/3/9 | 2021/3/8 |
| ETSTW-GSM 003 | Radio Communication Analyzer | MT8820C | 6201342073 | Anritsu | 2020/4/20 | 2021/4/19 |
| ETSTW-GSM 004 | Wideband Radio Communication Tester | CMW500 | 128092 | R&S | 2019/10/25 | 2020/10/24 |
| ETSTW-GSM 019 | Band Reject Filter | WRCTF824/849-822/851-40 /12+9SS | 3 | WI | 2020/1/13 | 2021/1/12 |
| ETSTW-GSM 020 | Band Reject Filter | WRCD1747/1748-1743/1752-32/5SS | 1 | WI | 2020/1/13 | 2021/1/12 |
| ETSTW-GSM 021 | Band Reject Filter | WRCD1879.5/1880.5-1875.5/1884.5-32/5SS | 3 | WI | 2020/1/13 | 2021/1/12 |
| ETSTW-GSM 022 | Band Reject Filter | WRCT901.9/903.1-904.25-50/8SS | 1 | WI | 2020/1/13 | 2021/1/12 |
| ETSTW-GSM 023 | Power Divider | 4901.19.A | None | SUHNER | 2020/9/8 | 2021/9/7 |
| ETSTW-GSM 024 | Radio Communication Analyzer | MT8821C | None | Anritsu | 2020/3/27 | 2021/3/26 |
| ETSTW-GSM 025 | Band Reject Filter | BRM19835 | 001 | Micro-Tronics | 2020/8/7 | 2021/8/6 |
| ETSTW-Cable 011 | SMA to N type Cable | RGU-400 | None | THERMAX | Pre-test Use NCR | |
| ETSTW-Cable 016 | BNC Cable | Switch Box | B Cable 1 | Schwarz beck | 2020/2/20 | 2021/2/19 |
| ETSTW-Cable 017 | BNC Cable | X Cable | B Cable 2 | Schwarz beck | 2020/2/20 | 2021/2/19 |
| ETSTW-Cable 018 | BNC Cable | Y Cable | B Cable 3 | Schwarz beck | 2020/2/20 | 2021/2/19 |
| ETSTW-Cable 019 | BNC Cable | Z Cable | B Cable 4 | Schwarz beck | 2020/2/20 | 2021/2/19 |
| ETSTW-Cable 020 | N TYPE Cable | OATS Cable 1 | N30N30-L335-15M | JYE BAO CO.,LTD. | 2020/7/1 | 2021/6/30 |
| ETSTW-Cable 027 | Microwave Cable | SUCOFLEX 104 | 279083 | HUBER+SUHNER | 2020/5/8 | 2021/5/7 |
| ETSTW-Cable 028 | Microwave Cable | FA147A0015M2020 | 30064-2 | UTIFLEX | 2020/9/8 | 2021/9/7 |
| ETSTW-Cable 029 | Microwave Cable | FA147A0015M2020 | 30064-3 | UTIFLEX | 2020/9/8 | 2021/9/7 |
| ETSTW-Cable 030 | Microwave Cable | SUCOFLEX 104 (S Cable 9) | 279067 | HUBER+SUHNER | 2020/2/20 | 2021/2/19 |
| ETSTW-Cable 043 | Microwave Cable | SUCOFLEX 104 | 317576 | HUBER+SUHNER | 2020/5/15 | 2021/5/14 |



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1

FCC ID: GX9EIR32F1919

| | | | | | | |
|-----------------|---------------------|-----------------------|----------|--------------|------------------|-----------|
| ETSTW-Cable 047 | Microwave Cable | SUCOFLEX 104 | 325518 | HUBER+SUHNER | 2020/7/3 | 2021/7/2 |
| ETSTW-Cable 058 | Microwave Cable | SUCOFLEX 104 | none | HUBER+SUHNER | 2020/6/5 | 2021/6/4 |
| ETSTW-Cable 064 | Microwave Cable | SUCOFLEX 104 | MY28891 | HUBER+SUHNER | 2020/5/15 | 2021/5/14 |
| ETSTW-Cable 071 | N TYPE CABLE | EMCCFD400-NM-NM-25000 | 170239 | EMCI | 2020/6/5 | 2021/6/4 |
| ETSTW-Cable 072 | SMA type cable (8m) | SUCOFLEX 104 | 805800/4 | HUBER+SUHNER | 2020/5/15 | 2021/5/14 |
| ETSTW-Cable 074 | SMA type cable (2m) | SUCOFLEX 104 | 802563/4 | HUBER+SUHNER | 2020/5/15 | 2021/5/14 |
| WTSTW-SW 002 | EMI TEST SOFTWARE | EZ EMC | None | Farad | Version ETS-03A1 | |
| WTSTW-SW 006 | EMI TEST SOFTWARE | e3 | None | AUDIX | Version 9.161014 | |
| WTSTW-SW 008 | Signal studio | Agilent | None | AUDIX | Version 2.0.0.1 | |
| ETSTW-TH 001 | Thermohygrometer | 608-H1 | 45204316 | Testo | 2020/9/8 | 2021/9/7 |
| ETSTW-TH 002 | Thermohygrometer | 608-H1 | 45204317 | Testo | 2020/9/8 | 2021/9/7 |



Registration number: W6M22009-20261-C-1

FCC ID: GX9EIR32F1919

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.10-2013 6.2 using a LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.10-2013 6.3 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz) METER READING + ACF + CABLE LOSS (to the receiver) = FS

33 20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.10-2013 6.2.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1

FCC ID: GX9EIR32F1919

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:


Average = Peak + Duty Factor

Duty Factor = $20 \log(\text{dwell time}/T)$

$T = 100\text{ms}$ when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANSI STANDARD C63.10-2013 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22009-20261-C-1

FCC ID: GX9EIR32F1919

3 Test results (enclosure)

| TEST CASE | Para. Number | Required | Test passed | Test failed |
|--|------------------|-------------------------------------|-------------------------------------|--------------------------|
| Peak Output Power | 15.247(b) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Equivalent radiated Power | 15.247(b) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Spurious Emissions radiated – Transmitter operating | 15.247(d) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Spurious Emissions conducted – Transmitter operating | 15.247 | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Carrier Frequency Separation | 15.247(a) (1) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Number of Hopping Frequencies | 15.247(a) (1)(i) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Time of Occupancy (Dwell Time) | 15.247(a) (1)(i) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| 20 dB Bandwidth | 15.247(a) (1)(i) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Band-edge Compliance of RF Emission | 15.247(d) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Radiated Emission from Receiver Part | 15.109 | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Power Line Conducted Emission | 15.207(a) | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

The follows is intended to leave blank.



Registration number: W6M22009-20261-C-1

FCC ID: GX9EIR32F1919

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.


The power was measured with modulation (declared by the applicant).

Test date: September 28, 2020


Temperature: 22.3 °C

Humidity: 58.6 %

Tester: Kent




MAX OUTPUT POWER
Date: 28.SEP.2020 17:38:00




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919



MAX OUTPUT POWER
Date: 28.SEP.2020 17:38:31



MAX OUTPUT POWER
Date: 28.SEP.2020 17:39:02



Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919


Maximum Peak Output Power

Limits:

| Frequency MHz | Number of hopping channels | | | |
|------------------|----------------------------|-----------|--------------|--------------|
| | ≥ 75 | ≥ 50 | $49 \geq 25$ | $74 \geq 15$ |
| 902-928 | -- | 30 dBm | 24 dBm | -- |
| 2400-2483.5 MHz | 30 dBm | -- | -- | 21 dBm |
| 5725-5850 MHz | 30 dBm | -- | -- | -- |

In case of employing transmitter antennas having antenna gain >dBi and using fixed point-to point operation consider §15.247 (b)(4).

Test equipment used: ETSTW-RE 055, ETSTW-RE 050, ETSTW-RE 064



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919

3.2 Equivalent Isotropic Radiated Power (EIRP)

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain
 EIRP = 11.71 dBm + (0.04 dBi [antenna gain claimed by manufacturer]) = 11.75 dBm = 14.96 mW

Test equipment used: ETSTW-RE 055

3.3 Exemption Limits for Routine Evaluation according to 47 CFR FCC Part 2 Subpart J, section 2.1091

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20 cm normally can be maintained between the user and the device.

MPE Calculation Method

(A) Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--------------------------|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f ²)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | -- | -- | f/300 | 6 |
| 1500-100,000 | -- | -- | 5 | 6 |

(B) Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--------------------------|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f ²)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | -- | -- | f/1500 | 30 |
| 1500-100,000 | -- | -- | 1.0 | 30 |


f = frequency in MHz

*Plane-wave equivalent power density

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)


The formula can be changed to $Pd \cdot \frac{30 \times P \times G}{377 \times d^2}$ mW/cm².



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919
Established separation distance is 20 cm.
Operating frequency band : 918.0375-924.48 MHz

The product meets RF exposure requirement.
Because the power density of 0.0030 mW/cm^2 at 918.0375 MHz is below the power density limit of 0.6120 mW/cm^2 .



Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

3.4 Transmitter Radiated Emissions in restricted Bands

FCC Rules: 15.247 (d), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26000 MHz.

For radiated emission tests, the analyzer setting was as followings:

RES BW VID BW

Frequency <1 GHz 100 kHz 100 kHz (Peak measurements)

Frequency >1 GHz 1 MHz 1 MHz (Peak measurements)

1 MHz 1 MHz (Average measurements)

Limits:

For frequencies below 1GHz :

| Frequency of Emission (MHz) | Field strength (microvolts/meter) | Field Strength (dB microvolts/meter) |
|-----------------------------|-----------------------------------|--------------------------------------|
| 30 – 88 | 100 | 40.0 |
| 88 – 216 | 150 | 43.5 |
| 216 – 960 | 200 | 46.0 |
| Above 960 | 500 | 54.0 |

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of FHSS Systems:

“If the emission is pulsed, modify the unit for continues operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.” Here the correction was added to the limit instead subtracted from the reading.

Duty cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Average measurements).

Limit – duty cycle correction

No duty cycle correction was added to the reading.

54.0dB μ V/m

For frequencies above 1GHz (Peak measurements).

Limit + 20dB

54.0dB μ V/m + 20 dB= 74 dB μ V/m

Test equipment used: ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 062, ETSTW-RE 142,
ETSTW-RE 147, ETSTW-RE 064

Explanation: See attached diagrams in appendix.



Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919

3.5 Spurious emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer). In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:
 Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.
 In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Marker-Delta-Method" or the „Duty-Cycle Correction Factor“.

Summary table with radiated data of the test plots

Model: EIR-32 Date: --
 Mode: -- Temperature: -- °C Engineer: --
 Polarization: Horizontal Humidity: -- %

| Frequency (MHz) | Reading (dBuV) | Detector | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Table Degree (Deg.) | Ant. High (cm) |
|-----------------|----------------|----------|-------------|-----------------|----------------|-------------|---------------------|----------------|
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |

| Frequency (MHz) | Reading (dBuV) | | Factor (dB) Corr. | Result (dBuV/m) | | Limit (dBuV/m) | | Margin (dB) | Table Degree (Deg.) | Ant. High (cm) |
|-----------------|----------------|------|-------------------|-----------------|------|----------------|------|-------------|---------------------|----------------|
| | Peak | Ave. | | Peak | Ave. | Peak | Ave. | | | |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919

Polarization: Vertical

| Frequency (MHz) | Reading (dBuV) | Detector | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Table Degree (Deg.) | Ant. High (cm) |
|-----------------|----------------|----------|-------------|-----------------|----------------|-------------|---------------------|----------------|
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |

| Frequency (MHz) | Reading (dBuV) | | Factor (dB) Corr. | Result (dBuV/m) | | Limit (dBuV/m) | | Margin (dB) | Table Degree (Deg.) | Ant. High (cm) |
|-----------------|----------------|------|-------------------|-----------------|------|----------------|------|-------------|---------------------|----------------|
| | Peak | Ave. | | Peak | Ave. | Peak | Ave. | | | |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |

- Note**
1. Correction Factor = Antenna factor + Cable loss - Preamplifier
 2. The formula of measured value as: Test Result = Reading + Correction Factor
 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
 4. All not in the table noted test results are more than 20 dB below the relevant limits.
 5. Please see attached diagrams in appendix.

All other not noted test plots do not contain significant test results in relation to the limits.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 030, ETSTW-RE 111, ETSTW-RE 088, ETSTW-RE 018, ETSTW-RE 064



Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

3.6 Carrier Frequency Separation

Carrier Frequency Separation was measured with modulation (declared by manufacturer).


According to FCC rules part 15 subpart C §15.247 frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or 20 dB bandwidth of the hopping channel, whichever is greater.

Test date: September 28, 2020

Temperature: 22.3 °C

Humidity: 58.6 %

Tester: Kent




FREQUENCY SEPARATION
Date: 28.SEP.2020 17:44:52




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919



FREQUENCY SEPARATION
 Date: 28.SEP.2020 17:45:40



FREQUENCY SEPARATION
 Date: 28.SEP.2020 17:46:20



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22009-20261-C-1

FCC ID: GX9EIR32F1919

Limits:

| Frequency Range MHz | Limits | |
|----------------------------|--------------------------|--------------------------|
| | 20 dB bandwidth < 25 kHz | 20 dB bandwidth > 25 kHz |
| 902-928 | 25 kHz | 20 dB bandwidth |
| 2400-2483.5 5725-5850.0 | 25 kHz | 20 dB bandwidth |

Test equipment used: ETSTW-RE 055, ETSTW-RE 064



Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919

3.7 Number of Hopping Frequencies

According to FCC rules part 15 subpart C §15.247 frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies. Frequency hopping systems in 5725-5850 MHz bands shall use least 75 hopping frequencies.


For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies; if the 20dB bandwidth of the hopping channel 250 kHz or greater, the system shall use at least 25 hopping frequencies.

Test date: September 28, 2020

Temperature: 22.3 °C

Humidity: 58.6 %

Tester: Kent



NUMBER OF HOPPING
 Date: 28.SEP.2020 17:36:43

Limits:

| Frequency Range MHz | Limit | |
|------------------------|---------------------|--------------------|
| | 20dB Bandwidth | Number of Channels |
| 902-928 MHz | Bandwidth < 250 kHz | ≥ 50 |
| | Bandwidth ≥ 250 kHz | ≥ 25 |
| 2400-2483.5 | not defined | 15 |
| 5725-5850.0 MHz | 1 MHz | 75 |

Test equipment used: ETSTW-RE 055, ETSTW-RE 064



Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

3.7.1 Pseudorandom Frequency Hopping Sequence


The generation of the hopping sequence is determined by the Bluetooth core specification and complies with the FCC requirements.

3.7.2 Coordination of hopping sequences to other transmitters

According to the Bluetooth core specification such a coordination is not possible. During scatternet function only one of the two hopping sequences will be used at a definite moment.

3.7.3 System Receiver Hopping Capability

According to the Bluetooth core specification. The system receivers shift frequencies in synchronization with the transmitted signals.



Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

3.8 Time of Occupancy (Dwell Time)

Frequency hopping systems operating in the 5725-5850 MHz band shall use an average time of occupancy on any frequency not greater than 0.4 seconds within a 30 second period.

In 2400-2483.5 MHz band the average time of occupancy on any channel shall not be greater than 0.4 seconds multiplied by the number of hopping channels employed.


For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20dB bandwidth of the hopping channel is 250 kHz or greater, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

Test date: September 28, 2020


Temperature: 22.3 °C

Humidity: 58.6 %

Tester: Kent




DWELL TIME
Date: 28.SEP.2020 17:55:01




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919



DWELL TIME(12.74ms * 7 event = 89.18ms)

Date: 28.SEP.2020 17:58:56




DWELL TIME

Date: 28.SEP.2020 17:55:43




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919



DWELL TIME(12.74ms * 7 event = 89.18ms)

Date: 28.SEP.2020 17:58:36




DWELL TIME

Date: 28.SEP.2020 17:56:23



Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919




DWELL TIME(12.74ms * 7 event = 89.18ms)
 Date: 28.SEP.2020 17:57:28

Limits and measurement periods:

| Frequency MHz | Number of channels | Measurement Periode | Limit |
|---------------|--------------------|---------------------------------|-------|
| 902 – 928 | ≥50 | 20 s | 0.4 s |
| | 49 ≥ 25 | 10 s | 0.4 s |
| 2400 – 2483.5 | ≥ 15 | 0.4 s * number of used channels | 0.4 s |
| 5725- 5850 | ≥ 75 | 30 s | 0.4s |

Test equipment used: ETSTW-RE 055, ETSTW-RE 064



Registration number: W6M22009-20261-C-1

FCC ID: GX9EIR32F1919

3.9 20dB Bandwidth

Frequency hopping systems operating in the 5725-5850 MHz bands shall use a maximum 20dB bandwidth of 1 MHz.

The 20dB bandwidth is measured on the lowest, middle and highest hopping channel.


For frequency hopping systems operating in the 902-928 MHz band the maximum 20dB bandwidth of the hopping channel is 500 kHz.

Test date: September 28, 2020

Temperature: 22.3 °C


Humidity: 58.6 %

Tester: Kent




20DB BANDWIDTH

Date: 28.SEP.2020 17:48:59




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919



20DB BANDWIDTH
 Date: 28.SEP.2020 17:49:31



20DB BANDWIDTH
 Date: 28.SEP.2020 17:50:00



Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

Limits:

| Frequency Range / MHz | Limit |
|-----------------------|----------------|
| 902-928 | ≤ 500 kHz |
| 2400-2483.5 | not defined |
| 5725-5850 | ≤ 1 MHz |

Test equipment used: ETSTW-RE 055, ETSTW-RE 064

3.9.1 System Receiver Input Bandwidth

It is determined in the Bluetooth core specification. The value matches to the bandwidth of transmitter signal.



Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

3.10 Band-edge Compliance of RF Emissions

According to FCC rules part 15 subpart C §15.247(c) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.


In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

Test date: September 28, 2020


Temperature: 22.3 °C

Humidity: 58.6 %

Tester: Kent




BANDEDGE
Date: 28.SEP.2020 17:51:27




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919



BANDEDGE
Date: 28.SEP.2020 17:51:01




BANDEDGE HOPPING MODE
Date: 28.SEP.2020 17:53:07



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919




BANDEDGE HOPPING MODE
 Date: 28.SEP.2020 17:53:24

Limits:

| Frequency Range / MHz | Limit |
|-----------------------|---------|
| 902 - 928 | - 20 dB |
| 2400 - 2483.5 | |
| 5725 - 5850 | |

Test equipment used: ETSTW-RE 055, ETSTW-RE 050, ETSTW-RE 064



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1

FCC ID: GX9EIR32F1919

3.11 Radiated Emissions from Receiver Part

Summary table with radiated data of the test plots

Model: EIR-32 Date: --
 Mode: -- Temperature: -- °C Engineer: --
 Polarization: Horizontal Humidity: -- %

| Frequency (MHz) | Reading (dBuV) | Detector | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Table Degree (Deg.) | Ant. High (cm) |
|-----------------|----------------|----------|-------------|-----------------|----------------|-------------|---------------------|----------------|
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |

| Frequency (MHz) | Reading (dBuV) | | Factor (dB) Corr. | Result (dBuV/m) | | Limit (dBuV/m) Peak Ave. | | Margin (dB) | Table Degree (Deg.) | Ant. High (cm) |
|-----------------|----------------|------|-------------------|-----------------|------|--------------------------|----|-------------|---------------------|----------------|
| | Peak | Ave. | | Peak | Ave. | | | | | |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |

Polarization: Vertical

| Frequency (MHz) | Reading (dBuV) | Detector | Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Table Degree (Deg.) | Ant. High (cm) |
|-----------------|----------------|----------|-------------|-----------------|----------------|-------------|---------------------|----------------|
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |

| Frequency (MHz) | Reading (dBuV) | | Factor (dB) Corr. | Result (dBuV/m) | | Limit (dBuV/m) Peak Ave. | | Margin (dB) | Table Degree (Deg.) | Ant. High (cm) |
|-----------------|----------------|------|-------------------|-----------------|------|--------------------------|----|-------------|---------------------|----------------|
| | Peak | Ave. | | Peak | Ave. | | | | | |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |

- Note**
1. Correction Factor = Antenna factor + Cable loss - Preamplifier
 2. The formula of measured value as: Test Result = Reading + Correction Factor
 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
 4. All not in the table noted test results are more than 20 dB below the relevant limits.
 5. The test results are listed in the separated test report no.: W6M22009-20261-P-15B.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22009-20261-C-1
 FCC ID: GX9EIR32F1919

3.12 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Model: EIR-32 Date: --
 Mode: -- Temperature: -- °C Engineer: --
 Polarization: N Humidity: -- %

| Frequency (MHz) | Reading (dBuV) | | Factor (dB) Corr. | Result (dBuV) | | Limit (dBuV) | | Margin (dB) |
|--------------------|-------------------|------|-------------------------|------------------|------|-----------------|------|----------------|
| | QP | Ave. | | QP | Ave. | QP | Ave. | |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| | | | | | | | | |

Polarization: L1


| Frequency (MHz) | Reading (dBuV) | | Factor (dB) Corr. | Result (dBuV) | | Limit (dBuV) | | Margin (dB) |
|--------------------|-------------------|------|-------------------------|------------------|------|-----------------|------|----------------|
| | QP | Ave. | | QP | Ave. | QP | Ave. | |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| | | | | | | | | |

Limits:

| Frequency of Emission (MHz) | Conducted Limit (dBuV) | |
|-----------------------------|------------------------|----------|
| | Quasi Peak | Average |
| 0.15-0.5 | 66 to 56 | 56 to 46 |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

- Note:**
1. The formula of measured value as: Test Result = Reading + Correction Factor
 2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
 4. All not in the table noted test results are more than 20 dB below the relevant limits.
 5. The test is not required because the EUT was powered by battery.

Test equipment used: ETSTW-CE 001, ETSTW-CE 016, ETSTW-RE 045.



Registration number: W6M22009-20261-C-1
FCC ID: GX9EIR32F1919

Appendix

Measurement diagrams

Spurious Emissions radiated



Radiated Emission Measurement

Operator: Vincent

File :1

Data :#1


Date: 9/29/2020

Temperature:25.7 °C

100.0 dBuV/m

Time: 5:09:29 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 918.0375MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 140.9218 | 28.61 | peak | -6.69 | 21.92 | 74.00 | 100 | 126 | -52.08 | |
| * | 247.5150 | 28.52 | peak | -7.88 | 20.64 | 46.00 | 100 | 326 | -25.36 | |



Radiated Emission Measurement

Operator: Vincent

File :1

Data :#2


Date: 9/29/2020

Temperature:25.7 °C

100.0 dBuV/m

Time: 5:11:18 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22009-20261

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Vertical**

Power : 3 Vd.c.

Distance: 3m

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 131.7234 | 28.25 | peak | -6.79 | 21.46 | 43.50 | 100 | 236 | -22.04 | |
| | 265.9118 | 27.31 | peak | -6.86 | 20.45 | 46.00 | 100 | 73 | -25.55 | |



Radiated Emission Measurement

Operator: Vincent

File :2

Data :#1


Date: 9/29/2020

Temperature:25.7 °C

100.0 dBuV/m

Time: 5:12:47 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 918.0375MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 797.9960 | 29.72 | peak | 1.62 | 31.34 | 74.00 | 100 | 243 | -42.66 | |
| * | 983.1662 | 27.74 | peak | 4.98 | 32.72 | 54.00 | 100 | 196 | -21.28 | |



Radiated Emission Measurement


Operator: Vincent

File :2
 100.0 dBuV/m

Data :#2

Date: 9/29/2020
 Time: 5:15:07 PM

Temperature:25.7 °C
 Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22009-20261

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Vertical**

Power : 3 Vd.c.

Distance: 3m

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 768.5371 | 39.80 | peak | 1.10 | 40.90 | 74.00 | 100 | 318 | -33.10 | |
| * | 960.7214 | 33.97 | peak | 4.66 | 38.63 | 54.00 | 100 | 243 | -15.37 | |



Radiated Emission Measurement

Operator: Vincent

File :3

Data :#1


Date: 9/29/2020

Temperature:25.7 °C

90.0 dBuV/m

Time: 11:46:28 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 918.0375MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 1837.675 | 52.59 | peak | -6.74 | 45.85 | 74.00 | 150 | 44 | -28.15 | |



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Vincent

File :3

Data :#5


Date: 9/29/2020

Temperature:25.7 °C

90.0 dBuV/m

Time: 11:54:49 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 918.0375MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 1837.675 | 59.17 | peak | -6.74 | 52.43 | 74.00 | 150 | 60 | -21.57 | |

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Vincent

File :3

Data :#2


Date: 9/29/2020

Temperature:25.7 °C

90.0 dBuV/m

Time: 11:47:29 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 918.0375MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 2753.507 | 53.24 | peak | -5.36 | 47.88 | 74.00 | 150 | 110 | -26.12 | |
| | 3675.351 | 61.57 | peak | -2.92 | 58.65 | 74.00 | 150 | 325 | -15.35 | |
| * | 3675.351 | 47.43 | AVG | -2.92 | 44.51 | 54.00 | 150 | 325 | -9.49 | |



Radiated Emission Measurement

Operator: Vincent

File :3

Data :#6


Date: 9/29/2020

Temperature:25.7 °C

90.0 dBuV/m

Time: 11:55:50 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 918.0375MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 2753.507 | 42.75 | peak | -5.36 | 37.39 | 74.00 | 150 | 312 | -36.61 | |
| * | 3675.351 | 50.86 | peak | -2.92 | 47.94 | 74.00 | 150 | 48 | -26.06 | |



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Vincent

File :3

Data :#3


Date: 9/29/2020

Temperature:25.7 °C

90.0 dBuV/m

Time: 11:48:31 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 918.0375MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 4593.186 | 58.89 | peak | -2.32 | 56.57 | 74.00 | 195 | 315 | -17.43 | |
| * | 4593.186 | 44.75 | AVG | -2.32 | 42.43 | 54.00 | 195 | 315 | -11.57 | |

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Vincent

File :3

Data :#7


Date: 9/29/2020

Temperature:25.7 °C

90.0 dBuV/m

Time: 11:56:52 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 918.0375MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 4585.170 | 43.73 | peak | -2.32 | 41.41 | 74.00 | 150 | 174 | -32.59 | |



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Vincent

File :3

Data :#4


Date: 9/29/2020

Temperature:25.7 °C

90.0 dBuV/m

Time: 11:52:58 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 918.0375MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|

*:Maximum data x:Over limit !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Vincent

File :3

Data :#8


Date: 9/29/2020

Temperature:25.7 °C

90.0 dBuV/m

Time: 11:57:59 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 918.0375MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Vincent

File :1

Data :#1


Date: 9/29/2020

Temperature:25.7 °C

100.0 dBuV/m

Time: 5:40:38 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 133.3466 | 29.12 | peak | -6.76 | 22.36 | 43.50 | 100 | 233 | -21.14 | |
| | 265.9118 | 28.56 | peak | -6.86 | 21.70 | 46.00 | 100 | 159 | -24.30 | |



Radiated Emission Measurement

Operator: Vincent

File :2

Data :#1


Date: 9/29/2020

Temperature:25.7 °C

100.0 dBuV/m

Time: 5:35:54 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 733.4670 | 27.59 | peak | 0.49 | 28.08 | 74.00 | 100 | 281 | -45.92 | |
| * | 998.5972 | 26.05 | peak | 5.21 | 31.26 | 54.00 | 100 | 327 | -22.74 | |



Radiated Emission Measurement

Operator: Vincent

File :2

Data :#2


Date: 9/29/2020

Temperature:25.7 °C

100.0 dBuV/m

Time: 5:37:35 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

Polarization: **Vertical**

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 768.5371 | 39.79 | peak | 1.10 | 40.89 | 74.00 | 100 | 185 | -33.11 | |
| * | 960.7214 | 33.74 | peak | 4.66 | 38.40 | 54.00 | 100 | 271 | -15.60 | |



Radiated Emission Measurement

Operator: Allen

File :3

Data :#1


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:19:16 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 1845.691 | 53.07 | peak | -6.84 | 46.23 | 74.00 | 150 | 105 | -27.77 | |



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Allen

File :3

Data :#5


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:24:01 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 1843.687 | 59.02 | peak | -6.82 | 52.20 | 74.00 | 150 | 299 | -21.80 | |

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Allen

File :3

Data :#2


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:20:17 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 2765.531 | 52.74 | peak | -5.32 | 47.42 | 74.00 | 150 | 315 | -26.58 | |
| * | 3687.375 | 51.36 | peak | -2.96 | 48.40 | 74.00 | 150 | 65 | -25.60 | |



Radiated Emission Measurement

Operator: Allen

File :3

Data :#6


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:25:02 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 2765.531 | 44.13 | peak | -5.32 | 38.81 | 74.00 | 150 | 181 | -35.19 | |
| * | 3687.375 | 51.19 | peak | -2.96 | 48.23 | 74.00 | 150 | 72 | -25.77 | |



Radiated Emission Measurement

Operator: Allen

File :3

Data :#3


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:21:19 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 4609.218 | 49.93 | peak | -2.32 | 47.61 | 74.00 | 150 | 150 | -26.39 | |



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Allen

File :3

Data :#7


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:26:04 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 4609.218 | 42.57 | peak | -2.32 | 40.25 | 74.00 | 150 | 42 | -33.75 | |

*:Maximum data x:Over limit !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Allen

File :3

Data :#4


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:22:59 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|

*:Maximum data x:Over limit !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Allen

File :3

Data :#8


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:27:08 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 921.98MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Vincent

File :1

Data :#1


Date: 9/29/2020

Temperature:25.7 °C

100.0 dBuV/m

Time: 5:52:23 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 924.48MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 125.2305 | 29.41 | peak | -7.05 | 22.36 | 43.50 | 100 | 212 | -21.14 | |
| | 248.5972 | 27.62 | peak | -7.82 | 19.80 | 46.00 | 100 | 90 | -26.20 | |



Radiated Emission Measurement

Operator: Vincent

File :1

Data :#2


Date: 9/29/2020

Temperature:25.7 °C

100.0 dBuV/m

Time: 5:52:38 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 924.48MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 133.3466 | 27.38 | peak | -6.76 | 20.62 | 43.50 | 100 | 255 | -22.88 | |
| | 260.5010 | 26.56 | peak | -7.25 | 19.31 | 46.00 | 100 | 127 | -26.69 | |



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Vincent

File :2

Data :#1


Date: 9/29/2020

Temperature:25.7 °C

100.0 dBuV/m

Time: 5:54:25 PM

Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 924.48MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 720.8416 | 29.49 | peak | 0.26 | 29.75 | 74.00 | 100 | 248 | -44.25 | |
| * | 960.7214 | 28.72 | peak | 4.66 | 33.38 | 54.00 | 100 | 259 | -20.62 | |

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement


Operator: Vincent

File :2
 100.0 dBuV/m

Data :#2

Date: 9/29/2020
 Time: 5:55:43 PM

Temperature:25.7 °C
 Humidity:62.2 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22009-20261

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Vertical**

Power : 3 Vd.c.

Distance: 3m

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 768.5371 | 40.75 | peak | 1.10 | 41.85 | 74.00 | 100 | 126 | -32.15 | |
| * | 960.7214 | 34.12 | peak | 4.66 | 38.78 | 54.00 | 100 | 185 | -15.22 | |



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Allen

File :3

Data :#1


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:33:49 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 924.48MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 1849.699 | 55.95 | peak | -6.90 | 49.05 | 74.00 | 150 | 179 | -24.95 | |

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Allen

File :3

Data :#5


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:40:17 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 924.48MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 1849.699 | 60.81 | peak | -6.90 | 53.91 | 74.00 | 150 | 329 | -20.09 | |



Radiated Emission Measurement

Operator: Allen

File :3

Data :#2


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:34:50 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 924.48MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 2773.547 | 52.64 | peak | -5.30 | 47.34 | 74.00 | 150 | 38 | -26.66 | |
| * | 3699.399 | 51.59 | peak | -3.00 | 48.59 | 74.00 | 150 | 224 | -25.41 | |



Radiated Emission Measurement

Operator: Allen

File :3

Data :#6


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:41:18 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22009-20261

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Vertical**

Power : 3 Vd.c.

Distance: 3m

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| | 2773.547 | 44.24 | peak | -5.30 | 38.94 | 74.00 | 150 | 285 | -35.06 | |
| * | 3699.399 | 51.68 | peak | -3.00 | 48.68 | 74.00 | 150 | 166 | -25.32 | |



Radiated Emission Measurement

Operator: Allen

File :3

Data :#3


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:35:51 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 924.48MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 4617.234 | 50.28 | peak | -2.33 | 47.95 | 74.00 | 150 | 40 | -26.05 | |



Radiated Emission Measurement

Operator: Allen

File :3

Data :#7


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:42:20 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 924.48MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
| * | 4617.234 | 43.61 | peak | -2.33 | 41.28 | 74.00 | 150 | 77 | -32.72 | |



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Allen

File :3

Data :#4


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:38:33 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Horizontal*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 924.48MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|

*:Maximum data x:Over limit !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei
 Tel:+886-2-6606-8877
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Allen

File :3

Data :#8


Date: 9/30/2020

Temperature:26.3 °C

90.0 dBuV/m

Time: 12:43:24 AM

Humidity:48.7 %



Site : Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

Polarization: *Vertical*

EUT : W6M22009-20261

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 924.48MHz

Note :

| Mk. | Frequency (MHz) | Reading (dBuV) | Detector | Corr. factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Ant.Pos (cm) | Tab.Pos (deg.) | Margin (dB) | Comment |
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|
|-----|-----------------|----------------|----------|---------------------|-----------------|----------------|--------------|----------------|-------------|---------|

*:Maximum data x:Over limit !:over margin