

**FCC RF Exposure Exemption report**

**for**

**Wall Pull Cord**

**Model No.: PCU<sub>x</sub>-xxxxx-xxxxx Series**

**(x=0~9, A~Z or blank)**

**FCC ID: GX9PCU8**

of

Applicant: CLIMAX TECHNOLOGY CO., LTD.

Address: No. 258, Sinhu 2nd Rd., Neihu District, Taipei City 114,  
Taiwan ( R.O.C.)

Tested and Prepared

by

**Worldwide Testing Services (Taiwan) Co., Ltd.**

**FCC Registration No.: TW1072, TW1140, TW1146, TW1477, TW0037**

**Industry Canada filed test laboratory Reg. No.: 20037, 31634**



**Report No.: W6M22406-23516-EE**

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.  
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: [wts@wts-lab.com](mailto:wts@wts-lab.com)



# **Worldwide Testing Services(Taiwan) Co., Ltd.**

Registration number: W6M22406-23516-EE  
FCC ID: GX9PCU8

## **TABLE OF CONTENTS**

<b>1</b>	<b>GENERAL INFORMATION.....</b>	<b>2</b>
1.1	NOTES .....	2
1.2	TESTING LABORATORY .....	3
1.2.1	Location .....	3
1.2.2	Details of accreditation status .....	3
1.3	APPLICATION DETAILS .....	3
1.4	GENERAL INFORMATION OF TEST ITEM.....	4
1.5	TEST STANDARDS .....	4
<b>2</b>	<b>TEST CONFIGURATION .....</b>	<b>5</b>
2.1	TEST ENVIRONMENT .....	5
2.2	MEASUREMENT UNCERTAINTY .....	5
2.3	TEST EQUIPMENT LIST.....	5
<b>3</b>	<b>EQUIVALENT ISOTROPIC RADIATED POWER (EIRP).....</b>	<b>6</b>
3.1	EXEMPTION LIMITS FOR ROUTINE EVALUATION ACCORDING TO FCC KDB PUBLICATION.....	6



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22406-23516-EE

FCC ID: GX9PCU8

## 1 General Information

### 1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

### **Tester:**

June 19, 2024

Ken Kang

Date

WTS-Lab.

Name

Signature

### **Technical responsibility for area of testing:**

June 19, 2024

Kevin Wang

Date

WTS

Name

Signature



# **Worldwide Testing Services(Taiwan) Co., Ltd.**

Registration number: W6M22406-23516-EE

FCC ID: GX9PCU8

## **1.2 Testing laboratory**

### **1.2.1 Location**

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,  
New Taipei City 207, Taiwan (R.O.C.)

Xizhi Lab

No. 99, Sec. 1, Balian Rd., Xizhi Dist.,  
New Taipei City 221032, Taiwan (R.O.C.)

Worldwide Testing Services (Taiwan) Co., Ltd.  
6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,  
Taipei City 114, Taiwan (R.O.C.)  
Tel: 886-2-6606-8877

### **1.2.2 Details of accreditation status**

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634

**Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :**

Name: ./.  
Accredited no.: ./.  
Street: ./.  
Town: ./.  
Country: ./.

## **1.3 Application details**

### **Approval holder**

Name: CLIMAX TECHNOLOGY CO., LTD.  
Street: No. 258, Sinhu 2nd Rd., Neihu District,  
Town: Taipei City 114,  
Country: Taiwan ( R.O.C.)

### **Manufacturer: (if applicable)**

Name: ./.  
Street: ./.  
Town: ./.  
Country: ./.



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22406-23516-EE

FCC ID: GX9PCU8

## Test date

Date of receipt of test item: June 04, 2024

Date of test: from June 05, 2024 to June 18, 2024

## 1.4 General information of Test item

Type of test item: Wall Pull Cord

Model no.: PCUx-xxxxx-xxxxx Series (x=0~9, A~Z or blank)

Multi-listing model no.: ./.

Brand name: ./.

Power supply: Battery 1.5Vd.c.\*2

Type of antenna: PCB antenna

Antenna gain: -1.99 dBi

### Technical data

Mode	Frequency	Power (dBm)
900MHz	918.0375 MHz	10.41
	924.48 MHz	10.34

Operation modes: Duplex

Modulation type: FSK

Sample no.: #01

### Classification:

Fixed Device	<input type="checkbox"/>
Mobile Device (Human Body distance > 20cm)	<input type="checkbox"/>
Portable Device (Human Body distance < 20cm)	<input checked="" type="checkbox"/>
Modular Radio Device	<input type="checkbox"/>

## 1.5 Test standards

FCC KDB Publication

447498 D01 General RF Exposure Guidance v06

### Special statement:

1. This test report is valid in connection to the model has been tested, any modification to the product which is different from the test model will avoid the certification of the test report.
2. This test report shall always be duplicated in full pages unless the written approval of the testing.
3. The x in model number is representing different case shape, case colors, led mask color, and control ID.
4. The model number of EUT is PCU-8. This model does not contain logo.



Registration number: W6M22406-23516-EE

FCC ID: GX9PCU8

**2 Test configuration**

**2.1 Test environment**

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Extreme conditions parameters: ./.

**2.2 Measurement uncertainty**


Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter))	Expanded Uncertainty : 1.64 dB

The decision rule is: Measurement uncertainty is not included in the calculation of test results.

**2.3 Test Equipment List**

**Max output power**

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2024/2/16	2025/2/15
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2024/3/7	2025/3/6
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2024/2/16	2025/2/15
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2024/2/16	2025/2/15



Registration number: W6M22406-23516-EE

FCC ID: GX9PCU8

### **3 Equivalent Isotropic Radiated Power (EIRP)**

FCC Rule: 15.247

EIRP = max. conducted output power + antenna gain

EIRP = 10.41 dBm + (-1.99 dBi [antenna gain claimed by manufacturer]) = 8.42 dBm = 6.95 mW

#### **3.1 Exemption Limits for Routine Evaluation according to FCC KDB Publication**

##### **RESULT:**

Test standard : FCC KDB Publication  
447498 D01 General RF Exposure Guidance v06

#### **3.3.1 Exemption Limits for Routine Evaluation – SAR Evaluation**

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table .

Table: SAR evaluation — Exemption limits for routine evaluation based on frequency and separation distance

MHz	5	10	15	20	25	mm
918.0375	15.88	31.76	46.70	62.58	78.46	SAR Test Exclusion Threshold (mW)

MHz	30	35	40	45	50	mm
918.0375	94.34	110.25	125.16	141.04	156.92	SAR Test Exclusion Threshold (mW)

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power.

Established separation distance is 5 mm.

Operating frequency band : 918.0375-924.48 MHz

Max. output power level at 5 mm separation distance at 918.0375 MHz according to table is: 15.88 mW

The product is exempt from SAR Evaluation/Testing because the output power of 6.95 mW is below the exemption limit of 15.88 mW.