

REPORT OF MEASUREMENTS

FOR

DTC COMMUNICATIONS, INC.

BEACON TRANSMITTER

MODEL: H25PB5-150

**FCC ID: H25PB5-150**

## CERTIFICATION INFORMATION

*Applicant/Manufacturer:* **DTC Communications, Inc.  
486 Amherst Street  
Nashua, NH 03062**

*Equipment under Test (EUT):* **The EUT is a Beacon transmitter used in Law Enforcement to track packages.**

*Model:* **H25PB5-150**

*FCC ID Number:* **FCC ID: H25PB5-150**

*Applicable Test Standard:* **FCC Parts 2 & 90**

*EUT Frequency Range:* **150 To174MHz**

*Emission Designator:* **11K0F3N (Event Mode)  
6K00PON (Tracker Mode)**

*Measured Power Output* **1.0 Watts**

*Channel Spacing* **12.5kHz**

*Transmit Modes:* **Tracking (pulsed CW) and Event/Alarm (FM)**

*Antenna Connector Type:* **MMCX Female**

*Antenna Type:* **Wire Whip**

*Input Power:* **6VDC (4AA Batteries)**

*RF Exposure:* **See Attached Installation/Users Manual and MPE Evaluation**

*Measurements Required by FCC:* **See Report Section 1 (Summary of Test Program) and the following Test Report Data Attachments:**

- RF Power Output**
- Modulation Characteristics**
- Occupied Bandwidth**
- Spurious Emissions at Antenna Terminals**
- Effective Radiated Power of Spurious Radiation**
- Frequency Stability**

**SECTION 1**  
**SUMMARY OF TEST PROGRAM**

RF POWER OUTPUT

Measurement Procedure:

The RF output connector of the test sample was connected through external attenuators to a spectrum analyzer. The test sample was configured to output an unmodulated CW signal. Testing was performed at 1 frequency within the operational band. The level of the maximized output power level was recorded and shown below.

Frequency (MHz)	Output (dBm)	Output (Watts)
162.0	30.2	1.05

For complete test data, see electronic Test Report Attachment, **RF Power Output Data**.

TRANSIENT FREQUENCY BEHAVIOR 90.214

Measurement Procedure:

The difference between the actual transmitter frequency to the assigned transmitter frequency was measured, as a function of time, when the transmitter RF output was switched on or off. Using the method of measurement described in TIA/EIA-603, 2.2.19 the transient frequency behavior was measured and compared to the limit specified in 90.214 for equipment operating in the 150 to 174MHz band designed to operate on 12.5kHz channels.

For complete test data, see electronic Test Report Attachment, **Transient Frequency Behavior**

## MODULATION CHARACTERISTICS 2.1047/90.211 (a)

Transmitters using analog emissions that are equipped with an audio low pass filter must meet the emission limitations specified in 90.210.

For complete test data, See Electronic Test Report Attachment, **Modulation Characteristics Data**.

## OCCUPIED BANDWIDTH 2.1049/90.210 (d)

Measurement Procedure:

The test sample's RF output was connected through proper attenuation to a spectrum analyzer. The test sample was operated in both unmodulated Tracker Mode and modulated event/alarm mode. In event mode the test sample was self modulated with 1000Hz. Sine wave. FCC Part 90.210 (d) states that for transmitters designed to operate with a 12.5kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

1. On any frequency removed from the center of the authorized bandwidth  $f_0$  to 5.625kHz removed from  $f_0$ : zero dB
2. On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 5.625kHz but no more than 12.5kHz: At least  $7.27 (f_d - 2.88\text{kHz})$  dB
3. On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 12.5kHz: At least  $50 + 10\log (P)$  dB or 70dB whichever is lesser attenuation.

For complete test data, see electronic Test Report Attachment, **Occupied Bandwidth Data**.

## ANTENNA PORT SPURIOUS EMISSIONS 2.1051

### Measurement Procedure:

A spectrum analyzer was connected to the RF output port of the test sample. The test sample was operated in both unmodulated Tracker Mode and modulated event/alarm mode. In event mode the test sample was self modulated with 1000Hz sine wave. The level of any spurious emission was recorded. Testing was performed in the frequency range of 30MHz to 1.74GHz. The spurious emissions limit is -20Bm as specified in FCC Part 90.210 (d)

For complete test data, including harmonic and spurious emissions measured at antenna terminal, see electronic Test Report Attachment, **Antenna Conducted Data**.

## EFFECTIVE RADIATED POWER OF SPURIOUS RADIATION 2.1053/TIA/EIA-603

### Measurement Procedure:

The test sample was placed on a 80cm high wooden test stand which was located 3 meters from the test antenna on an FCC listed test site. A shielded load of proper impedance was connected to the RF output connector of the test sample. The test sample was operated in both unmodulated Tracker Mode and modulated event/alarm mode. In event mode the test sample was self modulated with 1000Hz sine wave. The effective radiated power of each out of band spurious emission was measured using the substitution method specified in TIA/EIA-603. The frequency range of the test was 30MHz – 1.74GHz. The limit for out of band spurious emissions is -20dBm as specified in Part 90.210 (d)

For complete test data, see electronic Test Report Attachment, **Radiated Emissions Data**.

## FREQUENCY STABILITY MEASUREMENTS 2.1055/90.213

### Measurement Procedure (Frequency vs. Voltage & Temperature):

Testing was performed at frequency versus input voltage and temperature. The test sample was placed in a temperature chamber with the RF output of the test sample connected to a spectrum analyzer. FCC Part 2.1055 states that the primary supply voltage for battery operated equipment be reduced to the battery operating end point as specified by the manufacturer. The manufacturer specifies that the operating end point is 4VDC. The temperature was varied from -30 degrees c to +50 degrees c in 10 degree increments. The output frequency from the test sample was measured and recorded and compared to the limit specified in 90.213 (5.0ppm) .0005%.

For complete test data, see electronic Test Report Attachment, **Frequency Stability Data**.

**SECTION 2**  
**EQUIPMENT LISTS**

RF Power Output

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
4895	Spectrum Analyzer	Hewlett Packard	9kHz - 22GHz	8593EM	2/13/02	2/13/03
4962	Attenuator	Narda	DC - 18 GHz	757C-20dB	11/6/02	11/6/03

Occupied Bandwidth

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
4962	Attenuator	Narda	DC - 18 GHz	757C-20dB	11/6/02	11/6/03
5010	Graphics Plotter	Hewlett Packard	N/A	7470A	4/18/02	4/18/03
R411	Spectrum Analyzer	Hewlett Packard	30 Hz - 2.9 GHz	AT-8560E	1/8/03	1/8/05

Spurious Emissions at Antenna Terminals

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
3128	20 dB Attenuator	Lucas Weinscher	DC - 18 GHz	2	1/8/03	1/8/04
4895	Spectrum Analyzer	Hewlett Packard	9kHz - 22GHz	8593EM	2/13/02	2/13/03
4962	Attenuator	Narda	DC - 18 GHz	757C-20dB	11/6/02	11/6/03

Spurious Radiated Emissions

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
3258	Double Ridge Guide	EMCO	1 - 18 GHz	3115	5/6/02	5/6/03
4029	Test Site Attenuation	Retlif	3 / 10 Meters	RNH	11/27/02	11/27/03
4202	Biconilog	EMCO	26 MHz - 2 GHz	3142	7/25/02	7/25/03
4895	Spectrum Analyzer	Hewlett Packard	9kHz - 22GHz	8593EM	2/13/02	2/13/03
4921	Graphics Plotter	Hewlett Packard	N/A	7550A	9/20/02	9/20/03

## EQUIPMENT LISTS

### Frequency Stability

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
3117	Power Supply	B&K Precision	0-30 Vdc, 3.0 A	1630	2/25/02	2/25/03
4962	Attenuator	Narda	DC - 18 GHz	757C-20dB	11/6/02	11/6/03
4997	Digital Thermometer	Omega	N/A		12/19/02	12/19/03
520N	Digital Multimeter	Wavetek	N/A	25XT	11/26/02	5/26/03
557	Temperature Chamber	Associated Env.	-73 C - +177 C	SK 3105	6/11/02	6/11/03
R411	Spectrum Analyzer	Hewlett Packard	30 Hz - 2.9 GHz	AT-8560E	1/8/03	1/8/05

### Transient Frequency Behavior

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
073	Interference Analyzer	Electro-Metrics	10 kHz - 1 GHz	EMC-25	1/27/03	1/27/04
3118	Broadband Pre-Amplifier	Electro-Metrics	10 KHz - 1 GHz	BPA-1000	1/31/03	1/31/04
3233	Graphics Plotter	Hewlett Packard	N/A	7470A	4/16/02	4/16/03
3448	0-11 DB Stepattenuator	Midwest Microwave	DC - 18 GHz	1092	2/25/02	2/25/03
4001	Oscilloscope	Tektronix	N/A	TDS 520A	4/11/02	4/11/03
4961	Attenuator	Narda	DC - 18 GHz	757C-30dB	11/6/02	11/6/03
4999	50 ohm Adapter	Boonton Electronics	.01 - 1200 MHz	952002	12/10/02	12/10/03
5006	RF Millivoltmeter	Boonton Electronics	10 kHz - 1.2 GHz	9200	11/8/02	11/8/03
5017	RF Probe	Boonton Electronics	10 kHz to 1200 MHz	91-12F	12/10/02	12/10/03
5020	RF Detector	Pasternack	100 KHz - 1 GHz	PE8000-50	1/27/03	1/27/04
532	High Power Dir Coupler	Werlatone Inc.	.01 - 1000 MHz	C2630	1/3/03	1/3/04