

## Maximum Permissive Exposure

FCC ID: H3RTISS1001  
Product: RF Module  
Model No.: iT-IS

1. According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	---	---	f/300	6
1500-100,000	---	---	5.0	6
(B) Limits for General Population / Uncontrolled Exposures (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	---	---	f/1500	30
1500-100,000	---	---	1.0	30

### 2. MPE Calculation

**TLV CO., LTD.** declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

RF Exposure Calculations:  $S = (P * G) / (4 * \pi * r^2)$  or  $r = \sqrt{(P * G) / (4 * \pi * S)}$

#### 2.1. Estimation Result

Mode	Frequency (MHz)	Output power (dBm)	Output power (mW)	antenna Gain (dBi)	antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )
O-QPSK	2405	6.761	4.74	2.14	1.64	0.001545
	2440	7.342	5.42	2.14	1.64	<b>0.001767</b>
	2480	7.050	5.07	2.14	1.64	0.001652

Based on **safety** distance (r) **20cm**, the antenna gain (G) is **1.64Numerical**, and the highest power output (P) is **5.42mW**, the power density (S) is **0.001767mW/cm<sup>2</sup>**.