




Note:



1. Material: SUS304+SWIC(plated with nickel)
2. 3D surface and curve refer to Pro/E file.
3. CTA=Critical to assemble(01~03)
4. Unspecified tolerance:

SELECT V	V			
DIM. LEVEL	A	B	C	D
~ 5	±0.03	±0.05	±0.08	±0.10
5 ~ 10	±0.05	±0.08	±0.10	±0.15
10 ~ 50	±0.08	±0.10	±0.15	±0.20
50 ~ 100	±0.10	±0.15	±0.20	±0.25
100 ~	±0.10	±0.15	±0.20	±0.25

5. The part is according to the latest version "HS-301" of LITEON.


FCC ID: H4IDG8160

IC: 4491A-DG8160
CMIIT ID: XXXXXXXXXX
IFT: XXXXXXXXXXXXX


MADE IN CHINA
Model: SD-8160
RATING: 5V = 100mA
ANATEL: XXXXXX
XXXX
CNC ID: XXXXXX

PART NO	DESCRIPTION	QTY	MAT'L	TRETING	REMARK
SCALE: FREE	TOLERANCE : UNSPECIFIED	 SILITEK ELECTRONICS(DONGGUAN)CO.,LTD DONGGUAN LITE ON COMPUTER CO., LTD.			
UNIT: mm	.XXX ± 0.05 .XX ± 0.1 .X ± 0.15 ANGLE ± 0.25°				
DRAWN:		TITLE: SD8160_iron shell			
DESIGER:					
CHECKED:	SHEET	1 OF 1			
APPROVED:	DRAWING NO:				