



Neutron Engineering Inc.

Radio Test Report

FCC ID: H4IMS9662

This report concerns (check one) : ☒ Original Grant ☐ Class II Change

Issued Date : Jan. 24, 2013
Project No. : 1301015
Equipment : Wireless Mouse
Model Name : SM-9662

Applicant : LITE-ON TECHNOLOGY CORP.
Address : 18F, 392, Ruey Kuang Road, Neihu,
Taipei 11492, Taiwan, R.O.C

Tested by: Neutron Engineering Inc. EMC Laboratory
Date of Receipt: Jan. 08, 2013
Date of Test: Jan. 08, 2013 ~ Jan. 17, 2013

Testing Engineer: Rush Kao
(Rush Kao)

Technical Manager: Jeff Yang
(Jeff Yang)

Authorized Signatory: Andy Chiu
(Andy Chiu)

Neutron Engineering Inc.
B1, No. 37, Lane 365, YangGuang St.,
NeiHu District 114, Taipei, Taiwan.
TEL: +886-2-2657-3299
FAX: +886-2-2657-3331





Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



Table of Contents

REPORT ISSUED HISTORY	4
1 CERTIFICATION	5
2 . SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3 GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	10
3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
3.4 DESCRIPTION OF SUPPORT UNITS	12
4 RADIATED SPURIOUS EMISSION (9 KHZ TO 1 GHZ)	13
4.1 LIMIT	13
4.2 MEASUREMENT INSTRUMENTS LIST	14
4.3 MEASURING INSTRUMENTS SETTING	14
4.4 TEST PROCEDURES	16
4.5 DEVIATION FROM TEST STANDARD	16
4.6 TEST SETUP LAYOUT	16
4.7 EUT OPERATING CONDITIONS	17
4.8 TEST RESULTS	18
5 RADIATED SPURIOUS EMISSION (ABOVE 1 GHZ)	20
5.1 LIMIT	20
5.2 MEASUREMENT INSTRUMENTS LIST	21
5.3 MEASURING INSTRUMENTS SETTING	21
5.4 TEST PROCEDURES	22
5.5 DEVIATION FROM TEST STANDARD	22
5.6 TEST SETUP LAYOUT	22
5.7 EUT OPERATING CONDITIONS	23
5.8 TEST RESULTS	24
5.9 TEST RESULTS (RESTRICTED BANDS)	36
5.10 TEST RESULTS - THE TENTH HARMONIC	40
6 EUT TEST PHOTO	42



REPORT ISSUED HISTORY

Revised Version No.	Description	Issued Date
-	Initial Issue.	Jan. 24, 2013



1 CERTIFICATION

Equipment : Wireless Mouse
Brand Name : acer
Model Name : SM-9662
Applicant : LITE-ON TECHNOLOGY CORP.
Date of Test : Jan. 08, 2013 ~ Jan. 17, 2013
Standards : FCC Part 15, Subpart C: 2011
ANSI C63.4: 2009

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.
The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-1301015) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).



2. SUMMARY OF TEST RESULTS

FCC Part 15, Subpart C: 2011		
Standard Clause	Test Item	Result
15.207	Conducted Emission	N/A
15.249(d) or 15.209	Radiated Spurious Emission	PASS
15.205	Restricted Bands	PASS

NOTE:

(1) N/A: denotes test is not applicable in this Test Report



2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

Radiated emission Test (Below 1 GHz):

CB08: (FCC RN: 614388; FCC DN: TW1054; IC Assigned Code: 4428C-1)
1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Radiated emission Test (Above 1 GHz):

CB08: (VCCI RN: G-91; FCC RN: 614388; FCC DN: TW1054; IC Assigned Code: 4428C-1)
1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

2.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty is not specified by FCC rules and for reference only.

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95%**.

The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

Radiated emission test:

Test Site	Item	Measurement	Frequency Range	Uncertainty	NOTE
CB08	Radiated emission at 3m	Horizontal Polarization	30 - 200MHz	3.35 dB	
			200 - 1000MHz	3.11 dB	
			1 - 18GHz	3.97 dB	
			18 - 40GHz	4.01 dB	
		Vertical Polarization	30 - 200MHz	3.22 dB	
			200 - 1000MHz	3.24 dB	
			1 - 18GHz	4.05 dB	
			18 - 40GHz	4.04 dB	

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our U_{lab} values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called U_{CISPR} , as follows:

Conducted Disturbance (mains port) – 150 kHz – 30 MHz: 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) –
30 MHz – 1000 MHz: 5.2 dB

It can be seen that our U_{lab} values are smaller than U_{CISPR} .

If U_{lab} is less than or equal to U_{CISPR} , then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{CISPR} , then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{CISPR})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{CISPR})$, exceeds the disturbance limit.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless Mouse	
Brand Name	acer	
Model Name	SM-9662	
OEM Brand/Model Name	N/A	
Model Difference	N/A	
Product Description	The EUT is a Wireless Mouse.	
	Operation Frequency	2403 MHz to 2480 MHz
	Modulation Type	GFSK
	Bit Rate of Transmitter	2 Mbps
	Number Of Channel	Please refer to the Note 2.
	Antenna Designation	Please refer to the Note 3.
	Antenna Gain(Peak)	Please refer to the Note 3.
	Field strength	94.32dBuV@3m
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Power Source	Battery supplied.	
Power Rating	I/P: DC 1.5V 30mA	
Connecting I/O Port(s)	Please refer to the User's Manual	
Products Covered	N/A	
EUT Modification(s)	N/A	



NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2403	27	2429	53	2455
02	2404	28	2430	54	2456
03	2405	29	2431	55	2457
04	2406	30	2432	56	2458
05	2407	31	2433	57	2459
06	2408	32	2434	58	2460
07	2409	33	2435	59	2461
08	2410	34	2436	60	2462
09	2411	35	2437	61	2463
10	2412	36	2438	62	2464
11	2413	37	2439	63	2465
12	2414	38	2440	64	2466
13	2415	39	2441	65	2467
14	2416	40	2442	66	2468
15	2417	41	2443	67	2469
16	2418	42	2444	68	2470
17	2419	43	2445	69	2471
18	2420	44	2446	70	2472
19	2421	45	2447	71	2473
20	2422	46	2448	72	2474
21	2423	47	2449	73	2475
22	2424	48	2450	74	2476
23	2425	49	2451	75	2477
24	2426	50	2452	76	2478
25	2427	51	2453	77	2479
26	2428	52	2454	78	2480

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Printed	N/A	-0.02



3.2 DESCRIPTION OF TEST MODES


To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Items	Mode	Data Rate	Channel	Note
Radiated Spurious Emission (30 MHz to 1 GHz)	GFSK	2 Mbps	2441 MHz	
Radiated Spurious Emission (above 1 GHz)	GFSK	2 Mbps	2403 MHz / 2441 MHz / 2480 MHz	
Restricted Bands	GFSK	2 Mbps	2403 MHz / 2441 MHz / 2480 MHz	

NOTE: The measurements are performed at the highest, middle, lowest available channels.



3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED





3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	Wireless Mouse	acer	SM-9662	H4IMS9662	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
N/A	-	-	-	-

NOTE: The support equipment was authorized by Declaration of Conformity (DOC).



4 RADIATED SPURIOUS EMISSION (9 KHZ TO 1 GHZ)

4.1 LIMIT

20 dB in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency Range: 9 kHz to 1 GHz		
FREQUENCY (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Frequency Range: above 1 GHz				
FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
above 1 GHz	80	60	74	54

NOTE:

1. The limit for radiated test was performed according to FCC PART 15B.
2. The tighter limit applies at the band edges.
3. Emission level (dBuV/m)=20log Emission level (uV/m).
4. The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain (if use)
 Margin Level = Measurement Value – Limit Value

FCC Part15, Subpart C (15.249)	
Limit	Frequency Range (MHz)
Field strength of fundamental 50000 μ V/m (94 dB μ V/m) @ 3 m	2400-2483.5
Field strength of harmonics 500 μ V/m (54 dB μ V/m) @ 3 m	Above 2483.5



4.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-40	100129	Oct. 01, 2013
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 16, 2013
3	Microwave Pre_amplifier	Agilent	8449B	3008A01714	Apr. 17, 2013
4	Microflex Cable	N/A	N/A	1m	Apr. 14, 2013
5	Microflex Cable	AISI	S104-SMAP-1	10m	Apr. 14, 2013
6	Microflex Cable	N/A	N/A	3m	Apr. 14, 2013
7	Test Cable	N/A	LMR-400	966_12m	May. 15, 2013
8	Test Cable	N/A	LMR-400	966_3m	May. 15, 2013
9	Pre-Amplifier	EMC	EMC-330	980001	May. 31, 2013
10	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jun. 12, 2013

Remark: "N/A" denotes No Model Name, No Serial No. or No Calibration specified.

4.3 MEASURING INSTRUMENTS SETTING

EMI Test Receiver	Parameter Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



DUTY CYCLE: TX 2403 MHz (2 Mbps)

Dwell time = ON/ON+OFF

ON: 0.21 msec


ON+OFF (total time): 9.37 msec

Dwell time: 2.24%

AV = PK + 20 log(Dwell time)

AV = PK – 32.99

Total time (ON+OFF) = 9.37 msec; ON = 0.21 msec





4.4 TEST PROCEDURES

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1 GHz. For frequencies above 1 GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m Semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. The testing follows the guidelines in ANSI C63.4 and FCC Public Notice DA 00-705 Measurement Guidelines. In case the emission is fail due to the used RBW/VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.


NOTE:

- a. Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode with Detector BW=120 kHz; SPA setting in RBW=100 kHz, VBW =100 kHz, Swp. Time = 0.3 sec./ MHz.
- b. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.

4.5 DEVIATION FROM TEST STANDARD

No deviation

4.6 TEST SETUP LAYOUT





4.7 EUT OPERATING CONDITIONS


The EUT was programmed to be in continuously transmitting mode.



4.8 TEST RESULTS

E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2441 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	61.0400	43.59	-19.23	24.36	40.00	-15.64	peak	
2		72.6800	45.34	-21.30	24.04	40.00	-15.96	peak	
3		140.5800	40.21	-18.80	21.41	43.50	-22.09	peak	
4		371.4400	38.27	-16.51	21.76	46.00	-24.24	peak	
5		421.8800	37.45	-15.20	22.25	46.00	-23.75	peak	
6		555.7399	33.85	-12.49	21.36	46.00	-24.64	peak	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2441 MHz		

Polarization: Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	74.6200	46.33	-21.78	24.55	40.00	-15.45	peak	
2		121.1800	45.60	-20.88	24.72	43.50	-18.78	peak	
3		152.2200	43.46	-18.95	24.51	43.50	-18.99	peak	
4		406.3598	40.98	-15.55	25.43	46.00	-20.57	peak	
5		429.6400	41.25	-15.02	26.23	46.00	-19.77	peak	
6		526.6400	38.34	-13.09	25.25	46.00	-20.75	peak	



5 RADIATED SPURIOUS EMISSION (ABOVE 1 GHz)

5.1 LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency Range: 9 kHz to 1 GHz		
FREQUENCY (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Frequency Range: above 1 GHz				
FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
above 1 GHz	80	60	74	54

NOTE:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain(if use)
 Margin Level = Measurement Value – Limit Value



5.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-40	100129	Oct. 01, 2013
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 16, 2013
3	Microwave Pre_amplifier	Agilent	8449B	3008A01714	Apr. 17, 2013
4	Microflex Cable	N/A	N/A	1m	Apr. 14, 2013
5	Microflex Cable	AISI	S104-SMAP-1	10m	Apr. 14, 2013
6	Microflex Cable	N/A	N/A	3m	Apr. 14, 2013
7	Test Cable	N/A	LMR-400	966_12m	May. 15, 2013
8	Test Cable	N/A	LMR-400	966_3m	May. 15, 2013
9	Pre-Amplifier	EMC	EMC-330	980001	May. 31, 2013
10	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jun. 12, 2013

Remark: "N/A" denotes No Model Name, No Serial No. or No Calibration specified.

5.3 MEASURING INSTRUMENTS SETTING

Spectrum Analyzer	Parameter Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

5.4 TEST PROCEDURES

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m Semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.
- The testing follows the guidelines in ANSI C63.4 and FCC Public Notice DA 00-705 Measurement Guidelines. In case the emission is fail due to the used RBW/VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.


NOTE:

- Reading in which marked as Peak means measurements by using are Peak Mode with instrument setting in RBW= 1 MHz, VBW= 1 MHz, Swp. Time = Auto.
Reading in which marked as AV means measurements by using are Average Mode with instrument setting in RBW= 1 MHz, VBW= 10 Hz, Swp. Time = Auto.
- All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform.

5.5 DEVIATION FROM TEST STANDARD

No deviation

5.6 TEST SETUP LAYOUT





5.7 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.



5.8 TEST RESULTS

E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2403 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2400.000	21.44	33.05	54.49	74.00	-19.51	peak	
2		2400.000	-11.55	33.05	21.50	54.00	-32.50	AVG	
3		2402.800	49.33	33.06	82.39	114.0	-31.61	peak	
4		2402.800	16.34	33.06	49.40	94.00	-44.60	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2403 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.080	51.16	7.41	58.57	74.00	-15.43	peak	
2		4804.080	18.17	7.41	25.58	54.00	-28.42	AVG	
3	*	7206.020	48.87	14.79	63.66	74.00	-10.34	peak	
4		7206.020	15.88	14.79	30.67	54.00	-23.33	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2403 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2400.000	27.49	33.05	60.54	74.00	-13.46	peak	
2		2400.000	-5.50	33.05	27.55	54.00	-26.45	AVG	
3		2402.600	59.90	33.06	92.96	114.0	-21.04	peak	
4		2402.600	26.91	33.06	59.97	94.00	-34.03	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2403 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.040	50.03	7.41	57.44	74.00	-16.56	peak	
2		4804.040	17.04	7.41	24.45	54.00	-29.55	AVG	
3	*	7206.020	49.67	14.79	64.46	74.00	-9.54	peak	
4		7206.020	16.68	14.79	31.47	54.00	-22.53	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2441 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2440.800	52.78	33.27	86.05	114.0	-27.95	peak	
2		2440.800	19.79	33.27	53.06	94.00	-40.94	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2441 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.030	49.00	7.70	56.70	74.00	-17.30	peak	
2		4882.030	16.01	7.70	23.71	54.00	-30.29	AVG	
3	*	7323.030	50.15	15.10	65.25	74.00	-8.75	peak	
4		7323.030	17.16	15.10	32.26	54.00	-21.74	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2441 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2441.400	61.05	33.27	94.32	114.0	-19.68	peak	
2		2441.400	28.06	33.27	61.33	94.00	-32.67	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2441 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.040	48.47	7.70	56.17	74.00	-17.83	peak	
2		4882.040	15.48	7.70	23.18	54.00	-30.82	AVG	
3	*	7323.030	48.46	15.10	63.56	74.00	-10.44	peak	
4		7323.030	15.47	15.10	30.57	54.00	-23.43	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2480 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2480.000	51.00	33.48	84.48	114.0	-29.52	peak	
2		2480.000	18.01	33.48	51.49	94.00	-42.51	AVG	
3	*	2483.500	21.40	33.50	54.90	74.00	-19.10	peak	
4		2483.500	-11.59	33.50	21.91	54.00	-32.09	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2480 MHz		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.110	50.26	7.98	58.24	74.00	-15.76	peak	
2		4960.110	17.27	7.98	25.25	54.00	-28.75	AVG	
3	*	7440.070	50.64	15.40	66.04	74.00	-7.96	peak	
4		7440.070	17.65	15.40	33.05	54.00	-20.95	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2480 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2480.200	57.41	33.48	90.89	114.0	-23.11	peak	
2		2480.200	24.42	33.48	57.90	94.00	-36.10	AVG	
3	*	2483.500	21.57	33.50	55.07	74.00	-18.93	peak	
4		2483.500	-11.42	33.50	22.08	54.00	-31.92	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	60%
Test Voltage	DC 1.5V		
Test Mode	2480 MHz		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.080	49.80	7.98	57.78	74.00	-16.22	peak	
2		4960.080	16.81	7.98	24.79	54.00	-29.21	AVG	
3	*	7440.070	49.58	15.40	64.98	74.00	-9.02	peak	
4		7440.070	16.59	15.40	31.99	54.00	-22.01	AVG	



5.9 TEST RESULTS (RESTRICTED BANDS)

E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	24°C	Relative Humidity	46%
Test Voltage	DC 1.5V		
Test Mode	2403 MHz		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2400.000	21.44	33.05	54.49	74.00	-19.51	peak	
2		2400.000	-11.55	33.05	21.50	54.00	-32.50	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	24°C	Relative Humidity	46%
Test Voltage	DC 1.5V		
Test Mode	2403 MHz		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2400.000	27.49	33.05	60.54	74.00	-13.46	peak	
2		2400.000	-5.50	33.05	27.55	54.00	-26.45	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	24°C	Relative Humidity	46%
Test Voltage	DC 1.5V		
Test Mode	2480 MHz		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2483.500	21.40	33.50	54.90	74.00	-19.10	peak	
2		2483.500	-11.59	33.50	21.91	54.00	-32.09	AVG	



E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	24°C	Relative Humidity	46%
Test Voltage	DC 1.5V		
Test Mode	2480 MHz		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

Polarization: Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2483.500	21.57	33.50	55.07	74.00	-18.93	peak	
2		2483.500	-11.42	33.50	22.08	54.00	-31.92	AVG	



5.10 TEST RESULTS - THE TENTH HARMONIC


E.U.T	Wireless Mouse	Model Name	SM-9662
Temperature	26°C	Relative Humidity	46%
Test Voltage	DC 1.5V		
Test Mode	2407 MHz/2441 MHz/2473 MHz		

2403 MHz/10 Harmonic of the frequency





2441 MHz/10 Harmonic of the frequency



2480 MHz/10 Harmonic of the frequency

