

FCC TEST REPORT
for
Remote Control
Model No.: TRX970HCA

of

Applicant: Advance Security Inc.
Address: 3F, 48 Ta-An Street, Hsi-Chih Taipei Hsien, Taiwan R.O.C.

Tested and Prepared
by



ETS Product Service (Taiwan) Co., Ltd.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679

A2LA Accredited No.: 2300.01

PTCRB Accredited Type Certification Test House

FCC ID : H50TR24

Report No.: W6M20705-8131-P-15

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: ets@ets-bzt.com.tw

TABLE OF CONTENTS

1	GENERAL INFORMATION	2
1.1	Notes	2
1.2	Testing laboratory	3
1.2.1	Location	3
1.2.2	Details of accreditation status	3
1.3	Details of approval holder	3
1.4	Application details	4
1.5	General information of Test item	4
1.6	Test standards	5
2	TECHNICAL TEST	6
2.1	Summary of test results	6
2.2	Test environment	6
2.3	Test Equipment List	7
2.4	General Test Procedure	9
3	TEST RESULTS (ENCLOSURE)	11
3.1	Peak Output Power (transmitter)	12
3.2	Equivalent isotropic radiated power	14
3.3	RF Exposure Compliance Requirements	14
3.4	Out of Band Radiated Emissions	14
3.5	Transmitter Radiated Emissions in restricted Bands	15
3.6	Spurious emissions (tx)	16
3.7	Carrier Frequency Separation	35
3.8	Number of Hopping Frequencies	36
3.8.1	Pseudorandom Frequency Hopping Sequence	37
3.8.2	Coordination of hopping sequences to other transmitters	37
3.8.3	System Receiver Hopping Capability	37
3.8.4	Equal Hopping Frequency Use	37
3.9	Time of Occupancy (Dwell Time)	38
3.10	20dB Bandwidth	40
3.10.1	System Receiver Input Bandwidth	40
3.11	Band-edge Compliance of RF Emissions	41
3.12	Radiated Emissions from Digital Part	42
3.13	Power Line Conducted Emission	43

Registration number: W6M20705-8131-P-15
FCC ID : H5OTR24

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has Passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that is performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the ETS Product Service (Taiwan) Co., Ltd.

Tester:

July 05, 2007

Jay Chaing



Date

ETS-Lab.


Name

Signature

Technical responsibility for area of testing:

July 05, 2007

Steven Chuang



Date

ETS

Name

Signature

Registration number: W6M20705-8131-P-15
FCC ID : H5OTR24

1.2 Testing laboratory

1.2.1 Location

OATS
No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)

Company
ETS Product Service (Taiwan) Co., Ltd.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.
Tel : 886-2-66068877
Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2300.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679

PCTRB Accredited Type Certification Test House

1.3 Details of approval holder

Name	: Advance Security Inc.
Street	: 3F, 48 Ta-An Street, Hsi-Chih
Town	: Taipei Hsien
Country	: Taiwan R.O.C.
Telephone	: +886-2-86481688
Fax	: +886-2-86481689

Registration number: W6M20705-8131-P-15
FCC ID : H5OTR24

1.4 Application details

Date of receipt of test item : May 25, 2007
Date of test : from May 26, 2007 to July 04, 2007

1.5 General information of Test item

Type of test item : Remote Control
Model Number : TRX970HCA
Multi-listing model number : without
Photos : see Annex

Technical data

Frequency band : 909 - 921.778MHz
Frequency (ch A) : 909MHz
Frequency (ch B) : 915.5MHz
Frequency (ch C) : 921.778MHz

Transmitter

Unom

Normal Mode
Power (ch A or ch 1) : Conducted: 19.48 dBm
Power (ch B or ch 13) : Conducted: 19.64 dBm
Power (ch C or ch 25) : Conducted: 19.63 dBm

Power supply adaptor Adapter : Input : 100-240 VAC (ac/dc adaptor) Output : 5 VDC
Battery : 4.2 VDC

Operation modes : duplex

Modulation Type : FSK

Antenna Type : Helical antenna

Antenna gain : <6 dBi

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

Host device : none

Classification :

Fixed Device	<input type="checkbox"/>
Mobile Device (Human Body distance > 20cm)	<input type="checkbox"/>
Portable Device (Human Body distance < 20cm)	<input checked="" type="checkbox"/>

Manufacturer:
 (if applicable)

Name : ./.
 Street : ./.
 Town : ./.
 Country : ./.

Additional information : The test sample is designed as TRX970HCA device. Its pseudorandom hopping scheme, authentication, receiver parameters, synchronization procedure and other parameters are determined by TRX970HCA Specification.

1.6 Test standards

Technical standard : FCC RULES PART 15 Subpart B / SUBPART C § 15.247 (2007-05)

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 3 were ascertained in the course of the tests performed.

2.2 Test environment

Temperature : 23 °C

Relative humidity content : 20 ... 75 %

Air pressure : 86 ... 103 kPa

Power supply adaptor Adapter : Input : 100-240 VAC (ac/dc adaptor) Output : 5 VDC
 Battery : 4.2 VDC

Extreme conditions parameters : test voltage : -- extreme
 min :-- V
 max :-- V

Registration number: W6M20705-8131-P-15

FCC ID : H5OTR24

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2006/10/16	2007/10/15
ETSTW-CE 002	PREREULATOR MODE DC POWER SUPPLY	None	None		Function Test	
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V-NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2006/10/16	2007/10/15
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	2006/10/16	2007/10/15
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	In House Certificate	
ETSTW-CE 008	ABSORBING CLAMP	MDS 21	3469	Schwarzbeck	2005/10/24	2007/10/23
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2006/8/17	2007/8/16
ETSTW-CE 013	CISPR 22 TWO BALANCED TELECOM PAIRS IMPEDANCE STABILIZATION NETWORK	FCC-TLISN-T4-02	20242	FCC	2005/12/8	2007/12/7
ETSTW-CE 014	CISPR 22 TWO BALANCED TELECOM PAIRS IMPEDANCE STABILIZATION NETWORK	FCC-TLISN-T2-02	20241	FCC	2005/12/7	2007/12/6
ETSTW-CE 015	CISPR 22 TWO BALANCED TELECOM PAIRS IMPEDANCE STABILIZATION NETWORK	FCC-TLISN-T8-02	20307	FCC	2006/11/7	2008/11/6
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2006/11/21	2007/11/20
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	2005/10/14	2007/10/13
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2006/10/20	2007/10/19
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2006/10/30	2007/10/29
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2006/10/12	2007/10/11
ETSTW-RE 010	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070181	MOTECH	Function Test	
ETSTW-RE 011	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070165	MOTECH	Function Test	
ETSTW-RE 017	Log-Periodic Antenna	HL025	352886/001	R&S	2006/5/4	2008/5/3
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2004/11/8	2007/11/7
ETSTW-RE 020	MICROWAVE HORN ANTENNA	AT4002A	306915	AR	Function Test	
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	2006/10/11	2007/10/10
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	EMCO	In House Certificate	
ETSTW-RE 028	Log-Periodic Dipole Array Antenna	3148	34429	EMCO	2006/5/26	2008/5/25
ETSTW-RE 029	Biconical Antenna	3109	33524	EMCO	2006/5/26	2008/5/25
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	EMCO	2006/5/3	2008/5/2
ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	2006/10/11	2007/10/10
ETSTW-RE 033	WaveRunner 6000A Serie Oscilloscope	WAVERUNNER 6100A	LCRY0604P14508	LeCroy	2006/7/27	2007/7/26
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	2005/10/17	2007/10/16
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2007/1/11	2009/1/10
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2006/5/8	2008/5/7
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2006/5/29	2008/5/28

Registration number: W6M20705-8131-P-15

FCC ID : H5OTR24

ETSTW-RE 048	Triple Loop Antenna	HXYZ 9170	HXYZ 9170-134	Schwarzbeck	2005/3/22	2008/3/21
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2007/5/02	2009/5/01
ETSTW-RE 055	SPECTRUM ANALYZER	FSU-26	200074	R&S	2006/7/28	2007/7/27
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	

Registration number: W6M20705-8131-P-15
FCC ID : H5OTR24

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz) METER READING + ACF + CABLE LOSS (to the receiver) = FS
33 20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2003 Section 13.1.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by ETS Product Service (Taiwan) Co., Ltd. at the registered open field test site located No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.). The Registration Number: **930600**.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

Registration number: W6M20705-8131-P-15

FCC ID : H5OTR24

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

T = 100ms when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Equivalent radiated Power	15.247(b)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions radiated – Transmitter operating	15.247(c)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions conducted – Transmitter operating	15.247	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Carrier Frequency Separation	15.247(a) (1)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Number of Hopping Frequencies	15.247(a) (1)(i)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Time of Occupancy (Dwell Time)	15.247(a) (1)(i)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
20 dB Bandwidth	15.247(a) (1)(i)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Band-edge Compliance of RF Emission	15.247(c)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission from Digital Part	15.109	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Power Line Conducted Emission	15.207(a)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

The follows is intended to leave blank.

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

Test conditions	Conducted Power		
	Channel A [dBm]	Channel B [dBm]	Channel C [dBm]
T _{nom} = 23°C V _{nom} = 4.2 V	19.48	19.64	19.63

Test conditions	Signal Field strength TX highest power mode
T _{nom} = 23°C, V _{nom} = 4.2 V Frequency [MHz]	dBμV/m
--	--
Measurement uncertainty	< 3 dB

The diagrams for peak output power measurements are included in Appendix.

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

Maximum Peak Output Power

Limits:

Frequency MHz	Number of hopping channels			
	≥ 75	≥ 50	$49 \geq 25$	$74 \geq 15$
902-928		30 dBm	24 dBm	
2400-2483.5 MHz	30 dBm	-		21 dbm
5725-5850 MHz	30 dBm	-		

In case of employing transmitter antennas having antenna gain >dBi and using fixed poin-to point operation consider §15.247 (b)(4).

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055 ETSTW-RE 064

Registration number: W6M20705-8131-P-15
FCC ID : H5OTR24

3.2 Equivalent isotropic radiated power

FCC Rule: 15.239(b), 15.35

Because using an internal antenna there are no deviations from the radiated test results according 3.1.

3.3 RF Exposure Compliance Requirements

According to Supplement C, Edition 01-01 to OET Bulletin 65, Edition 97-01 this spread spectrum transmitter is categorically excluded from routine environmental evaluation because of the low power level, where there is a high likelihood of compliance with RF exposure standards.

3.4 Out of Band Radiated Emissions

FCC Rule: 15.247(c) , 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies below 1GHz :

Max. reading – 20 dB

Guidance on Measurement of FHSS Systems:

“If the emission is pulsed, modify the unit for continuous operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.” Here the correction was added to the limit instead subtracted from the reading.

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Peak measurements).

Limit = max. aver. reading-20dB +20dB(because Peak detector is used)

For frequencies above 1GHz (Average measurements).

Max. reading – 20 dB - duty cycle correction:

No duty cycle correction was added to the reading

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 017 ETSTW-RE 021 ETSTW-RE 028
ETSTW-RE 030 ETSTW-RE 043 ETSTW-RE 044 ETSTW-RE 064

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

3.5 Transmitter Radiated Emissions in restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26000 MHz.

For radiated emission tests, the analyzer setting was as followings:

RES BW VID BW

Frequency <1 GHz 100 kHz 100 kHz (Peak measurements)

Frequency >1 GHz 1 MHz 1 MHz (Peak measurements)

1 MHz 1 MHz (Average measurements)

Limits:

For frequencies below 1GHz :

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of FHSS Systems:

“If the emission is pulsed, modify the unit for continues operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.” Here the correction was added to the limit instead subtracted from the reading.

Duty cycle correction = 20 log (dwell time/100ms)

For frequencies above 1GHz (Average measurements).

Limit – duty cycle correction

No duty cycle correction was added to the reading.

54.0dBμV/m

For frequencies above 1GHz (Peak measurements).

Limit + 20dB

54.0dBμV/m + 20 dB= 74 dBμV/m

Comments: See attached diagrams as 3.6.

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 017ETSTW-RE 028
 ETSTW-RE 029 ETSTW-RE 030 ETSTW-RE 042 ETSTW-RE 043
 ETSTW-RE 044 ETSTW-RE 064

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

3.6 Spurious emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer). In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:


Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.


In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Marker-Delta-Method" or the „Duty-Cycle Correction Factor“.

Summary table with radiated data of the test plots




Registration number: W6M20705-8131-P-15
FCC ID : H5OTR24



Site : site #1
Condition : FCC Restriction Band 30-300
Company : W6M20705-8131
EUT Model: TRX970HCA
Execute Program : low channel


Polarization: Vertical
Power : 4.2 VDC
Distance: 3m



Site : site #1
Condition : FCC Restriction Band 300-1000
Company : W6M20705-8131
EUT Model: TRX970HCA
Execute Program : low channel


Polarization: Horizontal
Power : 4.2 VDC
Distance: 3m

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24



Site : site #1
 Condition : FCC Restriction Band 300-1000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : low channel

Polarization: *Vertical*
 Power : 4.2 VDC
 Distance: 3m




Site : site #1
 Condition : FCC Restriction Band 1000-2000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : low channel
 Note :

Polarization: *Horizontal*
 Power : 4.2 VDC
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1819.639	64.87	peak	-8.42	56.45	200.00	160	130	-143.5	


Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24



Site : site #1
 Condition : FCC Restriction Band 1000-2000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : low channel
 Note :

Polarization: *Vertical*
 Power : 4.2 VDC
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1819.639	66.11	peak	-8.42	57.69	200.00	145	130	-142.3	




Site : site #1
 Condition : FCC Restriction Band 2000-4000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : low channel
 Note :

Polarization: *Horizontal*
 Power : 4.2 VDC
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2725.451	52.56	peak	-3.97	48.59	74.00	165	125	-25.41	
	3635.271	56.33	peak	-0.51	55.82	74.00	155	130	-18.18	
*	3636.083	52.99	AVG	-0.50	52.49	54.00	150	130	-1.51	


Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24



Site : site #1
 Condition : FCC Restriction Band 2000-4000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : low channel
 Note :

Polarization: *Vertical*
 Power : 4.2 VDC
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2725.451	49.51	peak	-3.97	45.54	74.00	155	130	-28.46	
*	3635.271	46.49	peak	-0.51	45.98	74.00	140	120	-28.02	





Site : site #1
 Condition : FCC Restriction Band 4000-8000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : low channel
 Note :



Polarization: *Horizontal*
 Power : 4.2 VDC
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4545.080	51.72	AVG	-1.92	49.80	54.00	160	70	-4.20	
	4545.090	58.56	peak	-1.92	56.64	74.00	160	70	-17.36	
	5450.902	45.50	peak	2.21	47.71	74.00	145	70	-26.29	
	6364.730	44.85	peak	4.05	48.90	200.00	150	70	-151.1	


Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24



Registration number: W6M20705-8131-P-15
FCC ID : H5OTR24




Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24



Site : site #1
 Condition : FCC Restriction Band 300-1000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : middle channel

Polarization: *Vertical*
 Power : 4.2 VDC
 Distance: 3m




Site : site #1
 Condition : FCC Restriction Band 1000-2000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : middle channel
 Note :

Polarization: *Horizontal*
 Power : 4.2 VDC
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1831.663	63.94	peak	-8.37	55.57	200.00	155	130	-144.4	


Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24



Site : site #1
 Condition : FCC Restriction Band 1000-2000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : middle channel
 Note :

Polarization: *Vertical*
 Power : 4.2 VDC
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1831.663	64.88	peak	-8.37	56.51	200.00	155	130	-143.4	




Site : site #1
 Condition : FCC Restriction Band 2000-4000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : middle channel
 Note :

Polarization: *Horizontal*
 Power : 4.2 VDC
 Distance: 3m


Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2745.491	54.04	peak	-3.87	50.17	74.00	150	130	-23.83	
*	3662.069	52.67	AVG	-0.22	52.45	54.00	145	130	-1.55	
	3663.327	55.72	peak	-0.20	55.52	74.00	145	130	-18.48	

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24



Site : site #1
 Condition : FCC Restriction Band 2000-4000 Polarization: **Vertical**
 Company : W6M20705-8131 Power : 4.2 VDC
 EUT Model: TRX970HCA Distance: 3m
 Execute Program : middle channel
 Note :


Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2745.491	54.36	peak	-3.87	50.49	74.00	160	130	-23.51	
	3663.327	49.73	peak	-0.20	49.53	74.00	155	130	-24.47	



Site : site #1
 Condition : FCC Restriction Band 4000-8000 Polarization: **Horizontal**
 Company : W6M20705-8131 Power : 4.2 VDC
 EUT Model: TRX970HCA Distance: 3m
 Execute Program : middle channel
 Note :


Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4577.154	58.02	peak	-1.79	56.23	74.00	155	105	-17.77	
*	4577.645	54.18	AVG	-1.79	52.39	54.00	155	105	-1.61	
	5490.982	47.27	peak	2.61	49.88	200.00	140	110	-150.1	
	6412.826	48.14	peak	3.89	52.03	200.00	140	110	-147.9	

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24




Site : site #1
 Condition : FCC Restriction Band 4000-8000 Polarization: *Vertical*
 Company : W6M20705-8131 Power : 4.2 VDC
 EUT Model: TRX970HCA Distance: 3m
 Execute Program : middle channel
 Note :

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4577.154	54.45	peak	-1.79	52.66	74.00	165	105	-21.34	
	5490.982	42.43	peak	2.61	45.04	200.00	155	110	-154.9	
	6412.826	41.33	peak	3.89	45.22	200.00	150	115	-154.7	




Site : site #1
 Condition : FCC Restriction Band 8000-12750 Polarization: *Horizontal*
 Company : W6M20705-8131 Power : 4.2 VDC
 EUT Model: TRX970HCA Distance: 3m
 Execute Program : middle channel

Registration number: W6M20705-8131-P-15
FCC ID : H5OTR24



Site : site #1
Condition : FCC Restriction Band 30-300
Company : W6M20705-8131
EUT Model: TRX970HCA
Execute Program : high channel


Polarization: *Vertical*
Power : 4.2 VDC
Distance: 3m




Site : site #1
Condition : FCC Restriction Band 300-1000
Company : W6M20705-8131
EUT Model: TRX970HCA
Execute Program : high channel

Polarization: *Horizontal*
Power : 4.2 VDC
Distance: 3m

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24




Site : site #1
 Condition : FCC Restriction Band 300-1000 Polarization: *Vertical*
 Company : W6M20705-8131 Power : 4.2 VDC
 EUT Model: TRX970HCA Distance: 3m
 Execute Program : high channel



Site : site #1
 Condition : FCC Restriction Band 1000-2000 Polarization: *Horizontal*
 Company : W6M20705-8131 Power : 4.2 VDC
 EUT Model: TRX970HCA Distance: 3m
 Execute Program : high channel
 Note :


Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1843.687	64.27	peak	-8.33	55.94	200.00	135	130	-144.0	

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24



Site : site #1
 Condition : FCC Restriction Band 1000-2000 Polarization: *Vertical*
 Company : W6M20705-8131 Power : 4.2 VDC
 EUT Model: TRX970HCA Distance: 3m
 Execute Program : high channel
 Note :


Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1843.687	63.33	peak	-8.33	55.00	200.00	155	130	-145.0	



Site : site #1
 Condition : FCC Restriction Band 2000-4000 Polarization: *Horizontal*
 Company : W6M20705-8131 Power : 4.2 VDC
 EUT Model: TRX970HCA Distance: 3m
 Execute Program : high channel
 Note :

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2765.531	53.78	peak	-3.77	50.01	74.00	155	130	-23.99	
	3687.155	55.95	peak	0.06	56.01	74.00	160	130	-17.99	
*	3687.155	52.05	AVG	0.06	52.11	54.00	160	130	-1.89	


Registration number: W6M20705-8131-P-15
 FCC ID : H50TR24



Site : site #1
 Condition : FCC Restriction Band 2000-4000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : high channel
 Note :

Polarization: *Vertical*
 Power : 4.2 VDC
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2765.531	53.03	peak	-3.77	49.26	74.00	160	130	-24.74	
*	3687.375	51.21	peak	0.06	51.27	74.00	160	130	-22.73	




Site : site #1
 Condition : FCC Restriction Band 4000-8000
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program : high channel
 Note :

Polarization: *Horizontal*
 Power : 4.2 VDC
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4608.978	55.65	peak	-1.68	53.97	74.00	155	105	-20.03	
*	4608.978	52.63	AVG	-1.68	50.95	54.00	155	105	-3.05	
	5531.062	46.42	peak	2.76	49.18	200.00	140	110	-150.8	
	6452.906	51.57	peak	4.17	55.74	200.00	140	110	-144.2	

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24



- Note**
1. Correction Factor = Antenna factor + Cable loss - Preamplifier
 2. The formula of measured value as: Test Result = Reading + Correction Factor
 3. All not in the table noted test results are more than 20 dB below the relevant limits.

All other not noted test plots do not contain significant test results in relation to the limits.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 017 ETSTW-RE 028
 ETSTW-RE 029 ETSTW-RE 030 ETSTW-RE 042 ETSTW-RE 043
 ETSTW-RE 044 ETSTW-RE 064

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

3.7 Carrier Frequency Separation

Carrier Frequency Separation was measured with modulation (declared by manufacturer).

According to FCC rules part 15 subpart C §15.247 frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or 20 dB bandwidth of the hopping channel, whichever is greater.

Test conditions		Channel Separation	
		Channel 0	Channel 0+1
$T_{nom} = 23^{\circ}C$	$V_{nom} = 4.2 V$	498.865245897 kHz	

Test conditions		Channel Separation	
		Channel 12	Channel 12+1
$T_{nom} = 23^{\circ}C$	$V_{nom} = 4.2 V$	498.999965892 kHz	

Test conditions		Channel Separation	
		Channel 24	Channel 24+1
$T_{nom} = 23^{\circ}C$	$V_{nom} = 4.2 V$	499.258654120 kHz	

Limits:

Frequency Range MHz	Limits	
	20 dB bandwidth < 25 kHz	20 dB bandwidth > 25 kHz
902-928	25 kHz	20 dB bandwidth
2400-2483.5 5725-5850.0	25 kHz	20 dB bandwidth

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055 ETSTW-RE 064

Comment: See attached diagrams as appendix.

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

3.8 Number of Hopping Frequencies

According to FCC rules part 15 subpart C §15.247 frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies. Frequency hopping systems in 5725-5850 MHz bands shall use least 75 hopping frequencies.

For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies; if the 20dB bandwidth of the hopping channel 250 kHz or greater, the system shall use at least 25 hopping frequencies.

Test conditions		Operating Mode	Number of Channels
$T_{nom} = 23^{\circ}C$	$V_{nom} = 4.2 V$	normal transmitting	25

Limits:

Frequency Range MHz	Limit			
	20dB Bandwidth		20dB Bandwidth < 250 kHz	20dB Bandwidth ≥ 250 kHz
	≤ 1MHz			
902-928 MHz			≥ 50	≥ 25
2400-2483.5	≥ 15	≥ 15		
5725-5850.0 MHz	≥ 75			

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055 ETSTW-RE 064

Comment: See attached diagrams as appendix.

Registration number: W6M20705-8131-P-15
FCC ID : H5OTR24

3.8.1 Pseudorandom Frequency Hopping Sequence

This FHSS transmitter is controlled by a microchip to generate the Pseudorandom Frequency Hopping Sequence. There are three hopping sequences listed below:

Sequence A : 915.5, 914, 912.47, 910.5, 913.45, 911.5, 910, 909, 909.5, 911, 912.96, 914.5, 916.51, 916, 915, 917.6, 919.6, 921.77, 920.29, 918.11, 919.11, 921.29, 920.8, 918.62, 917.05

Sequence B : 921.29, 919.11, 917.6, 919.6, 918.11, 916, 914.5, 912.96, 910.5, 909, 911, 909.5, 911.5, 910, 912.47, 914, 913.45, 915, 917.05, 915.5, 916.51, 918.62, 920.8, 921.77, 920.29

Sequence C : 913.45, 915.5, 918.11, 920.29, 920.8, 918.62, 916.51, 915, 912.96, 911, 910, 911.5, 909.5, 909, 910.5, 912.47, 914, 916, 917.6, 919.6, 921.77, 921.29, 919.11, 917.05, 914.5

3.8.2 Coordination of hopping sequences to other transmitters

This transmitter does not have the ability of being coordinated with other FHSS system for as soon as the transmitter is in operation, the hopping frequency will follow the selected hopping sequence to transmit independently and no coordination is possible. Especially, this transmitter is used as a duplex car alarm system, so no coordination of hopping frequency is required.

3.8.3 System Receiver Hopping Capability

There are two steps to make the receiver to shift the frequencies in synchronization with the transmitted signals:

First, the Transmitter will emit a preamble signal of 50 ms and the receiver will scan this signal by 2ms sweeping until the preamble signal is caught. Second, the preamble signal is coded with the information of hopping sequence and the next transmitting frequency, so the receiver will be able to shift the receiving frequencies in synchronization with the transmitted signals.

3.8.4 Equal Hopping Frequency Use

Due to each hopping frequency will be transmitted in accordance to the frequency tables described above, there is no any frequency will be able to hop more times than others. Therefore each frequency will be used equally.

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

3.9 Time of Occupancy (Dwell Time)

Frequency hopping systems operating in the 5725-5850 MHz band shall use an average time of occupancy on any frequency not greater than 0.4 seconds within a 30 second period.

In 2400-2483,5 MHz band the average time of occupancy on any channel shall not be greater than 0,4 seconds multiplied by the number of hopping channels employed.

For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the average time of occupancy on any frequency shall not greater than 0.4 seconds within a 20 second period; if the 20dB bandwidth of the hopping channel is 250 kHz or greater, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

Test conditions	Operating mode	Measurement period	Time of Occupancy
T _{nom} = 23°C V _{nom} = 4.2 V Channel 1	normal transmitting		387.023 ms

Test conditions	Operating mode	Measurement period	Time of Occupancy
T _{nom} = 23°C V _{nom} = 4.2 V Channel 13	normal transmitting		387.023 ms

Test conditions	Operating mode	Measurement periode	Time of Occupancy
T _{nom} = 23°C V _{nom} = 4.2 V Channel 25	normal transmitting		387.143 ms

Registration number: W6M20705-8131-P-15

FCC ID : H5OTR24

Limits and measurement periods:

Frequency MHz	Number of channels	Measurement Periode	Limit
902 – 928	≥ 50	20 s	0,4 s
	$49 \geq 25$	10 s	0,4 s
2400 – 2483,5	≥ 15	0,4 s * number of used channels	0,4 s
5725- 5850	≥ 75	30 s	0,4s

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055 ETSTW-RE 064

Comment: See attached diagrams, which show the On-time and the number of counted events during the measurement period

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

3.10 20dB Bandwidth

Frequency hopping systems operating in the 5725-5850 MHz bands shall use a maximum 20dB bandwidth of 1 MHz.

The 20dB bandwidth is measured on the lowest, middle and highest hopping channel.

For frequency hopping systems operating in the 902-928 MHz band the maximum 20dB bandwidth of the hopping channel is 500 kHz.

Test conditions		20 dB Bandwidth		
		Channel A	Channel B	Channel C
$T_{nom} = 23^{\circ}C$	$V_{nom} = 4.2 V$	399.2 kHz	396.8 kHz	374.4 kHz

Limits:

Frequency Range / MHz	Number of channels	Limit
902-928	< 50	< 250 kHz
	$49 \geq 25$	$500 \text{ kHz} \geq 250 \text{ kHz}$
2400-2483.5	≥ 15	not determined
5725-5850	75	$\leq 1 \text{ MHz}$

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 055 ETSTW-RE 064

Comment: See attached diagrams as appendix.

3.10.1 System Receiver Input Bandwidth

The receiver’s bandwidth is 420kHz and transmitter’s signal is about 380kHz, so the receiver’s bandwidth can match the bandwidth of the transmitter.

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

3.11 Band-edge Compliance of RF Emissions

According to FCC rules part 15 subpart C §15.247(c) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

Test conditions		Attenuation at or outside band-edges	
		Single Frequency	
		Lower Band-edge	Upper Band-edge
T _{nom} = 23°C	V _{nom} = 4.2 V	58.80 dB	57.85 dB

Test conditions		Attenuation at or outside band-edges	
		Hopping Frequency	
		Lower Band-edge	Upper Band-edge
T _{nom} = 23°C	V _{nom} = 4.2 V	56.42 dB	53.59 dB

Limits:

Frequency Range / MHz	Limit
902 – 928	- 20 dB
2400 – 2483.5	
5725 - 5850	

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 017 ETSTW-RE 028
 ETSTW-RE 030 ETSTW-RE 043 ETSTW-RE 044 ETSTW-RE 064

Comment: See attached diagrams as appendix.

Registration number: W6M20705-8131-P-15
FCC ID : H5OTR24

3.12 Radiated Emissions from Digital Part

FCC Rule: 15.109

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 017 ETSTW-RE 028
ETSTW-RE 029 ETSTW-RE 030 ETSTW-RE 042 ETSTW-RE 043
ETSTW-RE 044 ETSTW-RE 064

Comment: This test is not required because the frequency is above 960MHz.


Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24

3.13 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.


Frequency	Level (dBμV)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line



Site : site #1
 Condition : FCC Class B Conduction(QP)
 Company : W6M20705-8131
 EUT Model: TRX970HCA
 Execute Program :
 Note :
 Operator: Charles
 Date: 2007/05/30
 Time: 上午 11:32:05
 Temperature: 26 °C
 Humidity: 60 %
 Phase: N
 Power : AC 110V/60Hz

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Comment
	0.4059	33.64	QP	10.10	43.74	57.73	-13.99	
*	0.4059	24.51	AVG	10.10	34.61	47.73	-13.12	
	2.0829	32.29	QP	10.10	42.39	56.00	-13.61	
	2.0829	13.91	AVG	10.10	24.01	46.00	-21.99	
	3.3450	24.41	QP	10.10	34.51	56.00	-21.49	
	3.3450	6.74	AVG	10.10	16.84	46.00	-29.16	

Registration number: W6M20705-8131-P-15
 FCC ID : H5OTR24



Site : site #1
 Condition : FCC Class B Conduction(QP) Phase: L1
 Company : W6M20705-8131 Power : AC 110V/60Hz
 EUT Model: TRX970HCA
 Execute Program :
 Note :

Mk.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Comment
	0.4055	34.33	QP	10.10	44.43	57.74	-13.31	
	0.4055	22.68	AVG	10.10	32.78	47.74	-14.96	
*	2.0485	35.55	QP	10.10	45.65	56.00	-10.35	
	2.0485	15.23	AVG	10.10	25.33	46.00	-20.67	
	3.3100	28.56	QP	10.10	38.66	56.00	-17.34	
	3.3100	9.94	AVG	10.10	20.04	46.00	-25.96	

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- Note:**
1. The formula of measured value as: **Test Result = Reading + Correction Factor**
 2. The **Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss**
 3. **Detector function in the form : PK = Peak, QP = Quasi Peak, AVG = Average**
 4. **All not in the table noted test results are more than 20 dB below the relevant limits.**

Test equipment used: ETSTW-CE 001 ETSTW-CE 003 ETSTW-CE 004 ETSTW-CE 006 ETSTW-RE 064


Appendix

A Measurement diagrams

1. Peak Output Power
2. Carrier Frequency Separation
3. Number of Hopping Frequencies
4. Time of Occupancy (Dwell Time)
5. 20dB Bandwidth
6. Band-edge Compliance of RF Conducted Emissions

B Photos


1. External Photos
2. Internal Photos
3. Set Up Photo of Radiated Emission
4. Set Up Photo of Conducted Emission



Tx Channel			
Bandwidth	300 kHz	Power	19.48 dBm
Adjacent Channel			
Bandwidth	500 kHz	Lower	-----
Spacing	16.5 MHz	Upper	-----
Alternate Channel			
Bandwidth	500 kHz	Lower	-----
Spacing	27.5 MHz	Upper	-----

Max output power low channel


Date: 7.JUN.2007 20:40:27



Tx Channel			
Bandwidth	300 kHz	Power	19.64 dBm
Adjacent Channel			
Bandwidth	500 kHz	Lower	-----
Spacing	16.5 MHz	Upper	-----
Alternate Channel			
Bandwidth	500 kHz	Lower	-----
Spacing	27.5 MHz	Upper	-----

Max output power middle channel

Date: 7.JUN.2007 20:40:11




Tx Channel		Power	19.63 dBm
Bandwidth	300 kHz		
Adjacent Channel		Lower	-----
Bandwidth	500 kHz	Upper	-----
Spacing	16.5 MHz		
Alternate Channel		Lower	-----
Bandwidth	500 kHz	Upper	-----
Spacing	27.5 MHz		

Max output power high channel

Date: 7.JUN.2007 20:40:44



Ref 36 dBm *Att 20 dB *RBW 100 kHz Delta 1 [T1]
*VBW 100 kHz 0.26 dB
*SWT 300 ms 498.865245897 kHz




Ferquency separation low channel

Date: 7.JUN.2007 20:35:10




Ref 36 dBm *Att 20 dB *RBW 100 kHz Delta 1 [T1] 0.00 dB
*VBW 100 kHz *SWT 300 ms 498.999965892 kHz



Ferquency separation middle channel

Date: 7.JUN.2007 20:36:04




Number of hopping

Date: 7.JUN.2007 20:38:34



Ref 6.5 dBm *Att 20 dB RBW 100 kHz
*VBW 100 kHz SWT 10 s




Dwell time 909MHz =55.289 ms*7=387.023ms

Date: 29.JUN.2007 17:52:31



RBW 100 kHz Delta 1 [T1]
*VBW 100 kHz -34.06 dB
SWT 100 ms 55.288462 ms
Ref 6.5 dBm *Att 20 dB

1 AP
CLRWR




Center 909 MHz 10 ms/

Dwell time 909MHz =55.289 ms*7=387.023ms

Date: 29.JUN.2007 17:53:27



Ref 6.5 dBm *Att 20 dB RBW 100 kHz
*VBW 100 kHz SWT 10 s




Dwell time 915.5MHz =55.289 ms*7=387.023ms

Date: 29.JUN.2007 17:56:45



Ref 6.5 dBm *Att 20 dB RBW 100 kHz Delta 1 [T1] -30.01 dB
*VBW 100 kHz SWT 100 ms 55.288462 ms




Dwell time 915.5MHz =55.289 ms*7=387.023ms

Date: 29.JUN.2007 17:54:22



Ref 6.5 dBm *Att 20 dB RBW 100 kHz
*VBW 100 kHz SWT 10 s




Dwell time 921.778MHz =55.449 ms*7=387.143ms

Date: 29.JUN.2007 17:55:32



Ref 6.5 dBm *Att 20 dB RBW 100 kHz Delta 1 [T1]
*VBW 100 kHz -0.27 dB
SWT 100 ms 55.448718 ms




Dwell time 921.778MHz =55.449 ms*7=387.143ms

Date: 29.JUN.2007 17:55:57




Ref 36 dBm *Att 20 dB *RBW 50 kHz Marker 1 [T1] 15.37 dBm
*VBW 100 kHz *SWT 300 ms 909.103200000 MHz



20dB bandwidth low channel
Date: 7.JUN.2007 20:28:50



Ref 36 dBm *Att 20 dB *RBW 100 kHz Delta 1 [T1]
*VBW 100 kHz 58.80 dB
*SWT 300 ms 7.120000000 MHz




Bandedge low channel

Date: 7.JUN.2007 20:32:03



Ref 36 dBm *Att 20 dB *RBW 100 kHz Delta 1 [T1]
*VBW 100 kHz 57.85 dB
*SWT 300 ms -6.320000000 MHz




Bandedge high channel

Date: 7.JUN.2007 20:31:34



Ref 36 dBm *Att 20 dB *RBW 100 kHz Delta 1 [T1] 56.42 dB
*VBW 100 kHz *SWT 300 ms 6.923076923 MHz




Bandedge low channel hopping mode

Date: 4.JUL.2007 17:42:52



Ref 36 dBm *Att 20 dB *RBW 100 kHz Delta 1 [T1]
*VBW 100 kHz 53.59 dB
*SWT 300 ms -6.121794872 MHz



Bandedge high channel hopping mode

Date: 4.JUL.2007 17:42:01